

C S 9015

F I E L D N O T E S .

Township 2 N. Range 9 W. S. B. M.

- West Line Sec. 32
- North Line Sec. 32
- North Line Sec. 29
- South Line Sec. 19 } *Portions on offsets*
- West Line Sec. 19
- West Line Sec. 18
- West Line Sec. 7
- West Line Sec. 6
- North Line Sec. 28
- North Line sec. 27
- North Line Sec. 26
- North Line Sec. 25

-----0-----
 S Line Sec. 31
 E " " 20

No Notes

T.3N.	R.10W.						R.9W.		R.9W.				R.9W.	R.8W.	T.3N.
T.2N.	2.3	6	5	4	3	2	1								T.2N.
	2.7	8	9	10	11	12									
	1.2	10	17	16	15	14	13								
	1.10N	19	20	21	22	23	24								
	3.10	29	28	27	26	25									
	3.3	32	33	34	35	36									
T.1N.	R.10W.												R.9W.	R.8W.	T.1N.
T.1N.	3.4														

Pearson 1883

See C.S. 9246

From the Field Notes of G. H. Pearson, 1883.

North between sections 25 and 30.


Var. 14° 26½' East.

80.00 Set a sand stone 20 x 11 x 9 in., 15 in. in the ground for corner to sections 19, 24, 25 and 30.

Marked with 4 notches on the South edges and raised mound of stone alongside.

Land mountainous. Soil second rate.

Timber scattering Pine and Oak. Dense undergrowth of chaparral.



? Secs. 19 + 24

North on the East boundary of T. 2 N. R. 10 W., between sections 25 and 30.

Var. 14° 26½' East.

40.00 Set a granite stone 19x11x8 in., 12 in. in the ground, for ¼ section corner, marked ¼ on West face and raised mound of stone alongside.

Pits impracticable.

80.00 Set a granite stone 16 x 10 x 7 in., 11 in. in the ground for corner to sections 13, 18, 19 and 24.

Marked with 2 notches on the North and South edges and raised a mound of stone alongside.

Pits impracticable. Land mountainous.

Soil third rate. Timber none, dense undergrowth of chaparral.



North between section 13 and 18.

Var. 14° 27' East.

Descending.

40.00 Set granite stone 16 x 11 x 5 in., 11 in. in the ground for ¼ section corner, marked ¼ on West face and raised mound of stone alongside.

Pits impracticable.

60.00 West fork of San Gabriel River 70 lks. wide, course South 40° East in a canyon 3 and 3.10 chs. wide,

1 mile to Gar North JDB

80.00	<p>course S. 40° E. and ascend.</p> <p>Set a granite stone 14 x 11 x 9 in., 9 in. in the ground for corner to sections 7, 12, 13 and 18. Marked with 4 notches on South and 2 notches on North edges and raised mound of stone along side.</p> <p>Pits impracticable. Land mountainous.</p> <p>Soil third rate. Timber Pine, Fir and Oak in canyons.</p>
7	<p style="text-align: center;">-----o-----</p> <p>North between section 7 and 12.</p> <p style="text-align: right;">Var. 14° 27' East.</p> <p>Ascend.</p>
27.50	<p>Top of spur brs. S. 85° E and descend.</p>
40.00	<p>Set granite stone 12 x 11 x 4 in., 7 in. in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on West face and raised mound of stone alongside.</p>
71.15	<p>North fork of San Gabriel River, 40 lks. wide, course Southeast in canyon, 2.30 chs. wide, course Southeast and ascending.</p>
80.00	<p>Set granite stone 15 x 11 x 9 in., 10 in. in the ground for corner to sections 1, 6, 7 and 12, marked with 5 notches on South and 1 notch on North edges and raised mound of stone alongside.</p> <p>Pits impracticable. Land mountainous.</p> <p>Soil third rate.</p> <p>Timber Pine, Fir and Oak in canyons. Dense undergrowth of Chaparral.</p>
	<p style="text-align: center;">-----o-----</p> <p>North between sections 1 and 6.</p> <p style="text-align: right;">Var. 14° 27' East.</p> <p>Ascending.</p>
40.00	<p>Set granite stone 16 x 9 x 8 in., in the ground for $\frac{1}{4}$ section, marked $\frac{1}{4}$ on West face and raised mound of stone alongside.</p>

82.10 To a point 2.51 chs. West to corner to Tps. 2 and 3 N.,
Rs. 9 and 10 W., which is a post 4 x 4 in. firmly set
in large mound of rocks, marked T. 3 N., R. 9 W.
section 31 on Northeast and

T. 2 N., R. 9 W., Section 6 on Southeast.

T. 2 N., R. 10 W., Section 1 on Southwest and

T. 3 N., R. 10 W., Section 36 on Northwest faces
and which point of intersection set granite stone 21 x
18 x 11 in., 16 in. in the ground for closing corner
to section 1 and 6.

T. 2 N., Rs. 9 and 10 marked

C. C. with 6 notches on South, East and West
edges, and raised mound of rocks alongside.

Pits impracticable.

Land mountainous. Soil third rate. Timber none.

~~Dense undergrowth of Chaparral.~~

-----O-----

East on a random line between section 31 and 6, re-
tracing 37 chs,

Var. 14° 28' East.

40.00 Set temporary $\frac{1}{2}$ section corner.

45.00 Unable after diligent survey to find witness corner,
I continue East and at

80.21 To a point 25 lks. South of the corner to sections
5, 6, 31 and 32, Tps. 1 and 2, N. Rs. 9 W., which
is a part of decayed post, in mound of rocks, I re-
build corner by setting sand stone 15 x 11 x 7 in.,
10 in. in the ground for corner to sections 5, 6, 31
and 32. Marked with 1 notch on West and 5 notches
on the East edges and rebuild mound of rocks along
side.

Pits impracticable.

Thence I run


South 89° 49' West on a true line between sections

6 and 31 with same variations.
 Descending.
 26.50 Enter San Gabriel Canyon, course Southeast.
 31.00 San Gabriel River 60 lks. wide, course Southeast.
 38.00 Leave Canyon and ascend.
 40.00 Set granite stone 12 x 11 x 5 in., 7 in. in the ground
 for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on North face and
 raised mound of stone alongside.
 Pits impracticable.
 44.00 Top of spur bears Southeast and descend.
 69.00 Ravine 60 lks. wide, course Southeast and ascending.
 80.21 The corner to sections 1, 6, 31 and 36, Tps. 1 and 2
 North, Rs. 9 and 10 West.
 Land mountainous. Soil second rate,
 Timber Pine and Oak in the ravine. Dense undergrowth
 of Chaparral.



From the corner to sections 5, 6, 31 and 32 on the
 South boundary of the Tp. I run North between sections
 31 and 32.
 Var. 14° 15' East.

Descending.
 11.50 Leave hills and enter valley of San Gabriel.
 27.50 To San Gabriel River 75 lks. wide, course Southwest.
 34.00 Leave Valley of San Gabriel and ascend.
 40.00 Set a Redwood post 3 x 3 in, 3 ft. long, in a mound of
 rocks for $\frac{1}{4}$ section corner,
 Thence, along the South slope of mountain.
 80.00 Set an Oak post 4 x 4 in., 3 ft. long in a mound of
 rocks on side hill, faces Northeast for corner to
 sections 29, 30, 31 and 32.
 Land very rough, Mineral places with scattering
 Oak, Sycamore and Alder.



East on a true line between sections 29 and 32.
 Var. 14° 15' East.

5.50 Cross gulch 25 lks. wide course Southeast.
 Thence over foot hills ascending.

14.50 Summit, Thence descend.

24.00 Leave hills and enter valley of San Gabriel, course
 North and South.

33.00 To waters of San Gabriel 75 lks. wide, course South-
 west.

40.00 Set an Alder in mound of rocks as instructed, for $\frac{1}{4}$
 sections corner,
 From which an
 Alder tree 6 in. dia. brs. S. 70° W., 08 lks.
 Alder tree 7 in. dia. brs. N. 59° W., 17 lks.
 Station #1 on Northeast Corner of the Justice
 Placer-Minining claim brs. S. 10 chs. dist.

50.50 Leave San Gabriel Valley ascending, course Northeast
 and South.

73.50 Summit of spur, course Southwest and Northeast and
 descending.

80.00 Set granite rock 10 x 16 x 24 in, in a mound of rocks
 as instructed, for corner to sections 28, 29, 32 and
 33.

-----o-----

From the corner to sections 28, 29, 32 and 33 I run
 North between sections 28 and 29.
 Var. 14° 15' East.

80.00 Set an Alder post 4 x 4 in., 3 $\frac{1}{2}$ ft. long in a large
 mound of rocks, as instructed, for corner to sections
 20, 21, 28 and 29. In Northern boundary of
 Baker and Austin Placer Mine.
 Land very rough mineral placers with scattering
 timber Oak, Alder and Sycamore in Canadas.

-----o-----

East on a true line between sections 21 and 28.

Var. 14° 15' East.

10.00

Intersect the East boundary of Baker and Austin Placer Mining Claim, 5.00 chs. South of corner # 1 of said Calim set an Alder post 3-x 3 in., and 3 ft. long at post of intersection as instructed, for corner to frac. section 21 and 28.

15.00

Corner # 4 of the Bud Placer Mining Claim. 5.00 chs. North.

16.50

Leave Valley ascending along North slope of mountain.

35.00

Corner # 1 of the Ford Placer Mining Claim. 5.00 chs. North. Cross gulch 20 lks. wide, course Northwest

40.00

Set a Sycamore post 3 x 3 in., 3 ft. long in mound of rocks on steep side hill, face North, as instructed, for 1/2 section corner,

From which an

Oak tree 2 ft. in dia. brs. S. 89° E., 35 lks. The corner # 5 of the Woodman Placer Mining Claim bears North 5.00 chs., thence trough Claim.

80.00

The corner # 1 of the Woodman Placer Mining Claim, also post for corner to sections 21, 22, 27 and 28 falling on steep side hill, not a suitable place to build a monument I set a Sycamore post 4 x 4 in., 3 1/2 ft. long, in a large mound of rocks at foot of hill 2.80 chs. East as instructed for witness to corner to sections 21, 22, 27 and 28.

From which a

Liver Oak 30 in. dia. brs. N. 29° E., 24 lks. Land rough Placer Mine with scattering timber of Oak Sycamore and Alder.

East on a true line between section 22 and 27/

Var. 14° 15' East.

2.80

Witness post, enter Canada San Gabriel, thence up

Handwritten calculations:
2.80
16.80
187.8
5.280
5764.80

5280
1320
660

5280
1320
660

145
6
810
470
957.10
1320

5280
2640
7920

265
1590
1590
1749.15
5280
7029

72
6
78
432
4152
5280
10037

6350
3750
375
4125
10588
4775

Canadas.

14.50 Cross San Gabriel River 30 lks. wide, course Northwest.
20.00 Corner # 2 of the Furgerson Placer Mining Claim.

26.50 Cross San Gabriel River 30 lks. wide, course Southwest,
Thence along on South side of same.

40.00 Set a Cottonwood post 3 x 3 in., and 3 ft. long in a
mound of rocks at foot of gravel wash from tailings of
hydraulic mining,

From which a

Sycamore tree 6 in. in dia. bears. S. 6 1/2° W., 29 lks.
Hydraulic works 2.50 chs. South.

60.00 Corner # 1 of Furgerson Claim on South slope bank of
San Gabriel River 30 lks. wide, course Northwest.

72.00 Leave Canadas and ascend gravelly hill along South
side of a gulch.

80.00 Set a sycamore post 4 x 4 in., 3 1/2 ft. long in a mound
of rocks on side hill facing West as instructed for
corner to sections 22, 23, 26 and 27.

Land along bottom of river mostly worthless gravelly
bed, mineral placer. This is also # 1 of the
Graham and Cecil Placer Mining Claim.

-----o-----

East on a true line between sections 25 and 26.

Var. 14° 15' East.

Along on South slope of mountain.

40.00 Set an Oak post 3 x 3 in., 3 ft. long in a mound of
rocks as instructed for 1/4 sections corner.

62.50 Cross gulch 20 lks. wide, course South and ascend
steep side of hill.

80.00 Set a Redwood post 4 x 4 in., 3 1/2 ft. long in a mound
of rocks as instructed for corner to sections 23, 24,
25 and 26, about 20 chs. North of the River.
Land over rolling hills. Third rate soil.
Cow brush.

-----o-----

From the corner sections 20, 21, 28 and 29 I run West on a true line between sections 20, and 29.

Var. 14° 15' East.

- 5.00 Cross San Gabriel River 3 lks. wide, course Southwest.
- 8.50 Leave Canadas and ascend.
- 13.00 Cross gulch 100 lks. wide, course South.
- 40.00 Set a Sycamore post 3 x 3 in., 3 ft long, in a mound of rocks on South edge of rocky bluff for $\frac{1}{4}$ section corner,
Thence descend.
- 48.00 Leave hills into Canadas of the North fork of San Gabriel River.
- 50.00 Cross North fork 40 lks. wide, course Southeast.
- 60.00 Find it impossible to run this line further West, I set a Sycamore post 3 x 3 in., 3 ft., long in a mound of rocks at the foot of high mountain for $\frac{1}{8}$ section corner
- From which a
- Live Oak 20 in. dia. brs. N. 88 $\frac{1}{2}$ ° E., 4.81 chs.
Thence North on $\frac{1}{8}$ section line.
- Var. 14° 15' East.
- 10.00 Cross North fork 30 lks. wide, course Southeast.
- 18.50 Leave Canadas and ascend.
- 20.00 Set a sand rock 10 x 16 x 30 in., in a mound of rocks on steep side of hill facing South, as instructed, for $\frac{1}{8}$ section corner.
Thence West.
- 10.00 Enter Canadas, thence up same.
- 20.00 To line between sections 19 and 20, 20,00 chs. North of the corner to section 19, 20, 29 and 30.
Being unable to run South to establish the corner I set a Willow post 3 x 3 in., 3 ft. long in a mound of rocks on North side of Canadas, as instructed, for $\frac{1}{8}$

section corner and continued

20.00 West on 1/8 section line up Canadas in section 19. Counting distance from section line set a Sycamore post 3 x 3 in., and 3 ft. long in a mound of rocks as instructed, for 1/8 section corner and run South on 1/8 section line.

1.50 To North fork of San Gabriel 20 links wide, course East.

1.80 Over same thence along bottom land.

20.00 Set a Sycamore post 4 x 4 in., 3 ft. long in a mound of rocks as instructed for 1/8 section corner 20.00 chs West of the corner to sections 19, 20, 29 and 30.

From which a

Live Oak 3 ft. in. dia. brs. S. 25° W., 192 chs.

Land along river bottom which is first and second rates with scattering timber Oak, Sycamore and Cottonwood.

-----o-----

West between sections 19 and 30.

Var. 14° 15' East.

13.00 Leave Canadas and ascending, course Northwest and Southeast.

20.00 Set a Sycamore post 3 x 3 in., and 3 ft. long in a mound of rocks as instructed for 1/4 section corner on side hill facing East.

40.00 Being unable to run further on this line West set a sand rock 10 x 20 x 36 in., in a mound of rocks on top of high hill for 1/8 section corner.

Land mostly second rate.

Timber Oak and Sycamore.

-----o-----

From the 1/4 section corner between sections 19 and 30 I run

South on 1/4 section line through center of section 30.

Var. 14° 15' East.

30.50 Cross gulch with Oak timber, thence ascend

40.00 Set a Redwood post 3 x 3 in., and 3 ft. long in a mound of rocks as instructed for $\frac{1}{4}$ section corner in center of section 30.
This is as far South on West as it is practicable to run this line, I, therefore, run East on $\frac{1}{4}$ section line through section 30.

Var. 14° 15' East.

Ascending.

39.00 Summit of ridge, course Northwest and Southeast
Thence along same

40.00 Set a sand rock 10 x 10 x 10 in., in a mound of rocks on top of a high barren ridge, as instructed, for $\frac{1}{4}$ section corner between sections 29 and 30.

This is all the land in this direction that is practicable to subdivide.

Land very rough, good Oak timber in places.

-----O-----

From the corner to sections 23 and 24, 25 and 26, I run

?

East on a random line between sections ²⁴22 and 25.

Var. 14° 26 $\frac{1}{2}$ ' East.

40.00 Set temporary $\frac{1}{4}$ section corner.

30.68 Intersect East boundary of Tp. 49 lks. South of corner to sections 19, 24, 25 and 30.

Thence I run

South 89° 39' West on a true line between sections 24 and 25.

Var. 14° 26 $\frac{1}{2}$ ' East.

Ascend.

40.34 Set sand stone 17 x 14 x 9 in., 13 in. in the ground for $\frac{1}{4}$ section corner, Marked $\frac{1}{4}$ on North face and raised a mound of stone alongside.

Pits Impracticable.

62.00 Low point of spur bears Southwest and descend.

80.68 The corner to sections 23, 24, 25 and 26.

Land mountainous.

Soil third rate.

Timber none.

Dense undergrowth of Chaparral.