

R9W.					
6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
11	10	9	8	7	6
5	31	10	32	9	33
4	3	2	3	2	1
4	6	15	5	4	12
15	14	12	11	19	18
5	7	4	8	2	9
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

9020

— Hancock :- 1855

— Friel :- 1900

T. 4 & 5 N., R. 9 W. S.B.M.

East boundary of section 36, T. 5 N., R. 9 W. and  
East boundary of sections 1, T. 4 N., R. 9 W., S.B.M.  
in the Field Notes of T. 4 & 5 N., R. 9 W., S.B.M.

---

SOUTH BOUNDARY T. 5 N., R. 9 W., S.B.M.

Var. 14<sup>o</sup> 5' East

From the corner of Tp. 4 and 5 N., Rgs. 8 and 9 W.,  
West on the south boundary of section 36.

- 6.00 Cross dry bed of arroyo 150 lks. wide, coarse N.  
13.50 Cross another arroyo 15 lks. wide course N.  
40.00 Drive 1/2 section post and dug trench as per instructions  
From which bears a cedar 5 in. dia. N. 67° E., 125 lks.  
51.00 East bank of ravine.  
54.00 To center of gully and cross dry arroyo 12 lks. wide,  
course N.  
56.00 Cross dry arroyo 1 chain wide, coarse N.  
66.00 Cross dry arroyo 1 ch. wide, and 15 ft. deep coarse N.  
79.00 To east bank of a ravine.  
89.00 Set section post and charred stake in mound of rock  
and earth with trench and pits on west face of ravine,  
course N.  
120.00 Stand 100 ft. on north bank of a large cut and west of  
high foot ridge of the mountain side. Come 1/2 to 1 of a mile  
Soil very poor and rocky.
- 

West on south boundary of section 35.

- 2.00 Cross dry ravine.  
4.00 To center of another ravine, coarse N.  
6.00 To N. bluff of gully.  
8.00 Bank of ravine.  
1.00 Cross dry arroyo 60 lks. wide, to east, coarse N.

T. 4 & 5 N. R. 9 W. S.B.M.

- 31.00 To top of W. bank.  
40.00 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions.  
45.00 To east bank of dry arroyo.  
46.00 Cross same, course N.  
47.00 To top of west bank of same.  
62.00 Cross dry arroyo 15 lks. wide, course N.  
77.00 Cross arroyo 15 lks. wide, course N.  
79.00 To W. bank of arroyo  
80.00 Set section post and charred stake in mound with trench and pits as per instructions corner of sections 34, 35, 2 and 3 on west side of dry arroyo, course N.  
From which bears a cedar 6 in. dia. N.  $65^{\circ}$  W., 54 lks.  
Same as last mile.

---

West on south boundary of section 34.

- 6.50 Cross dry bed of arroyo 15 lks. wide, course N.  
16.00 Cross another dry bed of arroyo 50 lks. wide, course N. bank 4 ft. high.  
40.00 Drive  $\frac{1}{2}$  section post and charred stake.  
From which bears a Spanish Bayonet 6 in. dia. S.  $19^{\circ}$  W., 140 lks.  
Cedar 5 in. dia. N.  $52^{\circ}$  W., 130 lks.  
60.50 Cross dry arroyo 12 lks. wide, course N. banks 3 ft. high  
Set section post and charred stake in mound with trench and pits as per instructions, corner of sections 33, 34, 3 and 2.  
Same as last mile.

---

West on south boundary of section 33

- 32.40 To east bank of canada, course NW, from this point  
a point on east side of pass of the canada through foot

T. 4 & 5 N., R. 9 W. S.D.M.

hills of the boundary bears S.  $70^{\circ}$  E., pass distant about one mile

33.50 Into Canada

40.00 Set 1/2 section post and charred stake in a mound of rock and earth 5 ft. base,

From which bears the point (a bush) on east side of pass out of Canada before taken S.  $42\frac{1}{2}^{\circ}$  E.

40.50 Cross dry arroyo bed 1 ch. wide, course NW

41.00 Cross Canada and to top of W. bank of same.

40.00 Set section post and charred stake in mound with trench and pits as per instructions corner of sections 32, 33, 4 and 5.

Undulating land sloping to the north.

Soil of first half mile third rate.

Last mile second rate.

---

West on south boundary of section 32

40.00 Drive 1/2 section post and charred stake,

From which bears a cedar 7 in. dia. S.  $53\frac{1}{2}^{\circ}$  E., 106 lbs.

Spanish Bayonet 10 in. dia. N.  $60^{\circ}$  E., 177 lbs.

Small bush on top of conical hill on north face of

Range of foot hills having a base of about 20 obs. dist. about

40 obs. S.  $31\frac{1}{2}^{\circ}$  E.

75.50 To E. bluff of a river or a plain (Río Del Silencio)

50.00 Drive section post and charred stake and deep trench

as per instruction corner of sections 31, 32, 5 and 6.

At head of ravines making a river bottom,

From which bears a cedar 7 in. dia. S.  $29^{\circ}$  E., 69 lbs.

Cedar 5 in. dia. S.  $76^{\circ}$  W. 83 lbs.

Undulating land sloping N.

Soil second rate.

T. 4 S., R. 9 W. S.B.M.

West on south boundary of section 3

- 2.00 Top of bank.  
3.00 To east bank of ravine  
7.00 Into same, course NW  
11.00 To top of NW slope of spur.  
19.00 Into ravine 10 lks. wide, course N.  
12.50 To top of NW end of ridge  
16.00 To bottom land of river.  
21.50 Cross bottom and Rio Del Slano 16 lks. wide, 6 in.  
deep and rapid course N.  
40.00 Set 1/2 section post and charred stake in mound with trench  
and pits as per instructions.  
50.00 Set Tp. post and charred stake in mound with trench and  
pits as per instructions corner of Tps. 4 and 5 N. Rgs.  
9 and 10 W., on east slope of high hill.  
Broken land.  
Soil generally third rate.

---

On west boundary of T. 4 N., R. 9 W.

Var. 14°08' East

From the corner of Tp. 4 and 5 N., R. 9 W. and 10 W.

South on west boundary of section 6

- 12.00 Top of ridge, course E and W  
37.00 To top of another ridge course SE and NW on south face of  
high hill.  
40.00 Set 1/2 section post and charred stake in mound with trench and  
pits as per instructions.  
52.50 Cross ravine taking easterly towards the river and  
cross trail leaving, to a swamp about a mile N and S  
being about a mile land from E. to W., and 20 or so  
from N to S. and cross wagon trail, course northwest  
57.50 To E. slope of spur near E. point.  
63.50 To S. base of high hill and cross dry arroyo 50 lks. wide.

T. 4 & 5 E., R. 9 W. S.B.M.

course E., the outlet of the swamp above mentioned,  
during the rainy season.

50.00 Set section post and charred stake in mound with trench  
and pits as per instructions corner of sections 1, 6, 7  
and 12.

Hilly land.

Soil second and third rate.

South on west boundary of section 7, being the east  
boundary of section 12, T. 4 E., R. 10 W.

1.00 To north base of mountain bearing NW

3.50 Cross gully 50 lks. wide, course NW

40.00 Set  $\frac{1}{2}$  section post and charred stake in mound with trench  
and pits as per instructions on N. base of spur,  
from which bears a

Bush on point of hill at the east head and near the S. side  
of a valley some 2 miles long and one mile wide, traversed  
by the river from SE to NW; S.  $69^{\circ}$  E. and a high ledge on  
ridge of hills (courses E and W.) on the S. side of  
valley, N.  $9 \frac{1}{2}^{\circ}$  E.,

69.00 Cross valley 5 lks. wide, course NW

50.00 Set section post and charred stake in mound with shallow  
trench and pits for nearness of ledge to surface on NE  
slope of spur, course to sections 7, 12, 13 and 18,  
from which bears the bush on point of hill before taken and find on  
ridge of hills S. of valley, N.  $69^{\circ}$  E. and find it insurpassing  
rough mountains on south. Return to the Tp. corner to T. 4 & 5 E.,  
Rgs. 9 and 10 W.

On west boundary of T. 5 E., R. 9 W.

VAR. 14-68-100

North on west boundary of section 31.

51.00 To top of ridge sloping E. with indications of a vein

T. 4 & 5 N., R. 9 W. S.B.M.

of Copper Ore.

40.00 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions (deposit only 5 in. for rock)

50.00 Set section post and charred stake in mound with trench and pits as per instructions corner of sections 25, 30, 31 and 36 on N. face of range of high hills from E. to W.

Land hilly.

Soil third rate.

Timber scattering cedar.

---

By Henry Hancock,

1855

---

T. 5 N., R. 9 W., S.B.M.

North on true line between sections 35 and 36.

Var.  $14^{\circ}00'$  East

30.50 Wagon road, course N., cross same.

Drive  $\frac{1}{2}$  section post and charred stake,

From which bears a Spanish Bayonet 5 in. dia. S.  $5^{\circ}0$  E., 53 lks.

Spanish Bayonet 10 in. dia. N.  $64^{\circ}0$  W. 165 lks.

50.00 Drive section post and charred stake and dug trench as per instructions for corner of sections 25, 26, 35 and 36

From which bears a Spanish Bayonet 10 in. dia. S.  $59^{\circ}0$  E. 194 lks.

Spanish Bayonet 10 in. dia. S.  $3^{\circ}0$  W., 121 lks.

Timber scattering cedar.

Land sloping to the N.

Soil second rate.

---

East on a random line between sections 25 and 36

Var.  $14^{\circ}00'$  east.

T. 5 N., R. 9 W. S.B.M.

- 14.50 Cross dry arroyo 20 lks. wide, course north.  
37.00 Cross dry arroyo 15 lks. wide, course north.  
40.00 Set temporary  $\frac{1}{4}$  section corner  
58.00 Cross dry arroyo 12 lks. wide, course north.  
77.50 Cross dry arroyo 30 lks. wide, course north.  
97.70 Intercept the east boundary of sp. 24 lks. north of corner  
of sections 25 and 36,  
From which I run  
West on a true line between sections 25 and 36.

Var.  $13^{\circ}58'$  East

- 39.85 Set  $\frac{1}{4}$  section post and charred stake in mound with  
trench and pits as per instructions.  
79.70 To corner of sections 25, 26, 35 and 36.  
Land undulating. Soil second rate.  
Vegetation partly chemical and bunchgrass.

North between sections 34 and 35.

Var.  $15^{\circ}06'$  east

- 9.00 Leave dry arroyo 30 lks. wide, course NW  
37.00 Cross wagon road course N.  
40.00 Drive  $\frac{1}{4}$  section post and charred stake,  
From which bears a spanish bayonet 6 in. dia. N.  $77^{\circ}W.$ , 34 lks.  
Spanish Bayonet 10 in. dia. N.  $55\frac{1}{2}' E.$ , 70 lks.  
50.00 Set section post and charred stake in mound with trench  
and pits as per instructions, corner of sections 26, 27  $\frac{1}{4}$  and  
35.  
Land sloping to the north  
Soil mostly second rate.

East on a random line between sections 26 and 35

Var.  $14^{\circ}05'$  east

- 40.00 Set temporary  $\frac{1}{4}$  section corner.

T. 5 N., R. 9 W., S.S.M.

47.00 Cross dry arroyo 25 lks. wide, course north.

50.23 Intersect the N. and S. line 50 lks. E. of corner of sections 25, 26, 35 and 36.

From which I run

West on a true line between sections 26 and 35

Var.  $13^{\circ}47'$  East

40.11 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions.

50.23 To corner of sections 26, 27, 34 and 35.

Land sloping to the NW

Soil for the most part second rate.

North between sections 33 and 34

Var.  $14^{\circ}05'$  East

34.00 Cross road course W.

40.00 Drive  $\frac{1}{2}$  section post and charred stake and dig trench as per instructions

From which bears a

Spanish Bayonet 6 in. dia. N.  $15^{\circ}$  E., 70 lks.

50.00 Drive section post and charred stake and dug trench and pits as per instructions, corner of sections 27, 28, 33 and 34.

From which bears a spanish bayonet 11 in. dia. N.  $13^{\circ}$  E. 53 lks.

Spanish Bayonet 12 in. dia. N.  $29^{\circ}$  W.

Land sloping to the north.

Soil second rate but stoney

East on random line between sections 27 and 34

Var.  $14^{\circ}05'$  East

40.00 Set temporary  $\frac{1}{2}$  section post.

50.11 Intersect the N. and S. line 72 lks. E. of corner of sections 26, 27, 34 and 35

From which I run

T. 5 N., R. 9 W. S.B.M.

West on a true line between sections 27 and 34

Var. 13°37' East

- 40.05 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions.  
40.11 To corner of sections 27, 28, 33 and 34.  
Land gently sloping to the NW  
Soil second rate.

---

North between sections 32 and 33

Var. 14°05' east

- 28.50 Cross dry arroyo 30 lks. wide, course NW  
33.50 Cross wagon road west.  
40.00 Drive  $\frac{1}{2}$  section post and charred stake,  
From which bears a Spanish bayonet 5 in. dia. N. 5° W., 47 lbs.  
Spanish Bayonet 5 in. dia. S. 76° W., 54 lbs.  
50.00 Set section post and charred stake in mound with trench and pits as per instructions, corner of sections 28, 29, 32 and 33.  
Land sloping to the north.  
Soil second rate.
- 

East on a random line between sections 28 and 33

Var. 14°05' east

- 40.00 Set temporary  $\frac{1}{2}$  section corner  
79.58 Intersect the N and S. line 34 lks. E. of corner of sections 27, 28, 33 and 34.  
From which I run west on a true line between sections 28 and 33

Var. 13°52' east

- 39.79 Drive  $\frac{1}{2}$  section post and charred stake  
From which bears a

T. 5 N., R. 9 W. S.B.M.

Spanish Bayonet 13 in. dia. E. 11° W., 117 lbs.

Spanish Bayonet 10 in. dia. S. 39 $\frac{1}{2}$ ° W. 295 lbs.

79.58 The corner of sections 28, 29, 30 and 33.

Land sloping to the north.

Soil second rate

---

North between sections 31 and 32

Var. 14°05' east

1.00 Top of bank of ravine.

38.50 Top of bank of bottom land of the river to the plain

39.00 To base of same and cross wagon road, course NW

40.00 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions.

43.50 Cross dry bed of an arroyo 1 ch. wide, course NE

54.00 To dry and rocky ancient bed of the Rio Del Slano

75.00 Cross same.

80.00 Set section post and charred stake in mound with trench and pits as per instructions, corner of sections 29, 30, 31 and 32.  
First half mile inclined plain of base of high range of hills.

Land sloping to the N and W.

Soil second rate.

Last  $\frac{1}{2}$  mile rocky.

---

East on a random line between sections 29 and 32

Var. 14°05' east

4.00 To ancient and rocky bed of Rio Del Slano.

10.00 Cross same.

28.50 To bank of bottom land.

29.00 To top of same.

40.00 Set temporary  $\frac{1}{2}$  section post.

50.00 Intersect the N and S. line 9 lbs. N. of corner of sections 28, 29, 32 and 33.

From which I run

T. 5 N., R. 9 W. S.B.M.

West on a true line between sections 29 and 32

Var.  $14^{\circ}04'$  east

- 40.40 Set  $\frac{1}{2}$  section post and charred stake in mound with trench and pits as per instructions.
- 50.50 To corner of sections 29, 30, 31 and 32.  
First  $\frac{1}{2}$  mile sloping to the N. and W.  
Soil second rate.  
Last  $\frac{1}{2}$  mile mostly level and rocky.

West on a random line between sections 30 and 31.

Var.  $14^{\circ}05'$  east

- 20.50 To winter bed of Rio Del Slano.  
26.00 Cross same and rocky, course NE  
37.50 Cross a rapid stream of water some 9 in. deep, 15 lks.  
wide, course NW  
46.00 Set temporary  $\frac{1}{2}$  section corner.  
60.00 Leave bottom land for the inclined plain to the NE of  
the base of high hills on the south.  
75.55 Intersect the west boundary of Tp. 175 lks. S. of corner  
of sections 25, 30, 31 and 36.  
From which I run

East on a true line between sections 30 and 31

Var.  $12^{\circ}53'$  east

- 75.55 Drive  $\frac{1}{2}$  section post and charred stake  
From which bears a cedar 5 in. dia. S.  $33\frac{1}{2}$  E., 43 lks.  
Cedar 5 in. dia. N.  $29^{\circ}$  E., 67 lks.  
75.55 To corner of sections 29, 30, 31 and 32.  
Mostly in rocky bottom land unfit for cultivation.

By

Henry Hancock,

1855.

T. 4 N., R. 9 W. S.B.M.

From the corner of sections 3, 4, 33 and 34

South between sections 3 and 4

Var. 14°08' east

- 36.00 To bluff of canada ranging NW  
Set  $\frac{1}{2}$  section post and charred stake on E. side of canada,  
From which bears a spanish bayonet 7 in. dia. S. 13° E., 60 lbs.  
Spanish bayonet 7 in. dia. W. 132 lbs.  
Cross canada and dry arroyo 2 shs. wide, course NW and to  
base of range of hills.  
Cross mouth of dry arroyo 12 lks. wide, course NE  
To top of NE slope of spur ascend 100 ft.  
Cross ravine 20 lks. wide, course NE and descend 60 ft.  
To top of NE slope of spur ascend 120 ft.  
Into ravine 50 lks. wide, to NE  
Set section post and charred stake and dig trench as  
per instructions corner to sections 3, 4, 9 and 10  
From which bears a  
Cedar 10 in. dia. N. 1° E. 75 lbs.  
First  $\frac{1}{2}$  mile sloping to the E.  
Last  $\frac{1}{2}$  mile rough, third rate soil.

North between sections 3 and 9.

Var. 14° 08' East

- 50.00 Set section post and charred stakes in ground with trench  
and pits as per instructions corner of sections 4, 5, 8 and 9  
First half mile level land.  
Soil apparently first rate but rocky.  
Last half mile soil second rate.

East on a random line between sections 4 and 9

Var. 14°08' East

T. 4 N., R. 9 W. S.B.M.

- 9.00 To crest of range of hills, course S.  $80^{\circ}$  E.  
40.00 Set temporary & section corner.  
72.00 Center of ravine 5 chs. from bluff to bluff, course NE  
75.50 Cross another ravine, 3 chs. from bluff to bluff, course NE  
80.17 Intersect the N and S line 72 lks. S. of corner of sections  
3, 4, 9 and 10.  
From which I run  
West on a true line between sections 4 and 9

Var.  $14^{\circ} 39'$  East

- 40.00 Set & section post and charred stake in mound (deposit  
only 5 in. for rocky with trench and pits as per instructions)  
80.17 The corner to sections 4, 5, 8 and 9.  
This mile is hilly - partly on N. slope of crest of  
range of hills.  
Soil disintegrated granite.  
Tolerable pasture of bunchgrass.  
Timber scattering Cedar.

---

North on a random line between sections 4 and 5

Var.  $14^{\circ} 08'$  E.

- 40.00 Set temporary & section corner.  
80.36 Intersect the north boundary 47 lks. E. of corner of  
sections 4, 5, 32 and 33.  
From which I run  
South on a true line between sections 4 and 5

Var.  $14^{\circ} 28'$  E.

- 40.36 Set & section post and charred stake (only 12 in. for rock)  
From which bears a cedar 5 in. dia. N.  $85^{\circ}$  E., 70 lks.  
Cedar 4 in. dia. S.  $32^{\circ}$  W., 74 lks.

- 80.36 To corner of sections 4, 5, 8 and 9.

T. 4 N., R. 9 W. S.B.M.

North face of range of hills partly ascent 400 ft.

Soil disintegrated granite

Tolerable pasture.

Timber scattering cedar.

---

North between sections 7 and 8

Var. 14°05' E.

- 50.00 Set section post and charred stake and dug trench as per instructions, corner of sections 5, 6, 7 and 8  
From which bears a cedar 6 in. dia. H. 34 $\frac{1}{2}$  ft., 58 lbs.  
Alternate patches of arable land and rocky ridges.  
From this corner  
Peak A. bears S. 23 $\frac{1}{2}$ ° E.  
Peak B. bears S. 13° E. and  
Peak C. bears S. 3 W.
- 

East on a random line between sections 5 and 8

Var. 14°05' E.

- 40.00 Set temporary  $\frac{1}{4}$  section  
50.35 Intersect the N and S. line at post corner of sections 4, 5, 6 & 8.  
From which I run west on a true line between sections 5 and 8  
var. 14°05' E.  
40.17 Set  $\frac{1}{4}$  section post and charred stake and dug trench as per instructions  
From which bears a cedar 6 in. dia. H. 59 $\frac{1}{2}$  ft., 61 lbs.  
The corner to sections 5, 6, 7 and 8.  
Broken land being principally on S. face of range of hills.  
Soil second rate generally.

T. 4 N., R. 9 W. S.B.M.

West on a random line between sections 6 and 7

Var. 14°08' E.

- 15.50 To bottom land of river, course NW  
37.00 Cross Rio Del Slamo 25 lks. wide, course NW  
40.00 Set temporary & section corner.  
41.00 Cross river bottom and to base of hills  
51.00 To plain (undulating) ascend 150 ft.  
65.50 Cross undulating plain and to bluff of valley on the W.  
73.50 Cross ravine 1 ch. wide, course NE  
79.00 To base of hills and in valley.  
81.10 Intersect the West boundary 309 lks. S. of corner of  
sections 1, 6, 7 and 12.

From which I run east on a true line between sections 6 and 7

Var. 11°56' E.

- 41.10 Set & section post and charred stake in mound with trench  
and pits as per instructions  
81.10 To corner of sections 5, 6, 7 and 8  
Broken land.  
Soil principally second rate.  
In bottom first rate.

North on a random line between sections 5 and 6

Var. 14°08' E.

- 33.00 To summit of range of hills ascend 40 ft.  
40.00 Set temporary & section corner.  
81.26 Intersect the north boundary 41 lks. east of corner of  
sections 1, 6, 31 and 36.

From which corner I run south on a true line between sections 5 and 6

Var. 14°26' E.

- 41.26 Set & section post and charred stake in a rock mound 4 ft. ~~4 ft.~~  
at base and 30 in. high.

81.26 To corner of sections 5, 6, 7 and 8.

Land hilly.

Soil principally second rate.

Timber scattering cedar.

---

By Henry Hancock,

1855

---

N. 0801° W. between sections 11 and 12.

60.00 Set a sycamore post 3 ft. long, 4 in. sq., 24 in. in the ground for corner of sections 1, 2, 11 and 12, marked

T. 4 N., S. 1 on NE

R. 9 W., S. 12 on SE

S. 11 on SW and

S. 2 on NW faces

with 5 notches on the south and 1 notch on the east edges

From which bears a Juniper 12 in. dia. S. 52°00' W. 97 lks.

Raised mound of rocks 3 ft. base, 1½ ft. high W. of corner.

Land mountainous and sloping.

Soil sandy and third rate.

No timber.

Mountainous land and dense undergrowth 54.00 chs.

---

East on a line between sections 1 and 2

40.00 Set temporary § section corner.

79.95 Intersect the east boundary of Tp. 7.10 chs. S. 0°03' E.  
of the corner to sections 1, 2, 6 and 7.

I remove all reference to sections 1 and 12 from old  
corner and set a sycamore post 3 ft. long, 4 in. sq.,  
with marked stone 24 in. in the ground for C.C. to sections 1 and 2  
marked

C.C. T. 4 N., R. 9 W on W.

S. 1 on N. and

T. 4 N., R. 9 W. S.S.M.

S. 12 on S. faces

with 5 groves on S. and 1 grove on N. face and raised  
mound of rock 3 ft. base 2 ft. high N. of corner.

Thence I run

West on a true line between sections 1 and 12.

Descend through dense growth of Juniper

14.50 Cross Dead Man's canon N. and ascend.

39.97 $\frac{1}{2}$  Set a sycamore post 3 ft. long, 3 in. sq. with marked  
stone 24 in. in the ground for  $\frac{1}{4}$  section corner between  
sections 1 and 12, marked

$\frac{1}{4}$  S. on N. and

$\frac{1}{4}$  S. on S. faces

Dig pits 16x16x12 in. E. and W. and 4 ft. dist.

Raised mound of earth  $3\frac{1}{2}$  ft. base  $1\frac{1}{2}$  ft. high N. of corner.

57.80 Road in dry wash, course N and S and ascend

79.95 Corner of sections 1, 2, 11 and 12.

Land mountainous.

Soil gravelly and sandy, third rate.

No timber.

Mountainous land and dense growth 79.95 obs.

---

N. 0°01' W. on a random line between sections 1 and 2

40.00 Set temporary  $\frac{1}{4}$  section corner.

67.43 Intersect the north boundary of Tp. 29 like. E. of corner  
to sections 1 and 2, a juniper post, witnessed as  
described by the surveyor general

Thence I run

S. 0° 12' E. on a true line between sections 1 and 2

Ascend along steep slope

47.43 Set a juniper post 3 ft. long, 3 in. sq., with a marked  
stone 24 in. in the ground for  $\frac{1}{4}$  section corner between  
sections 1 and 2, marked  $\frac{1}{4}$  S. 1 on E. and  $\frac{1}{4}$  S. 2 on W. faces

T. 4 N., R. 9 W., S.B.M.

and raised mound of earth and stone  $\frac{3}{4}$  ft. base and  
 $1\frac{1}{2}$  ft. high W. of corner.

Thence through undergrowth of juniper.

87.43 To corner of sections 1, 2, 11 and 12.

Land mountainous and sloping.

Soil gravelly fourth rate.

No timber.

Mountainous land and dense growth 40.00 chs.

---

N.  $0^{\circ}01'$  W. between sections 10 and 11

89.00 Set a sycamore post 3 ft. long, 4 in. sq. 24 in. in the ground  
for corner to sections 2, 3, 10 and 11, marked

T. 4 N., S. 2 on NE

R. 9 W., S. 11 on SE

S. 10 on SW and

S. 3 on NW faces

with 5 notches on the south and 2 notches on the east edges,

From which bears a juniper 10 in. dia. S.  $41^{\circ}$  E., 59 lbs.

Marked T. 4 N., R. 9 W., S. 11 S.T.

Juniper 6 in. dia. N.  $75^{\circ}$  W., 69 lbs.

Marked T. 4 N., R. 9 W., S. 3 S.T.

Dig pits 15x15x12 in. in each section  $\frac{5}{8}$  ft. dist.

and raised mound of earth 4 ft. base 2 ft. high W. of corner.

Land mountainous and sloping.

Soil gravelly and fourth rate.

Mountainous land 46.50 chains.

---

East on a random line between sections 2 and 11

89.00 Set temporary § section corner.

89.05 Intercept the N and S line 5 lbs. E. of corner of sections 1, 2, 11 and  
12,

T. 4 N., R. 9 W. S.B.M.

Thence I run

N.  $59^{\circ}55'$  W. on a true line between sections 2 and 11

From N. slope of hill covered with a dense growth of juniper

20.00 Ravine 1 ch. wide, course N.

40.00 Set a sycamore post 3 ft. long, 3 in. sq., with mound of stone 24 in. in the ground for  $\frac{1}{4}$  section corner between sections 2 and 11 marked

$\frac{1}{4}$  S. 2 on N. end

$\frac{1}{4}$  S. 11 on S. faces

raised mound of rocks 3 ft. base 2 ft. high N. of corner.

41.00 Ravine 50 lds. wide, course N.

78.00 Ravine 1 ch. wide, course N.

60.05 The corner of sections 2, 3, 10 and 11.

Land mountainous.

Soil gravelly fourth rate.

Mountainous land and dense growth go.05

---

West on blank line between sections 3 and 10.

40.00 Set temporary  $\frac{1}{4}$  section corner.

50.30 Intersect the N and S. line S. 56 one. S. go old corner of sections 1, 4, 9 and 10, I re-moved all marks referring to sections 3 and 10, from old corner and set a juniper post 3 ft. long,  $4\frac{1}{2}$  in. sq., with marked stone 24 in. in the ground for C. C. to sections 3 and 10 marked

C.C. T. 4 N., R. 9 W. on E.

S. 3 on N. end

S. 10 on S. face

with 5 grooves on S. and 3 grooves on E. face and raised mound of rock E. of corner.

Thence I run

East on a true line between sections 3 and 10.

Descending.

19.00

Road in ravine 50 lds. wide, course N.  $20^{\circ}$  W. and ascend

T. 4 N., R. 9 W. S.B.M.

steep hill side.

- 40.15 Set a sycamore post 3 ft. long 4 in. sq., 24 in. in the ground for  $\frac{1}{4}$  section corner between sections 3 and 10 marked  $\frac{1}{4}$  S. 3 on N. and  $\frac{1}{4}$  S. 10 on S. faces  
From which bears a juniper 5 in. dia. N.  $74^{\circ}$  E., 50 lks.  
marked  $\frac{1}{4}$  S.B.T.  
Dug pits 15x15x12 in. E. and W. of corner 4 ft. distant and raised mound of earth  $3\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high north of corner.
- 45.00 Summit of ridge bears N.  $80^{\circ}$  W. and S.  $80^{\circ}$  E. and along N. slope covered with a dense growth of juniper.
- 66.00 Ravine 1 ch. wide, course N.
- 58.30 To the corner of sections 2, 3, 10 and 11.  
Land mountainous.  
Soil rocky fourth rate.  
No timber.  
Mountainous land 50.30 chs.

---

N.  $0^{\circ}01'$  W. on a random line between sections 2 and 3

Descend.

- 40.00 Set temporary  $\frac{1}{4}$  section
- 50.43 Intersect the north boundary of Tp. 36 lks. E. of corner to sections 2 and 3, a juniper post marked and witnessed as described by the Surveyor General  
Thence I run S.  $0^{\circ}15'$  E. on a true line between sections 2 and 3  
Ascending and through dense undergrowth of Juniper
- 40  
45.43 Set a sycamore 3 ft. long, 4 in. sq., with marked stone 24 in. in the ground for  $\frac{1}{4}$  section corner between sections 2 and 3, marked  $\frac{1}{4}$  S. 2 on E. and  $\frac{1}{4}$  S. 3 on W. faces

T. 4 N., R. 9 W. S.B.M.

and raised mound of stone 3 ft. base 2 ft. high W. of corner.

50.43 The corner of sections 2, 3, 10 and 11.

Land mountainous.

Soil gravelly fourth rate.

No timber.

Mountainous land and dense growth 50.43 obs.

By

LeGrand Friel,

1900