

T. 2 S., R. 11 W., S.B.M.

Surveyed by Henry Hancock
Contract of 1853.
Book 167 Part 2.

(W.B.T. 2S., R. 10 W.)

South on West bdy. of Sec 7.

80.00 Set sec. post & charred stake in mound cor. of secs. 7 & 18.
Soil of last $\frac{3}{4}$ mile 2nd. rate.

On west boundary of sec. 18.

20.00 Base of point.

24.00 Top of slope to east.

32.00 Trail S. 45°W.

40.00 Set $\frac{1}{4}$ sec. post & charred stake in mound.

South on west boundary of sec. 18.

80.00 Set sec. post & charred stake in mound cor. of secs. 18 & 19.

Soil 2nd rate.

On west boundary of sec. 19.

40.00 Set $\frac{1}{4}$ sec. post & charred stake in mound.

43.00 Dry gulch S 7°E.

55.00 Mountain base.

64.00 Top of point.

72.00 Top of ridge.

74.50 Ravine at right angles

78.50 E. slope of spur.

80.00 Set sec. post & charred stake in mound cor. of secs. 19 & 30.

Soil 2nd. rate.

South Bdy. T 1 S., R 11 W.

West

On south bdy. of sec. 35.

80.00 Set sec. post & charred stake in mound cor. of secs. 34, 35,
3, 2.

Broken prairie of 2nd. rate soil.

S.B. T. 1 S., R. 11 W., S.B.M.

On south bdy. of sec. 34.

28.46 Road to Los Angeles, S.W.

40.00 Set $\frac{1}{4}$ sec. post & charred stake in mound.

45.06 Bluff of Riv. bottom.

46.00 Bottom of Riv. San Gabriel.

80.00 Drove sec. post & charred stake from which bears

A willow 12 in. diam. S $17\frac{1}{2}^{\circ}$ E. 66 links dist. do do

N $18\frac{1}{2}^{\circ}$ 6 in. diam.

A sycamore S 41° W. 5 in. diam. 170 links dist. also

A cottonwood 12 in. diam. N $78\frac{1}{2}^{\circ}$ W. 218 L. dist. cor. of

secs. 34, 33, & 3 & 4.

T. 2 S., R. 11 W., S.B.M. Surveyed by Henry Janson
Contract of 1868
Book 240 Part 17.
North bet. secs. 25 and 26. Variation 14° East.

- 80.00 Set a cement rock 8 X 10 X 14 in for cor. to secs. 23, 24,
26 and 25 as per instructions.
Land hilly.
Soil 2nd. rate. -----
East on a random line bet. secs. 24 and 25.
Variation 14° East.
- 36.00 Enter ravine 2 chs. wide.
- 40.00 Set a rock for temp. quarter section corner.
- 41.00 Leave ravine S 75° W.
- 50.00 Across a prickly pear patch 100 lks. in diameter.
- 80.00 Intersect the east boundary of the township but after
diligent search being unable to find the original mound
I replace it with the corner with a sandstone 6 X 10 X 14 in.
for corner to sections 24, 19, 25 and 30 and run West
on true line bet. secs. 24 and 25.

Variation 14° East.

- 40.00 Set granite rock 8 X 12 X 14 in. as per instructions on
south side of ravine for a quarter section corner.
- 80.00 To corner to sections 23, 24, 26 and 25.
Land rough and hilly.
Soil 2nd. rate. -----

North bet. secs. 23 and 24.

Variation 14° East.

- 29.00 Across ravine 1 chain wide course S.W.
- 40.00 Set sandstone rock 10 X 12 X 14 in. for a quarter sec.
corner as per instructions.
- 71.25 Enter ravine course S.W.
- 73.50 Leave same.
- 80.00 Set a sandstone rock 5 X 12 X 15 in. as per instructions on
north slope of hills for corner to sections 14, 13, 23, 24.
Land rough and hilly.
Soil 2nd. rate. -----

East, bet. secs. 13 and 24 on true line.

Variation 14° East.

- 9.90 To forks of a ravine 1 chain wide course southeasterly.
12.86 Intersect tht traverse line of the south boundary of the
Rancho La Puente and set a granite rock 4 x 12 x 18 in.
as per instructions at point of intersection.

North between sections 13 and 14.

Variation 14° East.

- 5.59 Set a granite rock 5 x 8 x 14 in. at intersection of the
traverse line of the Southern boundary of the previously
surveyed Rancho of La Puente as per instructions.

January 30, 1868.

North between sections 22 and 23.

Variation 14° East.

- 80.00 Set a sandstone rock 8 x 8 x 8 in. for cor. to secs. 15, 14,
22 and 23 per instructions.
Land rough and hilly.
Soil 2nd. rate.

East on a random line bet. secs. 14 and 23.

Variation 14° East.

- 27.00 Cross ravine 1 chain wide course S.W.
40.00 Set sandstone rock for temp. quarter section corner.
80.67 Intersect N. and S. line 43 lks. north of cor. to secs.
14, 13, 23 and 24, from which I run
N. 89° 42' W. on a true line bet. secs. 14 and 23.

40.33 Set a sandstone rock 4 x 10 x 13 in. for a quarter section
corner as per instructions.
80.67 To corner to sections 14, 15, 22, 23.
Land rough and hilly.
Soil principally second rate.

January 31, 1868.

T. 2 S., R. 11 W., S.B.M.

North bet. secs. 14 and 15.

Variation 14° East.

35.50 Across ravine 2 chs. wide, course S. 85° W.

40.00 Set a sandstone rock 6 x 7 x 18 in. for a quarter section corner as per instructions, 40 lks. south of a sandstone rock 10 ft. high.

79.98 Intersect the traverse of the Southern boundary of the Rancho La Puente and set a sandstone rock 6 x 10 x 15 in. as per instructions at intersection.

North bet. secs. 15 and 16.

Variation 14° East.

80.00 Set a sandstone rock 7 x 9 x 20 in. as per instructions for corner to sections 9, 10, 16, 15.

Land broken and hilly. Soil third rate.

East on a true line bet. secs. 10 and 15.

Variation 14° East.

16.00 Across ravine 50 lks wide course north.

40.00 Set granite rock 8 x 10 x 12 in. for quarter section corner as per instructions.

78.00 Ravine 50 lks. wide course north.

79.50 Intersect the traverse line of the south boundary of the Rancho of La Puente and set a sandstone rock 8 x 12 x 18 in. as per instructions, at intersection.

Land hilly.

Soil third rate.

February 1.

North bet. secs. 9 and 10.

Variation 14° East.

1.75 Across ravine 50 lks. wide course S. W.

13.00 Across ravine 50 lks. wide course East, and to a perpendicular ledge of sandstone 30 ft. high, course east.

40.00 Set sandstone rock 8 x 8 x 14 in. for quarter sec. cor. as per instructions.

51.80 Across a gully 40 lks. wide course west.

80.00 Set sandstone rock 5 X 7 X 14 in. for corner to sections
4, 3, 9, and 10, as per instructions.

Land rough and hilly.

Soil third rate.

East on true line bet. secs. 3 and 10.

Variation 14° East.

24.81 Intersect the traverse of the south bdy. of the Rancho
La Puente and set a sandstone 6 X 14 X 16 in. at point of
intersection N. $55\frac{1}{4}^\circ$ W. 10.00 chs. from Station number 13 of
the said rancho.

North on a true line bet. secs. 3 and 4.

Variation 14° East.

17.21 Set a sandstone rock 6 X 8 X 18 in. at intersection of the
traverse line of the south boundary of the Rancho La Puente.

Final survey of the Rancho La Puente. Surveyed by Henry H. ...
 Contract of 1857
 Book D Part 2.

N. $19\frac{1}{4}^{\circ}$ E. 37.50 Across a dry arroyo 12 lks. wide in ravine on
 the S. face of hills covered with a thick growth
 of walnut, course of the ravine south 80° west.

63.50 Across road for Carritas hauling wood,
 course N. 70° W.

65.00 To summit of hills, ranging N. 70° W.

121.00 To station No. 23 and set a post with charred
 stake in mound with pits as per instructions
 from which a willow 10 ins. diam. bears N. 69° E.
 distant 12.43 chs.;

Thence

N. $80\frac{1}{2}^{\circ}$ W. 166.00 To station No. 24 and set a post and charred
 stake in mound.

N. $66\frac{3}{4}^{\circ}$ W. 129.75 Intersected the west bdy. township No. 2,
 south of the base line of range No. 10 west of
 the San Bernardino Meridian 28.25 chs. south of
 corner to secs. 18, 19, 13 and 24, and drove a
 stake at the point of intersection.

26.00 To station No. 25, and drove a stake and
 charred stake in mound.

N. 34° W. 160.00 To station No. 26, and set post in mound ;
 Thence

N. $55\frac{1}{4}^{\circ}$ W. 63.00 Leave hills and to a point opposite the dam
 on the San Jose Creek agreed upon as a point
 in line between the Ranchos La Puente and San
 Bartole and set a rock 2 ft. long 15 ins. wide
 and 12 ins. thick on line.

64.00 Across San Jose Creek at dam or toma 14 lks.
 wide, course ^{S.} 65° west.

105.50 To left bank of the River Gabriel and set
 rock 14 ins. long 10 ins. wide and 8 ins. thick
 on line for witness to Sta. 27.

107.00 To Sta. No. 27 in center of River San Gabriel.