

FIELD NOTES.

T. 1 N., R. 9 W., S. B. M.

E.B. Sections 5, 6.  
N.B. " 5, 6.

also

T. 2 N., R. 9 W.

E.B. Sections 29, 31, 32.  
N.B. " 28, 29, 32.

Copied from notes loaned by Mr. L. Friel.

R. 9 W.

	19	20	21	22
		5	5	
	30	29	4	28
		4	4	
	31	4	32	33
T. 2 N.	1	2		
T. 1 N.	2	2		
	6	1	3	5
		1	3	4
	7	3	8	3
			9	10

NORWAY 1875  
PEARSON 1884

SUBDIVISIONS.

EAST between Sections 6 and 7, from  $\frac{1}{4}$  section corner.  
Var.  $14\frac{1}{4}^{\circ}$  E.

40.00 Set a sycamore post 4 x 4 ins. 3 ft. long, in mound of rocks on steep side hill facing west, as per instructions, for corner to Sections 5, 6, 7 and 8.  
Land 2nd and 3rd rate.  
Timber, Live oak, Sycamore and Cottonwood.  
The land is too rough to run North or East, from this point I run WEST 20.00 chains and set a sycamore post 3 x 3 ins. 3 ft. long in mound of rocks as per instructions for  $\frac{1}{8}$  section corner, from which  
A sycamore 12 ins. dia. brs. N.  $3\frac{1}{4}^{\circ}$  E. 145 lks.

NORTH through the East  $\frac{1}{2}$  of Section from  $\frac{1}{8}$  corner on line.  
Var.  $14\frac{1}{4}^{\circ}$  E.

5.50 Leave valley and ascend point of hill.  
21.50 Leave hill and enter valley, course E & W.  
31.00 Leave valley and ascend.  
40.00 Set oak post 3 x 3 ins.  $3\frac{1}{2}$  ft. long in mound of rock on side hill facing NE. as per instructions for  $\frac{1}{8}$  corner. Thence

EAST on  $\frac{1}{4}$  section corner in Section 6. Var.  $14\frac{1}{4}^{\circ}$  E.

14.00 Leave hill and enter river bottom, course NW & SE.  
20.00 Set sycamore post 3 x 3 ins. 3 ft. long, in mound of rocks on right bank of San Gabriel River, as per instructions for  $\frac{1}{4}$  section corner between Sections 5 and 6. From which bears a  
Sycamore 24 ins. dia. S.  $85^{\circ}$  W. 2.13 chs.  
Live Oak 24 ins. dia. N.  $15\frac{1}{2}^{\circ}$  W. 2.13 chs.  
Land rough.  
Timber, oak, sycamore and cottonwood.

NORTH between Sections 5 and 6, from  $\frac{1}{4}$  section corner.  
Var.  $14\frac{1}{4}^{\circ}$  E.

13.00 Cross San Gabriel River 50 lks. wide, course SE.  
15.00 Leave valley and ascend.  
40.00 Set an oak post 4 x 4 ins.  $3\frac{1}{2}$  ft. long in mound of rocks as per instructions for corner to Sections 5, 6, 31 and 32, on North boundary of township.  
Land rough, timber scattering sycamore and cottonwood.

In order to establish the corner to Townships 1 and 2 North, Ranges 9 and 10 West, I run

WEST on North boundary of Section 6.

28.00 Enter valley of San Gabriel River, course N & SE.  
35.50 San Gabriel River 50 lks. wide, course SE.  
37.00 To the foot of large rocky bluff, finding it impracticable to run further on this line or get back to the range line, I set a sycamore post 4 x 4 ins. 3 ft. long, in mound of rocks as per instructions for witness to  $\frac{1}{4}$  section corner. From which an  
Alder tree 6 ins. dia. brs. N.  $46^{\circ}$  E. 27 lks.  
Land rough, 2nd rate.  
Timber, oak, sycamore, alder and cottonwood, scattering.

(Above notes rearranged in copying) November 26, 1875.  
(County Surveyor's Office, March 12, 1917).

From the corner to Sections 31, 32, 5 and 6, on South boundary of Township, I run

EAST on South boundary of Section 32. Var.  $14\frac{1}{4}^{\circ}$  E.

- 40.00 Along on the North slope of mountain.  
Set a Redwood post 3 x 3 ins. 3 ft. long, in a mound of rocks as per instructions for  $\frac{1}{4}$  section corner.
- 80.00 Set an Oak post 4 x 4 ins.  $3\frac{1}{2}$  ft. long in a mound of rocks on side hill sloping NW. as per instructions for corner to Sections 4, 5, 32 and 33.  
Land along the north slope of mountainous gulch with low brush and scattering oak timber.

W. H. Norway, 1875.

-----

The corner to Sections 6 and 5 on the North boundary of the Township having been established by the old survey, I commence at the established corner to Tps. land 2 North, Ranges 9 and 10 West, (granite stone 16 x 12 x 9 ins. marked with 6 notches on the N, S, E and W edges, with mound of stone alongside) and run

EAST on a RANDOM line between Sections 31 and 6, Retracing 37 chs.

Var.  $14^{\circ} 28'$  E.

- 40.00 Set temp.  $\frac{1}{4}$  sec. corner.
- 43.00 Unable to find witness corner (after diligent search) I continue East and at
- 80.00 To a point 25 lks. South of the corner to Secs. 5, 6, 31 and 32, Tps. 1 and 2 N., R. 9 W., which is a part of decayed post in mound of rocks, I rebuild corner by setting sand stone 15 x 11 x 7 ins. 10 ins. in the ground for corner to Sections 5, 6, 31 and 32, marked with 1 notch on West and 5 notches on the East edges and rebuilt mound of rocks alongside. Pits impracticable.  
Thence I run

S.  $89^{\circ} 49'$  W; on a TRUE line between Secs. 6 and 31, same variation.

Descend.

- 26.50 Enter San Gabriel Canyon, course SE.
- 31.00 San Gabriel River 60 lks. wide, course SE.
- 38.00 Leave canyon and ascend.
- 40.00 Set granite stone 12 x 11 x 5 ins. 7 ins. in the ground for  $\frac{1}{4}$  sec. corner marked  $\frac{1}{4}$  S on N. face and raised mound of stone alongside.  
Pits impracticable.
- 44.00 Top of spur bears E and descend.
- 69.00 Ravine 60 lks. wide course SE. and ascend.
- 80.21 The corner to Sections 1, 6, 31 and 36, Tps. 1 and 2 N., Rs. 9 & 10 W.  
Land mountainous. Soil 2nd rate.  
Timber, Pine and Oak in ravines. Dense undergrowth of chaparral.

-----

From the established corner to Sections 5, 6, 31 and 32, Tps. 1 and 2 N., R. 9 W., I run

EAST on a TRUE line between Sections 5 and 32, retracing.

Var.  $14^{\circ} 28'$  E.

- 40.00 Ascend gradually along north slope of mountain.  
To old  $\frac{1}{4}$  sec. cor. which is part of decayed post in mound of rocks, I rebuild cor. by setting sandstone 16 x 11 x 5 ins. 11 ins. in the ground for  $\frac{1}{4}$  sec. cor. marked  $\frac{1}{4}$  on N. face and raised a mound of stone alongside. Pits impracticable.
- 80.30 The corner to Sections 4, 5, 32 and 33, Tps. 1 and 2 N., R. 9 W., which is a greatly decayed post with marks nearly obliterated, in stone mound partly destroyed. I rebuild corner by setting a sandstone

18 x 12 x 9 ins. 13 ins. in the ground for corner to Secs, 4, 5, 32 and 33, marked with 2 notches on the West and 4 notches on the East edges and rebuild mound alongside.  
Land mountainous. Soil 3rd rate.  
Timber, none. Dense undergrowth of chaparral.

George W. Pearson, 1884.

RE-SURVEY.

NORTH between Secs. 8 and 9. Var. 14°27' E.

80.00 Set granite rock 13 x 12 x 10 ins. 8 ins. in the ground for corner to Sections 4, 5, 8 and 9, marked with 5 notches on the South and 4 notches on the East edges and raised a mound of stone alongside.  
Pits impracticable. Land mountainous. Soil 2nd and 3rd rate.  
Timber, scattering pine and oak in Canada.  
Dense undergrowth of Chamisal.

NORTH on a RANDOM line between Secs. 4 and 5. Var. 14°27' E.

40.00 Set temp.  $\frac{1}{4}$  sec. corner.  
80.32 Intersect the North boundary of Tp. 40 lks. west of corner to Secs. 4, 5, 32 and 33. Thence I run S. 0°17' W. on a TRUE line between Secs. 4 and 5. Same variations.

40.32 Ascend.  
Set granite rock 15 x 12 x 10 ins. 10 ins. in the ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  S. on W. face and raised mound of stone alongside.  
Pits impracticable.  
46.50 Summit of ridge bears N. 15° E. and S. 15° W. and descend.  
80.32 The corner to Sections 4, 5, 8 and 9.  
Land mountainous. Soil 3rd rate.  
Timber, scattering pine and oak. Dense undergrowth of chaparral.  
March 27, 1884.

NORTH between Sections 7 and 8. Var. 14° 27' E.

80.00 After diligent search being unable to find old corner, I set sandstone 24 x 13 x 5 ins. 19 ins. in the ground for corner to Sections 5, 6, 7 and 8, marked with 5 notches on the S. and E. edges and raised mound of stone alongside. Pits impracticable.  
Land mountainous. Soil 3rd rate.  
Timber, pine and oak in ragine. Dense undergrowth of chaparral.

NORTH on a RANDOM line between Secs. 5 and 6. Retracing 40 chs. Var. 14°27' E.

40.00 After diligent search being unable to find corner I set temp.  $\frac{1}{4}$  sec. corner.  
79.78 Intersect the North boundary of Tp. 37 lks. east of corner to secs. 5, 6, 31 and 32. Thence I run S. 0°16' E. on a TRUE line between Secs. 5 and 6. Same variations.

25.00 Descend.  
Enter San Gabriel Canyon, course SE.  
31.00 San Gabriel River 80 lks. wide, course SE.  
39.78 Set granite stone 16 x 14 x 6 ins. 13 ins. in the ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  S on W. face and raised mound of stone alongside.  
Pits impracticable.  
48.00 San Gabriel River 80 lks. wide, course SW.  
50.00 Leave canyon, course SW. and ascend.  
79.78 The corner to Secs. 5, 6, 7 and 8.

Land mountainous. Soil 1st and 3rd rate.  
Timber, pine and oak in canyon.

George Pearson, 1884.

-----  
SUBDIVISIONS

T 2 N. R 9 W. S. B. M.

NORTH between Secs. 31 and 32.

Var.  $14\frac{1}{4}^{\circ}$  E.

Descend.

11.50 Leave hills and enter valley of San Gabriel, course SW & NE.  
27.50 To San Gabriel River 75 lks. wide, course SW.  
34.00 Leave valley of San Gabriel and ascend NE & SW.  
40.00 Set redwood post 3 x 3 ins. 3 ft. long in a mound of rocks as  
per instructions for  $\frac{1}{4}$  sec. corner.  
Ascend along on South slope of mountain.  
80.00 Set an Oak post 4 x 4 ins. 3 ft. long, in a mound of rocks as per  
instructions on side hill facing NE. for corner to Sections 29, 30,  
31 and 32.  
Land very rough.  
Mineral placer, Scattering Oak, Sycamore and Alder in river bottom.

-----  
EAST on a true line between Sections 29 and 32.

Var.  $14\frac{1}{2}^{\circ}$  E.

5.50 Cross gulch 25 lks. wide, course SE. and ascend. Over foot hill.  
14.50 Summit of hill thence descend.  
24.00 Leave hills enter valley of San Gabriel, course N & S.  
33.00 To waters of San Gabriel 73 lks. wide, course SW.  
40.00 Set an alder in mound of rocks as per instructions for  $\frac{1}{4}$  sec. corner.  
From which an  
Alder 6 ins. dia. brs. S.  $70^{\circ}$  W., 08 lks. dist.  
Alder 10 ins. dia. brs. N.  $59^{\circ}$  W., 14 lks. dist.  
Station No. 1 of the NE. corner of Justice Placer Mining Claim brs.  
S. 10 chs. dist.  
50.50 Leave San Gabriel Valley and ascend, course NE & S.  
75.30 Summit of spur course SW & NE and descend.  
80.00 Set granite stone 10 x 16 x 24 ins. in a mound of rocks as per in-  
structions for corner to Sections 28, 29, 32 and 33.

-----  
As the line between Sections 32 and 33 can be run part way South,  
I run

SOUTH between Sections 32 and 33.

Var.  $14\frac{1}{4}^{\circ}$  E.

11.50 Cross gulch 25 lks. wide, course N.  $80^{\circ}$  W.  
Thence ascending.  
40.00 Set an Oak post 3 x 3 ins. 3 ft. long, in a mound of rocks on side  
hill facing North, as per instructions for  $\frac{1}{4}$  sec. corner.  
Land rough Placer Mineral. Some timber in gulches.

-----  
From the corner to Sections 28, 29, 32 and 33 I run

NORTH between Sections 28 and 29.

Var.  $14\frac{1}{4}^{\circ}$  E.

Ascending.  
6.50 Summit of spur course NE & SW., ascending along west slope of high  
hill facing west.  
34.25 Cross gulch near head, course SW.  
40.00 Set a redwood post 3 x 3 ins. 3 ft. long, in mound of rocks on west  
slope of hill as per instructions for  $\frac{1}{4}$  sec. corner.  
70.00 Intersect the southern boundary of the Baker and Austin Placer  
Mining Claim, at corner No. 5 of said claim.

74.00 Enter valley of Canada of San Gabriel, course E & SW. an old cabin  
50 lks. east.  
80.00 Set an Alder post 4 x 4 ins. 3½ ft. long, in a large mound of rocks  
as per instructions for corner to Sections 20, 21, 28 and 29, in  
Northern boundary of Baker and Austin Placer Mine.  
Land very rough Mineral Placers with scattering timber of Oak, Alder  
and Sycamore in Canada.

December 7, 1875.

-----  
EAST on a TRUE line between Sections 21 and 28. Var. 14¼° E.

10.00 Intersect the eastern boundary of Baker and Austin Placer Mining  
Claim 5 chs. S. of corner No. 1 of said claim.  
Set an Alder post 3 x 3 ins. 3 ft. long, at point of intersection  
as per instructions for corner of fractional Sections 21 and 28.  
15.00 Corner No. 4 of Bud Placer Mining Claim 5 chs. North.  
16.50 Leave valley and ascend along north slope of mountain.  
35.00 Corner No. 1 of the Ford Placer Mining Claim 5 chs. North. Cross  
gulch 20 lks. wide course NW.  
40.00 Set a Sycamore post 3 x 3 ins. 3 ft. long, in a mound of rocks on  
side hill facing North, as per instructions, for ¼ sec. corner.  
From which an  
Oak 2 ft. dia. brs. S. 89° E. 35 lks.  
The corner No. 5 of Woodman Placer Mining Claim brs. N. 5 chs.  
Thence thru claims.  
80.00 To corner No. 1 of Woodman Placer Claim, also point for corner to  
Sections 21, 22, 27 and 28, falling on steep side hill not suitable  
place to build a monument, I set a Sycamore post 4 x 4 ins. 3½ ft.  
long, in large mound of rocks at foot of hill 2.50 chs. East, as  
per instructions for witness corner to Sections 21, 22, 27 and 28.  
From which a  
Live oak 30 ins. dia. brs. N. 29° E. 25 lks.  
Land rough Placer Mining with scattering timber of Oak, Sycamore  
and Alder.

-----  
From the corner to Sections 20, 21, 28 and 29, I run  
WEST on a TRUE line between Sections 20 and 29. Var. 14¼° E.

5.00 Cross San Gabriel River 30 lks. wide, course SW.  
8.50 Leave Canada and ascend.  
13.00 Cross gulch in Canada 100 lks. wide, course South.  
40.00 Set Sycamore post 3 x 3 ins. 3 ft. long, in mound of rocks on south  
edge of rocky bluff as per instructions for ¼ sec. corner.  
Thence descending.  
48.00 Leave hills enter Canada of the North Fork of San Gabriel River.  
50.00 Cross North Fork 40 lks. wide, course SE.  
60.00 Finding it impossible to run this line further West, I set a Syca-  
more post 3 x 3 ins. 3 ft. long, in mound of rocks at foot of mountain,  
as per instructions for 1/8 section corner. From which a  
Live Oak 20 ins. dia. brs. N. 88¼° E. 4.81 chs.

William H. Norway, 1875.

-----