

COPIED BY
A. C. JOHNSON
JULY 1942

FIELD NOTES
T 2 N, R 8 W. S. B. M.

COPIED FROM
Copies on file in
Cadastral Engineer's Office
Glendale, California
VOL. 362:3
SURVEYED BY
GEO. W. PEARSON
MARCH 1884

R 8 W

4A	6	5	4	3	2
15	15	13B	12B	11	8
14D	8	13A	12B	11	8
14C	7	13B	12B	10	7
14B	17	13A	12A	10	14
14A	20	13	12A	9	23
14	19	14A	12	9	24
14	30	14	12	9	25
13B	31	13B	11	8	35
13B	32	12B	11	8	36
1					

R 8 W

T 2 N

T 2 N

————— Grover 1884
————— Pearson 1884

T 2 N, R 8 W, S. B. M.
SOUTH BOUNDARY.

From the established corner to Tps. 1 and 2 N, Rs. 8 and 9 W. I run

Var. 14° 26' E.

I set temporary half mile and mile posts at every 40 and 80 chs. and find the Tp. line to be 6 miles, 1.47 chains long and intersect the E. boundary of the Tp. at a point 70 lks. N. of corner to Tp. 1 and 2 N. Rs. 7 and 8 W. which is a granite stone 20 x 18 x 7 ins. firmly set in the ground and marked with 6 notches on the N. S, E, and W. edges and a stone mound alongside.

The correction for the true line will therefore be 11 2/3 lks. S.

and 1.47 chs. E. per mile, Hence I run

N. 89° 55' W. on a TRUE line between sections 1 and 36.

Var. 14° 26' E.

Top of spur bears N. and descend. 40.00
Set a sandstone 12 x 10 x 9 ins. 7 ins. in the ground for 1/2 section corner, marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable.

35.50

Enter San Antonio Canyon, course South. 50.50
San Antonio Creek 12 lks. wide, course South. 53.00
Road bears N. & S. 60.00

60.00

Leave canyon, course South and ascend. 62.50

71.20

Gulch 20 lks. wide, course S. 20° W. 80.00

Set granite stone 14 x 11 x 7 ins. 9 ins. in the ground for corner to sections 1, 2, 35 and 36, marked with 5 notches on the West and 1 notch on the East edges and raised mound of stone alongside. Pits impracticable. Soil 2nd rate.

80.00

Timber Pine and Oak in canyon. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 2 and 35. Var. 14° 26' E.

Top of spur bears SW. and descend. 16.50
Gulch 30 lks. wide, course SW. and ascend. 36.50
Set sandstone 12 x 10 x 7 ins. 7 ins. in the ground for 1/2 section corner marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable.

40.00

Top of spur bears SW. and descend. 60.00
Set sandstone 15 x 12 x 6 ins. 10 ins. in the ground for corner to sections 2, 3, 34 and 35, marked with 4 notches on the West and 2 notches on the East edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate.

80.00

Timber Pine and Oak in Ravines. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 3 and 34. Var. 14° 26' E.

San Dimas Creek 9 lks. wide, course South and ascend. 20.50
Set sandstone 15 x 11 x 9 ins. 9" in the ground for 1/2 section corner marked 1/2 on North face and raised mound of stone alongside. Pits impracticable.

40.00

Set a granite stone 13 x 9 x 8 ins. 8 ins. in the ground for corner to sections 3, 4, 33 and 34, marked with 3 notches on the East and West edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber Pine and Oak in Ravines. Dense undergrowth of Chaparral.

80.00

N. 89° 55' W. between sections 4 and 33. Var. 14° 26' E.

Summit of divide bears N. 60° E. and S. 60° W. and descend. 5.00
Set a granite stone 11 x 10 x 7 ins. 6 ins. in the ground for 1/2 sec. corner, marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable.

40.00

80.00

Set sandstone 13 x 11 x 9 ins. 8 ins. in the ground for corner to

5.00 Cross gulch 11 lks. wide, course S. 60° W. ascend.
 10.00 Top of spur bears N. 88° E. and S. 88° W. and descend.
 12.00 Enter timber bears E. & W.
 33.10 Enter San Antonio Canyon, course S. 40° W.
 33.25 Cross San Antonio Creek 20 lks. wide, course S. 40° E.
 36.15 Leave San Antonio Canyon and ascend.
 38.00 Leave timber bears E. & W.
 40.00 Set a post 3 ft. long, 3 ins. sq. 24 ins. in the ground for $\frac{1}{2}$ section corner marked $\frac{1}{2}$ on west face. From which bears a
 pine 18 ins. dia. S. 5° E., 196 lks.
 pine 10 ins. dia. S. 13° W., 215 lks. Both marked $\frac{1}{2}$ S B T.
 47.12 Cross trail bears N. 30° E. and S. 30° W.
 80.00 Set a granite stone 16 x 10 x 5 ins. 11 ins. in the ground for corner sections 19, 24, 25 and 30, marked with 2 notches on the South and 4 notches on the N. edges and raised a mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 25 and 30. Var. 14° 26' E.

17.00 Top of spur bears N. 60° E. and S. 60° W. and descend.
 37.00 Cross ravine 20 lks. wide, course S. 55° W. and ascend.
 40.00 Set a quartz stone 20 x 16 x 5 ins. 15 ins. in the ground for $\frac{1}{2}$ section corner marked $\frac{1}{2}$ on west face and raised mound of stone alongside. Pits impracticable.
 64.46 Pine 10 ins. dia. and descend.
 80.00 Set a granite stone 36 x 12 x 12 ins. 27 ins. in the ground for corner to sections 25, 30, 31 and 36, marked with 1 notch on South and 5 notches on North edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Dense undergrowth of Chaparral.

NORTH between sections 31 and 36. Var. 14° 26' E.

From the corner to Tps. 1 and 2 N., Rs. 7 and 8 W., 1 run

EAST BOUNDARY.

31.00 Top of spur bears NW.
 40.00 Set sandstone 12 x 11 x 7 ins. 7 ins. in the ground for $\frac{1}{2}$ sections corner, marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. Pits impracticable.
 80.00 Set a granite stone 13 x 12 x 9 ins. 8 ins. in the ground for corner to sections 5, 6, 31 and 32, marked with 5 notches on the East and 1 notch on the west edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.
 49.20 Top of spur bears NW. and descend.
 81.47 The corner to Tps. 1 and 2 N., Rs. 8 and 9 W. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of Chaparral.
 GEORGE W. PEARSON, 1884.

N. 89° 55' W. between sections 5 and 32. Var. 14° 26' E.

sections 4, 5, 32 and 33, marked with 4 notches on the East and 2 notches on the West edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

J. R. GLOVER, 1884.

80.00 Dense undergrowth of Manzanita. Pits impracticable. Land mountainous. Soil 2nd and 3rd rate. edge and raised mound of stone alongside. Set a granite stone 24 x 10 ins. 11 ins. in the ground for corner to Tps. 2 and 3 N., Rs. 7 and 8 W., marked with 6 notches on each Pits impracticable.

40.00 Set a granite stone 16 x 12 x 12 ins. 11 ins. in the ground for corner marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Pits impracticable.

26.50 Top of San Gabriel Range of Mountains bears N. 68 $\frac{1}{2}$ ° E. and S. 69° W. and descend.

NORTH between sections 1 and 6. Var. 14° 26' E.

80.00 Timber Pine and Oak. Dense undergrowth of Manzanita. Pits impracticable. Land mountainous. Soil 2nd and 3rd rate. and 1 notch on the North edges and raised mound of stone alongside. Set a granite stone 15 x 10 x 6 ins. 10 ins. in the ground for corner to sections 1, 6, 7 and 12, marked with 5 notches on the South Bed of Cattle canyon, course S. 86° W. and ascend abruptly. Pits impracticable.

54.00 corner, marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Pits impracticable.

40.00 Set granite stone 20 x 10 x 8 ins. 15 ins. in the ground for corner. Leave timber bears E. & W.

NORTH between sections 7 and 12. Var. 14° 26' E.

80.00 Dense undergrowth of Chaparral. Soil 3rd rate. Land mountainous. Timber Pine and Oak. No other trees within limits. T 2 N, R 8 W, S 13 BT. Pine 12 ins. dia. S. 68° W. 58 lks. marked T 2 N, R 7 W, S 18 BT. Pine 18 ins. dia. S. 60° E. 96 lks. marked with 4 notches on S and 2 notches on N. edges for corner to sections 7, 12, 13 and 14, from which bears a S 12 on NW faces, R 8 W, S 13 on SW and R 7 W, S 18 on SE T 2 N, S 7 on NE A white pine 36 ins. dia. which I mark Top of ridge bears NE & SW and along same. Pits 30 ins. dia. S. 28° W. 29 lks. Both marked $\frac{1}{2}$ S B T. Pits 20 ins. dia. N. 14° E. 64 lks. section corner marked $\frac{1}{2}$ on W. face and from which bears a Set a granite stone 18 x 10 x 6 ins. 12 ins. in the ground for corner marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Enter timber bears E. & W. and descend. Cross stream 5 lks. wide, in Bear Canyon, S. 16° E. and ascend. 21.46 Set a granite stone 18 x 10 x 6 ins. 12 ins. in the ground for corner marked $\frac{1}{2}$ on W. face and from which bears a

NORTH between sections 13 and 18. Var. 14° 26' E.

80.00 Dense undergrowth of Chaparral. Land mountainous. Soil 2nd and 3rd rate. Timber Oak and Pine. and S. edges and raised mound of stone alongside. Set a granite stone 16 x 12 x 8 ins. 11 ins. in the ground for corner to sections 13, 18, 19 and 24, marked with 3 notches on the N. Cross West Fork of Bear Creek 6 lks. wide, course S. 70° E. Ascend. Pits impracticable.

55.10 corner marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Pits impracticable.

40.00 Set a granite stone 12 x 10 x 7 ins. 8 ins. in the ground for corner. Top of spur bears E. & W. and descend.

WEST BOUNDARY

Sections 31, 6

From the established corner to Trs. 1 and 2 N., No. 8 and 9 W. 1 Tm

Var. 14266' E.

North between sections 31 and 36

Summit of spur bears S.W. and ascend along top of spur
Set granite stone 15 x 7 x 6 ins. in the ground for 7 section
corner, marked 4 on west face raised mound of stone along side.
Pits impracticable.

Set a sandstone 11 x 11 x 7 ins. 6 ins. in the ground for corner to
sections 25, 30, 31 and 36, marked with 5 notches on the north and
1 notch on the south edge and raised mound of stone along side.
Pits impracticable. Soil and rate. Timber consisting pine and oak
Dense undergrowth of chaparral.

Var. 14267' E.

NORTH between sections 25 and 30

Summit of divide bears E and W about 500' above township corner and
descend along east slope of spur

Set granite stone 14x9x8 ins. 9 ins. in the ground for 1/4 section
corner, marked 1/4 on west face and raised a mound of stone along side.
Pits impracticable

Enter San Gabriel Canyon Course West

San Gabriel River 60 links wide Course West

Leave San Gabriel Canyon Course West and ascend along east slope
of spur

Set sandstone 20x12x9 ins. 15 ins. in the ground for cor. 19, 24,
25, 30 marked with 4 notches on north and 2 notches on so. edges
and raised a mound of stone along side.
Pits impracticable Land mountains, soil and rate,
Timber consisting pine and oak, Dense undergrowth of chaparral

NORTH between sections 19 and 24

Var. 14268' E.

Ascend along east slope of spur
Set granite rock 16 x 11 x 5 ins. in the ground for 1/4
sec. cor. marked 1/4 on west face and raised mound of stone
along side.

Pits impracticable

Sandstone 21x12x4 ins. 16 ins. in the ground for corner to
sections 13, 18, 19 and 24 marked with 5 notches on north and
south edges and raised a mound of stone along side

Pits impracticable Land mountains, soil and rate, Timber
consisting pine and oak Dense undergrowth of chaparral.

NORTH between sections 13 and 18

Var. 14269' E.

Ascend
Set granite stone 16 x 11 x 5 ins. in the ground for 1/4
section corner, marked 1/4 on W face and raised a mound of stone
along side.

Pits impracticable

Top of ridge bears Northwest and South 20° East and descend

Set sandstone 17 x 11 x 9 ins. in the ground for cor. to Secs. 7, 12, 13, 14, marked with 2 notches on North and 4 notches on South edges and raised a mound of stone along side

Pls impracticable - Land mountainous, Soil 2nd rate, Timber consisting pine and oak Dense undergrowth of chaparral brush

North between sections 7 and 12
 Var. 14-26, 15
 Descend
 Having 1.12 cms. wide
 Course S.E. and ascend

Set Granite stone 17 x 10 x 8 ins 12 ins. in ground for 1/4 Sec. Cor. marked 1/4 on W face and raised a mound of stone along side Pls impracticable

Top of ridge bears N.W. and S.E. and descend

Set sandstone 14 x 8 x 9 ins. 9 ins. in ground for Cor. to Secs. 1, 6, 7 and 12, marked with 1 notch on North and 5 notches on South edges and raised a mound of stone along side

Pls impracticable, Land mountainous Soil 2nd rate
 Timber consisting pine and oak Dense undergrowth of chaparral

February 21, 1884

North between sections 1 and 6
 Var. 14-26, 15

Descend

Set sandstone 14 x 11 x 6 ins. 9 ins. in the ground for 1/4 Sec. Cor. marked 1/4 on W face and raised a mound of stone along side Pls impracticable

To a point, 1.63 chains N of Cor. to Trs. 2 and 3 North N 8 and 9 W which is a well preserved post plainly marked with

1 1/2 N Sec 11 on N E
 N 8 W Sec. 6 on S E
 1 1/2 N Sec 1 on S W
 N 9 W Sec. 16 on NW face

with 6 notches on N, S, E and W edges and large mound of rock around post with pits,

At which point set sandstone 19 x 12 x 10 ins. 14 ins. in ground for elevating cor. to 1 1/2 N 8 & 9 W marked 0 with 6 notches on S, E and W edges and raised a mound of rock along side.

Pls impracticable
 Land mountainous, Soil 2nd rate
 Timber none
 Dense undergrowth of chaparral

NORTH BOUNDARY

from the opening corner to T 2 N, R. 8 and 9 W., I run
N 81° 1.67' E. to corner to Tps. 2 and 3 N., R. 8 and 9 W.

Thence I run

EAST on a narrow line between said townships.

Var. 14° 24' E

I set temporary half mile and mile posts at each 40 and 80 chains
and find the T. line to be 6 miles 2 chs. and 36 lks. long and the
falling to be 2 chs. 75 lks. north of the corner to Tps. 2 and 3 N.,
R. 7 and 8 W., which is a grey granite stone 24 x 20 x 10 ins.
firmly set in the ground marked with 6 notches on the north, south
east and west edges with mound of stone alongside.
The location of the true line will therefore be 45 5/6 lks. south
and 2.36 chs. E. per mile and its course will be N. 89° 40' W.

N. 89° 40' W. on a TRUE line between sections 1 and 36

Var. 14° 26' E

22.60

Having 60 lks. wide, course S. 40° W. and second
set sections 17 x 11 x 9 ins. in the ground for 1/4
section corner marked $\frac{1}{4}$ on N. face and raised mound of stone
alongside

40.00

Set a granite stone 17 x 12 x 4 ins. in the ground for
corner to sections 1, 2, 15 and 36, marked with 1 notch on east
and 5 notches on the west edge and raised mound of stone
alongside.

50.00

Timbered ravine 50 lks. wide course S. and ascend. 34.60
 Set sandstone 16 x 11 x 4 ins. in the ground for $\frac{1}{2}$ section corner and raised mound of stone alongside. Pits impracticable. 40.00
 To the corner to Tps. 2 and 3 N., Rs. 8 and 9 W. 82.36
 Land mountainous. Soil 3rd rate. Timber pine and Oak in ravines. Dense undergrowth of Chaparral.

NORTH 89° 40' W. on a TRUE line between sections 6 and 31. Var. 14° 26' E.

Top of ridge bears N. 10° E. and S. 10° W. and descend. 56.60
 Set sandstone 13 x 11 x 10 ins. 8 ins. in the ground for corner to sections 5, 6, 31 and 32, marked with 5 notches on the E. and 1 notches on W. edges and raised mound of stone alongside. Pits impracticable. 80.00
 Dense undergrowth of Chaparral.
 Cross San Gabriel River 40 lks. wide course SW. and ascend. 9.10
 No. 3 of Noverto Placer mine bears S. 20 chs. dist. 30.00
 Set sandstone 15 x 11 x 7 ins. 10 ins. in the ground for $\frac{1}{2}$ section corner, marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. 40.00
 Pits impracticable.
 N. 89° 40' W. on a TRUE line between sections 5 and 32. Var. 14° 26' E. 9.10

Set granite stone 16 x 12 x 14 ins. 11 ins. in the ground for corner to sections 4, 5, 32 and 33 marked with 2 notches on W. and 4 notches on E. edges and raised mound of stone alongside. Pits impracticable. 80.00
 Land mountainous. Soil 3rd rate. Timber, none. Dense Undergrowth of Chaparral.
 Set a sandstone 18 x 9 x 6 ins. 13 ins. in the ground for $\frac{1}{2}$ section corner, marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. 40.00
 Pits impracticable.
 N. 89° 40' W. on a TRUE line between sections 4 and 33. Var. 14° 26' E.

Top of ridge bears N. 10° E. and S. 10° W. and descend. 71.20
 Set sandstone 14 x 11 x 9 ins. 9 ins. in the ground for corner to sections 3, 4, 33 and 34, marked with 3 notches on E. & W. edges and raised mound of stone alongside. Pits impracticable. 80.00
 Land mountainous. Soil 3rd rate. Timber, none, undergrowth Chaparral.
 Ravine 4 lks. wide, course S. 10° W. and ascend. 5.50
 Set sandstone 21 x 11 x 6 ins. 16 ins. in the ground for $\frac{1}{2}$ section corner marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. 40.00
 Pits impracticable.
 N. 89° 40' W. on a TRUE line between sections 3 and 34. Var. 14° 26' E.

Top of ridge bears N. 20° E. and S. 20° W. and descend. 17.60
 Set a granite stone 15 x 10 x 8 ins. 10 ins. in the ground for $\frac{1}{2}$ section corner, marked $\frac{1}{2}$ on N. face, raised mound of stone alongside. Pits impracticable. 40.00
 Set a sandstone 19 x 16 x 4 ins. 14 ins. in the ground for corner to sections 2, 3, 34 and 35, marked with 4 notches on the West and 2 notches on the East edges and raised mound of stone alongside. 80.00
 Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Undergrowth of Chaparral.
 N. 89° 40' W. on a TRUE line between sections 2 and 35. Var. 14° 26' E.

Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

SUBDIVISIONS

T 2 N, R 8 W, S. B. M.

From the corner to sections 1, 2, 35 and 36 on the SOUTH Boundary of the Township, I run

22.00	Having 40 lks. wide, course SE. and ascend. Set granite stone 19 x 11 x 9 ins. 14 ins. in the ground for $\frac{1}{2}$ sec. corner marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Pits impracticable.
44.00	Top of ridge bears N. 5° W. and SE. thence along E. slope of ridge. Summit of ridge bears NE. & SW. and descend. Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for corner to sections 25, 26, 35 and 36, marked with 1 notch on the E. & S. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate. Timber Pine and Oak in ravine. Dense undergrowth of Chaparral.
80.00	EAST on a RANDOM line between sections 25 and 36. Var. 14° 26 $\frac{1}{2}$ ' E.
40.00	Set temporary $\frac{1}{2}$ section corner. Intersect the East boundary of Tp. 69 lks. N. of the corner to secs. 25, 30, 31 and 36, which is a white granite stone 36 x 12 x 12 ins. 27 ins. in the ground marked with 1 notch on S. and 5 notches on N. edges with mound of stone alongside. Thence I run N. 89° 31' W. on a TRUE line between sections 25 and 36 with same Variation.
10.00	Enter San Antonio Canyon course S. San Antonio Creek 25 lks. wide, course S. Leave canyon course S. and ascend. Trail bears NE. & SW.
37.20	Set sandstone 14 x 9 x 7 ins. 9 ins. in the ground for $\frac{1}{2}$ section corner, marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. Pits impracticable.
79.00	Top of ridge bears NE. & SW. and descend. The corner to sections 25, 26, 35 and 36. Land mountainous. Soil 1st and 2nd rate. Timber Pine and Oak and Sycamore in canyon. Dense undergrowth of Chaparral.
80.27	NORTH between sections 25 and 26. Var. 14° 26 $\frac{1}{2}$ ' E.
40.00	Set sandstone 16 x 12 x 4 ins. 11 ins. in the ground for $\frac{1}{2}$ section corner, marked $\frac{1}{2}$ on W. face and raised mound of stone alongside. Pits impracticable.
49.50	Gulch 30 lks. wide, course S. & W. and ascend. Set granite stone 15 x 11 x 9 ins. 10 ins. in the ground for corner to sections 23, 24, 25 and 26, marked with 1 notch on E. and 2 notches on S. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.
80.00	EAST on a RANDOM line between sections 24 and 25. Var. 14° 26 $\frac{1}{2}$ ' E.
40.00	Set temporary $\frac{1}{2}$ section corner. Intersect the E. boundary of the Tp. at 41 lks. N. of corner to secs. 19, 24, 25 and 30, which is a granite stone 16 x 10 x 5 ins. firmly set in the ground marked with 4 notches on the N. and 2 notches on the S. edges and mound of stone alongside. Thence I run N. 89° 43' W. on a TRUE line between sections 24 and 25, with same Variation.
40.16	Set granite stone 17 x 11 x 9 ins. 12 ins. in the ground for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ on N. face and raised mound of stone alongside.

57.20 Pits impracticable.
 Top of ridge bears N. 5° E. and S. 5° W. and descend.
 Head of gulch course S. and ascend.
 The corner to sections 23, 24, 25 and 26.
 Land mountainous. Soil 3rd rate. Timber, none.
 Dense undergrowth of Chaparral.

 NORTH between sections 23 and 24.
 Var. 14° 26' E.

18.90 Summit of divide bears NE. & SW. and descend.
 Set sandstone 16 x 12 x 8 ins. in the ground for 1/4 section
 corner, marked 1/4 on W. face and raised mound of stone alongside.
 Pits impracticable.
 Set gray stone 11 x 11 x 10 ins. 7 ins. in the ground for corner to
 sections 13, 14, 23 and 24, marked with 1 notch on E. and 3 notches
 on S. edges and raised mound of stone alongside.
 Pits impracticable. Soil 3rd rate. Timber scattering oak and pine
 on NW. slope of divide. Dense undergrowth of Chaparral.

 EAST on a RANDOM LINE between sections 13 and 24.
 Var. 14° 26' E.

40.00 Set temporary 1/4 section corner.
 Intersect the E. boundary of Tp. 33 lks. N. of corner to sections
 13, 18, 19 and 24, which is a granite stone 17 x 11 x 7 ins. firmly
 set in the ground with 3 notches on the N. & S. edges with mound of
 stone alongside. Pits impracticable. Thence I run
 N. 89° 46' W. on a TRUE line between sections 13 and 24, with same
 Variation.
 Set granite stone 13 x 11 x 6 ins. 8 ins. in the ground for 1/4 sec.
 corner, marked 1/4 on N. face and raised mound of stone alongside.
 Pits impracticable.
 Summit of divide bears N. & S. and descend.
 The corner to sections 13, 14, 23 and 24.
 Land mountainous. Soil 2nd rate. Timber scattering pine and oak.
 Dense undergrowth of Chaparral.

 NORTH between sections 13 and 14.
 Var. 14° 26' E.

21.60 Enter Cow Canyon, course S. W.
 Creek 10 lks. wide, course SW. Thence in canyon.
 Set sandstone 16 x 10 x 9 ins. 11 ins. in the ground for 1/4 section
 corner, marked 1/4 on W. face and raised mound of stone alongside.
 Pits impracticable.
 Set sandstone 20 x 14 x 15 ins. 15 ins. in the ground for corner to
 sections 11, 12, 13 and 14, marked with 4 notches on the S. and 1
 notch on the E. edges and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd rate.
 Timber pine and oak in canyon. Dense undergrowth of Chaparral.

 EAST on a RANDOM line between sections 12 and 13.
 Var. 14° 26' E.

40.00 Set temporary 1/4 section corner.
 Intersect the E. boundary 25 lks. N. of corner to sections 7, 12,
 13 and 18, which is a
 white pine 38 ins. dia. marked
 T 2 N, S 7 on NE.
 R 7 W, S 19 on SE.
 R 8 W, S 13 SW. and
 S 12 on NW. with earth mound around tree, from which
 bears a
 pine 18 ins. dia. S. 60° E. 96 lks.
 pine 12 ins. dia. S. 68° W. 58 lks. Thence I run
 N. 89° 49' W. on a TRUE line between sections 12 and 13 with same
 Variation.
 Summit of divide bears N. 15° E. and S. 15° W. and descend.
 Set sandstone 26 x 19 x 10 ins. 20 ins. in the ground for 1/4 section
 corner marked 1/4 on N. face and raised mound of stone alongside.
 36.00

From which bears a
 pine 14 ins. dia. N. 20° W. 1.17 chs.
 pine 16 ins. dia. S. 29° E. 86 lks. Both marked S B T.
 In Cow Canyon, course South.
 Creek 11 lks. wide, course South.
 The corner to sections 11, 12, 13 and 14.
 Land mountainous. Soil 2nd rate. Timber Pine and Oak.
 Dense undergrowth of Chaparral.

NORTH between sections 11 and 12.
 Var. 14° 26' E.

9,20
 Leave canyon, course S. 15° W. and ascend.
 Set granite stone 11 x 11 x 10 ins. 6 ins. in the ground $\frac{1}{2}$ section
 corner, marked $\frac{1}{2}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 Summit of high ridge bears NE and S. 20° W. and descend.
 Set sandstone 14 x 11 x 8 ins. 9 ins. in the ground for corner to
 sections 1, 2, 11 and 12, marked with 5 notches on S. and 1 notch
 on E. edges and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd rate.
 Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 1 and 12.
 Var. 14° 26' E.

40.00
 Set temporary $\frac{1}{2}$ section corner.
 Intersect the East boundary of Tp. at 11 lks. N. of corner to secs.
 1, 6, 7 and 12, which is a granite stone 15 x 10 x 6 ins. 10 ins. in
 the ground marked with 5 notches on the S. and 1 notch on the N. edges
 and mound of stone alongside. Thence I run
 N. 89° 55' W. on a TRUE line between sections 1 and 12 with same
 Variation.
 Set granite stone 16 x 9 x 8 ins. 11 ins. in the ground for $\frac{1}{2}$ sec.
 corner marked $\frac{1}{2}$ on N. face and raised mound of stone alongside.
 Pits impracticable.
 Top of ridge bears N. 50° E. and S. 50° W. and descend.
 The corner to sections 1, 2, 11 and 12.
 Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak.
 Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 1 and 2.
 Var. 14° 26' E.

40.00
 Set temporary $\frac{1}{2}$ section corner.
 Intersect the N. boundary 4 1/2 lks. west of corner to sections 1, 2,
 35 and 36. Thence I run
 S. 0° 17' W. on a TRUE line between sections 1 and 2, with same
 Variation.
 Set granite stone 16 x 12 x 4 ins. 11 ins. in the ground for $\frac{1}{2}$ sec.
 corner marked $\frac{1}{2}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 Having, 50 lks. wide, course SW. and ascend.
 The corner to sections 1, 2, 11 and 12.
 Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak
 Dense undergrowth of Chaparral.

From the corner to sections 2, 3, 34 and 35 on the S. boundary of the
 Tp. I run
 NORTH between sections 34 and 35.
 Var. 14° 26' E.

40.00
 Set sandstone 17 x 9 x 6 ins. 12 ins. in the ground for $\frac{1}{2}$ section corner,
 marked $\frac{1}{2}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 Set sandstone 16 x 11 x 5 ins. 11 ins. in the ground for corner to
 sections 26, 27, 32 and 35, marked with 2 notches on the E. and 1
 notch on the S. edge and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd rate.
 Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 26 and 35. Var. 14° 26' E. 40.00

Set temporary 1/2 section corner. Intersect the N. & S. line 55 lks. N. of corner to sections 25, 26, 35 and 36. Thence I run 80.60

N. 89° 36' W. on a TRUE line between sections 26 and 35 with same Variations. 13.50

Gulch 30 lks. wide, course S. and ascend. Top of ridge bears N. & S. and descend. 30.00

Set sandstone 12 x 11 x 7 ins. in the ground for 1/2 section corner, marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable. 40.30

Gulch 10 lks. wide, course S. and ascend. Summit of ridge bears N. 5° W. and S. 5° E. and descend. The corner to sections 26, 27, 34 and 35. 78.00

Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral. 80.60

NORTH between sections 26 and 27. Var. 14° 26' E. 6.00

Summit of ridge bears N. and S. 5° E. Set sandstone 12 x 9 x 6 ins. in the ground for 1/2 section corner, marked 1/2 on W. face and raised mound of stone alongside. Pits impracticable. From which bears a Pine 11 ins. dia. S. 27° W. 170 lks. marked 1/2 S B T. No other trees within limits. 40.00

Leave summit bears NE. & SW. and descend. Head of gulch, course W. and ascend. Top of spur bears N. 60° W. and descend. 45.50

Set sandstone 14 x 9 x 8 ins. in the ground for corner to sections 22, 26 and 27, marked with 2 notches on the S. & E. edges and raised mound of stone alongside. Pits impracticable. From which bears an Oak 14 ins. dia. S. 23 3/4° W. 167 lks. marked T 2 N, R 8 W, S 27 BT. Pine 8 ins. dia. N. 7° E. 261 lks. marked T 2 N, R 8 W, S 23 BT. No other trees within limits. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral. 80.00

EAST on a RANDOM line between sections 23 and 26. Var. 14° 26' E. 40.00

Set temporary 1/2 section corner. Intersect the N. & S. line 21 lks. S. of corner to sections 23, 24, 25 and 26. Thence I run 80.38

S. 89° 51' W. on a TRUE line between sections 23 and 26, with same Variation. Summit of divide bears NE. & SW. and descend. Set sandstone 10 x 11 x 9 ins. 6 ins. in the ground for 1/2 section corner marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable. 40.19

Cross gulch near head, course SW. and ascend. The corner to sections 22, 23, 26 and 27. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral. 51.60

NORTH between sections 22 and 23. Var. 14° 26' E. 40.00

Enter Cow Canyon, course West. Creek 10 lks. wide, course West. Leave canyon, course West and ascend. Set sandstone 15 x 9 x 8 ins. 10 ins. in the ground for 1/2 section corner, marked 1/2 on W. face and raised mound of stone alongside. From which bears a Pine 12 ins. dia. N. 70° E. 217 lks. Pine 10 ins. dia. S. 61° W. 300 lks. Both marked 1/2 S B T. 11.20

17.00

19.20

40.00