

T 2 N, R 8 W. S. B. M.

COPIED FROM
Copies on file in
Cadastral Engineer's Office
Glendale, California
VOL. 362:3

SURVEYED BY
GEO. W. PEARSON
MARCH 1884

R 8 W						
5	5	5	5	5	4B	
4A 6 14D	15 5 15	13B 4 13B	12B 3 12B	11 2 11	8 1 8	3
5 7 14C	14D 8 14C	13A 9 13A	12B 10 12A	10 11 10	8 12 7	3
4 18 14B	14C 17 14B	13A 16 13A	12A 15 12A	10 14 10	7 13 7	3
4 19 14	14A 20 14A	13 21 13	12A 22 12	9 23 9	7 24 6	2
4 30 13B	14 29 14	13 28 12B	12 27 11	9 26 9	6 25 6	2
4 31 1	13B 32 1	12B 33 1	11 34 1	8 35 1	6 36 1	2
R 8 W						

Grover 1884

Pearson 1884

T 2 N, R 8 W, S. B. M.
SOUTH BOUNDARY.

From the established corner to Tps. 1 and 2 N, Rs. 8 and 9 W. I run EAST on a RANDOM line between said Townships.

Var. 14° 26' E.

I set temporary half mile and mile posts at every 40 and 80 chs. and find the Tp. line to be 6 miles, 1.47 chains long and intersect the E. boundary of the Tp. at a point 70 lks. N. of corner to Tp. 1 and 2 N. Rs. 7 and 8 W. which is a granite stone 20 x 18 x 7 ins. firmly set in the ground and marked with 6 notches on the N. S, E, and W. edges and a stone mound alongside. The correction for the true line will therefore be 11 2/3 lks. S. and 1.47 chs. E. per mile, Thence I run N. 89° 55' W. on a TRUE line between sections 1 and 36.

Var. 14° 26' E.

35.50	Top of spur bears N. and descend.
40.00	Set a sandstone 12 x 10 x 9 ins. 7 ins. in the ground for 1/4 section corner, marked 1/4 on N. face and raised mound of stone alongside. Pits impracticable.
50.50	Enter San Antonio Canyon, course South.
53.00	San Antonio Creek 12 lks. wide, course South.
60.00	Road bears N. & S.
62.50	Leave canyon, course South and ascend.
71.20	Gulch 20 lks. wide, course S. 20° W.
80.00	Set granite stone 14 x 11 x 7 ins. 9 ins. in the ground for corner to sections 1, 2, 35 and 36, marked with 5 notches on the West and 1 notch on the East edges and raised mound of stone alongside. Pits impracticable. Soil 2nd rate. Timber Pine and Oak in canyon. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 2 and 35. Var. 14° 26' E.

16.50	Top of spur bears SW. and descend.
36.50	Gulch 30 lks. wide, course SW. and ascend.
40.00	Set sandstone 12 x 10 x 7 ins. 7 ins. in the ground for 1/4 section corner marked 1/4 on N. face and raised mound of stone alongside. Pits impracticable.
60.00	Top of spur bears SW. and descend.
80.00	Set sandstone 15 x 12 x 6 ins. 10 ins. in the ground for corner to sections 2, 3, 34 and 35, marked with 4 notches on the West and 2 notches on the East edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate. Timber Pine and Oak in ravines. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 3 and 34. Var. 14° 26' E.

20.50	San Dimas Creek 9 lks. wide, course South and ascend.
40.00	Set sandstone 15 x 11 x 9 ins. 9" in the ground for 1/4 section corner marked 1/4 on North face and raised mound of stone alongside. Pits impracticable.
80.00	Set a granite stone 13 x 9 x 8 ins. 8 ins. in the ground for corner to sections 3, 4, 33 and 34, marked with 3 notches on the East and West edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber Pine and Oak in Ravines. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 4 and 33. Var. 14° 26' E.

5.00	Summit of divide bears N. 60° E. and S. 60° W. and descend.
40.00	Set a granite stone 11 x 10 x 7 ins. 6 ins. in the ground for 1/4 sec. corner, marked 1/4 on N. face and raised mound of stone alongside. Pits impracticable.
80.00	Set sandstone 13 x 11 x 9 ins. 8 ins. in the ground for corner to

sections 4, 5, 32 and 33, marked with 4 notches on the East and 2 notches on the West edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 5 and 32. Var. 14° 26' E.

31.00 Top of spur bears NW.
40.00 Set sandstone 12 x 11 x 7 ins. 7 ins. in the ground for $\frac{1}{4}$ sections corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
80.00 Set a granite stone 13 x 12 x 9 ins. 8 ins. in the ground for corner to sections 5, 6, 31 and 32, marked with 5 notches on the East and 1 notch on the West edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

N. 89° 55' W. between sections 6 and 31. Var. 14° 26' E.

40.00 Set sandstone 11 x 9 x 6 ins. 6 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
49.20 Top of spur bears NW. and descend.
81.47 The corner to Tps. 1 and 2 N., Rs. 8 and 9 W. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of Chaparral.

GEORGE W. PEARSON, 1884.

EAST BOUNDARY.

From the corner to Tps. 1 and 2 N., Rs. 7 and 8 W., I run

NORTH between sections 31 and 36. Var. 14° 26' E.

17.00 Top of spur bears N. 60° E. and S. 60° W. and descend.
37.00 Cross ravine 20 lks. wide, course S. 55° W. and ascend.
40.00 Set a Quartz stone 20 x 16 x 5 ins. 15 ins. in the ground for $\frac{1}{4}$ sec. corner marked $\frac{1}{4}$ on West face and raised mound of stone alongside. Pits impracticable.
64.46 Pine 10 ins. dia. and descend.
80.00 Set a granite stone 36 x 12 x 12 ins. 27 ins. in the ground for corner to sections 25, 30, 31 and 36, marked with 1 notch on South and 5 notches on North edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Dense undergrowth of Chaparral.

NORTH between sections 25 and 30. Var. 14° 26' E.

5.00 Cross gulch 11 lks. wide, course S. 60° W. ascend.
10.00 Top of spur bears N. 88° E. and S. 88° W. and descend.
12.00 Enter timber bears E. & W.
33.10 Enter San Antonio Canyon, course S. 40° W.
33.25 Cross San Antonio Creek 20 lks. wide, course S. 40° E.
36.15 Leave San Antonio Canyon and ascend.
38.00 Leave timber bears E. & W.
40.00 Set a post 3 ft. long, 3 ins. sq. 24 ins. in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on West face. From which bears a
Pine 18 ins. dia. S. 5° E., 196 lks.
Pine 10 ins. dia. S. 13° W., 215 lks. Both marked $\frac{1}{4}$ S B T.
47.12 Cross trail bears N. 30° E. and S. 30° W.
80.00 Set a granite stone 16 x 10 x 5 ins. 11 ins. in the ground for corner sections 19, 24, 25 and 30, marked with 2 notches on the South and 4 notches on the N. edges and raised a mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber Pine and Oak. Dense undergrowth of Chaparral.

9.50 Top of spur bears E. & W. and descend.
 40.00 Set a granite stone 12 x 10 x 7 ins. 8 ins. in the ground for $\frac{1}{4}$ sec.
 corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 55.10 Cross West Fork of Bear Creek 6 lks. wide, course S. 70° E. Ascend.
 80.00 Set a granite stone 16 x 12 x 8 ins. 11 ins. in the ground for cor-
 ner to sections 13, 18, 19 and 24, marked with 3 notches on the N.
 and S. edges and raised mound of stone alongside.
 Land mountainous. Soil 2nd and 3rd rate. Timber Oak and Pine.
 Dense undergrowth of Chaparral.

 NORTH between sections 13 and 18. Var. 14° 26' E.

8.50 Enter timber bears E. & W. and descend.
 21.46 Cross stream 5 lks. wide, in Bear Canyon, S. 16° E. and ascend.
 40.00 Set a granite stone 18 x 10 x 6 ins. 12 ins. in the ground for $\frac{1}{4}$
 section corner marked $\frac{1}{4}$ on W. face and from which bears a
 Fir 20 ins. dia. N. 14° E. 64 lks.
 Fir 30 ins. dia. S. 28° W. 29 lks. Both marked $\frac{1}{4}$ S B T.
 78.00 Top of ridge bears NE & SW and along same.
 80.00 A White Pine 36 ins. dia. which I mark
 T 2 N, S 7 on NE
 R 7 W, S. 18 on SE
 R 8 W, S 13 on SW and
 S 12 on NW faces,
 with 4 notches on S and 2 notches on N. edges for corner to sections
 7, 12, 13 and 14, from which bears a
 Pine 18 ins. dia. S. 60° E. 96 lks. marked
 T 2 N, R 7 W, S 18 BT.
 Pine 12 ins. dia. S. 68° W. 58 lks. marked
 T 2 N, R 8 W, S 13 BT.
 No other trees within limits.
 Soil 3rd rate. Land mountainous. Timber Pine and Oak.
 Dense undergrowth of Chaparral.

 NORTH between sections 7 and 12. Var. 14° 26' E.

1.00 Leave timber bears E. & W.
 40.00 Set granite stone 20 x 10 x 8 ins. 15 ins. in the ground for $\frac{1}{4}$ sec.
 corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 54.00 Bed of Cattle canyon, course S. 86° W. and ascend abruptly.
 80.00 Set a granite stone 15 x 10 x 6 ins. 10 ins. in the ground for cor-
 ner to sections 1, 6, 7 and 12, marked with 5 notches on the South
 and 1 notch on the North edges and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd and 3rd rate.
 Timber Pine and Oak. Dense undergrowth of Manzanita.

 NORTH between sections 1 and 6. Var. 14° 26' E.

26.50 Top of San Gabriel Range of Mountains bears N. 68 $\frac{1}{2}$ ° E. and S. 69° W.
 and descend.
 40.00 Set a granite stone 16 x 12 x 12 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
 corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
 Pits impracticable.
 80.00 Set a granite stone 24 x 20 x 10 ins. 11 ins. in the ground for cor-
 ner to Tps. 2 and 3 N., Rs. 7 and 8 W., marked with 6 notches on each
 edge and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd and 3rd rate.
 Dense undergrowth of Manzanita.

J. R. GLOVER, 1884.

WEST BOUNDARY

Sections 31, 6

From the established corner to Tps. 1 and 2 N., Rs. 8 and 9 W. I run
North between sections 31 and 36 Var. 14° 26½' E.

38.00 Summit of spur bears S.W. and ascend along top of spur
40.00 Set granite stone 15 x 7 x 8 ins. 10 ins. in the ground for ¼ section
corner, marked ¼ on West face raised mound of stone alongside.
Pits impracticable.
50.00 Set a sandstone 11 x 11 x 7 ins. 6 ins. in the ground for corner to
sections 25, 30, 31 and 36, marked with 5 notches on the North and
1 notch on the South edge and raised mound of stone alongside.
Pits impracticable. Soil 2nd rate. Timber scattering Pine and Oak
Dense undergrowth of Chaparral.

NORTH between Sections 25 and 30 Var. 14° 26½' E.

10.50 Summit of divide bears E and W about 500' above Township corner and
descend along East slope of spur
40.00 Set granite stone 14x9x8 ins. 9 ins. in the ground for 1/4 Section
Corner, marked 1/4 on West face and raised a mound of stone alongside.
Pits impracticable

67.00 Enter San Gabriel Canyon Course West
71.60 San Gabriel River 60 links wide Course West
75.70 Leave San Gabriel Canyon Course West and ascend along East slope
of spur

50.00 Set sandstone 20x11x9 ins. 15 ins. in the ground for Cors. 19, 24,
25, 30 marked with 4 notches on North and 2 notches on So. edges
and raised a mound of stone alongside.
Pits impracticable Land mountainous, soil 2nd rate,
Timber scattering pine and oak, Dense undergrowth of chaparral

NORTH between Sections 19 and 24 Var. 14° 26½' E.

40.00 Ascend along East slope of spur
Set granite rock 16 x 11 x 5 ins. 11 ins. in the ground for 1/4
Sec. Cor. marked 1/4 on West face and raise mound of stone
alongside.
Pits impracticable

50.00 Sandstone 21x19x4 ins. 16 ins. in the ground for corner to
Sections 13, 18, 19 and 24 marked with 3 notches on North and
South edges and raised a mound of stone alongside

Pits impracticable Land mountainous, soil 2nd rate, Timber
scattering pine and oak Dense undergrowth of chaparral.

NORTH between Sections 13 and 18 Var. 14° 26½' E.

40.00 Ascend
Set granite stone 16 x 11 x 5 ins. 11 ins. in the ground for 1/4
Section corner, marked 1/4 on W face and raised a mound of stone
alongside.
Pits impracticable

45.00 Top of ridge bears Northwest and South 20° East and Descend

50.00 Set sandstone 17 x 11 x 9 ins. 12 ins. in the ground for cor.
to Secs. 7, 12, 13, 18, marked with 2 notches on North
and 4 notches on South edges and raised a mound of stone
alongside

Pits impracticable - Land mountainous, Soil 2nd rate,
Timber scattering Pine and oak
Dense undergrowth of chaparral brush

North between Sections 7 and 12 Var. 14° 26½' E
Descend
20.60 Ravine 1.12 chs. wide Course S.E. and Ascend

40.00 Set granite stone 17 x 10 x 8 ins 12 ins. in ground for 1/4
Sec. Cor. marked 1/4 on W face and raised a mound of stone
alongside Pits impracticable

49.20 Top of ridge bears N.W. and S.E. and descend

50.00 Set sandstone 14 x 8 x 9 ins. 9 ins. in ground for Cor. to
Secs. 1, 6, 7 and 12, marked with 1 notch on North and
5 notches on South edges and raised a mound of stone
alongside

Pits impracticable, Land Mountainous Soil 2nd rate
Timber scattering pine and oak Dense undergrowth of chaparral

February 21, 1884

North between Sections 1 and 6 Var. 14° 26½' E
Descend

40.00 Set sandstone 14 x 11 x 6 ins. 9 ins. in the ground for 1/4
Sec. Cor. marked 1/4 on W face and raised a mound of stone
alongside
Pits impracticable

54.90 To a point, 1.63 chains W of Cor. to Tps. 2 and 3 North
R 8 and 9 W which is a well preserved post plainly marked
with

T 3 N Sec 31 on N E
R 8 W Sec. 6 on S E
T 2 N Sec 1 on S W
R 9 W Sec. 36 on NW face

with 6 notches on N, S, E and W edges and large mound of rock
around post with pits,

At which point set sandstone 19 x 12 x 10 ins. 14 ins. in
ground for closing cor. to T 2 N R 8 & 9 W marked G O with
6 notches on S, E and W edges and raised a mound of rock
alongside.

Pits impracticable
Land mountainous, Soil 3rd rate Timber none
Dense undergrowth of chaparral

NORTH BOUNDARY

From the Closing Corner to T 2 N, Rs. 8 and 9 W., I run
EAST 1.63 chs. to corner to tps. 2 and 3 N., Rs. 8 and 9 W.
Thence I run

EAST on a RANDOM line between said Townships. Var. 14° 26½' E

I set temporary half mile and mile posts at each 40 and 80 chains and find the Tp. line to be 6 miles 2 chs. and 36 lks. long and the falling to be 2 chs. 75 lks. North of the corner to Tps. 2 and 3 N., Rs. 7 and 8 W., which is a gray granite stone 24 x 20 x 10 ins. firmly set in the ground marked with 6 notches on the North, South East and West edges with mound of stone alongside. The correction of the true line will therefore be 45 5/6 lks. South and 2.36 chs. E. per mile and its course will be N. 89° 40' W.

N. 89° 40' W. on a TRUE line between Sections 1 and 36
Var. 14° 26½' E.

22.60 Ravine 60 lks. wide, course S. 40° W. and ascend
40.00 Set sandstone 17 x 11 x 9 ins. 12 ins. in the ground for 1/4
section corner marked $\frac{1}{4}$ on N. face and raised mound of stone
alongside
Pits impracticable
80.00 Set a granite stone 17 x 12 x 4 ins. 12 ins. in the ground for
corner to sections 1, 2, 35 and 36, marked with 1 notch on East
and 5 notches on the West edges and raised mound of stone
alongside.

Pits impracticable. Land mountainous. Soil 3rd rate.
Timber, none. Dense undergrowth of Chaparral.

N. 89° 40' W. on a TRUE line between sections 2 and 35.
Var. 14° 26½' E.

17.60 Top of ridge bears N. 20° E. and S. 20° W. and descend.
40.00 Set a granite stone 15 x 10 x 8 ins. 10 ins. in the ground for ¼
section corner, marked ¼ on N. face, raised mound of stone alongside.
Pits impracticable.
80.00 Set a sandstone 19 x 16 x 4 ins. 14 ins. in the ground for corner to
sections 2, 3, 34 and 35, marked with 4 notches on the West and 2
notches on the East edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber, none. Undergrowth of Chaparral.

N. 89° 40' W. on a TRUE line between sections 3 and 34.
Var. 14° 26½' E.

5.50 Ravine 4 lks. wide, course S. 10° W. and ascend.
40.00 Set sandstone 21 x 11 x 6 ins. 16 ins. in the ground for ¼ section
corner marked ¼ on N. face and raised mound of stone alongside.
Pits impracticable.
71.20 Top of ridge bears N. 10° E. and S. 10° W. and descend.
80.00 Set sandstone 14 x 11 x 9 ins. 9 ins. in the ground for corner to
sections 3, 4, 33 and 34, marked with 3 notches on E. & W. edges and
raised mound of stone alongside. Pits impracticable.
Land mountainous. Soil 3rd rate. Timber, none, undergrowth Chaparral.

N. 89° 40' W. on a TRUE line between sections 4 and 33.
Var. 14° 26½' E.

40.00 Set a sandstone 18 x 9 x 6 ins. 13 ins. in the ground for ¼ section
corner, marked ¼ on N. face and raised mound of stone alongside.
Pits impracticable.
80.00 Set granite stone 16 x 12 x 14 ins. 11 ins. in the ground for corner
to sections 4, 5, 32 and 33 marked with 2 notches on W. and 4 notches
on E. edges and raised mound of stone alongside. Pits impracticable.
Land mountainous. Soil 3rd rate. Timber, none. Dense Undergrowth
of Chaparral.

N. 89° 40' W. on a TRUE line between sections 5 and 32.
Var. 14° 26½' E.

9.10 Cross San Gabriel River 40 lks. wide course SW. and ascend.
30.00 No. 3 of Novento Placer Mine bears S. 20 chs. dist.
40.00 Set sandstone 15 x 11 x 7 ins. 10 ins. in the ground for ¼ section
corner, marked ¼ on N. face and raised mound of stone alongside.
Pits impracticable.
56.60 Top of ridge bears N. 10° E. and S. 10° W. and descend.
80.00 Set sandstone 13 x 11 x 10 ins. 8 ins. in the ground for corner to
sections 5, 6, 31 and 32, marked with 5 notches on the E. and 1
notches on W. edges and raised mound of stone alongside.
Pits impracticable. Soil 3rd rate. Timber, none.
Dense undergrowth of Chaparral.

NORTH 89° 40' W. on a TRUE line between sections 6 and 31.
Var. 14° 26½' E.

34.60 Timbered ravine 50 lks. wide course S. and ascend.
40.00 Set sandstone 16 x 11 x 4 ins. 11 ins. in the ground for ¼ section
corner and raised mound of stone alongside. Pits impracticable.
82.36 To the corner to Tps. 2 and 3 N., Rs. 8 and 9 W.
Land mountainous. Soil 3rd rate. Timber Pine and Oak in ravines.
Dense undergrowth of Chaparral.

GEORGE W. PEARSON, 1884

SUBDIVISIONS

T 2 N, R 8 W, S. B. M.

From the corner to sections 1, 2, 35 and 36 on the SOUTH Boundary of the Township, I run

NORTH between sections 35 and 36.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

22.00 Ravine 40 lks. wide, course SE. and ascend.
40.00 Set granite stone 19 x 11 x 9 ins. 14 ins. in the ground for $\frac{1}{4}$ sec. corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. Pits impracticable.
44.00 Top of ridge bears N. 5° W. and SE. thence along E. slope of ridge.
75.00 Summit of ridge bears NE. & SW. and descend.
80.00 Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for corner to sections 25, 26, 35 and 36, marked with 1 notch on the E. & S. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate. Timber Pine and Oak in ravine. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 25 and 36.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.27 Intersect the East boundary of Tp. 69 lks. N. of the corner to secs. 25, 30, 31 and 36, which is a white granite stone 36 x 12 x 12 ins. 27 ins. in the ground marked with 1 notch on S. and 5 notches on N. edges with mound of stone alongside. Thence I run

N. $89^{\circ} 31'$ W. on a TRUE line between sections 25 and 36 with same Variation.

10.00 Enter San Antonio Canyon course S.
19.50 San Antonio Creek 25 lks. wide, course S.
27.60 Leave canyon course S. and ascend.
37.20 Trail bears NE. & SW.
40.14 Set sandstone 14 x 9 x 7 ins. 9 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
79.00 Top of ridge bears NE. & SW. and descend.
80.27 The corner to sections 25, 26, 35 and 36. Land mountainous. Soil 1st and 2nd rate. Timber Pine and Oak and Sycamore in canyon. Dense undergrowth of Chaparral.

NORTH between sections 25 and 26.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set sandstone 16 x 12 x 4 ins. 11 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. Pits impracticable.
49.50 Gulch 30 lks. wide, course S. & W. and ascend.
80.00 Set granite stone 15 x 11 x 9 ins. 10 ins. in the ground for corner to sections 23, 24, 25 and 26, marked with 1 notch on E. and 2 notches on S. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 24 and 25.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.32 Intersect the E. boundary of the Tp. at 41 lks. N. of corner to secs. 19, 24, 25 and 30, which is a granite stone 16 x 10 x 5 ins. firmly set in the ground marked with 4 notches on the N. and 2 notches on the S. edges and mound of stone alongside. Thence I run
N. $89^{\circ} 43'$ W. on a TRUE line between sections 24 and 25, with same Variation.
40.16 Set granite stone 17 x 11 x 9 ins. 12 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.

57.20 Pits impracticable.
 65.00 Top of ridge bears N. 5° E. and S. 5° W. and descend.
 80.32 Head of gulch course S. and ascend.
 The corner to sections 23, 24, 25 and 26.
 Land mountainous. Soil 3rd rate. Timber, none.
 Dense undergrowth of Chaparral.

NORTH between sections 23 and 24. Var. 14° 26½' E.

18.90 Summit of divide bears NE. & SW. and descend.
 40.00 Set sandstone 16 x 12 x 8 ins. 11 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside.
 Pits impracticable.
 80.00 Set gray stone 11 x 11 x 10 ins. 7 ins. in the ground for corner to sections 13, 14, 23 and 24, marked with 1 notch on E. and 3 notches on S. edges and raised mound of stone alongside.
 Pits impracticable. Soil 3rd rate. Timber scattering oak and pine on NW. slope of divide. Dense undergrowth of Chaparral.

EAST on a RANDOM LINE between sections 13 and 24. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.
 80.20 Intersect the E. boundary of Tp. 33 lks. N. of corner to sections, 13, 18, 19 and 24, which is a granite stone 17 x 11 x 7 ins. firmly set in the ground with 3 notches on the N. & S. edges with mound of stone alongside. Pits impracticable. Thence I run
 N. 89° 46' W. on a TRUE line between sections 13 and 24, with same Variation.

40.10 Set granite stone 13 x 11 x 6 ins. 8 ins. in the ground for ¼ sec. corner, marked ¼ on N. face and raised mound of stone alongside.
 Pits impracticable.
 43.50 Summit of divide bears N. & S. and descend.
 80.20 The corner to sections 13, 14, 23 and 24.
 Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak.
 Dense undergrowth of Chaparral.

NORTH between sections 13 and 14. Var. 14° 26½' E.

21.60 Enter Cow Canyon, course S. W.
 39.00 Creek 10 lks. wide, course SW. Thence in canyon.
 40.00 Set sandstone 16 x 10 x 9 ins. 11 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside.
 Pits impracticable.
 80.00 Set sandstone 20 x 14 x 15 ins. 15 ins. in the ground for corner to sections 11, 12, 13 and 14, marked with 4 notches on the S. and 1 notch on the E. edges and raised mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 2nd rate.
 Timber Pine and Oak in canyon. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 12 and 13. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.
 80.12 Intersect the E. boundary 25 lks. N. of corner to sections 7, 12, 13 and 18, which is a
 White Pine 38 ins. dia. marked
 T 2 N, S 7 on NE.
 R 7 W, S 19 on SE.
 R 8 W, S 13 SW. and
 S 12 on NW. with earth mound around tree, from which bears a
 Pine 18 ins. dia. S. 60° E. 96 lks.
 Pine 12 ins. dia. S. 68° W. 58 lks. Thence I run
 N. 89° 49' W. on a TRUE line between sections 12 and 13 with same Variation.

36.00 Summit of divide bears N. 15° E. and S. 15° W. and descend.
 40.06 Set sandstone 26 x 19 x 10 ins. 20 ins. in the ground for ¼ section corner marked ¼ on N. face and raised mound of stone alongside.

From which bears a
Pine 14 ins. dia. N. 20° W. 1.17 chs.
Pine 16 ins. dia. S. 29° E. 86 lks. Both marked $\frac{1}{4}$ S B T.

63.10 In Cow Canyon, course South.
72.00 Creek 11 lks. wide, course South.
80.12 The corner to sections 11, 12, 13 and 14.
Land mountainous. Soil 2nd rate. Timber Pine and Oak.
Dense undergrowth of Chaparral.

NORTH between sections 11 and 12. Var. 14° 26 $\frac{1}{2}$ ' E.

9.20 Leave canyon, course S. 15° W. and ascend.
40.00 Set granite stone 11 x 11 x 10 ins. 6 ins. in the ground $\frac{1}{4}$ section
corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.
70.00 Summit of high ridge bears NE and S. 20° W. and descend.
80.00 Set sandstone 14 x 11 x 8 ins. 9 ins. in the ground for corner to
sections 1, 2, 11 and 12, marked with 5 notches on S. and 1 notch
on E. edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 2nd rate.
Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 1 and 12. Var. 14° 26 $\frac{1}{2}$ ' E.

40.00 Set temporary $\frac{1}{4}$ section corner.
79.88 Intersect the East boundary of Tp. at 11 lks. N. of corner to secs.
1, 6, 7 and 12, which is a granite stone 15 x 10 x 6 ins. 10 ins. in
the ground marked with 5 notches on the S. and 1 notch on the N. edges
and mound of stone alongside. Thence I run
N. 89° 55' W. on a TRUE line between sections 1 and 12 with same
Variation.

39.94 Set granite stone 16 x 9 x 8 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
corner marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable.
69.50 Top of ridge bears N. 50° E. and S. 50° W. and descend.
79.88 The corner to sections 1, 2, 11 and 12.
Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak.
Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 1 and 2. Var. 14° 26 $\frac{1}{2}$ ' E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.66 Intersect the N. boundary 41 lks. west of corner to sections 1, 2,
35 and 36. Thence I run
S. 0° 17' W. on a TRUE line between sections 1 and 2, with same
Variation.

40.66 Set granite stone 16 x 12 x 4 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.
51.00 Ravine, 50 lks. wide, course SW. and ascend.
80.66 The corner to sections 1, 2, 11 and 12.
Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak
Dense undergrowth of Chaparral.

From the corner to sections 2, 3, 34 and 35 on the S. boundary of the
Tp. I run
NORTH between sections 34 and 35. Var. 14° 26 $\frac{1}{2}$ ' E.

40.00 Set sandstone 17 x 9 x 6 ins. 12 ins. in the ground for $\frac{1}{4}$ section corner,
marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.
80.00 Set sandstone 16 x 11 x 5 ins. 11 ins. in the ground for corner to
sections 26, 27, 32 and 35, marked with 2 notches on the E. and 1
notch on the S. edge and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 2nd rate.
Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 26 and 35. Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.60 Intersect the N. & S. line 55 lks. N. of corner to sections 25, 26, 35 and 36. Thence I run

N. $89^{\circ} 36'$ W. on a TRUE line between sections 26 and 35 with same Variations.

13.50 Gulch 30 lks. wide, course S. and ascend.
30.00 Top of ridge bears N. & S. and descend.
40.30 Set sandstone 12 x 11 x 7 ins. 7 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
60.50 Gulch 10 lks. wide, course S. and ascend.
78.00 Summit of ridge bears N. 5° W. and S. 5° E. and descend.
80.60 The corner to sections 26, 27, 34 and 35. Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 26 and 27. Var. $14^{\circ} 26\frac{1}{2}'$ E.

6.00 Summit of ridge bears N. and S. 5° E.
40.00 Set sandstone 12 x 9 x 6 ins. 7 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. Pits impracticable. From which bears a
Pine 11 ins. dia. S. 27° W. 170 lks. marked $\frac{1}{4}$ S B T.
No other trees within limits.
41.00 Leave summit bears NE. & SW. and descend.
45.50 Head of gulch, course W. and ascend.
66.50 Top of spur bears N. 60° W. and descend.
80.00 Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for corner to sections 22, 23, 26 and 27, marked with 2 notches on the S. & E. edges and raised mound of stone alongside. Pits impracticable. From which bears an
Oak 14 ins. dia. S. $23\frac{3}{4}^{\circ}$ W. 167 lks. marked
T 2 N, R 8 W, S 27 BT.
Pine 8 ins. dia. N. 7° E. 261 lks. marked
T 2 N, R 8 W, S 23 BT.
No other trees within limits. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 23 and 26. Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.38 Intersect the N. & S. line 21 lks. S. of corner to sections 23, 24, 25 and 26. Thence I run

S. $89^{\circ} 51'$ W. on a TRUE line between sections 23 and 26, with same Variation.

17.50 Summit of divide bears NE. & SW. and descend.
40.19 Set sandstone 10 x 11 x 9 ins. 6 ins. in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
51.60 Cross gulch near head, course SW. and ascend.
80.38 The corner to sections 22, 23, 26 and 27. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 22 and 23. Var. $14^{\circ} 26\frac{1}{2}'$ E.

11.20 Enter Cow Canyon, course West.
17.00 Creek 10 lks. wide, course West.
19.20 Leave canyon, course West and ascend.
40.00 Set sandstone 15 x 9 x 8 ins. 10 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. From which bears a
Pine 12 ins. dia. N. 70° E. 217 lks.
Pine 10 ins. dia. S. 61° W. 300 lks. Both marked $\frac{1}{4}$ S B T.

70.00 Summit of high ridge bears NE. & SW. and descend.
80.00 Set granite rock 18 x 11 x 7 ins. 13 ins. in the ground for corner to sections 14, 15, 22 and 23, marked with 3 notches on the S. and 2 notches on the E. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 14 and 23. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.
80.27 Intersect the N. & S. line 32 lks. N. of corner to sections 13, 14, 23 and 24. Thence I run
N. 89° 46' W. on a TRUE line between sections 14 and 23, with same Variation.

7.00 Enter Cow Canyon, course South.
18.20 Creek 9 lks. wide, course South.
29.30 Leave canyon, course South and ascend.
40.14 Set sandstone 13 x 12 x 6 ins. 8 ins. in the ground for ¼ section corner, marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.
78.00 Top of high ridge bears N. 20° E. and S. 20° W. and descend.
80.27 The corner to sections 14, 15, 22 and 23. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 14 and 15. Var. 14° 26½' E.

40.00 Set sandstone 13 x 10 x 4 ins. 8 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside. Pits impracticable.
80.00 Set sandstone 18 x 11 x 6 ins. 13 ins. in the ground for corner to sections 10, 11, 14 and 15, marked with 4 notches on the S. and 2 notches on the E. edges and raised mound of stone alongside. Pits impracticable. From which bears a
Pine 10 ins. dia. S. 19° W. 177 lks. marked
T 2 N, R 8 W, S 15 BT.
Pine 12 ins. dia. N. 51½° E. 198 lks. marked
T 2 N, R 8 W, S 11 BT.
Oak 10 ins. dia. N. 80° E. 211 lks. marked
T 2 N, R 8 W, S 11 BT.
No other trees within limits. Soil 2nd rate. Timber Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 11 and 14. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.
80.10 Intersect the N. & S. line at 37 lks. N. of the corner to sections 11, 12, 13 and 14. Thence I run
N. 89° 44' W. on a TRUE line between sections 11 and 14 with same Variation.

39.00 Summit of divide bears N. 40° E. and S. 40° W. and descend.
40.05 Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for ¼ section corner marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.
80.10 The corner to sections 10, 11, 14 and 15. Land mountainous. Soil 2nd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 10 and 11. Var. 14° 26½' E.

6.00 Ravine 50 lks. wide, course SW. and descend.
40.00 Set sandstone 14 x 11 x 7 ins. 9 ins. in the ground for ¼ section corner marked ¼ on W. face and raised mound of stone alongside. Pits impracticable.
41.20 Summit of ridge bears NE. & SW. and descend.
80.00 Set sandstone 17 x 9 x 6 ins. 12 ins. in the ground for corner to

sections 2, 3, 10 and 11, marked with 5 notches on S. and 2 notches on E. edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on RANDOM line between sections 2 and 11. Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.00 Intersect the N. & S. line at 25 lks. N. of corner to sections 1, 2, 11 and 12. Thence I run

N. $89^{\circ} 49'$ W. on a TRUE line between sections 2 and 11, with same Variation.

21.70 Ravine 40 lks. wide, course SW. and ascend.
40.00 Set sandstone 20 x 11 x 9 ins. 15 ins. in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable.

58.00 Top of ridge bears N. 30° E. and S. 30° W. and descend.
80.00 The corner to sections 3, 2, 10 and 11.
Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak.
Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 2 and 3. Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
81.41 Intersect the North boundary of the Tp. 36 lks. West of corner to sections 2, 3, 34 and 35. Thence I run

S. $0^{\circ} 15'$ W. on a TRUE line between sections 2 and 3, with same Variation.

41.41 Set granite stone 17 x 9 x 8 ins. 12 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.

81.41 The corner to sections 2, 3, 10 and 11.
Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak.
Dense undergrowth of Chaparral.

From the corner to sections 34, 33, 3 and 4, on the South boundary of the Township, I run

NORTH between sections 33 and 34. Var. $14^{\circ} 26\frac{1}{2}'$ E.

12.30 Summit of divide bears NE. & SW. thence along summit.
37.00 Leave summit and descend.
40.00 Set granite stone 13 x 11 x 9 ins. 8 ins. in the ground for $\frac{1}{4}$ section corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
61.60 Cross gulch near head course N. 50° W. and ascend.
80.00 Set granite stone 12 x 11 x 9 ins. 7 ins. in the ground for corner to sections 27, 28, 33 and 34 and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 27 and 34. Var. $14^{\circ} 26\frac{1}{2}'$ E.

40.00 Set temporary $\frac{1}{4}$ section corner.
80.57 Intersect the N. & S. line 42 lks. S. of corner to sections 26, 27, 34 and 35. Thence I run

S. $89^{\circ} 42'$ W. on a TRUE line between sections 27 and 34 with same Variation.

20.00 San Dimas Creek near head 5 lks. wide, course S. and ascend.
40.28 Set granite stone 16 x 9 x 8 ins. 11 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable. Top of divide bears NE. & SW. and descend.
80.57 The corner to sections 27, 28, 33 and 34.
Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak.
Dense undergrowth of Chaparral.

NORTH between sections 27 and 28.

Var. 14. 26½' E.

- 30.00 Top of ridge bears NW. & SE. and descend
40.00 Set sandstone 16 x 9 x 9 ins. 11 ins. in the ground for ¼ section
corner, marked ¼ on W. face and raised mound of stone alongside.
Pits impracticable.
80.00 Set granite stone 21 x 14 x 6 ins. 16 ins. in the ground for corner
to sections 21, 22, 27 and 28 marked with 2 notches on the S. and 3
notches on E. edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 22 and 27

Var. 14. 26½' E.

- 40.00 Set temporary ¼ section corner.
80.43 Intersect the N. & S. line 19 lks. N. of corner to sections 22, 23,
26 and 27. Thence I run

N. 89° 52' W. on a TRUK line between sections 22 and 27 with same
Variation.

- 39.60 Summit of spur bears N. 60° W. and descend
40.22 Set sandstone 12 x 11 x 7 ins. in the ground for ¼ section
corner, marked ¼ on N. face and raised mound of stone alongside.
Pits impracticable.
77.60 Gulch 30 lks. wide, course NW. and ascend
80.43 Corner to sections 21, 22, 27 and 28
Land mountainous. Soil 3rd rate. Timber Pine and Oak
Dense undergrowth of Chaparral.

NORTH bet. Sections 21 and 22
Descend

Var. 14. 26½' E

- 1.70 Gulch 30 lks wide Course NW.
3.00 Enter Cow Canyon Course W
11.00 Creek 10 lks. wide Course W
12.50 Leave Canyon Course W and ascend
21.00 Point of spur bears SW. and descend
38.00 Timbered Rav. 50 lks. wide Course SW. and Ascend
40.00 Set sandstone 14x10x6 in. 9 in. in the ground for 1/4 Sec. corner
marked 1/4 on West face and raised a mound of stone alongside
From which bears a
Pine 12" diameter South 33° W. 81 lks. dist.
Sycamore 22" in diameter South 32½ East 1.37 chs. dist.
Both marked 1/4 S.B.T.

75.00 Top of spur bears South 30° W and descend

80.00 Set granite stone 16x11x9, 11 inches in the ground for corner to
Sections 15, 16, 21 and 22 marked with 3 notches on South and
East edges and raised a mound of stone alongside.

Pits impracticable

Land mountainous

Soil third rate

Timber scattering pine and oak dense undergrowth of chaparral.

EAST on random line between Sections 15 and 22

Var. 14. 26½' E.

- 40.00 Set temporary 1/4 Sec Cor.
80.19 Intersect the N & So. line 46 links N of cor. to Secs. 14, 15, 22, & 23
Thence I run

N 89°40' West on a true line bet. Sections 15 and 22 with same variation

Descend

36.00 Timbered ravine 50 lks. wide Course S 80° West and ascend

40.09 Set sandstone 16x10x4 inches 11 inches in the ground for 1/4 Sec.
corner marked 1/4 on N face from which bears a

Pine 16 inches diameter North 17° W. 3.00 chs. dist.
Oak 12 inches diameter South 31° E. 1.22 chains dist.
Both marked 1/4 S.B.T.

69.90 Top of ridge bears North 50° E and South 50° West and descend

80.19 The cor. to Sections 15, 16, 21 and 22

Land mountainous - Soil 2nd rate Timber pine and oak in ravines
Dense undergrowth of chaparral.

North between Sections 15 and 16

Var. 14°26 1/2' E.

Descend

29.15 Timbered ravine 60 lks. W Course South 80° W and ascend

40.00 Set sandstone 14x9x8 ins., 9 ins. in the ground for 1/4 Sec.
cor. marked 1/4 on W face and raised a mound of stone alongside
Pits impracticable.

80.00 Set granite stone 17x11x4 ins., 12 ins. in the ground for cor.
to Secs. 9, 10, 15 and 16 marked with 4 notches on South and
3 notches on E. edge and raised a mound of stone alongside.

Pits impracticable Land Mountainous
Soil 3rd rate
Timber, pine and oak in ravine, dense undergrowth of chaparral

EAST ON RANDOM line between Secs. 10 and 15 Var. 14° 26 1/2' E.

40.00 Set temporary 1/4 Sec. Cor.

79.90 Intersect North & South line 21 lks. So. of Cor. to Secs. 10, 11, 14 and 15

Thence I run

S. 89° 51' W. on a true line bet. Secs. 10 and 15, with same variation.

Descend

1.85 Timbered ravine 40 lks. W. Course South 20° W. and ascend

23.60 Top of ridge bears No. 15° E. and S. 15° W. and descend

39.95 Set a sandstone 17x12x8 ins., 12 ins. in the ground for 1/4 Sec. Cor.
marked 1/4 on No. face and raised a mound of stone alongside
Pits impracticable

46.75 Ravine 55 lks. wide Course So. 10° W. and ascend

79.90 The Cor. to Secs. 9, 10, 15 & 16.

Land mountainous

Soil 3rd rate

Timber, pine, oak and a few sycamore trees in ravines

Dense undergrowth of chaparral brush

NORTH between Sections 9 and 10
Ascend

Var. 14° 26½' E.

40.00 Set sandstone 20 x 18 x 6 ins. 15 ins. in the ground for ¼ section
Corner, marked ¼ on W. face and raised mound of stone alongside.
Pits impracticable
50.00 Set granite stone 17 x 9 x 7 ins. 12 ins. in the ground for corner
to sections 3, 4, 9 and 10, marked with 5 notches on the S. and 3
notches on the E. edges and raised mound of stone alongside
Pits impracticable. Land mountainous. Soil 3rd rate
Timber none. Dense undergrowth of chaparral.

EAST on a RANDOM line between Sections 3 and 10. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner
50.12 Intersect the N. & S. line at 29 lks. No. of corner to Sections 2, 3
10 and 11 Thence I run

N. 89° 47' W. on a TRUE line between Sections 10 and 3, with same
variation

11.45 Timbered ravine 40 lks. wide, course S. 5° W. and ascend
40.06 Set sandstone 11x10x10 ins. 6 ins. in the ground for ¼ section
corner marked ¼ on N. face and raised mound of stone alongside
Pits impracticable
50.12 The corner to sections 3, 4, 9 and 10
Land mountainous. Soil 3rd rate. Timber Pine and Oak in ravines
Dense undergrowth of chaparral.

NORTH on a RANDOM line between Sections 3 and 4. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner
52.31 Intersect the North boundary of Tp. at 52 lks. W. of corner to
Sections 3, 4, 33 and 34 Thence I run

S 0° 22' W. on a TRUE line between Sections 3 and 4 with same
variations

Ascend
42.31 Set sandstone 16 x 12 x 5 ins. 11 ins. in the ground for ¼ section
corner, marked ¼ on W. face and raised mound of stone alongside
Pits impracticable

59.75 Summit of high ridge bears N. 5° E. and S. 15° W. and descend
52.31 The corner to sections 3, 4, 9 and 10. Land mountainous
Soil 3rd rate. Timber none. Dense undergrowth of chaparral.

From the established corner to Sections 32, 33, 4 and 5 on the S.
boundary of the Township, I run

North between sections 32 and 33
Descend

Var. 14° 26½' E.

18 ins.
40.00 Set sand rock 24x17x9 ins./in the ground for ¼ section
corner, marked ¼ on W. face and raised mound of stone alongside
Pits impracticable.
73.60 Timber gulch 30 lks. wide, course N.W. and ascend
50.00 Set granite stone 19x11x5 ins. 14 ins. in the ground for corner
to sections 28, 29, 32 and 33, marked with 4 notches on the E. and
1 notch on the S. edges and raised mound of stone alongside
Pits impracticable. Land mountainous Soil 3rd rate.
Timber Oak and Pine Undergrowth of dense chaparral.

EAST on a RANDOM line between sections 28 and 33. Var. 14° 26½' E.

40.00 Set temporary ¼ section corner
50.63 Intersect the N. & S. line at 39 lks. N. of corner to sections 28,
27, 33 and 34. Thence I run
N. 89° 43' W. on a TRUE line between sections 28 and 33 with same
variation

Descend
 20 00 Ravine 30 lks. wide, course NW. and ascend
 40 31 Set sandstone 17 x 9 x 9 ins. in the ground for 1/4 Sec.
 cor. marked $\frac{1}{4}$ on N. face and raised mound of stone alongside
 Pits impracticable
 55.00 Top of spur course N. 50° W. and descend
 80.63 The corner to Sections 28, 29, 32 and 33
 Land mountainous. Soil 3rd rate. Timber scattering pine and oak
 Dense undergrowth of chaparral.

NORTH between Sections 28 and 29. Var. 14°26 $\frac{1}{2}$ ' E.
 Ascend

18.90 Top of spur bears N. 50° W. and descend
 29.60 Timbered ravine 30 lks. wide, course NW and ascend
 40 00 Set sandstone 10x9x5 ins. in the ground for $\frac{1}{4}$ section
 cor., marked on W. face $\frac{1}{4}$ and raised mound of stone alongside
 Pits impracticable.
 60.00 Top of spur bears N. 50° W. and descend
 80.00 Set granite stone 19 x 11 x 5 ins. 14 ins. in the ground for corner
 to sections 20, 21, 28 and 29, marked with 4 notches on E. and
 2 notches on the S. edge and raised a mound of stone alongside.
 Pits impracticable. Soil 3rd rate. Timber Oak and Pine
 Undergrowth of Oak and Chaparral.

Mar. 3, 1884

EAST on random line bet. Secs. 21 and 28 Var. 14°26 $\frac{1}{2}$ ' E.

40.00 Set temp. 1/4 Sec. Cor.
 80.00 Intersect N. & So. line at cor. to Secs. 21, 22, 27 and 28
 Thence I run
 West on a true line bet. Secs. 21 and 28 with same variation
 Descend gradually and along So. bank of creek in Cow Canyon
 40.00 Set granite stone 13x12x7 ins. 8 ins. in the ground for 1/4 Sec.
 cor. marked 1/4 on No. face.
 From which bears a
 Sycamore 14 ins. diam. North 20° W. 17 lks. dist.
 Pine 16" diam. S. 39° E. 1.17 chs. dist.
 Both marked 1/4 S B T
 72.00 Leave canyon and ascend N. slope of spur
 80.00 The cor. to Secs. 20, 21, 28 and 29
 Land mountainous, soil 2nd rate, Timber pine, oak and sycamore
 in canyon Dense undergrowth of chaparral.

North bet. Secs. 20 and 21 Var. 14°26 $\frac{1}{2}$ ' E.
 Descend

3.60 Enter Cow Canyon Course W.
 11.40 Creek 12 lks. wide, course West
 14.30 Leave Canyon and ascend Course West
 30.00 Point of spur bears West and descend
 40.00 Set granite stone 16x9x5 ins., 11 ins. in the ground for
 1/4 Sec. Cor. marked 1/4 on W. face and raised a mound of
 stone alongside
 Pits impracticable
 61.60 Timbered ravine 65 lks. wide Course SW. and ascend
 80.00 Set a granite stone 17x11x5, 12 ins. in the ground for Cor. to
 Secs. 16, 17, 20, 21 marked with 5 notches on So. and
 4 notches on E. edges and raised mound of stone alongside
 Pits impracticable. Land mountainous soil 3rd rate

40.00 East on random line between Secs. 16 and 21 Var. 14° 26½' E.
 80.31 Set temp. 1/4 Sec. Cor.
 Int. N. & S. line 57 lks. N. of cor. to Secs. 15, 16, 21, 22
 Thence I run
 North 89-44' W. on a true line bet. Secs. 16 and 21 with same
 variation

40.15 Descend
 Set sandstone 17x11x6 ins. 12 ins. in ground for 1/4 sec. cor.
 marked 1/4 on No. face and raised a mound of stone alongside.
 Pits impracticable

51.70 Timbered ravine 65 lks. wide Course Southwest and ascend
 80.31 The cor. to Secs. 16, 17, 20 and 21
 Land mountainous, Soil 3rd rate, Timber pine and oak in ravine
 Dense undergrowth of chaparral.

N. bet. Secs. 16 and 17 Var. 14-26½' E.
 Ascend
 11.20 Summit of ridge bears NE. and S.W. about 150 ft. above sec. cor.
 and descend
 40.00 Set sandstone 16x11x5 ins., 12 ins. in the ground for 1/4 sec.
 cor. marked 1/4 on W. face and raised a mound of stone
 alongside
 Pits impracticable
 60.00 Gulch 30 lks. wide Course S.W. and ascend
 80.00 Set granite stone 19x12x8 ins., 14 ins. in the ground for Cor.
 to Secs. 8, 9, 16 and 17 marked with 4 notches on So. and
 4 notches on E. edges and raised a mound of stone alongside
 Pits impracticable. Land mountainous. Soil 3rd rate
 Timber none, Dense undergrowth of chaparral.

E. on random line bet. Secs. 9 and 16 Var. 14-26½' E.
 40.00 Set temp. 1/4 Sec. Cor.
 80.40 Intersect N. and So. line 19 lks. So. of Cor. to Secs. 9, 10, 15, 16
 Thence I run
 South 89-52' W. on a true line bet. Secs. 9 and 16 with same
 variation Ascend
 40.20 Set a granite stone 14x12x11 ins., 9 ins. in the ground for
 1/4 Sec. Cor. marked 1/4 on N. face and raised a mound of stone
 alongside.
 Pits impracticable.
 41.00 Summit of high ridge bears North 10- E. and S. 10- W. about
 500 ft. above last mentioned sec. cor. and descend
 65.20 Gulch 20 lks. wide Course South 40- W. and ascend
 80.40 The cor. to Secs. 8, 9, 16 and 17
 Land mountainous, Soil 3rd rate, Timber none, Dense undergrowth
 of chaparral.

North bet. Secs. 8 and 9 Var. 14-26½' E.
 16.50 Top of spur bears S.W. and descend
 40.00 Set granite stone 16x10x9 ins. 10 ins. in the ground for 1/4 Sec. Co
 marked 1/4 on West face and raised a mound of stone alongside
 Pits impracticable
 51.70 Gulch 50 lks. wide, Course S. 80- W. and ascend
 80.00 Set granite stone 18x11x7 ins. 13 ins. in the ground for cor.
 to Secs. 4, 5, 8 and 9, marked with 5 notches on So. and
 4 notches on the E. edges and raised a mound of stone alongside
 Pits impracticable
 Land mountainous Soil 3rd rate Timber none
 Dense undergrowth of chaparral

EAST on random line bet. Secs. 4 and 9. Var. 14-26½' E.

40.00 Set temp. 1/4 Sec. Cor.
79.16 Intersect North and South line 17 links N. of cor. to
Secs. 3, 4, 9 and 10
Thence I run
North 89-53' W. on a true line bet. Secs. 4 and 9 same variation
Ascend
12.20 Top of high ridge bears North 10° E. and S. 10° W. about 150 ft.
above Sec. Cor. and descend
39.00 Head of gulch Course S.W. and ascend
39.90 Set sandstone 16x9x8 ins., 11 ins. in the ground for 1/4 Sec. Cor.
marked 1/4 on No. face, and raised a mound of stone alongside.
Pits impracticable.
79.80 The cor. to Secs. 4, 5, 8 and 9
Land mountainous Soil 3rd rate, Timber none Dense
Undergrowth of chaparral

NORTH on a RANDOM line between Sections 4 and 5. Var. 14-26½' E.
Ascend

40.00 Set temp. 1/4 sec. cor.
83.16 Intersect the North boundary of Tp. 23 lks. E. of corner to secn.
4, 5, 32 and 33. Thence I run
S. 8-10' E. on a TRUE line between Sections 4 and 5 with same
variation
43.16 Set granite rock 19x14x5 ins. 14 ins. in the ground for 1/4 sec.
cor. marked 1/4 on W. face and raised mound of stone alongside
Pits impracticable
62.30 Top of spur bears W. and descend
83.16 The corner to sections 4, 5, 8 and 9
Land mountainous. Soil 3rd rate. Timber, none
Dense undergrowth of Chaparral

From the corner to Sections 5, 6, 31 and 32 on the South boundary
of the Township, I run

NORTH between Sections 31 and 32 Var. 14-26½' E.
Ascend

40.00 Set granite stone 14x9x6 ins., 9 ins. in the ground for 1/4 sec.
cor., marked 1/4 on W. face and raised mound of stone alongside
Pits impracticable.
80.00 Set sandstone 14x9x8 ins. 9 ins. in the ground for corner to
sections 29, 30, 31 and 32, marked with 1 notch on the S. and 5
notches on the E. edges and raised a mound of stone alongside
Pits impracticable. Soil 3rd rate
Land mountainous, Timber and Oak and Pine. Undergrowth of Chaparral

WEST on a RANDOM line between Sections 30 and 31. Var. 14-26½' E.

40.00 Set temporary 1/4 sec. cor.
82.13 Intersect the W. boundary of Tp. 23 lks. N. of corner to sections
25, 30, 31 and 36. Thence I run
N. 89-50' E. on a true line between Sections 30 and 31 with same
Ascend variation
5.40 Summit of ridge bears N. & S. about 50 ft. above sec. cor. Descend
42.13 Set sandstone 17 x 12 x 6 ins. 12 ins. in the ground for 1/4 Sec.
Cor, marked 1/4 on N. face, and raised mound of stone alongside.
Pits impracticable
48.70 Ravine 60 lks. wide course N. 50° W. and ascend

82.13 The corner to Sections 29, 30, 31 and 32
Land mountainous. Soil 3rd rate. Timber, none
Undergrowth Chaparral.

40.00 EAST on a RANDOM line between Sections 29 and 32. Var. 14° 26½' E.
Set temporary ¼ section corner
80.26 Intersect the N. & S. line 34 lks. S. of corner to sections 28, 29,
32 and 33. Thence I run

S. 89° 45' W. on a TRUE line between sections 29 and 32 with same
variation

Descend
5.80 Ravine 40 lks. wide, course NW and ascend
40.13 Set sandstone 19 x 12 x 6 ins. 14 ins. in the ground for ¼ section
corner, marked ¼ on N. face and raised mound of stone alongside
Pits impracticable.

80.26 The corner to sections 29, 30, 31 and 32
Land mountainous. Soil 3rd rate. Timber none
Dense undergrowth of Chaparral.

NORTH between sections 29 and 30 Var. 14° 26½' E.
Ascend
11.60 Top of spur bears N. 40° W. and descend
40.00 Set sandstone 16 x 11 x 9 ins. 11 ins. in the ground for ¼ section
corner, marked ¼ on W. face and raised mound of stone alongside
Pits impracticable.

63 20 Enter Canyon of Cow Creek, course West
73 15 San Cow Creek 40 lks. wide, course West

73.25 Leave canyon, course West and ascend abruptly

80.00 Set granite stone 12 x 11 x 8 ins. 7 ins. in the ground for corner
to sections 19, 20, 29 and 30, with 2 notches on the S. and
5 notches on the E. edges. From which bears a
Pine 22 ins. dia. N. 71° E., 109 lks. marked
T. 2 N., R S W., S 29 BT
Pine 8 ins. dia. N. 47° W., 94 lks. marked
T. 2 N., R S W., S 19 BT
Pine 10 ins. dia. S. 81° W., 78 lks. marked
T. 2 N., R S W., S 30 BT
Pine 14 ins. dia. S. 14° E. 66 lks. marked
T. 2 N., R S W., S 29 BT
Pits impracticable
Land mountainous
Timber Pine and Oak
Dense undergrowth of chaparral.

West on a random line between sections 19 and 30
Var. 14° 26½' E.

40.00 Set temporary 1/4 sec. cor.
82.88 Intersect west boundary and township 47 links north of corner to
sections 19, 24, 25 and 30.
Thence I run
North 89° 40' East on a true line between sections 19 and 30
with same variation. Descend
21.00 Enter San Gabriel Canyon course South 10° West.

21.70 San Gabriel River 60 links wide course South 10° West
 28.60 Leave canyon course South 10° West and ascend
 42.88 Set granite stone 17 x 9 x 8 inches, 12 inches in the ground for
 1/4 section corner marked 1/4 on N. face and raised mound of
 stone alongside. Pits impracticable
 47.60 Point of spur bears southwest and descend
 82.88 The corner to Sections 19, 20, 29 and 30
 Land mountainous
 Soil third rate
 Timber pine and oak in ravine
 Dense undergrowth of chaparral brush

East on a random line between Sections 20 and 29

Variation 14° 26 1/2' E.

40.00 Set temporary ^{1/4} section corner
 50.18 Intersect north and south line 41 links S. of corner to
 Secs. 20, 21, 28 and 29 Thence I run
 South 89° 42' West on a true line between Sections 20 and 29
 with same variation. Ascend
 22.60 Point of spur bears northwest and descend
 40.09 Set granite stone 13x11x7 ins., 8 ins. in the ground for 1/4
 section corner marked 1/4 on N. face, from which bears an
 Oak 14 inches in diameter South 19° E. 42 lks. distant
 Pine 18 inches diameter South 22° West 93 links distant
 Both marked 1/4 S. B. T.
 41.60 Enter Cow Canyon course South
 47.00 Creek 12 links wide course south
 48.15 Leave canyon course south and ascend
 80.18 The corner to sections 19, 20, 29 and 30
 Land mountainous
 Soil 2nd rate
 Timber pine and oak in canyon
 Dense undergrowth of chaparral.

North between Secs. 19 and 20

Variation 14° 26 1/2' E.
 Ascend

30.40 Top of ridge bears NE. and SW about 200 ft. above Sec. Cor. and
 descend
 40.00 Set sandstone 12x11x7 ins., 7 ins. in the ground for 1/4
 Sec. cor. and marked 1/4 on the N. face and raised a mound of
 stone alongside
 Pits impracticable

63.00 Enter San Gabriel Canyon Course S. 40° West

66.70 San Gabriel River 50 lks. wide Course S. 40° West
 68.50 Leave Canyon and ascend over low point
 80.00 Set sandstone 17x12x6 ins. 12 ins. in the ground for corner
 to Secs. 17, 18, 19, 20 marked with 3 notches on South
 and 5 notches on east edges, from which bears a

Pine 14 ins. diameter North 11° E. 49 lks. dist.
 marked T 2 N., R. 8 W., Sec. 17 B T

Pine 18 ins. diameter North 17½° W. 1.19 chs. dist.
 marked T. 2 N R. 8 W. Sec. 18 B T

Oak 20 ins. in diameter, South 60° West 1.33 chs. dist.
 marked T. 2 N., R. 8 W. Sec. 19 B T

Pine 20 ins. in diameter South 45° E. 1.46 chs.
 dist. marked T 2 N., R. 8 W. Sec. 20 B T

Land mountainous, soil 2nd rate, Timber Pine and oak in
 canyons. Dense undergrowth of chaparral

March 5, 1884

West on random line bet. 18 and 19 Var. 14° 26½' E.

40.00 Set Temp. 1/4 Sec. Cor.
 52.34 Int. W. bdy. of Tp. 19 lks South of cor to Secs. 13, 18, 19 and 24

Thence I run

South 59° 52' E. on a true line bet. Secs. 18 and 19 with
 same variation Ascend

22.60 Top of ridges bears N. & S., About 100 ft. above Sec. Cor. and
 descend

42.34 Set sandstone 11x11x9 ins. 6 ins. in the ground for 1/4
 Sec. Cor. Marked 1/4 on N face and raised a mound of stone
 alongside

Pits impracticable

52.34 The corner to Sections 17, 18, 19 and 20
 Land mountainous, soil 3rd rate, Timber none
 Dense undergrowth of chaparral

East on a random line between Secs. 17 and 20 Var. 14° 26½' E.

40.00 Set temp. 1/4 Sec. Cor.

50.12 Intersect North and South line at 29 lks. S. of cor. to
 Secs. 16, 17, 20 and 21

Thence I run

South 59° 48' W. on a true line between Sections 17 and 20
 with same variation Ascend

10.00 Top of high ridge bears N.E. and S.W. and descend
 40.06 Set sandstone 12x10x5 ins., 7 ins. in the ground for 1/4 Sec. Cor.
 marked 1/4 on N face. Raised a mound of stone alongside
 Pits impracticable.

71.00 Enter San Gabriel Canyon Course South
 72.70 San Gabriel River 70 lks. Wide Course South
 76.00 Leave canyon and ascend
 80.12 The corner to Secs. 17, 18, 19, 20
 Land mountainous
 Soil 2nd rate
 Timber pine and oak in canyon
 Dense undergrowth of chaparral

North bet. Sections 17 and 18 Variation 14° 26½' E.

Ascend on low point

11.00 Leave point and descend abruptly into San Gabriel Canyon
 19.00 Cross San Gabriel River 45 lks. wide Course So. 30° East
 Thence up canyon

30.00 San Gabriel River 50 lks. Wide Course So. 40° West
 36.00 Leave canyon Course South 40° West and ascend

40.00 Set sandstone 14x12x6 ins. 9 ins. in the ground for 1/4
 Sec. Cor. marked 1/4 on West face from which bears a

Pine 14 ins. diam. North 50° E. 2.10 chs. dist.
 Oak 18 ins. diam. N. 46° W. 1.55 chs. dist.
~~Oak 18 ins. diam. North 46° W. 1.55 chs. dist.~~
 Both marked 1/4 S B T

56.50 Point of spur bears South 10° East and descend
 80.00 Set sandstone 15x11x7 ins. 10 ins. in the ground for
 cor. to Secs. 7, 8, 17, 18 and marked with 4 notches
 on So. and 5 notches on east edges and raised a mound
 of stone alongside

Pits impracticable Land mountainous Soil 3rd rate
 Timber pine and oak in Canyons Dense undergrowth of chaparral

West on random line bet. Secs. 7 and 18 Variation 14° 26½' E.

40.00 Set temp. 1/4 Sec. Cor.
 81.79 Int. W. bdy. of Twp. 31 links N. of cor. to Secs. 7, 12, 13, 18
 Thence I run
 North 89° 47' E. on a true line bet. Secs. 7 and 18 with same
 variation Descend

18.00 Ravine 40 links Wide Course S.E. and Ascend
 41.79 Set granite stone 14x9x8 ins., 9 ins. in the ground for
 1/4 Sec. cor. marked 1/4 on N. face and raised a mound of
 stone alongside

Pits impracticable
 66.70 Top of spur bears S.E. and descend
 81.79 The Cor. to Secs. 7, 8, 17 and 18
 Land mountainous
 Soil 3rd rate,
 Timber scattering of pine and oak
 Dense undergrowth of chaparral

March 6, 1884

EAST on random line between Secs. 8 and 17
 Sec.

40 00 Set temp. 1/4 Cor. Variation 14° 26½' E.

80.10 Int. N. & So. line 21 lks. So. of Cor. to Secs. 8, 9, 16, 17
 Thence I run
 South 89° 51' W. on a true line bet. Secs. 8 and 17 with
 same variation Ascend

17.30 Top of spur Bears SW. and descend
 40.05 Set granite stone 13x8x7 ins., 8 ins. in the ground for
 1/4 Sec. Cor. marked 1/4 on No. face and raised
 a mound of stone alongside
 Pits impracticable

56.40 Enter San Gabriel Canyon Course South 3° East
 58.70 San Gabriel River 45 lks. wide Course S. 3° East

61.50 Leave Canyon Course S.E. and descend

80.10 The cor. to Secs. 7, 8, 17 and 18
 Land mountainous
 Soil 2nd rate,
 Timber pine and oak in Canyon
 Dense undergrowth of chaparral

North bet. Secs. 7 and 8 Variation 14.26 1/2' E.
 Descend

21.70 Enter San Gabriel Canyon Course South 15° East
 31.40 San Gabriel River 50 lks. wide Course S. 15° E.

40.00 Set sandstone 12x9x8 ins., 7 ins. in ground for 1/4 sec. cor.
 marked 1/4 on W. face and raised a mound of stone
 alongside

40.80 San Gabriel River 50 lks. wide, Course S. 20° West

51.00 Leave canyon Course So. 15° West and ascend spur

80.00 Set granite stone 13x11x10 ins. 8 ins. in the ground for
 cor. to Secs. 5, 6, 7, 8 marked with 5 notches on the
 So. and east edges and raised a mound of stone alongside.
 Pits impracticable.
 Land mountainous
 Soil 3rd rate,
 Timber Pine and Oak in Canyons Dense undergrowth of chaparral

West on random line bet. Secs. 6 and 7 Variation 14° 26 1/2' E.

40.00 Set temp. 1/4 Sec. Cor.
 82.07 Int. W. boundary of Twp. 57 lks. N. of the cor. to Secs. 1, 6, 7
 and 12
 Thence I run
 North 89° 36' E. on a true line bet. Secs. 6 and 7 with
 same variation Descend

42.07 Set a granite stone 12x11x9 ins., 7 ins. in the ground for
 1/4 Sec. Cor. marked 1/4 on N. face. Raise a mound
 of stone alongside
 Pits impracticable

59.00 Ravine 45 lks. wide Course So. and Ascend

78.60 Top of spur bears North 3° East and South 3° West and descend

82.07 The cor. to Secs. 5, 6, 7 and 8

Land mountains, Soil 2nd rate, Timber pine and oak
in ravine. Dense undergrowth of chaparral

March 7, 1884

East on a random line bet. Secs. 5 and 8 Variation 14°26½' E
40.00 Set temp. Sec. Cor.
79.82 Intersect North and South line 31 lks. So. of Cor. to Secs. 4, 5, 8 & 9
Thence I run
South 89°47' West on a true line bet. Secs. 5 and 8 with same
variation Ascend
25.00 Top of Spur bears S. 40° W. and descend
39.91 Set granite stone 19x12x8 ins., 14 ins. in the ground for 1/4
Sec. Cor. marked 1/4 on N face and raised a mound of
stone alongside
Pits impracticable
53.20 Enter San Gabriel Canyon Course S. 5° West
59.40 San Gabriel River Course S. 5° West 40 lks. Wide
62.50 Leave Canyon Course S. and ascend
79.82 The cor. to Secs. 5, 6, 7 and 8
Land mountainous Soil 3rd rate Timber, pine and oak in
ravine and canyon
Dense undergrowth of chaparral

NORTH on a RANDOM line between Sections 5 and 6 Var. 14° 26½' E.
40.00 Set temporary 1/4 sec. cor.
83.97 Intersect the N. boundary of Twp. 73 lks. West of corner to secs.
5, 6, 31 and 32 Thence I run
S. 0° 31' W. on a TRUE line between Sections 5 and 6 with same
variation
43.97 Set granite stone 18x11x7 ins. 13 ins. in the ground for 1/4 sec.
cor. marked 1/4 on W. face and raised mound of stone alongside.
Pits impracticable
69.00 Top of spur bears S. 5° W. and descend
83.97 The corner to sections 5, 6, 7 and 8
Land mountainous
Soil 3rd rate
Timber scattering Oak and Pine
Dense undergrowth of Chaparral

GEORGE W. PEARSON 1884

U. S. SURVEYOR GENERAL'S OFFICE

SAN FRANCISCO SEPTEMBER 15, 1884

The foregoing field notes of the survey of the subdivision division lines of T. 3 N., R. 8 W., S.B.M. in the State of California, executed by G. W. Pearson, United States Deputy Surveyor, under his contract dated December 10, 1883, having been critically examined and the necessary correction and explanation made, the said field notes they describe are hereby approved.

SEAL

W. H. BROWN

U.S. SURVEYOR GENERAL FOR
CALIFORNIA

U. S. SURVEYOR GENERAL'S OFFICE

SAN FRANCISCO SEPTEMBER 15, 1884

I, U.S. Surveyor General for California, do hereby certify that the foregoing transcript has been correctly copied from the original field notes, as same remain on file in this office.

ATTEST my hand and official seal the day and date herein above written.

W. H. BROWN

U.S. SURVEYOR GENERAL FOR CALIFORNIA