

FIELD NOTES.

T 2 N, Rs. 8 and 9 W. S.B.M.

W B, (part) T 2 N, R 8 W.
(Sections 7, 18, 19.)

E B, (part) T 2 N, R 9 W.
(Sections 12, 13, 24)

ALSO

SUBDIVISIONS.

T 2 N, R ⁹ W.

Between Sections

| | |
|------------------------|------------------------|
| 25 & 26 | 26 & 35 |
| 26 & 27 | 25 & 36 |
| 27 & 28 | 27 & 34 |
| 27 & 34 | 34 & 35 |
| 35 & 36 | |

and

SUBDIVISIONS.

T 2 N, R ⁸ W.

Between Sections

| | |
|---------|------------------------|
| 4 & 9 | 17 & 20 |
| 5 & 8 | 16 & 21 |
| 6 & 7 | 15 & 22 |
| 8 & 9 | 19 & 20 |
| 9 & 10 | 20 & 21 |
| 10 & 15 | 21 & 22 |
| 9 & 16 | 22 & 23 |
| 7 & 18 | 21 & 28 |
| 15 & 16 | 27 & 28 |
| 16 & 17 | 28 & 29 |
| 18 & 19 | 29 & 30 |

Copied from notes loaned by Mr. L. Friel.

| R. 9 W. | | | | R. 8 W. | | | | | | |
|---------|------|------|------|---------|------|------|------|------|----|---------|
| 4 | 3 | 2 | 1 | 6 | 5 | 4 | 3 | 2 | | |
| 9 | 10 | 11 | 12 | 9 7 | 9 8 | 7 9 | 5 10 | 11 | | |
| 16 | 15 | 14 | 13 | 8 18 | 17 | 6 16 | 5 15 | 14 | | |
| T. 2 N. | 21 | 22 | 23 | 24 | 8 19 | 8 20 | 6 21 | 5 22 | 23 | T. 2 N. |
| 28 | 3 27 | 3 26 | 1 25 | 30 | 7 29 | 5 28 | 4 27 | 26 | | |
| 33 | 3 34 | 2 35 | 1 36 | 31 | 32 | 33 | 34 | 35 | | |

T 2 N, Rs. 8 & 9 W. S.B.M.

West Boundary of T 2 N, R 8 W. being also the
East Boundary of T 2 N, R 9 W.

NORTH between sections 19 and 24.

- 40 00 Set granite rock 16 x 11 x 5 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
corner, marked $\frac{1}{4}$ on W. face and raised a mound of stone alongside.
Pits impracticable.
- 80 00 Set a sandstone 21 x 9 x 4 ins. 16 ins. in the ground for corner to
sections 13, 18, 19 and 24, marked with 3 notches on N & S. edges
and raised mound of stone alongside. Pits impracticable.
Land mountainous. Soil 2nd rate.
Timber, scattering Pine and Oak. Undergrowth of Chaparral brush.

NORTH between sections 13 and 18. Var. $14^{\circ} 26\frac{1}{2}'$ E.

Ascending.

- 40 00 Set granite stone 16 x 11 x 5 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.
- 45 00 Top of ridge bears NW & S. 20° E. and descend.
- 80 00 Set sandstone 17 x 11 x 9 ins. 12 ins. in the ground for corner to
sections 7, 12, 13 and 18, marked with 2 notches on the North and
4 notches on the South edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 2nd rate.
Timber, scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 7 and 12. Var. $14^{\circ} 26\frac{1}{2}'$ E.

Descend.

- 20 60 Ravine 112 lks. wide, course SE. and ascend.
- 40 00 Set granite stone 17 x 10 x 5 ins. 12 ins. in the ground for $\frac{1}{4}$ sec.
corner marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
Pits impracticable.
- 49 20 Top of ridge bears NW and SE. and descend.
- 80 00 Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for corner to
sections 1, 6, 7 and 12, marked with 1 notch on North and 5 notches
on South edges and raised mound of stone alongside. Pits impracti-
cable. Land mountainous. Soil 2nd rate.
Timber, scattering Pine and Oak. Dense undergrowth of Chaparral.

Surveyed by G. W. PEARSON, 1884.

SUBDIVISIONS.

T 2 N, R 9 W., S. B. M.

From the established corner to sections 35 and 36, 1 and 2 on the
South boundary of the Township, I run

NORTH between sections 35 and 36. Var. $14^{\circ} 26\frac{3}{4}'$ E.

Ascend.

- 80 00 Set a granite stone 19 x 11 x 15 ins. 14 ins. in the ground for cor.
to sections 25, 26, 35 and 36, marked with 1 notch on the South and
East edges and raised mound of stone alongside. Pits impracticable.
Land mountainous. Soil 3rd rate. Timber, none.

EAST on a RANDOM line between sections 25 and 36.

- 40 00 Set temporary $\frac{1}{4}$ section corner. Var. $14^{\circ} 26\frac{3}{4}'$ E.
- 80 94 Intersect the East boundary of Tp. 36 lks. S. of the corner to secs.
25, 30, 31 and 36. Thence I run

S. $89^{\circ} 45'$ W. on a TRUE line between sections 25 and 36.

Descend. Same variation.
 20 00 Head of gulch, course S. and ascend.
 40 24 Set granite stone 18 x 11 x 6 ins. 13 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.
 41 00 Summit of divide bears N. 10° E. and S. 10° W. and descend.
 52 00 Head of gulch, course N. and ascend.
 65 00 Top of ridge bears N. 85° W. and SE. and descend.
 80 49 The corner to sections 25, 26, 35 and 36. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 25 and 26. Var. 14° 26 $\frac{3}{4}$ ' E.
 40 00 Set temporary $\frac{1}{4}$ section corner.
 80 00 To a point 19 lks. East of corner to sections 23, 24, 25 and 26, which is a part of a decayed post in mound of rocks partially destroyed. I re-build corner by setting a granite stone 20 x 10 x 8 ins. 15 ins. in the ground for corner to sections 23, 24, 25 and 26, marked with 2 notches on the South and 1 notch on the East edges and re-built mound of stones alongside. Pits impracticable. Thence I run S. 0° 08' E. between sections 25 and 26 with same variation.

Ascend.
 3 00 Point of spur W & SW. and descend.
 20 00 San Gabriel River 40 lks. wide, coursed West in canyon 2.14 chs. wide course West and ascend.
 36 00 Top of ridge bears N. 80° W. and S. 80° E. and descend.
 40 00 Set granite stone 20 x 16 x 5 ins. 16 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. Pits impracticable.
 52 30 Ravine 50 lks. wide, course N. 80° W. and ascend.
 71 76 Top of ridge bears N. 85° W. and S. 85° E. and descend.
 80 00 The corner to sections 25, 26, 35 and 36. Land mountainous. Soil 3rd rate. Timber, Pine and Fir along river. Dense undergrowth of Chaparral.

From the corner to sections 34, 35, 2 and 3, on the South boundary of the Township I run
 NORTH between sections 34 and 35. Var. 14° 26 $\frac{3}{4}$ ' E.

80 00 Set granite stone 23 x 11 x 9 ins. 18 ins. in the ground for corner to sections 26, 27, 34 and 35, marked with 2 notches on the East and 1 notch on the South edges, from which bears a
 Fir 16 ins. dia. N. 61° E. 97 lks. marked
 T 2 N, R 9 W, S 26 BT.
 Pine 16 ins. dia. S. 14° E. 210 lks. dist. marked
 T 2 N, R 9 W, S 35 BT.
 Fir 12 ins. dia. S. 44° W. 130 lks. dist. marked
 T 2 N, R 9 W, S 34 BT.
 Fir 14 ins. dia. N. 12 $\frac{1}{2}$ ° W. 47 lks. marked
 T 2 N, R 9 W, S 27 BT.
 Land mountainous. Soil 3rd rate. Timber, Pine and Fir in ravine. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 26 and 35. Var. 14° 26 $\frac{3}{4}$ ' E.
 40 00 Set temporary $\frac{1}{4}$ section corner.
 80 53 Intersect the N & S. line 22 lks. South of the corner to sections 25, 26, 35 and 36. Thence I run S. 89° 51' W. on a TRUE line between sections 26 and 35 with same Variations.

Descend.
 40 26 Set granite stone 16 x 11 x 7 ins. 15 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.

80 53 Pits impracticable.
 The corner to sections 26, 27, 34 and 35.
 Land mountainous. Soil 3rd rate. Timber, none.
 Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 26 and 27, re-tracing 40 chs.

40 00 After diligent search being unable to find old corner I set temporary
 ¼ section corner.

80 12 To a point 14 lks. East of the corner to sections 22, 23, 26 and 27,
 which is a post 4 x 4 ins. firmly set in a mound of rocks marked
 T 2 N, R 9 W, S 23 on NE.
 T 2 N, R 9 W, S 26 on SE.
 T 2 N, R 9 W, S 27 on SW.
 T 2 N, R 9 W, S 22 on NW. faces, thence I run

S. 0°06' E. on a TRUE line between sections 26 and 27, with the
 Same Variations.

Ascend.

1 60 Low point of spur NW. and descend.
 7 20 San Gabriel River 5 lks. wide, course W. in canyon 1.95 chs. wide,
 course W. and ascend.

13 76 Point of spur bears W. and descend.
 20 00 Timbered ravine 60 lks. wide, course NW. and ascend.
 40 06 Set granite stone 17 x 11 x 9 ins. 12 ins. in the ground for ¼ sec.
 corner, marked ¼ on W. face and raised mound of stone alongside.
 Pits impracticable.

65 00 Top of ridge bears E & W. and descend.
 80 12 The corner to sections 26, 27, 34 and 35.
 Land mountainous. Soil 3rd rate. Timber, Pine and Fir.
 Dense undergrowth of Chaparral.

NORTH between sections 33 and 34. Var. 14° 26¼' E.

80 00 Set a granite stone 14 x 9 x 8 ins. 9 ins. in the ground for corner
 to sections 27, 28, 33 and 34, marked with 3 notches on the East
 and 1 notch on the South edges and raised a mound of stone alongside.
 Pits impracticable. Land mountainous. Soil 3rd rate.
 Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 27 and 34. Var. 14° 26¼' E.

40 00 Set temporary ¼ section corner.
 80 14 Intersect the N & S. line 45 lks. South of the corner to sections
 26, 27, 34 and 35. Thence I run

S. 89° 41' W. on a TRUE line between sections 27 and 34, with same
 Variations.

Descend.

7 30 Ravine 70 lks. wide, course N. 50° W. and ascend.
 40 07 Set granite stone 16 x 11 x 4 ins. 11 ins. in the ground for ¼ sec.
 corner, marked ¼ on N. face and raised mound of stone alongside.
 Pits impracticable.

60 20 Top of ridge bears N. 60° W. and S. 60° E. and descend.
 80 14 The corner to sections 27, 28, 33 and 34.
 Land mountainous. Soil 3rd rate. Timber, none.
 Dense undergrowth of Chaparral.

NORTH on a RANDOM line between sections 27 and 28, re-tracing 40 chs.
 Var. 14° 26¼' E.

40 00 After diligent search being unable to find ¼ section corner, I set
 temporary ¼ section corner.

80 20 To a point 14 lks. East of the true point for corner to sections 21,
 22, 27 and 28, and 2.66 chs. W. of Witness Corner to sections 21, 22,
 27 and 28, which is a post 4 x 4 ins. firmly set in a large mound of
 rocks marked

T 2 N, R 9 W, S 22 W.C. on NE.
T 2 N, R 9 W, S 27 W.C. on SE.
T 2 N, R 9 W, S 28 W.C. on SW.
T 2 N, R 9 W, S 21 W.C. on NW. faces, from which bears a

Live Oak 30 ins. dia. N. 29° E. 25 lks. marked
T 2 N, R 9 W, S 22 BT. Thence I run

S. 0° 06' E. on a TRUE line between sections 27 and 28, with same
Variations.

Ascend.

20 00 Top of spur bears N. 80° W. and descend.
39 00 Ravine 60 lks. wide, course N. 80° W. and ascend.
40 10 Set granite stone 16 x 9 x 8 ins. 11 ins. in the ground for $\frac{1}{4}$ sec.
corner, marked $\frac{1}{4}$ on West face and raised mound of stone alongside.
Pits impracticable.
73 20 Top of ridge bears N. 80° W. and S. 80° E. and descend.
80 20 The corner to sections 27, 28, 33 and 34.
Land mountainous. Soil 3rd rate. Timber, none.
Dense undergrowth of Chaparral.

G. W. PEARSON, 1884.

SUBDIVISIONS.

T 2 N, R 8 W. S. B. M.

NORTH between sections 22 and 23.

Var. 14° 26 $\frac{1}{2}$ ' E.

Descend.

80 00 Set granite rock 18 x 11 x 7 ins. 13 ins. in the ground for corner
to sections 14, 15, 22 and 23, marked with 4 notches on the South
and 2 notches on the East edges and raised mound of stone alongside.
Pits impracticable. From which bears a
Pine 10 ins. dia. S. 19° W. 177 lks. marked
T 2 N, R 8 W, S 15 BT.
Pine 12 ins. dia. N. 51 $\frac{1}{2}$ ° E. 198 lks. marked
T 2 N, R 8 W, S 14 BT.
Oak 10 ins. dia. N. 80° E. 211 lks. marked
T 2 N, R 8 W, S 23 BT.

No other tree within limits.

Land mountainous. Soil 2nd rate. Timber, Pine and Oak.
Dense undergrowth of Chaparral.

NORTH between sections 27 and 28.

Var. 14° 26 $\frac{1}{2}$ ' E.

80 00 Set a granite stone 21 x 14 x 6 ins. 16 ins. in the ground for corner
to sections 21, 22, 27 and 28, marked with 2 notches on South and 3
notches on the East edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber, scattering Pine and Oak. Dense undergrowth of Chaparral.

NORTH between sections 21 and 22.

Var. 14° 26 $\frac{1}{2}$ ' E.

Descend.

1 70 Gulch 30 lks. wide, course NW.
3 00 Enter Cow Canyon course West.
11 00 Creek 10 lks. wide, course West.
12 50 Leave canyon, course West and ascend.
21 00 Point of spur bears SW. and descend.
38 00 Timbered ravine 50 lks. wide, course SW. and ascend.
40 00 Set sandstone 14 x 10 x 6 ins. 9 ins. in the ground for $\frac{1}{4}$ section
corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside.
From which bears a
Pine 12 ins. in dia. S. 33° W. 81 lks.
Sycamore 22 ins. dia. S. 32 $\frac{1}{2}$ ° E. 137 lks. both marked $\frac{1}{4}$ S BT.

75 00 Top of spur bears S. 30° W. and descend.
80 00 Set granite stone 16 x 11 x 9 ins. 11 ins. in the ground for corner to sections 15, 16, 21 and 22, marked with 3 notches on the East and South edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber scattering Pine and Oak. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 15 and 22. Var. 14° 26½' E.

40 00 Set temporary ¼ section corner.
80 19 Intersect the N & S. line 46 lks. N. of the corner to sections 14, 15, 22 and 23. Thence I run.

N. 89° 40' W. on a TRUE line between sections 15 and 22 with the same Variations.

Descend.

36 00 Timbered ravine 50 lks. wide, course S. 80° W. and ascend.
40 09 Set sandstone 16 x 10 x 14 ins. 11 ins. in the ground for ¼ section corner, marked ¼ on North face, from which bears a Pine 16 ins. dia. N. 17° W. 3.00 chs. Oak 12 ins. dia. S. 31° E. 1.22 chs. both marked ¼ S BT.

69 90 Top of ridge bears N. 50° E. and S. 50° W. and descend.
80 19 The corner to sections 15, 16, 21 and 22.
79 Land mountainous. Soil 2nd rate. Timber, Pine and Oak in ravine. Dense undergrowth of Chaparral.

NORTH between sections 15 and 16. Var. 14° 26½' E.

29 15 Timbered ravine 60 lks. wide, course S. 80° W. and ascend.
40 00 Set sandstone 14 x 9 x 8 ins. 9 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside. Pits impracticable.

80 00 Set granite stone 17 x 11 x 4 ins. 12 ins. in the ground for corner to sections 9, 10, 15 and 16, marked with 4 notches on South and 3 notches on East edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, Pine and Oak in ravine. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 10 and 15. Var. 14° 26½' E.

40 00 Set temporary ¼ section corner.
79 90 Intersect the N & S. line 21 lks. S. of the corner to sections 10, 11, 14 and 15. Thence I run

S. 89° 51' W. on a TRUE line between sections 10 and 15 with same Variations.

Descend.

1 85 Timbered ravine 40 lks. wide, course S. 20° W. and ascend.
23 60 Top of ridge bears N. 15° E. and S. 15° W. and descend.
39 95 Set a sandstone 17 x 12 x 8 ins. 12 ins. in the ground for ¼ section corner, marked ¼ on N. Face and raised mound of stone alongside. Pits impracticable.

46 75 Ravine 55 lks. wide, course S. 10° W. and ascend.
79 90 The corner to sections 9, 10, 15 and 16. Land mountainous. Soil 3rd rate. Timber, Pine and Oak and a few Sycamore trees in ravine. Dense undergrowth of Chaparral.

NORTH between sections 9 and 10. Var. 14° 26½' E.

Ascend.

40 00 Set a sandstone 20 x 18 x 6 ins. 15 ins. in the ground for ¼ section corner, marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.

80 00 Set granite stone 17 x 9 x 7 ins. 12 ins. in the ground for corner to sections 3, 4, 9 and 10, marked with 5 notches on the South and 3 notches on the East edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

NORTH between sections 28 and 29. Var. 14° 26½' E.

80 00 Set granite stone 19 x 11 x 5 ins. 14 ins. in the ground for corner to sections 20, 21, 28 and 29, marked with 4 notches on the East and 2 notches on the South edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, Pine and Oak in ravine. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 21 and 28. Var. 14° 26½' E.

40 00 Set temporary ¼ section corner.

80 00 Intersect N & S. line at corner to sections 21, 22, 27 and 28. Thence I run

WEST on a TRUE line between sections 21 and 28 with the same Variations.

40 00 Descend gradually and along S. bank of Creek in Cow Canyon. Set granite stone 13 x 12 x 7 ins. 8 ins. in the ground for ¼ sec. corner, marked ¼ on N. face, from which bears a Sy Sycamore 14 ins. dia. N. 20° W. 17 lks. Pine 16 ins. dia. S. 39° E. 117 lks. both marked ¼ S BT.

72 00 Leave canyon and ascend North slope of spur.

80 00 The corner to sections 20, 21, 28 and 29. Land mountainous. Soil 2nd rate. Timber, Pine, Oak and Sycamore in canyon. Dense undergrowth of Chaparral.

NORTH between sections 20 and 21. Var. 14° 26½' E.

Descend.

3 60 Enter Cow Canyon, course W.

11 40 Creek 12 lks. wide, course W.

14 30 Leave Canyon and ascend, course W.

30 00 Point of spur bears West and descend.

40 00 Set granite stone 16 x 9 x 8 ins. 11 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside. Pits impracticable.

61 60 Timbered ravine 65 lks. wide, course SW. and ascend.

80 00 Set granite stone 17 x 11 x 5 ins. 12 ins. in the ground for corner to sections 16, 17, 20 and 21, marked with 3 notches on the South and 4 notches on the East edges and raised mound of stone alongside. Pits impracticable. Timber Pine and Oak in ravines. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 16 and 21. Var. 14° 26½' E.

40 00 Set temporary ¼ section corner.

80 31 Intersect the N & S. line 37 lks. N. of the corner to sections 15, 16, 21 and 22. Thence I run

N. 89° 44' W. on a TRUE line between sections 16 and 21, same Variations.

Descend.

40 00 Set sandstone 17 x 11 x 6 ins. 12 ins. in the ground for ¼ section corner, marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.

51 70 Timbered ravine 65 lks. wide, course SW. and ascend.

80 31 The corner to sections 16, 17, 20 and 21. Land mountainous. Soil 3rd rate. Timber, Pine and Oak in ravines. Dense undergrowth of Chaparral.

NORTH between sections 16 and 17. Var. 14° 26½' E.

Ascend.

11 20 Summit of ridge bears NE & SW. about 150 ft. above corner. Descend.

40 00 Set sandstone 16 x 11 x 5 ins. 11 ins. in the ground for ¼ section corner, marked ¼ on W. face and raised mound of stone alongside. Pits impracticable.

60 00 Gulch 30 lks. wide, course SW. and ascend.

80 00 Set granite stone 19 x 12 x 8 ins. 14 ins. in the ground for corner

to sections 8, 9, 16 and 17, marked with 4 notches on S. and 4 notches on E. edges and raised mound of stone alongside.
Pits impracticable. Land mountainous. Soil 3rd rate.
Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 9 and 16.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

40 00 Set temporary $\frac{1}{4}$ section corner.
80 40 Intersect the N & S. line 19 lks. S. of the corner to sections 9, 10, 15 and 16. Thence I run.

S. $89^{\circ} 52'$ W. on a TRUE line between sections 9 and 16 with the same variations.

40 20 Set granite stone 14 x 12 x 11 ins. 9 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.

41 00 Summit of high ridge bears N. 10° E. and S. 10° W. about 500 feet above last section corner and descend.

65 20 Gulch 20 lks. wide, course S. 40° W. and ascend.

80 40 The corner to sections 8, 9, 16 and 17.
Land mountainous. Soil 3rd rate. Timber, none.
Dense undergrowth of Chaparral.

NORTH between sections 8 and 9.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

Ascend.

16 50 Top of spur bears SW. and descend.

40 00 Set granite stone 15 x 10 x 9 ins. 10 ins. in the ground for $\frac{1}{4}$ sec. corner, marked $\frac{1}{4}$ on W. face and raised mound of stone alongside. Pits impracticable.

51 70 Gulch 30 lks. wide, course S. 80° W. and ascend.

80 00 Set granite stone 18 x 11 x 7 ins. 13 ins. in the ground for corner to sections 4, 5, 8 and 9, marked with 5 notches on the S. and 4 notches on the E. edges and raised mound of stone alongside. Pits impracticable. Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 4 and 9.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

40 00 Set temporary $\frac{1}{4}$ section corner.

79 80 Intersect the N & S. line 17 lks. N. of the corner to sections 3, 4, 9 and 10. Thence I run.

N. $89^{\circ} \frac{55}{33}'$ W. on a TRUE line between sections 4 and 9, with the same variations.

Ascend.

12 20 Top of high ridge bears N. 10° E. and S. 10° W. about 150 feet above section corner and descend.

39 00 Head of gulch, course SE. and ascend.

39 90 Set sandstone 16 x 9 x 8 ins. 11 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside. Pits impracticable.

79 80 The corner to sections 4, 5, 8 and 9.

Land mountainous. Soil 3rd rate. Timber, none.
Dense undergrowth of Chaparral.

NORTH between sections 29 and 30.

Var. $14^{\circ} 26\frac{1}{2}'$ E.

80 00 Set granite stone 12 x 11 x 8 ins. 7 ins. in the ground for corner to sections 19, 20, 29 and 30, marked with 2 notches on the South and 5 notches on the E. edges, from which bears a

Pine 22 ins. dia. N. 71° E. 1.09 chs. marked

T 2 N, R 8 W, S 20 BT.

Pine 18 ins. dia. N. 47° W. 94 lks. marked

T 2 N, R 8 W, S 19 BT.

Pine 10 ins. dia. S. 81° W. 78 lks. marked

T 2 N, R 8 W, S 30 BT.

Pine 14 ins. dia. S. 14° E. ^{66 lks.} marked

T 2 N, R 8 W, S. 29 BT.

Land mountainous. Soil 3rd rate. ^{Timber} Pine & Oak in Canyon.
Dense undergrowth of Chaparral.

NORTH between sections 19 and 20.

Var. 14° 26½' E.

Ascend.

30.40 Top of ridge bears NE & SW. about 200 ft above section corner.

Descend.

40.00 Set sandstone 12 x 11 x 7 ins. 7 ins. in the ground for ¼ section corner, marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.

63.00 Enter San Gabriel Canyon, course S. 40° W.

66.70 San Gabriel River 50 lks. wide, course S. 40° W.

68.50 Leave canyon and ascend low point.

80.00 Set sandstone 17 x 12 x 6 ins. 12 ins. in the ground for corner to sections 17, 18, 19 and 20, marked with 3 notches on S. and 5 notches on E. edges, from which bears a

Pine 14 ins. dia. N. 11° E. 49 lks. marked 33±
T 2 N, R 8 W, S 17 BT.

Pine 18 ins. dia. N. 17½° W. 1.19 chs. marked 79±
T 2 N, R 8 W, S 18 BT.

Oak 20 ins. dia. S. 60° W. 1.33 chs. marked 88±
T 2 N, R 8 W, S 19 BT.

Pine 20 ins. dia. S. 48° E. 1.46 chs. marked 96±
T 2 N, R 8 W, S 20 BT.

Land mountainous. Soil 2nd rate. Timber Pine and Oak in Canon. Dense undergrowth of Chaparral.

WEST on a RANDOM line between sections 18 and 19.

Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.

~~50.00~~ 82.34 Intersect the West boundary of Tp. 19 lks. S. of the corner to secs 13, 18, 19 and 24. Thence I run

S. 89° 52' E. on a TRUE line between sections 18 and 19 with the same Variations.

22.60 Top of ridge bears N & S. about 100 ft. above sec. corner. Descend.

42.34 Set sandstone 11 x 11 x 9 ins. 6 ins. in the ground for ¼ section corner marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.

82.34 The corner to sections 17, 18, 19 and 20.

Land mountainous. Soil 3rd rate. Timber, none. Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 17 and 20.

Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.

80.12 Intersect the N & S. line 29 lks. S. of corner to sections 16, 17, 20 and 21. Thence I run

S. 89° 48' W. on a TRUE line between sections 17 and 20 with the same Variation.

Ascend.

10.00 Top of high ridge bears NE & SW and descend.

40.06 Set sandstone 12 x 10 x 5 ins. 7 ins. in the ground for ¼ section corner marked ¼ on N. face and raised mound of stone alongside. Pits impracticable.

71.00 Enter San Gabriel Canyon, course South.

72.70 San Gabriel River 70 lks. wide, course South.

80.12 The corner to sections 17, 18, 19 and 20.

Land mountainous. Soil 2nd rate. Timber Pine and Chaparral in canyon. Dense undergrowth Chaparral.

WEST on a RANDOM line between sections 7 and 18.

Var. 14° 26½' E.

40.00 Set temporary ¼ section corner.

81.79 Intersect the W. boundary of Tp. 31 lks. N. of corner to sections 7, 12, 13 and 18. Thence I run

N. 89° 47' E. on a TRUE line between sections 7 and 18 with same Variation.

Descend.

- 18 00 Ravine 40 lks. wide, course SE. and ascend.
41 ~~71~~ Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for $\frac{1}{4}$ section
79 corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable.
66 70 Top of spur bears SE. and descend.
81 ~~89~~ The corner to sections 7, 8, 17 and 18.
Land mountainous. Soil 3rd rate. Timber Pine and Oak.
Undergrowth Chaparral.

WEST on a RANDOM line between sections 6 and 7.

Var. 14° 26 $\frac{1}{2}$ ' E.

- 40 00 Set temporary $\frac{1}{4}$ section corner.
82 07 Intersect the West boundary of Tp. 57 lks. North of the corner to
sections 1, 6, 7 and 12. Thence I run

N. 89° 36' E. on a TRUE line between sections 6 and 7, with the Same Variation.

Descend.

- 42 07 Set granite stone 12 x 11 x 9 ins. 7 ins. in the ground for $\frac{1}{4}$ sec.
corner marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable.
59 00 Ravine 45 lks. wide, course S. and ascend.
78 60 Top of spur bears N. 3° E. and S. 3° W. and descend.
82 07 The corner to sections 5, 6, 7 and 8.
Land mountainous. Soil 3rd rate. Timber Pine and Oak in ravine.
Dense undergrowth of Chaparral.

EAST on a RANDOM line between sections 5 and 8.

Var. 14° 26 $\frac{1}{2}$ ' E.

- 40 00 Set temporary $\frac{1}{4}$ section corner.
79 82 Intersect the N & S. line 31 lks. S. of the corner to sections 4,
5, 8 and 9. Thence I run

S. 89° 47' W. on a TRUE line between sections 5 and 8, same Variation.

Ascend.

- 25 00 Top of spur bears S. 40° W. and descend.
39 91 Set granite stone 19 x 12 x 8 ins. 14 ins. in the ground for $\frac{1}{4}$ sec.
corner, marked $\frac{1}{4}$ on N. face and raised mound of stone alongside.
Pits impracticable.
53 26 Enter San Gabriel Canyon, course S. 5° W.
59 40 San Gabriel River course S. 5° W. 40 lks. wide.
62 50 Leave canyon, course S. and ascend.
79 82 The corner to sections 5, 6, 7 and 8.
Land mountainous. Soil 3rd rate.
Timber, Pine and Oak in ravine and canyon.
Dense undergrowth of Chaparral.

G. W. PEARSON, 1884.
