

T 5 N, R 15 W, S.B.M.

From the corner to sections 35, 36, 1 and 2, on the South boundary
I run

NORTH between sections 35 & 36.

Var. 14° 25' E.

Descend.

14.50

Cross gulch 50 lks. wide, course West and ascend.

40.00

Set a post 4 ins. dia. 1 ft in earth, 1 ft above stone mound 4 ft dia. at base by 2 ft high for $\frac{1}{4}$ section corner.

68.50

Top of ridge bears N & S.

Ascend along same.

80.00

The point for corner to sections 25, 26, 35 & 36 falling on steep side hill a place not suitable to build mound, set post 4 ins. sq. 1 ft in earth, 1 ft above stone mound $4\frac{1}{2}$ ft dia. at base by 2 ft high, 35 lks. East for witness post to corner to secs. 25, 26, 35 & 36. Land mountainous.

Soil 2nd rate.

Timber and undergrowth of Cedar, Oak and Chaparral.

North between sections 34 & 35.

Var. 14° 25' E.

Ascend.

40.00

Set post 4 ins. dia. 1 ft in earth, 1 ft above stone mound 4 ft dia. at base by 2 ft high for $\frac{1}{4}$ section corner.

49.50

Top of ridge bears E & W. and descend.

70.50

Cross wash course West and ascend.

71.50

Leave canada and ascend.

80.00

Set post 4 ins. sq. 1 ft in earth, 1 ft above stone mound $4\frac{1}{2}$ ft dia. at base by 2 ft high for corner to sections 26, 27, 34 & 35.

Land mountainous except in valley.

First rate and second rate soil.

Timber and undergrowth of oak, cedar and Manzanita.

By William H. Norway,

October, 1879.



CS 9099 - E. Bdy. Top 5N. R.15W. and
S. Bdy. Top 6N. R.15W.
CS 9101 - For all interior lines