

Subdivision of parts of  
T's 2 & 3 S, R 9 W.

These notes were copied from the original  
Field Books of Henry Hancock, loaned by his son  
Mr. Allan Hancock, to County Surveyor, April, 1918.  
Book No 7 was also marked "#P P 4," and "B 2."  
Book No 8 was also marked "P No 4," and "Book A."

TWP. 2 S. R. 9 W. Govt Field Notes Sec. 31 to 36 C.S. 7850

R 10 W R 9 W	Hancock, 1858						R 9 W R 8 W
	6	5	7 4	3	2	1	
	7	8	9	10	11	12	
	18	17	16	15	14	13	
	19	20	21	22	23	24	
	30	29	28	27	26	25	
	31	32	33	34	35	36	
	6	5	4	3	2	1	
	7	8	9	10	11	12	
	18	17	16	15	14	13	

Var 13° 30' E.  
Nov 29, 1858.

From corner of Secs 9 - 10 - 15 - 16, near the old road to China  
I run  
EAST bet secs 10 & 15.

40 00 Set gray granite rock 15x10x7 for  $\frac{1}{4}$  sec cor. at the head of a small  
valley running into the Canada de Brea  
47 00 To arroyo Course NW. Has oak and sycamore timber.  
63 50 Int. Ranch line of Nogo. Set a post and charred post as per inst.  
Thence to corner of 15 - 14 - 22 - 23.

NORTH bet secs 15 & 14.

3 00 Top of a point on ridge bearing N 20° E.  
35 00 Top of ridge, N 60° W.  
40 00 Set a blue granite rock 14x10x6 for  $\frac{1}{4}$  sec cor. on the North side  
of a hill brg N 60° W.  
45 00 Cross dry ravine course W.  
70 00 Int Ranch line of the Nogal. Set a post and charred post as per inst.  
Land hilly. Oak timber in ravine. Soil good 2nd rate. Thence  
To corner of Secs 15 - 14 - 22 - 23.

SOUTH bet secs 22 & 23.

10 00 Cross dry ravine course S 52° W. emptying in Canyon de Brea.  
30 00 Top of low ridge course S 60° W.  
40 00 Set a gray granite rock 18x16x5 for  $\frac{1}{4}$  sec cor on S side of low hill.  
45 00 Cross dry arroyo. Has oak timber. SE.  
50 50 Cross dry ravine, gen'l course S 10° W. emptying Canada de Brea.  
Has oak timber.  
68 50 Enter thick growth of oak, chaparal & sage brush.  
80 00 Set a brown sandstone 18x10x6 for cor of secs 22-23-27-26. in small  
ravine course W. Chaparal & brush very thick. Surface smooth ex-  
cept last 25 chs. Soil good 2nd rate. Hilly sloping SW. Thence

EAST bet secs 23 & 26.

40 00 Set a brown sandstone 22x12x3 for  $\frac{1}{4}$  sec cor. All hills, brush,  
sloping S generally. Surface rough. Soil 2nd rate.  
42 50 Arroyo has some water course S. Valley brs N & S.  
50 00 Cross valley enter hills.  
80 00 Set a brown sand rock 16x11x6 for cor of secs 23-24-25-26, on E side  
of a small canada course NW. Thence

SOUTH bet secs 26 & 27.

36 00 Enter canada de Brea bearing N 67° W.  
40 00 Set a brown sandstone 16x6x5 for  $\frac{1}{4}$  sec cor. Surface rough. Has a  
thick growth of chaparal. Hilly, sloping W. This corner is about  
20 lks from a spring of water, S & E.  
41 00 Cross arroyo, has some water, course N 67° W.  
43 00 Enter hills.  
72 00 Top of ridge bears E & W.  
73 00 Int South boundry of La Brea 39.31 S 67 $\frac{1}{2}$ ° W of Sta 18.  
Set a post and charred post. Thence from a point at 80 chs I ran W.  
on section lines between secs 27 & 34.

17 50 Int Traverse line of Brea 8.25 from post See other book.

30 00 Arroyo course N 30° W. Oak timber  
40 00 (40 00) Set a post & charred stake, mound, trench & pits  
45 00 Ridge N & S.  
62 00 Arroyo N 70° W. Oak.  
80 00 Set a brown granite rock 14x10x10 for cor of secs 28-27-33-34.  
Surface rough, mostly last 40 chs. Scattering chaparal. Sloping  
NW & SW. Soil 2nd rate. Thence

NORTH bet secs 28 & 27.  
 6 50 Cross dry deep ravine course S 60° W. Thick chaparal.  
 11 50 Top of ridge course W.  
 20 00 To canada.  
 22 50 Cross water in arroyo.  
 26 50 Cross canada to hills. Set a rock.  
 40 00 Set a brown sandstone 24x12x3 on a low ridge brg N & S. Has sage br.  
 80 00 Set a brown sandstone 16x12x3 for cor of secs 21-22-28-27. Thence

EAST between secs 22 & 27.  
 20 00 Enter canada course S.  
 22 00 Leave canada.  
 28 00 Top of ridge brg S.  
 36 52 Dry arroyo course S.  
 40 00 Set a brown sandstone 16x12x7 for  $\frac{1}{2}$  sec cor. on W slope of ridge. S.  
 42 00 Top of ridge S.  
 48 00 Dry arroyo S.  
 55 00 Top of ridge course S.  
 60 00 Dry arroyo course S 40° E.  
 75 00 Dry arroyo course S. Has oak timber.  
 80 40 To cor of secs 22-23-27-26, 30 lks S. Surface rough and hilly and with oak brush and sage bushes. Soil 2nd rate. Thence

NORTH bet secs 21 & 22.  
 12 00 Cross ledge 10' high at head of small ravine with timber, S 50° W.  
 40 00 Set a brown sandstone 13x12x6 for  $\frac{1}{2}$  sec cor.  
 58 00 Top of high ridge S 50° W and N 50° E.  
 80 00 To cor of secs 16-15-21-22. Surface smooth generally. Last  $\frac{1}{2}$  mile very brushy, chaparal, sage and oak. Land slopes N & S from ridge.

INTERSECTION on the East of Rincon de la Brea.

NORTH bet secs 23 & 24.  
 40 00 Set a brown sandstone 18x8x5 for  $\frac{1}{2}$  sec cor. on E side of valley.  
 66 50 Int Ranch line. Set a post and charred stake as per inst. Thence

EAST between secs 24 & 25.  
 34 00 Top of ridge. Int Traverse line of R B. on East 74 lks N 28° W of Sta 23. Set a post and charred and a rock was marked T 2 S, R 9 W. Thence to cor of 23-24-25-26.

SOUTH bet secs 26 & 25.  
 10 00 Cross dry ravine course NW. Has thick growth of oak timber.  
 27 50 Top of ridge brg SE.  
 40 00 Set gray sandstone 18x12x5 for  $\frac{1}{2}$  sec cor. on E slope of a low hill about 3 chs NW of a thick clump of small oaks. Some sage brush.  
 48 50 Int. Traverse line of Brea 16.68 chs N 34 $\frac{3}{4}$ ° E of Sta 21. Set a post and charred stake as per inst. Surface smooth. Has some oak timber. Scattering walnut. Soil 2nd rate. Most of the land is covered with wild oats. Generally sloping N & NE. Thence

WEST bet secs 28 & 33.  
 26 50 Dry ravine course S 70° W.  
 31 50 Enter canada de Brea course S 60° W  
 38 00 Cross canada enter low hills.  
 40 00 Set gray granite rock 20x10x3 $\frac{1}{2}$  for  $\frac{1}{2}$  sec cor. Surface rough and brushy except in canada.  
 50 00 Dry ravine S 30° E.  
 60 00 Top of ridge S 30° E.  
 66 00 Dry ravine SE.  
 78 00 Top of ridge course SE.  
 80 00 Set a brown granite rock 12x7x7 for cor to secs 29-28-32-33 on the West side of a low ridge. Soil 2nd rate. Sage brush. Thence

NORTH bet secs 29 & 28. Var 13° 30' E.  
 2 00 Ridge SE.  
 11 00 Ravine SE.  
 20 00 Ridge SE.

40 00 Set brown granite rock 14x7x6 for  $\frac{1}{4}$  sec cor. Land slopes NW to valley brg W & E. Scattering walnut.

70 00 Enter valley.

80 00 Set a brown granite rock 12x12x10 for cor of secs 20-21-28-29. Surface smooth. Soil 1st rate. Thence

EAST bet 21 & 28.

15 00 Leave valley enter low hills. Scattering walnut.

35 00 Top of hill brs N 50° E.

40 00 Set a gray granite rock 20x10x5 $\frac{1}{2}$  for  $\frac{1}{4}$  sec cor.

45 00 Top of main ridge. NE & SW.

68 00 Dry ravine course SE. Has oak timber.

79 80 To cor of secs 21-22-28-27, 35 lks N of mound. Surface smooth. Soil goo Thence

NORTH 1 mile bet secs 20 & 21.

25 00 Leave valley enter low hills.

35 00 Top of low ridge S 70° W.

40 00 Set rock 12x10x5 for  $\frac{1}{4}$  sec cor on the West side of a small grass hollow course SE.

68 00 Top of hill E & W.

80 00 Set a post and charred stake in mound raised md of earth, trench and pits, on the West slope of ridge. Surface smooth. Soil 2nd rate. Thence

EAST bet secs 16 & 21.

5 00 Top of ridge E & W.

40 00 Enter grass hollow S 30° E.

59 00 Ridge S 30° E.

65 00 Enter grass hollow course S 20° E.

70 00 Ridge S 20° E.

73 00 Enter valley S 50° W.

78 00 Dry arroyo. course S 50° W.

79 90 Int N & S line of the post. Surface smooth, generally very hilly, sloping South mostly. 2nd rate Soil. Thence

NORTH bet secs 16 & 17.

13 00 Enter chaparal.

18 00 Dry ravine course NW.

40 00 Set a gray granite rock 20x7x4 for  $\frac{1}{4}$  sec cor. on N slope of low ridge in chaparal. Scattering oaks in gullies.

62 00 Road S 60° W.

64 00 Cross dry arroyo below the house about 15 chs. Has sycamore trees. course S 70° W.

80 00 Set post and charred stake in mound of earth, trench and pits, cor to secs 8-9-16-17 on side of low hill. Thence

EAST bet secs 9 & 16.

5 00 Top of ridge SE.

8 00 Enter valley S 60° E.

24 00 Gully 50 lks wide. Has some water, willow trees, course S 60° W.

40 00 To  $\frac{1}{4}$  sec cor. See other book. The other 40 chs was run west. Thence

NORTH bet secs 8 & 9.

8 00 Top of ridge E & W.

11 25 Enter bottom land E & W.

40 00 Set a post and charred stake in mound of earth, trench and pits.

63 40 Int Ranch line of Negales. Set post and charred stake as per inst. and pits and raised md of earth. Int about 8 chs E of low detached hill. Surface smooth. Soil 1st rate. Thence to cor secs 27-28-33-34.

SOUTH bet secs 33 & 34.

2 00 Top of ridge E & W.

8 00 Dry ravine course NW.

40 00 Set gray sandstone 14x12x8 for  $\frac{1}{4}$  sec corner.  
60 00 Set gray granite 20x10x8 for corner, marked R B Sec 33-34, about 2 chs from top of ridge, brs NE. Surface rough and rocky.

Thence WEST in Section 33 on ranche line.

15 00 Dry ravine. Course W.  
20 00 Ridge, bearing N.  
25 00 Dry arroyo. Course N.  
36 00 Ridge.  
65 00 Dry ravine. NW.  
78 00 Enter Canada. brs SW.  
80 00 A post and charred post for corner of ranche marked R B Section 32 & 33, from which a walnut 6" dia brs S. 58° E. 77 lks. Surface mostly smooth sloping N & S. Is very hilly. Scattering oaks in small ravines.

Thence NORTH on Section line bet 33 & 32.

7 00 Cross arroyo, has some water; bank on west about 8' high. Course here S. 70° W. General course SW. Enter low hills SW & NE.  
20 00 Set gray granite rock 12" sq. for  $\frac{1}{4}$  sec corner on the west side of low hill near ravine.

53 50 Dry ravine. Course S 30° E.

60 00 To corner to secs 29-28-32-33.  
Surface, some stony, hilly, has some sage, sloping mostly S.  
Soil 2nd rate.

Thence WEST bet secs 29 & 32.

3 00 Cross dry ravine. Course S 25° E.  
10 00 Top of ridge. S 30° E.  
20 00 Deep ravine. Course SE.  
33 00 Ridge. NE & SW.  
36 00 Ravine. NE.  
40 00 Set brown sandstone 20x10x4 for  $\frac{1}{4}$  sec corner. Very hilly, rough, rocky and brushy. Scattering oak timber.  
62 00 Enter canada. SW.  
64 00 Ravine. Has some water. SW.  
67 00 Cross road. ~~XXXXX~~  
80 00 Set gray sand rock 12" sq. for corner to sections 29-30-31-32 on a low point of hill on west side of canada. Surface last 40 chs smooth. Scattering oak and walnut timber, some elder. Soil in canada 1st rate. Heavy growth of wild oats.

Thence SOUTH bet 31 & 32.

14 00 Cross road.  
20 00 Cross creek, some water. SW. Enter hills.  
40 00 Marked a walnut 6" dia. for  $\frac{1}{4}$  sec corner, in deep canada. Course NW.  
58 00 Top of high peak on ridge, brs NE.  
60 00 Set a brown sand rock 14x10x5 for Sta on ranche line marked R B Sec 31  
Is on S side of a high peak of ridge, NE & W. Soil 1st rate.  
Mostly scattering oak and walnut. Sloping mostly to N.  
The line between this and a point 60 chs South of corner of 28-29-32 & 33 was not measured, but about 30 chs a deep bushy ravine course about SW. Arroyo in Canada de Brea crosses the line 300 west of the Sta 60, south of 29-28-32 & 33.  
Canada is about 4 chs wide. Course S. 60° W.

Thence WEST in Section 31 on Ranche line down the hill.

10 00 further, land slopes SE, NW & W.  
40 00 Set a post and charred stake from which an Oak 10" dia. brs N 72° W 44 lks. Another 8" dia brs N 35° E. 85 lks, are taken for bearing trees. (BT)  
Surface smooth and steep. Scattering oaks and walnuts.

Thence NORTH on Rancho Line.  
13 00 Ravine. S 35° W. 10' deep, has some water. Willow timber.  
40 00 Cross road. S 25° W.  
43 00 Enter low hills. NE & SW.  
60 00 Set gray sandstone 16x12x8 for  $\frac{1}{4}$  sec corner, marked  $\frac{1}{4}$  & R B; is on east side of brushy ravine. Course S 30° E.  
Surface smooth generally. Soil 2nd rate. Hilly except in Canada.

Thence EAST on Section line bet 30 & 31.  
20 00 Grass hollow. Course S.  
28 00 Top of ridge. Brs S.  
40 00 To corner of Sections 29-30-31-32.  
Surface smooth, brushy. Scattering walnut & oak.  
Sloping S generally. Soil 2nd rate. Thence

NORTH bet Sections 29 & 30. 1 mile.  
1 00 Enter hills. Sage brush.  
25 00 Top of high peak of ridge brg S 60° W.  
40 00 Set a brown sand rock for  $\frac{1}{4}$  sec corner on west side of a deep canada brg SE. Very thick chaparral the last 35 chs.  
45 00 Cross canada, SE. Has oak timber.  
70 00 Leave chaparral near top of hill.  
78 00 Cross dry ravine. Course E.  
80 00 Set a brown granite rock 20x10x6 for corner of sections 19-20- 29-30 on the east side of small ravine, course S in sage brush.  
Surface most of 80 chs rough and rocky, very brushy. Soil 2nd rate.

Thence WEST bet 19 & 30, up a small grass hollow.  
38 00 Top of low ridge N & S.  
40 00 To a point on the S side of a ravine brs NW.  
Set a post and charred post for  $\frac{1}{4}$  sec corner marked  $\frac{1}{4}$  R B, from which an Oak 15" dia brs N 62° E. 31 lks dist. Another oak brs N 72 $\frac{1}{2}$ ° W, 8" dia. 68 lks.  
Surface smooth. Scattering oak. Soil 2nd rate. Thence

EAST bet 29 & 20.  
20 00 Cross dry ravine. Course S.  
40 00 Leave hills. Set brown granite rock 13x8x8 for  $\frac{1}{4}$  sec corner.  
Last 20 chs rough and brushy.  
53 00 Crosses road. N 20° W.  
80 00 To corner Sections 20-21-28 & 29, 40 lks S of corner.  
Last half mile, land level. Soil 1st rate.  
Valley here about  $\frac{1}{2}$  mile wide, brs SW. Thence

NORTH bet 19 & 20.  
25 00 Top of hill. SW & NE.  
40 00 Set brown sandstone 20x7x2 $\frac{1}{2}$  on south side of small ravine in the bushes, oak and sage. Thence

WEST in Section 19.  
5 00 Cross dry ravine. Course S 80° W. Enter chaparral & Sage brush.  
40 00 Set a brown granite rock 20x8x8 marked R B Sec 19 on E side of small ravine. Course N.  
Soil 2nd rate. Hilly and brushy. Thence

EAST to  $\frac{1}{4}$  Section corner bet 19 & 20.

NORTH.  
60 00 To top of hill.  
66 00 Brushy ravine. Course N 20° W.  
80 00 Set post and charred stake in mound. Raised mound of earth, trench and pits. Soil 2nd rate. Hilly.

EAST between 17 & 20

20 00 Top of low ridge. N.  
30 00 Ravine N.  
40 00 Set brown granite rock 16x10x4 for  $\frac{1}{4}$  section corner on west bank of narrow dry ravine. Course SW from — & turns N.  
45 00 Top of ridge. Course NE & SW.  
52 00 Cross road N & S.  
80 45 To corner of 16-17-20 & 21 on mound.  
Surface mostly brushy, sloping E & W & N. Scattering oak & walnut.  
Thence  
NORTH between 18 & 17

14 00 Dry ravine. N 57° W. Low hills about E & W.  
40 00 Set a post and charred post in mound, trench & pits.  
Surface smooth. Soil 1st rate.  
65 00 An adobe, shingle roof, stands 1 ch to the east.  
66 00 Road, bears S 87° W.  
66 50 Zanja S 67° W., has been old fence  
80 00 Set a post and charred post, raised mound of earth, trench and pits, from which a new adobe, shingle roof, bears S 2 $\frac{1}{2}$ ° E. about 15 chs.  
Another adobe bears S 25° W. about 16 chs.  
Surface level. Soil 1st rate. Thence

EAST between sections 8 and 17.

8 50 Leave field. N & S.  
12 00 Cross road. N & S.  
40 00 Through tunas. Set a post and charred stake in mound, trench & pits.  
63 00 Enter low hills. N & S.  
80 00 To corner of 8-9-16 & 17, 10 lks north of post.  
Surface level and smooth except last 17 chs. Soil 2nd rate. Thence

NORTH between 7 and 8.

3 00 Leave field. S 70° W.  
27 00 Enter another field. S 50° W.  
38 50 San Jose Creek. S 69° W. 15 ft deep (Gully) 50 lks wide, water 4 lks wide, rapid current. Set a post.  
40 00 Set a post and charred post in mound, trench and pits. The house of Ramon Ybarra S 87° E. House of Richado Veja N. 12° E.  
68 00 Leave field, cross zanja, E & W.  
72 00 Cross road, W & E. Enter low hills.  
79 00 Top of low ridge. SE.  
80 00 Set a white sandstone 16x7x7 for corner of sections 5-6-7 & 8.  
The house of Richado Veja brs S 37° E. The house of Ramon Ybarra S 34 $\frac{1}{2}$ ° E. Soil 1st rate. Surface level and smooth except last 10 chs.  
Thence

EAST between 5 and 8.

Enter low land, cross road and zanja and enter field.  
40 00 Set post and charred post in mound, raised mound, trench and pits.  
Soil 1st rate.  
56 00 Leave field.  
68 00 Cross zanja and creek.  
75 34 Intersect Nogal Ranch line. Set post and charred post as per instructions. Surface smooth and level. Soil 1st rate. Thence

NORTH between 6 and 5.

40 00 Set a gray granite rock 10x10x8 for  $\frac{1}{4}$  section corner on N slope of low hill.  
81 40 Intersect Township line 80 lks east of mound. Thence

EAST on Township line 31.80 between sections 5 and 32. Intersect Ranch line 183 lks S 85° W of temporary station set by me the day we hunted so long for the mound.  
Set post and charred. as per instructions. Thence



SOUTH between 4 and 5.  
 30 00 Top of low hills.  
 40 00 Set brown sand rock 14x11x6.  
 42 00 Road E & W.  
 62 00 Zanja. S 23° W.  
 65 00 Arroyo San Jose. S 23° W.  
 70 50 Intersect line of Nogal  
 Set post and charred post as per instructions.

-----

Book 8.

September 1857.

T 3 S., R's 8 & 9 W.

Wednesday.

From established corner of 13-24-18 & 19 I run NORTH on Range Line

NORTH on Range line.  
 8 00 Enter sage brush at base of low range of hills bearing E & W.  
 19 00 Dry arroyo, course SE.  
 30 00 Leave sage brush.  
 40 00 Set gray granite rock 18x11x8 for  $\frac{1}{4}$  section corner on the south slope  
 of a low range of hills bearing E & W.  
 50 00 To top of ridge bears E & W.  
 76 50 Base of hills, enter dry arroyo SW.  
 79 00 Leave arroyo.  
 80 00 Set gray sand rock 20x14x7 for corner of sections 12-13-7 & 18.  
 Surface hilly sloping N & S. Soil 1st rate covered with wild oats  
 and scattering walnut. In ravine oaks and sycamores.

NORTH between sections 12 & 7

5 00 Bottom of hill bearing S 5° E. Enter sage brush.  
 40 00 Set a gray sand stone rock 16x6x6 for  $\frac{1}{4}$  section corner near top of  
 ridge, brs N & S, on SW slope.  
 60 00 Top of ridge, N 73° E., Have a fair view of Cucamonga.  
 80 00 Set a gray sand stone 24x8x7 for corner of 6-7-1 & 12, on northern  
 slope of a ridge.  
 Surface hilly, sloping SW & N. Scattering oak, sage and wild oats.  
 Soil 1st rate.

T 3 S., R 9 W.

NORTH between sections 1 & 6.  
 5 00 Thick oak brush.  
 15 00 Leave same. Enter open oat land. Wild oats. Bearing E & W.  
 Scattering black walnut.  
 23 00 To bottom of ridge. Enter canada. Dry arroyo, course E.  
 25 00 Cross canada. Base of hills bearing E & W.  
 33 00 Top of low ridge bearing N.  
 40 00 Set a gray sand rock 30x12x4 for  $\frac{1}{4}$  section corner on the eastern  
 slope of low ridge bearing N & S.  
 67 00 Top of ridge bearing E & W.  
 80 00 Set a gray sand rock 28x15x7 for corner of Townships 2 & 3 S, R's  
 8 & 9 W. Sections 1-6-31 & 36.  
 A large sandrock mostly imbedded in the ground, 30" sq., 4" above  
 ground was marked + is 100 lks from mound on line south.  
 An evergreen oak 13" dia. bears N. 33° E. 3.97 chs dist.  
 Surface hilly, mostly covered by sage brush, sloping S.  
 Soil 1st rate generally.



WEST on Township line between 1 and 36.

22 00 Dry ravine, course N.  
33 50 Top of ridge bearing NW & SE.  
66 50 Stream of water 10 lks wide, course SW.  
75 00 Top of low ridge bearing N & S.  
80 00 Set a post and charred stake in mound of earth for corner of sections 1-2-35 & 36, on right bank of dry ravine, course S.  
Surface hilly, sloping N mostly, covered by thick growth of sage and oak brush. Soil 1st rate.

WEST on Township line between 2 and 35.

1 00 Leave arroyo enter hills bearing N & S. Oak and sage brush.  
37 00 Top of ridge bearing SE & NW.  
40 00 Set gray sandstone 16x10x7 marked  $\frac{1}{4}$  for  $\frac{1}{4}$  section corner on SW slope of a ridge bearing SE & NW.  
54 50 Deep dry ravine, course S.  
71 50 Top of ridge bears N & S.  
80 00 Set a gray sand rock 16x14x5 for corner of sections 2-3-34 & 35 on southern slope of a low range bearing E & W.  
Surface hilly sloping SE generally. Has a thick growth of sage brush and oak, grass, wild oats. Soil 2nd rate.

WEST between sections 3 and 34, Township line.

18 00 Dry arroyo, course SE.  
40 00 Set a brown sandstone 15x12x8 on the south slope of the hill for  $\frac{1}{4}$  section corner.  
68 00 Dry arroyo, course S.  
80 00 Set a brown sand stone 15x10x8 for corner of sections 3-4-33 & 34 on NE slope of low ridge bearing NE.  
Surface hilly, sloping S & NE. Soil 1st rate. Burnt land.

WEST between sections 4 and 33.

11 50 Top of ridge bearing S & W.  
40 00 Set a brown sandrock 14x12x10 for  $\frac{1}{4}$  section corner.  
42 50 Top of low ridge bearing SW & E.  
66 50 Dry arroyo, course NW.  
73 50 Same (Dry arroyo C-NW)  
75 00 Low ridge bearing NW & SE.  
80 00 Set a brown sand rock 24 x 15 x 6 for corner of sections ~~4~~ 4-5-32 and 33 on the north slope of a ridge bearing SW & NE.  
Surface hilly, sloping N & S. Soil 2nd rate.  
Scattering oak and sage brush.

WEST between sections 5 and 32.

14 00 Small dry arroyo, course N.  
31 50 Large dry arroyo, course S.  
33 50 Leave arroyo enter hills bearing SW generally. Course of ravine SW.  
39 00 Dry arroyo, course S.  
40 00 Set a brown sand rock 18x12x4 for  $\frac{1}{4}$  section corner on the southern slope of a range bearing SW  
46 50 Dry arroyo, course S.  
62 50 Top of ridge, bears S.  
72 50 Dry arroyo, course S.  
80 00 Set a gray sand stone 21x9x6 for corner of 5-6-31 & 32. Mound on E slope of a high ridge bearing N & S.  
Surface hilly, sloping SE & W. Soil 1st rate, covered with wild oats.

NOTE: All of the land that has been subdivided in T 2 S, R 9 W., or that portion that was cut off from the Rincon de La Brea, is all hill except two small narrow valleys bearing in a southwesterly direction. About one-third part of surface covered with chaparral.

# SUBDIVISION

T 3 S., R 9 W.

Var 13° 25' E.

WEST from corner of 12-13-7 & 18.

- .50 Dry arroyo, course S.
  - 15 00 Top of ridge, bears N & S.
  - 21 50 Bottom of ridge, dry arroyo, course S.
  - 40 00 Set a post, made mound of earth, trench and pits for  $\frac{1}{4}$  section corner.
  - 44 00 Top of ridge, N & S.
  - 66 50 Bottom of ridge, dry arroyo, course S.
  - 80 00 Set a post and charred stake, made mound of earth for corner of sections 11-12-13 & 14.
- Surface hilly, sloping S mostly. Soil 1st rate, scattering sage and wild oats. Mound set on SE slope.

From the established corner of 11-12-13 & 14 I run

SOUTH between sections 13 & 14.

- 12 50 Bottom of hill. Large arroyo, course nearly W.
  - 14 00 Leave arroyo enter range of hills, E & W. Sage brush.
  - 30 00 Top of ridge, E & W.
  - 40 00 Marked a gray sand stone 16x12x6 for  $\frac{1}{4}$  section corner.
- Surface hilly, sloping N & S. Mound on SE slope. Soil 1st rate.

NORTH 1 mile between 11 & 12.

- 22 50 Top of ridge bearing NE & SW.
  - 32 00 Sage and oak brush.
  - 35 00 Dry arroyo, course NW.
  - 40 00 Set a gray sand stone 16x7x6 marked  $\frac{1}{4}$  for  $\frac{1}{4}$  section corner, on the NW slope of a hill.
  - 48 00 Top of ridge. NW & SE.
  - 80 00 Set a post, made mound of earth for corner of 1-2-11 & 12. Trench and pits and charred stake on N slope of a ridge about 8 chs from a deep ravine. N
- Surface hilly, sloping N. Soil 1st rate. Scattering walnut.

EAST on RANDOM line between 1 & 12.

- 7 50 Dry arroyo.
  - 18 00 Top of low ridge bearing N & S.
  - 40 00 Set post for temporary  $\frac{1}{4}$  section corner.
  - 79 90 Intersect N & S line 25 lks N of corner to sections 1-2-6 & 7.
- Surface hilly, sloping N. Scattering sage brush, black walnut, oak, wild oats. Soil 1st rate.

WEST on true line.

- 39 95 Set a post for  $\frac{1}{4}$  section corner, mound of earth, charred stake, trench & pits on N slope of hill.
- 79 90 To corner of sections 1-2-11 & 12.

NORTH 1 mile between sections 1 & 2.

- 5 00 Leave hills enter arroyo, course N.
  - 11 00 Leave arroyo, hill. E & W.
  - 39 00 Top of ridge, NE & SW.
  - 40 00 Set a post for  $\frac{1}{4}$  section corner from which an evergreen oak 10" dia bears N 7 $\frac{1}{2}$ ° E. 153 lks dist. An evergreen oak 10" dia bears N 29° W. 206 lks dist.
  - 63 00 A stream of water, course NW, 10 lks wide. Has oak and scattering sycamores. The general course of the canyon is SW.
  - 79 50 Intersect E & W line corner of sections 1-2-35 & 36, 40 lks E of md.
- Surface hilly, sloping N. Scattering sage brush, oak and scattering black walnut and wild oats. Soil 1st rate.

WEST between sections 11 & 14.

- 4 50 Top of ridge bears S.
- 14 50 Dry arroyo, course S.
- 26 50 Dry arroyo, course S.
- 40 00 Set a brown sand rock 30x12x4 for  $\frac{1}{4}$  section corner on southern slope of hill
- 55 00 Top of ridge bearing N & S.
- 80 00 Set a brown sand rock 18x12x10 for corner of sections 11-10-15-14 on the SW slope of a ridge bearing E & W, sloping S. Surface hilly. Soil 1st rate.

NORTH between 10 and 11.

- Top of ridge bearing E & W.
- 30 00 To bottom of ridge.
- 33 00 To a stream of water in canyon, course SW, 10 lks wide, strong saleratus, alum, not fit for use, at base of hill.
- 36 00 Top of a low point of hill bearing SW.
- 40 00 Set brown sand stone 18x10x5 for  $\frac{1}{4}$  section corner.
- 47 00 Cross dry arroyo, course SW.
- 80 00 Set a brown sand rock 16x12x10 for corner of sections 2-3-10-11 on west slope of a ridge bearing N & S. Surface hilly, sloping N & SW. Scattering sage and oak brush. Oaks and walnut in the canyon. Soil 1st rate. Grass, wild oats.

EAST on a RANDOM line between sections 2 and 11.

- 5 00 Top of ridge bearing N & S. Enter sage brush.
- 19 50 Cross stream of alkali water 10 lks wide in a canyon, course SW.
- 40 00 Set a brown sand stone for temporary  $\frac{1}{4}$  section corner on northern slope of a range bearing SW & NE.
- 46 50 Top of ridge bearing NE & SW.
- 69 00 Cross dry arroyo.
- 80 70 Intersect N & S line corner of sections 1-2-11-12 on the post.

WEST on TRUE line between 2 and 11

- 40 35 Set a brown granite stone for  $\frac{1}{4}$  section corner, 14x12x9.
- 80 70 To corner of sections 2-3-10-11. Surface very hilly, sloping SE & NW. Soil 1st rate.

NORTH between sections 17 & 18.

- 40 00 Set a post, made a mound of earth, charred stake, trench and pits for  $\frac{1}{4}$  section corner.
- 80 00 Set a post made of earth, charred stake, trench and pits for corner of sections 7-8-17-18. Surface gently rolling, sloping S. Soil 1st rate.

NORTH between sections 2 & 3.

- 8 00 Top of a ridge bearing N 12° W., and S 12° E.
- 40 00 Set a post for  $\frac{1}{4}$  section corner, mound of earth, charred stake, trench and pits, on SE slope of hill.
- 76 00 Dry ravine, course W.
- 79 49 Intersect E & W line west of post 12 lks. Surface very hilly. Scattering sage brush, sloping S & NW. Soil 1st rate, covered by wild oats.

SOUTH between sections 14 and 15.

- 21 50 Arroyo, course W.
- 37 50 Top of ridge bearing E & W.
- 40 00 Set a gray sand rock 18x8x4 for  $\frac{1}{4}$  section corner. Surface hilly, sloping N & S. Soil 1st rate. Wild oats.

WEST between sections 10 and 15.

- 36 00 Offset 3.50 chs to the north around head of deep ravine.
- 40 00 Set a gray sand rock 18x14x12 for  $\frac{1}{4}$  sec. cor. 3 $\frac{1}{2}$  chs due N. on top of a ridge bearing E & W.
- 80 00 S Surface hilly, sloping N & S. Soil 1st rate, covered by wild oats. A few scattering black walnut.

NORTH between sections 9 & 10.

7 00 Bottom of ridge.

14 00 Dry arroyo, course W.

19 00 Bottom of hills bearing E & W.

40 00 Set gray sand rock 25x12x6 on N slope of a small hill for  $\frac{1}{2}$  sec. cor.

41 00 Dry arroyo, course W. Enter sage.

56 50 Dry arroyo, course W.

72 00 Leave sage.

80 00 Set a gray sand stone for corner of sections 3-4-9-10, 13x12x8 on the southern slope of a hill.

Surface hilly, sloping SW. Scattering oak trees. Soil 1st rate.

EAST on a RANDOM line between 3 & 10.

7 50 Top of ridge.

20 50 Dry arroyo, course S.

25 00 Top of ridge. N & S.

40 00 Set a temporary  $\frac{1}{2}$  section corner.

59 00 Dry arroyo, course S.

80 08 Intersect N & S line on the post.

WEST on TRUE line.

40 04 Set a brown sand rock 20x12x10 for  $\frac{1}{2}$  section corner on SE slope of a hill.

80 08 To corner of sections 3-4-9-10.

Surface hilly, sloping S. Soil 1st rate. Scattering oak and walnut and sage brush on the hill. Wild oats.

NORTH between 8 and 9.

20 00 Leave valley, enter low hills. SE & NW.

35 00 Brella.

38 50 Leave Brella.

40 00 Set a blue slate stone 25x18x4 for  $\frac{1}{2}$  section corner on S slope of hill.

59 00 Dry arroyo, course SW.

72 00 Top of ridge. SW.

80 00 Set brown granite rock 18x9x9 for corner of sections 4-5-8-9.

Surface hilly, covered by sage, sloping S & SW. Soil 2nd rate.

EAST between Sections 4 & 9.

5 00 Top of ridge, bears N & S.

25 00 Dry arroyo, course S.

40 00 Set a brown sand rock 15x10x6 on west side of high ridge, N & S, on S side of canyon bearing NW & SE, with slope E & W. Soil 2nd rate.

NORTH between 4 & 5.

.50 Dry arroyo, course W.

10 00 Dry arroyo, course SW.

40 00 Set a brown granite stone 25x10x7 for  $\frac{1}{2}$  section corner, on S. slope of ridge, E & W.

60 00 Top of ridge.

79 40 Intersect E & W line 80 lks west of corner of sections 4-5-32-33.

NORTH between 7 and 8.

40 00 Set a post and charred post, trench and pits, mound of earth, east side of low hill, E & W.

80 00 Set a red sand stone 25x8x8 for corner of sections 5-6-7-8, on top of a ridge bearing SW & NE.

Surface rolling, sloping. Soil 1st rate.

EAST between 5 and 8.

38 50 Dry arroyo, SW.

40 00 Set a stone 18x8x5 for  $\frac{1}{2}$  section corner.

45 00 Top of low ridge bearing N & S.

71 00 Deep dry arroyo, course S.

80 25 Post on N & S line. South 20 lks.

NORTH between 5 and 6.

25 50 Cross a dry ravine, course SW.

40 00 Set a gray sand rock 25x5x5 for  $\frac{1}{4}$  section corner.

48 00 Top of low ridge bearing SE.

54 00 Dry arroyo, course SE.

Top of low ridge bearing SW.

79 90 Intersect E & W line 60 lks west.

Surface hilly. Soil 1st rate.

  

SOUTH between 15 and 16.

18 50 Bottom of ridge.

20 00 Dry arroyo, course W.

21 50 Base of hill bearing E & W.

39 00 Top of ridge bearing E & W.

40 00 Set a post for  $\frac{1}{4}$  section corner.

  

EAST between 8 & 17.

38 00 Ridge N & S.

40 00 Set a light colored free stone 30x24x6 for  $\frac{1}{4}$  section corner on west slope of low ridge bearing N & S.

60 00 Leave ridge, enter valley bearing N & S.

79 80 Intersect N & S line 40 lks N of post.