



18 N., R 17 W.  
 and  
 South Line La Liebre.  
 Copied from notes loaned to County Surveyor  
 by  
 Mr. V. J. Rowan.  
 August 1918.  
 Norris, 1854-5.  
 Collins 1880  
 Dues 1903.

T 8 N, R 17 W., S.B.M.

Exterior by R. W. Norris, December 23, 1854.  
Subdivisions by R. W. Norris, August 1, 1855.

Exterior lines of T 8 N, R 17 W., field notes of Exterior boundary according to survey made by Ralph W. Norris, Deputy Surveyor, under contract dated December 23, 1854.

### WEST BOUNDARY.

From the corner to Townships 8 and 9 North, Ranges 17 and 18 West I run

SOUTH along the east boundary of Sec 1. Var 14° 13' E.

20 00

To ravine, course N 60° W.

25 50

Across the same.

40 00

Set a post, charred and chalked for the  $\frac{1}{4}$  Sec corner and raise a

mound with trench and pits.

53 00

Leave hill and enter valley.

78 50

To hills brg S 40° E.

80 00

Set a post, charred, chalked and notched for the corner to Secs 1,

12, 6 and 7 and raise a mound with trench and pits.

SOUTH on the east boundary of Section 12. Var 14° 13' E.

22 00

To ravine N 45° E.

38 00

Across the same.

40 00

Set a post charred and chalked for the  $\frac{1}{4}$  section corner and raise

a mound with trench and pits per instructions.

46 00

To ravine course N 40° E

62 00

Set a post charred, chalked and notched for the corner to Secs 12,

13, 7 and 18 and raise a mound with trench and pits.

SOUTH on the east boundary of Section 13. Var 14° 13' E.

40 00

Set a post, charred and chalked for the  $\frac{1}{4}$  section corner and raise

(See C S 9027)

a mound with trench and pits.

80 00

Set a post charred, chalked and notched for the corner of secs 13,

24, 18 and 19 and raise a mound with trench and pits.

SOUTH bet Secs 19 and 24. Var 14° 13' E. (See C S 9027)

36 00

To road to Ft Tejon, course N 80° W.

40 00

Set a post, charred and chalked for the  $\frac{1}{4}$  sec cor. and raise a

mound with trench and pits.

60 00

A Lake bears N 69° W, about 30 chs dist.

71 00

To scrub and scattering pine.

80 00

Set a post charred, chalked and notched for the corner to Secs 24,

25, 19 and 30 and raise a mound with trench and pits.

A pine 20" dia brs S 34° E 108 lks.

I cannot survey further south on account of steep and brushy and

rugged mountains.

### EAST BOUNDARY.

From the corner to Tps 8 & 9 N, Rs 16 & 17 W. I run

SOUTH along the east bdy of Sec 1.

40 00

Set a post, charred and chalked for the  $\frac{1}{4}$  sec cor and raise a md

with trench and pits.

80 00

Set a post, charred and chalked and notched for the corner to Secs

1, 12, 6 and 7 and raise a md with trench and pits.

SOUTH on the east bdy of Sec 12. Var 14° 13' E.

Field notes of the subdivisions of T 8 N, R 17 W, according to survey made by Ralph W. Norris, Deputy Surveyor, under special instructions, dated August 1, 1855.

Subdivision commenced November 24, 1855, on the north boundary of township. From the corner to Sections 1, 2, 35 and 36 I ran

SOUTH between Sections 1 and 2, Var 14° E.

Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.

Set a post, charred, chalked and notched for the corner to Secs 1, 2, 11 and 12 and raise mound with trench and pits.

EAST on a RANDOM line between Sections 1 and 12. Var 13° 14' E.

Set post for temp  $\frac{3}{4}$  sec corner.

Intersect the east bdy of tp 48 lks north of the corner to Secs 1 and 12, from which corner I ran

WEST on a TRUE line between 1 and 12. Var 13° 52' E.

Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor and raise md with trench and pits as instructed.

To corner to Secs 1, 2, 11 and 12.

SOUTH between Sections 11 and 12. Var 14° 13' E.

Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.

Set a post charred, chalked and notched for the cor to Secs 11, 12, 13 and 14 and raise a mound with trench and pits.

Subdivisions.

T 8 N, R 17 W, S.B.M.

SOUTH on the east bdy of section 25. Var 14° 13' E.

Leave valley for steep hills.

To scattering pine.

Set a post charred, chalked and notched and raise a mound with trench and pits on the north side of ravine 80 feet wide and 80 feet deep at the foot of the mountain.

2 00 Enter steep hill.

18 00 Leave hill for valley.

40 00 Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.

47 50 Rim over hills isolated.

60 00 Leave hill for valley.

80 00 Set a post charred, chalked and notched for the corner to sections 24, 25, 19 and 30 and raise a mound with trench and pits.

SOUTH on the east bdy of Sec 24. Var 14° 13' E.

2 00

18 00 Leave hill for valley.

40 00 Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench.

45 60 John Philburn house brs S 21° E, 15 chs.

75 00 To road to Ft Teton, course N 15° W.

80 00 Set a post, charred and chalked and notched to the corner for Secs 13, 24, 18 and 19 and raised a mound with trench and pits as instructed.

SOUTH on the east bdy of Sec 13. Var 14° 13' E.

40 00 Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench.

45 60 John Philburn house brs S 21° E, 15 chs.

75 00 To road to Ft Teton, course N 15° W.

80 00 Set a post, charred and chalked and notched to the corner for Secs 12, 13, 7 and 18 and raise a mound with trench and pits.

40 00 Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.

80 00 Set a post, charred, chalked and notched for the corner to Secs 12, 13, 7 and 18 and raise a mound with trench and pits.

40 00 EAST on a RANDOM line bet secs 12 and 13. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. Intersect the east boundary of the tp 50 lks north of the corner to Secs 12 and 13, from which corner I run WEST on a true line bet secs 12 and 13. Var 13° 52' E. Set a post, charred and chalked for the  $\frac{3}{4}$  sec cor, raise a mound with trench and pits. The corner to secs 11, 12, 13 and 14. 80 23

40 00 SOUTH bet Secs 13 and 14. Var 14° 13' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor. and raise a mound with trench and pits. Cross road to Ft Tejon, course S. 85° W. To foot of hill brg N. 40° W. To summit and over a succession of low hills. Set a post charred, chalked and notched for the corner to secs 13, 14, 23 and 24, and raise a mound with trench and pits, from which a lone oak 42" dia brs S 35 $\frac{1}{2}$ ° E. 558 lks dist. 80 00

17 00 East on a RANDOM line bet Secs 13 and 24. Var 13° 14' E. To ravine course N. 42° E. Across same to foot of steep hill, which I ascend. To summit of hill and descend. 29 00

35 00 Set a post for temp  $\frac{3}{4}$  corner at foot of hill. Intersect the east bdy of tp 58 lks north of the corner to secs 13 and 24, from which corner I run WEST on a TRUE line bet secs 13 and 24. Var 13° 14' E. Set a post charred and chalked for the  $\frac{3}{4}$  section corner and raise a mound with trench and pits. The corner to sections 13, 14, 23 and 24. 80 26

11 00 SOUTH bet secs 23 and 24. Var 13° 14' E. Scattering live oak and pine. To ravine toward southeast. Across the same. 27 00

27 00 Set a post charred and chalked for the  $\frac{3}{4}$  sec corner, set a mound as per instructions from which an oak 7 inches dia brs N 72° E, 70 lks. SOUTH bet secs 2 and 3. Var 14° 13' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec corner and raise a mound with trench and pits. Set a post, charred, chalked and notched for the corner to secs 2, 3, 10 and 11 and raise a mound for trench and pits. 80 00

40 00 EAST on a RANDOM line between secs 2 and 11. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  section corner. Intersect N & S line 20 lks south of the corner to secs 1, 2, 11 and 12, from which corner I run WEST on a TRUE line bet secs 2 and 11. Var 14° 22' E. Set a post, charred and chalked for the  $\frac{3}{4}$  corner and raise a mound with trench and pits. The corner to Secs 2, 3, 10 and 11. 80 00

40 00 SOUTH bet secs 10 and 11. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. Intersect N & S line 28 lks north of the corner to secs 11, 12, 13 and 14 from which corner I run WEST on a TRUE line bet secs 11 and 14. Var ~~13° 57'~~ 13° 57' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits. The corner to secs 10, 11, 14 and 15. 80 32

40 00 EAST on a RANDOM line bet secs 11 and 14. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. Intersect N & S line 28 lks north of the corner to secs 11, 12, 13 and 14 from which corner I run WEST on a TRUE line bet secs 11 and 14. Var ~~13° 57'~~ 13° 57' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits. The corner to secs 10, 11, 14 and 15. 80 32

25 00 SOUTH bet Secs 14 and 15. Var 13° 14' E. To low hill.  
 40 00 Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.  
 54 00 Cross road to Ft Tejon, brs S 63° W.  
 77 50 To a grove of Oaks, extending 5 chs east, 5 chs west.  
 80 00 Set a post charred, chalked and notched for the corner to secs 14, 15, 22 and 23.  
 A pile of rocks from which an oak 14" dia brs N 77° W. 80 lks dist. An oak 15" dia brs N 21 $\frac{1}{2}$ ° E. 21 lks dist.  
 3 00 EAST on a RANDOM line bet secs 14 and 23. Var 14° 13' E. To scattering cedar and scrub.  
 5 00 To ravine, course N 70° -  
 20 00 Across the same.  
 37 00 To ravine, course N 30 $\frac{1}{2}$ ° E.  
 40 00 Set a post for temp  $\frac{3}{4}$  sec cor  
 45 00 Across ravine.  
 80 24 Intersect N & S line 18 lks north of the corner to secs 13 and 14, 23 and 24. From which course I ran  
 40 12 WEST on a line bet Secs 14 and 23. Var 14° 05' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.  
 80 24 The corner to sections 14, 15, 22 and 23.  
 3 00 SOUTH bet secs 22 and 23. Var 14° 13' E. To scattering cedar and oak;  
 20 00 To hill becoming steep and rocky and the scrub so thick I can proceed no further. Therefore, I set a post properly marked in a mound from which a cedar 5" dia brs N 12 $\frac{1}{2}$ ° E, 35 lks dist. A live oak 6" dia brs N 62° W, 72 lks dist.  
 40 00 SOUTH bet secs 3 and 4. Var 14° 13' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raise a mound with trench and pits.  
 80 00 Set a post charred, chalked and notched for the cor to secs 3, 4, 9 and 10. Raise the mound with trench and pits.  
 40 00 EAST on a RANDOM line bet secs 3 and 10. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner Intersect N & S line 12 lks south of the corner to secs 2, 3, 10 and 11, from which corner I ran  
 39 72 WEST on a TRUE line bet secs 3 and 10. Var 14° 18' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec corner and raise mound with trench and pits.  
 79 44 To corner of secs 3, 4, 9 and 10.  
 40 00 SOUTH bet secs 9 and 10. Var 14° 13' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor. with mound for trench and pits.  
 72 52 To hills.  
 80 00 To cor of secs 9, 10, 15 and 16.  
 22 00 EAST on a RANDOM line bet secs 10 and 15. Var 14° 13' E. Leave the hills for the level plain.  
 40 00 Set a post for temp  $\frac{3}{4}$  sec corner.  
 79 44 Intersect N & S line 32 lks south of the corner to secs 10, 11, 14 and 15 from which course I ran west  
 39 72 WEST on a TRUE line bet secs 10 and 15. Var 14° 27' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor, and raise a mound with trench and pits.  
 79 44 The corner to secs 9, 10, 15 and 16.  
 37 50 SOUTH bet secs 15 and 16. Var 14° 13' E. Leave hills for plain  
 40 00 Set post charred and chalked for the  $\frac{3}{4}$  sec cor. raise a mound with trench and pits.  
 77 50 Cross road to Ft Tejon, course S 57° W.  
 80 00 Set a post charred, chalked and notched for corner of Secs 15, 16, 21 and 22 and raise mound for trench and pits.

(In edge of live oak and underbrush), from which an oak 14" dia  
 brs S 51 $\frac{1}{2}$ ° E. 322 lks dist.  
 An oak 12" dia brs S 12° W. 291 lks.  
 EAST on a RANDOM line bet secs 15 and 22. Var 14° 13' E.  
 To stream of water 5 lks wide, course 30° E.  
 To hills.  
 19 00  
 Set a post for temp  $\frac{1}{2}$  sec cor in some scattered cedar.  
 Intersect N & S line 19 lks to corner of sections 14, 15, 22 and 23,  
 from which corner I ran  
 WEST on a TRUE line bet secs 15 and 22. Var 14° 21' E.  
 Set a post charred and chalked and mound for  $\frac{1}{2}$  sec cor, from which  
 A cedar 8" dia brs N 80 $\frac{1}{2}$ ° E. 182 lks.  
 Corner to secs 15, 16, 21 and 22.  
 79 50  
 SOUTH bet secs 21 and 22. Var 14° 13' E.  
 Leave oaks.  
 4 00  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec cor and raise a mound  
 with trench and pits.  
 40 00  
 Set a post charred, chalked and notched. Any depression for the  
 for the cor of secs 21, 22, 27 and 28, and raise mound with trenches  
 and pits, from which  
 A live oak 12" dia brs N 49° W. 128 lks dist.  
 A live oak 9" dia brs N 56 $\frac{1}{2}$ ° E. 314 lks.  
 A white oak 18" dia brs S 44 $\frac{1}{2}$ ° E. 750 lks dist.  
 EAST between secs 22 and 27. Var 14° 13' E.  
 25 00  
 To scattering white oak.  
 32 39  
 I marked a white oak 18" dia. As instructed, at the foot of a very  
 steep mountain, covered with a dense growth of oak shrub. I cannot,  
 therefore, proceed further. The tree is marked with the range,  
 township and sections.  
 Not being able to run south from the corner of sections 21, 22, 27  
 and 28, I go the corner to secs 4, 5, 32 and 33 and run  
 SOUTH bet secs 4 and 5. Var 14° 13' E.  
 23 00  
 To low hill.  
 40 00  
 Set a post charred and chalked for the  $\frac{1}{2}$  section corner and raised  
 a mound with trench and pits.  
 To ravine, course N 80° E.  
 71 00  
 Across same.  
 78 50  
 Set a post charred, chalked and notched on the corner to secs 4, 5,  
 8 and 9. Raised a mound with trench and pits.  
 80 00  
 EAST on a RANDOM line bet secs 4 and 9. Var 14° 13' E.  
 40 00  
 Set a post for temp  $\frac{1}{2}$  sec cor.  
 To valley or plane.  
 55 00  
 Intersect N & S line 12 lks south of the corner to secs 3, 4, 9 and  
 10, from which corner I ran  
 WEST on a TRUE line bet secs 4 and 9. Var 14° 18' E.  
 40 25  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec corner and raise a md  
 with trench and pits.  
 To the corner of secs 4, 5, 8 and 9.  
 80 50  
 SOUTH bet secs 8 and 9. Var 14° 13' E.  
 9 00  
 To ravine course N 75° E.  
 26 00  
 Across the same.  
 28 50  
 To ravine course N 62° E.  
 36 00  
 Across the same.  
 40 00  
 Set a post charred and chalked for the  $\frac{1}{2}$  section cor and raise and  
 with trench and pits.  
 To ravine. course N 70° E.  
 60 00  
 Across the same.  
 70 00  
 Set a post charred, chalked and notched for the corner to secs 8, 9,  
 and 17 and raised a mound with trench and pits.  
 80 00  
 EAST on a RANDOM line bet secs 9 and 16. Var 14° 13' E.  
 20 00  
 To ravine course N 45° E.  
 25 00  
 Across the same.  
 40 00  
 Set a post for temp  $\frac{1}{2}$  sec cor.

80 00	7 and 8 and raised a mound with trench and pits.
80 00	Set a post charred, chalked and notched at the cor of secs 5, 6, with trench and pits.
40 00	Set a post charred and chalked for $\frac{3}{4}$ sec cor, and raise a mound
25 00	To foot of low hills.
80 00	SOUTH bet secs 5 and 6. Var 14° 13' E.
80 00	any further.
53 00	This mound is on the side of a steep mountain and I could not go
80 00	secs 28, 29, 32 and 33, and raised a mound with trench and pits.
51 00	Center post, set a post charred, chalked and notched for the cor of
51 00	To foot of mountain.
51 00	Leave timber.
6 00	A white oak 24" dia brs S 66° W, 138 lks dist.
40 00	with trench and pits, from which
40 00	Set a post charred and chalked for the $\frac{3}{4}$ sec cor, and raised a mound
6 00	Leave scrub, 12 chs through the valley with scattering timber.
80 00	SOUTH bet secs 28 and 29. Var 14° 13' E. (See C S 9027.)
15 00	and pits.
15 00	a post charred, chalked and notched and raised a mound with trench
15 00	As I found it impossible to get through the thick oak shrub, I set
15 00	EAST on a RANDOM line bet secs 21 and 28. Var 14° 13' E.
80 00	28 and 29 and raise a mound with trench and pits.
80 00	Set a post charred, chalked and notched for the corner to secs 21,
40 00	12" dia brs N 89 $\frac{1}{2}$ ° W, 307 lks dist.
40 00	Set a post charred and chalked in mound for the $\frac{3}{4}$ sec cor. (In edge
40 00	of oak scrub) from which a <del>white</del> white oak 14" dia brs S 66° E, 150
17 00	lks dist. A white oak 15" dia brs S 3° W 198 lks dist. A white oak
11 50	Set a post charred and chalked in mound for the $\frac{3}{4}$ sec cor. (In edge
11 50	To foot of steep hill.
11 50	Across road to Ft Tejon, course S 62° W.
80 50	SOUTH bet secs 20 and 21. Var 14° 13' E.
80 50	The corner to secs 16, 17, 20 and 21.
40 25	with trench and pits.
40 25	Set a post charred and chalked for the $\frac{3}{4}$ sec cor and raise mound
80 50	WEST on a TRUE line bet secs 16 and 21. Var 14° 21' E.
80 50	and 22, from which I ran
80 50	Intersect N & S line 17 lks south of the corner to secs 15, 16,
62 00	N 17° E.
62 00	To the same road with it east for 8 chs and then leave it, course
55 00	Across road to Ft Tejon course S 28° E.
40 00	Set a post to temp $\frac{3}{4}$ sec corner.
36 50	Across road to Ft Tejon, course S 77 $\frac{1}{2}$ ° W.
36 50	EAST on a RANDOM line bet secs 16 and 21. Var 14° 13' E.
80 00	17, 20 and 21 (in edge of plane) raised a mound with trench and pits.
80 00	Set a post charred, chalked and notched for the corner of secs 16,
40 00	with trench and pits.
40 00	Set a post charred and chalked for the $\frac{3}{4}$ sec cor, and raise a mound
28 00	Across same.
18 00	To ravine course 80° E.
80 63	SOUTH bet secs 16 and 17. Var 14° 13' E.
80 63	The corner to secs 8, 9, 16 and 17.
40 31	with trench and pits.
40 31	Set a post charred and chalked for the $\frac{3}{4}$ sec cor, and raise a mound
80 63	WEST on a TRUE line to secs 9 and 16. Var 14° 22' E.
80 63	and 16, from which I ran
80 63	Intersect N & S line 21 lks south of the corner to secs 9, 10, 15
76 00	Across the same.
64 00	To ravine course N 40° E.

40 00 EAST on a RANDOM line bet secs 5 and 8. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. To ravine, course N 45° E. Across the same. 75 00 Intersect the N & S line 20 lks north of the corner to secs 4, 5, 8 and 9, from which corner I ran 79 55 WEST on a TRUE line bet secs 5 and 8. Var 14° 4' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor. and raised a mound with trench and pits. 39 77 To corner of secs 5, 6, 7 and 8. WEST on a RANDOM line bet secs 6 and 7. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. To valley. 40 00 To foot of hill. 78 00 Intersect the west bdy of the tp, 50 lks south of the corner to secs 6 and 7, from which corner I ran 79 60 EAST on a TRUE line bet secs 6 and 7. Var 13° 52' E. Set a post charred and chalked for the  $\frac{3}{4}$  section corner and raise a mound with trench and pits. 39 61 The cor to secs 5, 6, 7 and 8. 79 60 SOUTH bet secs 7 and 8. Var 14° 13' E. Set a post charred and chalked to the  $\frac{3}{4}$  sec corner and raise a mound with trench and pits. 40 00 To ravine or depression, course N 40° E. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec corner. Across ravine. 45 00 Intersect the N & S line 40 lks north of the corner to secs 8, 9, 16 and 17, from which corner I ran 79 67 WEST on a TRUE line bet secs 8 and 17. Var 13° 56' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec corner and raised a mound with trench and pits. 39 83 To corner to secs 7, 8, 17 and 18. 79 67 WEST on a RANDOM line bet secs 7 and 18. Var 14° 13' E. To ravine, course 45° N to E. 17 50 Across the same. 22 50 Set a post for temp  $\frac{3}{4}$  sec corner. 40 00 Intersect the west bdy of the tp. 58 lks south of cor to secs 17 and 18, from which course I ran 79 71 EAST on a TRUE line bet secs 7 and 18. Var 13° 48' E. Set a post charred and chalked for the  $\frac{3}{4}$  section corner and raised a mound with trench and pits. 39 70 The corner to secs 7, 8, 17 and 18. 79 70 SOUTH bet secs 17 and 18. Var 14° 13' E. Set a post charred and chalked for the  $\frac{3}{4}$  sec cor and raised a mound with trench and pits. 40 00 To ravine, course N 60° E. 47 00 Across the same. 53 00 To ravine, course N 50° E. 69 00 Across the same. 74 00 Set a post charred, chalked and notched for the cor to secs 17, 18, 19 and 20, and raised a mound with trench and pits. 80 00 EAST on a RANDOM line bet secs 17 and 20. Var 14° 13' E. Set a post for temp  $\frac{3}{4}$  sec cor. 40 00 Intersect N & S line 25 lks north of the cor to secs 16, 17, 20 & 21. From which corner I ran 79 60 WEST on a TRUE line bet secs 17 and 20. Var 14° 02' E. Set a post charred chalked to the  $\frac{3}{4}$  sec cor and raised a mound with trench and pits. 39 70 The corner to secs 17, 18, 19 and 20. 79 40



WEST on a RANDOM line bet secs 18 and 19. Var 14° 13' E. 40 00  
 Set a post for temp  $\frac{1}{2}$  sec corner. 79 68  
 Intersect the west bay of tp. 48 lks south of the corner to secs 18 and 19. From which corner I run EAST on a TRUE line bet secs 18 and 19. Var ----- 39 68  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec cor and raised a md with trench and pits. The corner to secs 17, 18, 19 and 20. 79 68  
 SOUTH bet secs 19 and 20. Var 14° 13' E. (See C S 9027) 34 00  
 To valley, course E & W. Across road to Ft Tejon, course E & W. 36 00  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec corner and raised a md with trench and pits. 40 00  
 To steep hill and white oak timber. 73 00  
 Set a post charred and chalked and notched for the corner to secs 19, 20, 29 and 30, with trench and pits. A white oak 18" dia brs south 47° E., 102 lks. A white oak 15" dia brs N. 85 $\frac{1}{2}$ ° E., 71 lks. A white oak 12" dia brs N 32° W. 325 lks. 80 00

EAST on a RANDOM line bet secs 20 and 29. Var 14° 13' E. 40 00  
 Set a post for temp  $\frac{1}{2}$  sec cor. Intersect N & S line 30 lks north of the corner to secs 20, 21, 28 and 29, from which corner I run WEST on a TRUE line bet secs 20 and 29. Var 14° E. 39 77  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec corner and raised a mound with trench and pits. The corner to secs 19, 20, 29 and 30. 79 55  
 WEST on a Random line bet secs 19 and 30. Var 14° 13' E. 40 00  
 Set a post for temp  $\frac{1}{2}$  sec corner. Intersect the ~~XXXXXXXXXX~~ west boundary of the tp., 54 lks south of the corner to secs 19 and 30, from which corner I run EAST on a TRUE line bet secs 19 and 30. Var 13° 50' E. 39 60  
 Set a post charred and chalked for the  $\frac{1}{2}$  sec corner and raised a md with trench and pits. The corner to secs 19, 20, 29 and 30. 79 60  
 SOUTH bet secs 29 and 30. Var 14° 13' E. (See C S 9027) 17 25  
 As I cannot survey further on account of the hills and the dense growth of oak shrub, I set a post charred, chalked and notched and raised a mound from which A pine 8" dia brs N 16 $\frac{1}{2}$ ° W. 104 lks.

## NOTE:

Certificate as to the foregoing made by J. W. Mandeville, U. S. Surveyor General of California, December 15, 1857.

Copied from Notes loaned County Surveyor by Mr. V. J. Rowan.  
August, 1918.

Survey commenced Jan 22, 1903 and completed Jan 26, 1903.  
As surveyed by James M. Duce, U. S. Deputy Surveyor,  
under his contract dated October 19, 1901, and Sept.  
25, 1906.

T 8 N, R 17 W.

Resurvey of a portion of the boundary line of  
of the  
Field Notes

Resurvey of SOUTH boundary of T 8 N., R 17 W., S.B.M.

After diligent search and being unable to find any trace of old corner of Townships 7 and 8 North, Range 17 West, I go to the  $\frac{3}{4}$  section corner between Sections 3 and 34, on South boundary of township, the nearest known corner on said South boundary, which is a badly decayed post, marked and witnessed as described by the Surveyor General. Bearing tree is nearly dead. I re-established same by setting a quartz rock 18x14x7, 12 ins in the ground, marked  $\frac{3}{4}$  S on north face, from which a live oak 10" dia brs S 12° W, 137 lks dist., marked  $\frac{3}{4}$  S 3 B E. Old three-pronged white oak 10" dia brs N 86° W, 283 lks dist, marked  $\frac{3}{4}$  S B T. From said  $\frac{3}{4}$  sec cor I run EAST on a random line along S boundary of township, making diligent search at every 40 chs for old corner, and being unable to find any trace of the same, setting temporary corners, and at 203.54 chains intersect range line 6.18 chains S of closing corner of Townships 7 and 8 North, Range 16 West, which is a stone 6 inches above stone mound, marked CC on E face, with 6 grooves on N, S and E faces, and stone mound E of corner. Set temporary closing corner.

I return to the  $\frac{3}{4}$  section corner between sections 3 and 34 on S bdy of township and run EAST on a true line between sections 3

and 34.  
Descend.

9 81 Gulch 25 lks wide, course N E. Ascend.  
12 80 Low ridge, brs NE & SW. Descend through dense brush.  
31 20 Gulch 20 lks wide, small stream of water 2 lks wide. Course N. Ascend.  
38 00 Top of ridge, bears N & S. Descend.  
40 71 Being still unable, after diligent search to find any trace of old corner of Sections 2, 3, 34 and 35, I re-establish same by setting a rock 20x8x8 15 inches in the ground, for cor of sections 2, 3, 34 and 35, marked with two notches on the E and D ur notches on W edges from which

A pine 6" dia brs S 39° E. 47 lks dist, marked T 7 N R 17 W S 2 BT.  
A pine 15" dia brs N 26 $\frac{1}{2}$ ° E. 110 lks dist, marked T 8 N R 17 W S 35 BT.  
A white oak 16" dia brs S 22° W. 53 lks dist, marked T 7 N R 17 W S 3 BT.  
A white oak 24" dia brs N 73° W. 104 lks dist, marked T 8 N R 17 W S 34 B T.

EAST on a TRUE line bet Secs 2 and 35.

9 71 Ravine 12 lks wide, course NE. Ascend through brush and scattered pine timber  
14 31 Rocky point, brs N. Descend.  
16 55 Gulch 10 lks wide, course NW. Ascend.  
25 30 Top of spur, brs NE. Descend.  
37 80 Gulch 20 lks wide, course NE. Ascend.  
39 30 Spur brs N. Descend.  
40 71 Being still unable after diligent search to find any trace of old  $\frac{3}{4}$  sec cor, I re-establish same by setting a granite stone 20x7x7 15" in the ground for  $\frac{3}{4}$  section cor, marked  $\frac{3}{4}$  on N face, from which  
A white oak 12" dia brs 60 $\frac{1}{2}$ ° W. 88 lks dist, marked  $\frac{3}{4}$  S 35 BT.  
A pine 24" dia brs S 77° W. 39 lks dist marked  $\frac{3}{4}$  S 2 BT.  
Gulch 25 lks wide, course N 20° W. Ascend.  
43 35 Top of ridge brs NE & SW. Descend.  
50 10 Main canyon with small stream of water 21 lks wide, course NE. Ascend.  
81 42 Being still unable after diligent search to find any trace of old corner, I re-establish same by setting a granite stone 20x5x7, 15" in the ground for cor of Secs 1, 2, 35 & 36, marked with 1 notch on E and 5 notches on W edge, from which  
A pine 8" dia brs S 18 $\frac{1}{2}$ ° E. (18 $\frac{1}{2}$ °) 72 lks dist, marked T 7 N R 17 W S 1 BT.