

FIELD NOTES

of

SECTION 5, TOWNSHIP 2 NORTH

RANGE 14 West, S.B.M.

Surveyed by W. A. Sickler, in 1902

Copied from notes loaned by Harry Waite, which he had copied and compared at Surveyor-General's office in San Francisco.



North Boundary Section 5,  
T 2 N, R 14 W, S. B. M.

May 5, 1902, at 8 h. o.m. A.M. 1 M.T. I set off  $34^{\circ}18'$  on lat. arc,  $16^{\circ}07'$  N. on decla. arc and determine a true meridian with the solar at the corner to Secs. 32 and 33 on N. boundary of township. Thence I run W. on random line between Secs. 5 and 32.

- Road, course N. and S.  
1 00 Dry wash at foot of steep mount., course S. Ascend.  
5 50 Top of ridge, course N. and S. Descend.  
10 00 Gulch 20 lks. wide, course S.  
16 00 Top of ridge, course N. and S.  
28 00 Old  $\frac{1}{4}$  sec. corner, marked and witnessed as described by Surveyor-  
38 00 General, I destroy all marks, referring to T. 3, and mark post  
 $\frac{1}{4}$  S. 5 on S. face.  
Set rock 18 x 10 x 8 in. 12 in. in ground for  $\frac{1}{4}$  sec. corner,  
40 00 marked  $\frac{1}{4}$  on N. face. Dig pits 18x18x12 in. E.&W. of corner  
3 ft. distant. Raise a mound of earth and rock 3 ft. base,  $1\frac{1}{2}$  ft.  
high, N. of corner.  
Gulch 20 lks. wide, course S.  
40 40 Top of ridge, course NW to SE.  
54 00 Road, course N. and S.  
75 80 Creek 30 lks. wide, course S.  
77 00 Old corner to Secs. 5, 6, 31 and 32 marked and witnessed as described  
77 50 by Surveyor-General, I destroy all marks on bearing trees, referring  
to Secs. 31 and 32. I destroy old post which was partly decayed  
and set a new elder post 3 ft. long and 4 in. square in old mound  
for cor. to secs. 5 and 6, marked S. G. F. R. on N., 00 on S., T. 2 N.  
S. 5 and E and R 14 W. S. 6 on W. faces, with 1 groove on W. and  
5 grooves on E. faces.  
Set a rock 12x12x8 in. 8 in. in ground for corner to secs. 31 and  
80 00 32, marked S G F R on N face, with 5 notches on E. and 1 Notch on W  
edges, from which a live oak 6 in. in diameter bears N.  $81^{\circ}$  W. 21  
lks. dist., marked T. 3 N., R. 14 W. S 31 B.T.  
A live oak 6 in. in diam. bears N.  $35^{\circ}$  E. 155 lks. distant, marked  
T 3 N., R. 14 W. S 32 B T.  
The returned course on true line is the same as random line reversed.  
Land mountainous. Soil rocky. No timber. Mountainous land 80 chs.

South Boundary Section 5

From corner to Secs. 4, 5, 8 & 9 west on true line between Secs.  
5 and 8.

Over nearly level land.

- 19 00 Intersect N. boundary of Rancho Tejunga at a point from which cor.  
No. 3 bears S.  $58^{\circ}30'$  east 4.82 chs. dist. Set rock 18x12x8 in.  
12 in. in ground for closing corner to fractional Secs. 5 and 8,  
marked 00 on E. T. on W. with 5 grooves on S. faces. Dig pits  
18x8x12 in. crosswise on each line N.  $56^{\circ}30'$  W. 3 ft. and E. 7 ft. from  
rock, raise mound of earth  $3\frac{1}{2}$  feet base,  $1\frac{1}{2}$  ft. high E. of corner.  
Level land. Soil first rate.

Western Boundary, Sec. 5  
T 2 N., R 14 W. S. B. M.

From corner to Secs. 5 and 6 on N. boundary of township I run south on true line between Secs. 5 and 6.

5 00 Along creek bottom.  
29 00 Foot of mountain.  
40 00 Top of ridge, course E. and W. Descend.  
Set a rock 18x12x8 in. 12 in. in ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  on W. face, \*Pits impracticable. This corner is on steep side of gulch, facing W.  
Descend, along E. side of gulch.  
55 25 Intersect N. boundary of Rancho San Fernando at a point from which corner No. 4 bears S. 82°22' east 379 lks. dist.  
Set a redwood post 3 ft. long, 4 in. square 24 in. in ground for closing corner to fractional secs. 5 and 6, marked: 00 T 2 N., R. 14 W. on N.; S. 5 with 5 grooves on E.; S 6 with 1 groove on W.; and S. F. on S. faces. Dig pits 18x18x12 in. crosswise on each line S. 82°22' E. and N. 82°22' W. 3 ft. on N. of post 7 ft. dist. Raise a mound of earth and rock  $3\frac{1}{2}$  ft. base, 2 ft. high N. of corner.  
Land mountainous and level land. Soil third rate. Mountainous land 50.25 chs.  
May 10, 1902

\*Raise a mound of rocks 2 ft. base,  $1\frac{1}{2}$  ft. high W. of corner.

East Boundary Sec. 5.

From corner to Secs. 4, 5, 8 and 9, I run N. 0°41' E on random line between Secs. 4 & 5.  
40 64 A point 4.8 lks. E. of  $\frac{1}{4}$  sec. corner, which is a post set firmly in the ground, marked and witnessed as described by the Surveyor-General.  
Thence I run south on true line between Secs. 4 and 5.  
12 00 Top of ridge 300 ft. above corner, course E. and W. Descend.  
40 64 Corner to Secs. 4, 5, 8 and 9.  
From  $\frac{1}{4}$  Sec. corner I run N. 0°56' E. on random line between Secs. 4 and 5.  
40 20 To a point 35 lks. east of corner to Secs. 4 and 5, thence I run S. 0°26' W. on true line between Secs. 4 and 5.  
4 00 Dry bed of Little Tejuanga Creek 40 lks. wide, course W.  
8 50 Road, course E and W. Ascend rough spur.  
23 00 Top of spur, course E. and W.  
32 00 Gulch, course N.W. Ascend.  
40 20  $\frac{1}{4}$  Sec. Cor.  
Land mountainous. Soil first rate. No timber. Mountainous land 50.84 chains.

May 12, 1902