

DEPARTMENT OF THE INTERIOR,  
OFFICE OF U. S. SURVEYOR-GENERAL.

San Francisco, California

November 10th, 1921

I, John Glover, U. S. Surveyor-General  
for California, do hereby certify that the annexed  
transcript of the field notes of the subdivisional lines of  
sections 6,7,18,19,30 and 31 of Township 9 North, Range 10 West  
and sections 1,12,13,24,25 and 36 of Township 9 North, Range 11  
West all of San Bernardino Meridian, California, is a

true and literal exemplification of the same on file in this office.

IN TESTIMONY WHEREOF I have hereunto subscribed my name and caused  
the seal of this office to be affixed on the day and year above  
written.

*John Glover*  
United States Surveyor-General  
for California.



R12W R11W	36	31	32	33	34 T10N.	35	36	R11W R10W	31	32	
	1	6	5	4	T9N. 3	2	5	1	6	9	5
						11	4	3	8		
							4	12	7	8	8
						14	4	3	8		
							3	13	18	7	17
						23	3	7	19	6	20
						26	2	6	30	6	29
							2	25	30	6	29
						35	2	1	5	6	32
					T9N. T8N.	2	1	36	31	5	32
						2	1	6	5		

	R11W R10W	
36	31	
9		T9N
1	6	T8N

Red = R.W. Norris survey - Contract dated Oct. 19, 1855  
Blue = Henry Hancock " - " " Mar. 7, 1865  
Green = R.W. Norris " - " " Oct. 1855

Between T. 9 & 10 N. R. 11 W. S. B. M.

80.00 West on a true line between secs. 5 and 32  
 Var. 14°29'E:  
 80.00 Set a charred post for cor. to secs. 5, 6, 31 and 32,  
 and raise mound with trench as per instructions.  
 x x x x x

40.00 West on a true line between secs. 6 and 31  
 Var. 14°29'E.  
 40.00 Set a charred post for 1/4 sec. cor. and raised mound with  
 trench as per instructions  
 81.89 The established corner to townships 9 and 10 N. Rs.  
 11 and 12 W.  
 Land hilly and 3d rate

chs. lks. T. 9 N., R. 11 W., S. B. M.  
 subdivision commenced June 24, 1856.  
 From the corner to sections 1, 2, 35 and 36, on the  
 South side of the township, I run  
 North between sections 35 and 36  
 Variation 14°13' East  
 40.00 Set charred post for 1/4 section corner and raised mound  
 with trench as instructed  
 80.00 Set charred post for corner to sections 25, 26, 35  
 and 36 and raised mound with trench as instructed  
 Land gently rolling, sandy soil 2nd rate. Growth  
 of palmetto, scrub and grass.

East on a random line between sections 25 and 36  
 Variation 14°13' East  
 40.00 Set a post for temporary 1/4 section corner  
 56.00 To dry bed of lake bearing North and South  
 80.00 Intersect East Boundary 31 links south of corner to  
 sections 25 and 36, from which corner I run

T. 9 N., R. 11 W., S.B.M.

Chs. lks.	
00.00	North between sections 23 and 24.
	Variation 14°13' East
40.00	Set a charred post for $\frac{1}{4}$ section corner and raised a mound with trench as per instructions
80.00	Set a charred post for corner to sections 13, 14, 23 and 24 and raised a mound of earth as per instructions.
	Land rolling, sandy soil, growth palmetto, scrub and grass.
00.00	East on a random line between sections 13 and 24
	Variation 14°13' East
40.00	Set a post for temporary $\frac{1}{4}$ section corner
80.02	Intersect East boundary 39 links South of corner to sections 13 and 24, from which corner I run
00.00	West on a true line between sections 13 and 24
	Variation 14°30' East
40.01	Set a charred post for $\frac{1}{4}$ section corner and raised a mound with trench as per instructions.
80.02	The corner to sections 13, 14, 23 and 24.
	Land rolling, sandy soil, growth greasewood and grass
00.00	North between sections 13 and 14
	Variation 14°13' East
25.00	To rolling hills, bearing East and West
40.00	Set a charred post for $\frac{1}{4}$ section corner and raised a mound with trench as instructed.
80.00	Set a charred post for corner to sections 11, 12, 13 and 14, and raised a mound with trench as per instructions.
	Land rolling hills 3rd rate, growth greasewood and scrub.
00.00	East on a random line between sections 12 and 13
	Variation 14°13' East

## T. 9 N., R. 11 W., S.B.M.

Chs. lks.

- 40.00 Set a post for temporary  $\frac{1}{4}$  section corner
- 79.92 Intersect East boundary 48 links south of corner to sections 12 and 13, from which corner, I run
- 
- West on a true line between sections 12 and 13  
Variation  $14^{\circ}34'$  East
- 39.96 Set a charred post for  $\frac{1}{4}$  section corner and raised a mound with trench as per instructions.
- 79.92 The corner to sections 11, 12, 13 and 14.  
Land rolling hills 3rd rate, Growth greasewood and scrub.
- 
- North between sections 11 and 12  
Variation  $14^{\circ}13'$  East
- 40.00 Set charred post for  $\frac{1}{4}$  section corner and raised a mound with trench as per instructions.
- 80.00 Set a charred post for corner to sections 1, 2, 11 and 12 and raised a mound with trench as per instructions.  
Land rolling hills, sandy soil, growth grass and scrub
- 
- East on a random line between sections 1 and 12  
Variation  $14^{\circ}13'$  East
- 40.00 Set a post for temporary  $\frac{1}{4}$  section corner
- 80.12 Intersect East boundary 41 links south of corner to sections 1 and 12 from which corner I run
- 
- West on a true line between sections 1 and 12  
Variation  $14^{\circ}31'$  East
- 40.06 Set a charred post for  $\frac{1}{4}$  section corner and raised a mound with trench as per instructions.
- 80.12 The corner to sections 1, 2, 11 and 12.  
Land rolling hills, sandy soil, growth grass and scrub
-

T. 9 N., R. 10 W., of S.B.M.

Chains.

79.00 south of corner to sections 30 and 31, from which corner I run

East on the true line between sections 30 and 31

Variation 13°53'E.

38.65 Set a charred post for the 1/4 section corner and made a mound with trench and pits as per instructions.

78.65 The corner to sections 29, 30, 31 and 32

Land generally level, clay bed of lake.

80.00 North between sections 29 and 30

Variation 14°11'E.

40.00 Set a charred post for the 1/4 section corner and made a mound with trench and pits as per instructions

80.00 Set a charred post for the corner to sections 19, 20, 29 and 30, and made a mound with trench as per instructions.

Land rolling and sandy with grass and bushes.

West on a random line between sections 29 and 30

Variation 14°11'E.

40.00 Set a post for temporary 1/4 section corner

79.00 Intersect the west boundary of the township 49 links south of the corner to sections 19 and 30, from which corner I run

East on the true line between sections 19 and 30

Variation 13°50'E.

39.00 Set a charred post for the 1/4 section corner and made a mound with trench as per instructions.

79.00 The corner to sections 19, 20, 29 and 30.

Land rolling and sandy with grass, bushes and palmetto

North between sections 19 and 20

Variation 14°11'E.

Chs. lks.

SECTION 1-11

North on a random line between sections 1 and 2

Variation 14°13' East

40.00 Set a post for temporary  $\frac{1}{4}$  section corner  
 48.00 Leave hills to rolling valley bearing North West.  
 81.34 Intersect North boundary 45 links East of corner to sections 1 and 2, from which corner, I run

39°00

South on a true line between sections 1 and 2.

Variation 14°32' East

41.34 Set a charred post for  $\frac{1}{4}$  section corner and raised a mound with trench as instructed  
 81:34 The corner to sections 1, 2, 11 and 12  
 80°00 Land South  $\frac{1}{2}$  hilly, North  $\frac{1}{2}$  level, sandy soil, scrub and grass.

SECTION 1-12

SECTION 1-12

Surveyed by R.W. Norris, Deputy Surveyor,  
Contract dated October 19, 1855.

SECTION 1-12

T. 9 N., R. 10 W., S.B.M.

North between sections 31 and 32

Variation 14°11' E.

30°00

In dry bed of lake

40°00  
40.00

Set a charred post for the  $\frac{1}{4}$  section corner and made a mound with trench and pits as per instructions

60.00

Leave dry bed of lake for rolling and sandy land.

80.00

Set a charred post for corner to sections 29, 30, 31

18°00

and 32, made a mound with trench and pits as per instructions.

36°00

Land for 60 links is clay bed of lake, the rest is sandy.

SECTION 1-22

West on a random line between sections 30 and 31

Variation 14°11' E.

16.00

To dry bed of lake bearing North and South

40.00

Set a post for temporary  $\frac{1}{4}$  section corner.

78.65

Intersect the West boundary of the township 43 links

T. 9 N., R. 10 W., of S.B.M.

Chains.	
5.00	The ground is ascending to the North
40.00	Set a charred post for the $\frac{1}{4}$ section corner and made a mound with trench and pits as per instructions
80.00	Set a charred post for the corner to sections 17, 18, 19 and 20 and made a mound with trench and pits as per instructions.
	Land ascending to the North and sandy with grass, palmetto and bushes.
<hr/>	
	West on a random line between sections 18 and 19
	Variation $14^{\circ}11'E.$
40.00	Set a post for temporary $\frac{1}{4}$ section corner
79.60	Intersect the West boundary of the township 49 links South of the corner to sections 18 and 19, from which corner, I run
	East on the true line between sections 18 and 19
	Variation $13^{\circ}50'E.$
39.60	Set a charred post for the $\frac{1}{4}$ section corner and made a mound with trench and pits as per instructions
79.60	The corner to sections 17, 18, 19 and 20
	Land rolling and sandy with some grass, bushes and palmetto and the soil is generally second rate.
<hr/>	
	North between sections 17 and 18
	Variation $14^{\circ}11'E.$
25.00	To base of low hills bearing East and West
35.00	To top and descend.
40.00	Set a charred post for the $\frac{1}{4}$ section corner and made a mound with trench and pits as per instructions
47.00	Leave hills bearing North $45^{\circ}$ West
80.01	Set a charred post for the corner to sections 7, 8, 17 and 18 and made a mound with trench and pits as per instructions.
	Land sandy with grass and palmetto.
<hr/>	

T. 9 N., R. 10 W. of S.E.M.

Chains.

West on a random line between sections 7 and 18

Variation 14°11'E.

40.00 Set a post for the temporary  $\frac{1}{4}$  section corner

60.00 To low hills bearing North 45° West

80.18 Intersect the West boundary of the township 55 links

South of the corner to sections 7 and 18, from  
which corner, I run

East on the true line between sections 7 and 18

Variation 13°47'E.

40.18 Set a charred post for the  $\frac{1}{4}$  section corner and made

a mound with trench and pits as per instructions

80.18 The corner to sections 7, 8, 17 and 18.

Land sandy and rolling with grass and some palmetto

North between sections 7 and 8

Variation 14°11'E.

40.00 Set a charred post for the  $\frac{1}{4}$  section corner and made

a mound with trench and pits as per instructions

80.00 Set a charred post for the corner to sections 5, 6, 7

and 8 and made a mound with trench and pits as per  
instructions.

Land level and sandy with grass, bushes and palmetto.

West on a random line between sections 6 and 7

Variation 14°11'E.

40.00 Set a post for temporary  $\frac{1}{4}$  section corner

80.40 Intersect the West Boundary of the township 50 links

South of the corner to sections 6 and 7, from which  
corner I run

East on the true line between sections 6 and 7

Variation 13°50'E.

40.40 Set a charred post for the  $\frac{1}{4}$  section corner and made a

mound with trench and pits as per instructions



T. 9 N., R. 10 W. of S.B.M.

Chains.

80.40 The corner to sections 5, 6, 7 and 8  
Land generally second rate and level.

---

North on a random line between sections 5 and 6  
Variation 14°11'E.

20.00 To low rolling hills bearing East and West

40.00 Set a post for temporary  $\frac{1}{4}$  section corner

81.31 Intersect the North boundary of the township 43 links  
West of the corner to sections 5 and 6, from which  
corner I run

South on the true line between sections 5 and 6  
Variation 13°53'E.

41.31 Set a charred post for the  $\frac{1}{4}$  section corner and made a  
mound with trench and pits as per instructions

to 81.31 The corner to sections 5, 6, 7 and 8  
Land generally second rate and level

---

Surveyed by Henry Hancock, Deputy Surveyor,  
Contract dated March 7, 1865.

Chains.

Tp. Lines N. and W. of S.B.M.

From the corner to townships 8 and 9 North, ranges 10  
and 11 West, I run

West on a true line between sections 1 and 36  
Variation 14°26'E.

5.00 Leave dry bed of lake

40.00 Set a post charred and chalked for the  $\frac{1}{4}$  section corner  
and made a mound with trench and pits as per  
instructions.

80.00 Set a post charred, chalked, and notched for the corner  
to sections 1, 2, 35 and 36 and made a mound with  
trench and pits as per instructions.

Generally second rate and sandy soil with scattering  
palmetto and sage.

---

Surveyed by Ralph W. Norris, Deputy Surveyor,  
Contract dated October 1855.