

FIELD NOTES OF SURVEY OF  
 Section 14, and half mile between sections  
 10 & 15, and half mile between sections 12  
 & 13, in Township 1 South, Range 17 West,  
 S. B. M.

---

Copied December 3, 1921, from Notes loaned by  
 C. E. Bailey.

	R.18 W.	R.17 W.	31	32	33	34	35	36	R.17 W.	R.16 W.	T.1 N.
1			6	5	4	3	2	1			715 6
12			7	8	9	10	11	12			7
19			18	17	16	15	14	13			18
24			19	20	21	22	23	24			19
25			30	29	28	27	26	25			30
36			31	32	33	34	35	36			31 713
			6	5	4	3	2	1			725

T 1 S, R 17 W, S.B.M.

North between sections 23 and 24

x x x x x

Var. 14°15'E.

80.00

Set a sandstone 26x12x10 inches, 19 inches in the ground for corner to sections 13, 14, 23 and 24, marked with 3 notches on S. and 1 notch on E. edges. Dug pits on each section 5½ feet distant, and raised an earth mound 2 ft high, 4½ ft base alongside. Oct. 29, 1895

-----  
North between sections 13 and 14.

Var. 14°14'E.

Ascend.

1.00  
13.00  
17.50  
25.40  
33.00  
37.92  
40.00

Top of ridge bears E. and W. and descend.  
Cross gulch, 3 lks. wide, course NE. and ascend.  
Top of spur, bears N. 55°E. and S. 55°W. and descend.  
Cross gulch 3 links wide, course NE. and ascend.  
Top of spur, bears NE. and SW. and descend.  
Cross gulch, 3 links wide, course NE. and ascend.  
Set a sandstone 20x16x10 inches 15 inches in the ground for quarter section corner marked ¼ on W. face. Dug pits 18x18x12 inches N. and S. of stone, 5½ ft. distant, and raised on earth mound 1½ ft. high 3½ ft. base alongside.

40.20

Top of Sierra Madre de Santa Monica mountains, bears N. 60° E. and S. 60° W. and descend.

46.50  
54.50  
62.80  
69.70  
74.54  
76.50  
80.00

Cross ravine, 6 lks. wide, course E. and ascend.  
Top of ridge bears E. and W. and descend.  
Cross gulch, 5 lks. wide, course E. and ascend.  
Top of spur bears NE. and SW. and descend.  
Cross gulch, 3 lks. wide, course E. and ascend.  
Top of spur, bears NE. and SW. and descend.  
Set a sandstone 20x14x12 inches 15 inches in the ground for corner to sections 11, 12, 13 and 14, marked with 1 notch on E. and 4 notches on S. edges. Dug pits 18x18x12 inches in each section 5½ ft distant, and raised an earth mound 2 ft. high, 4½ ft. base alongside.  
Land, mountainous, Soil, 3rd rate.

Scattering oak timber and dense undergrowth of chaparral. Oct. 30, 1895.

-----  
East on a random line bet. sections 12 and 13.

Var. 14°30'E.

40.00  
80.28

Set temporary quarter section corner.  
Intersect east boundary of township 24 lks. south of corner to sections 7, 12, 13 and 18. Thence I run South 89°50' West on true line between sections 12 and 13. Var. 14°42'E.

Ascend.

x x x x x

40.14

Set a sandstone 30x14x10 inches 22 inches in the ground for quarter section corner, marked ¼ on N. face, from which bears a

Live oak 15 in dia. S. 25°E. 57 lks. distant, marked ¼ S.B.T.

Live oak 8 in dia. S. 12-3/4°W. 32 lks. dist. marked ¼ S.B.T.

51.50  
56.00  
63.00  
67.00

Top of spur bears N. and S. and descend.  
Cross gulch, 4 lks. wide, course N. 3° W. and ascend.  
Top of spur bears N. 60° E. and S 60° W. and descend.  
Cross gulch, 3 lks. wide, course N. and ascend.

## T 1 S, R 17 W, S. B. M.

- 75.10 Top of spur bears NE. and SW. and descend.  
 80.28 The corner to sections 11, 12, 13 and 14.  
 Land, mountainous. Soil, second and third rate.  
 Scattering oak timber and dense undergrowth of chaparral.
- 
- From corner sections 22, 23, 26, and 27, I run  
 North between sections 22 and 23. Var. 14°06'E.  
 Descend.
- x x x x x
- 80.00 Set a sandstone 28 x 12 x 8 inches, 21 inches in the ground  
 for corner to sections 14, 15, 22 and 23, marked with 3  
 notches on S. and 2 notches on E. edges, and raised a stone  
 mound alongside. Pits impracticable.
- 
- East on a random line between sections 14 and 23.  
 Var. 14°15'E.
- 40.00 Set temporary quarter section corner.  
 79.92 Intersect N. and S. line 31 lks. S. of corner to secs.  
 13, 14, 23 and 24. Thence  
 South 89°47'W on a true line between sections 14 and 23.  
 Var. 14°14'E.
- Descend.
- 3.10 Cross head of gulch, course S. and ascend.  
 6.00 Top of spur, bears N. and S. and descend.  
 20.16 Cross head of gulch course S. 12°W and ascend.  
 26.50 Top of spur bears N. and S. and descend.  
 39.96 Set a sandstone 17 x 15 x 10 inches 11 inches in the ground  
 for quarter section corner, marked  $\frac{1}{4}$  on N. face and  
 raised a stone mound alongside. Pits impracticable.
- 44.87 Cross gulch, 3 lks. wide, course S. 10° W. and ascend.  
 59.00 Top of spur bears NW. and SE. and descend.  
 71.64 Cross Mateo Canon 8 lks. wide, course S. and ascend.  
 79.92 The corner to sections 14, 15, 22 and 23.  
 Land, mountainous. Soil, third rate.  
 Scattering oak timber and dense undergrowth of chaparral.  
 November 4, 1895.
- 
- North between sections 14 and 15.  
 Var. 14°15'E.
- Ascend.
- 14.00 Top of spur bears NW. and SE. and descend.  
 21.76 Cross gulch, 4 lks. wide, course S. 40°E. and ascend.  
 40.00 Set a sandstone 27 x 15 X 9 inches, 20 inches in the ground  
 for quarter section corner, marked  $\frac{1}{4}$  on W. face and  
 raised a stone mound alongside. Pits impracticable.
- 45.00 Top of Sierra Madre de Santa Monica mountains bears N.70°  
 E. and S.70°W. and descend.
- 76.60 Cross gulch, 4 lks. wide, course W. and ascend.  
 80.00 Set sandstone 22 x 14 x 10 inches. 16 inches in ground for cor-  
 ner to sections 10, 11, 14 and 15, marked with 2 notches  
 on E. and 4 notches on S. edges, and raised a stone mound  
 alongside. Pits impracticable.  
 Land, mountainous. Soil, third rate.  
 Scattering sycamore and oak timber, and dense undergrowth  
 of chaparral.
-

## T 1 S, R 17 W, S. B. M.

East on a random line between sections 11 and 14.  
Var. 14° 15' E.

40.00 Set a temporary quarter section corner.  
80.19 Intersect N. and S. line 18 lks. N. of corner to sections  
11, 12, 13 and 14. Thence  
North 89° 52' W. on a true line between sections 11 and 14.  
Var. 14° 30' E.

Descend.

5.90 Cross gulch, 5 lks. wide, course N. 10° E. and ascend.  
9.00 Top of spur, bears N. and S. and descend.  
18.77 Cross gulch, 4 lks. wide, course N. 10° W. and ascend.  
29.74 Top of spur, bears N. and S. and descend.  
35.73 Cross ravine, 20 lks. wide, course N. 44° E. and ascend.  
40.09 Set a sandstone 24 x 14 x 10 inches 18 inches on the ground  
for quarter section corner. Marked  $\frac{1}{4}$  on N. face, and  
raised a stone mound alongside. Pits impracticable.  
58.72 Top of divide, bears N. 10° E. and S. 10° W. and descend.  
80.19 The corner to sections 10, 11, 14 and 15.  
Land, mountainous. Soil, third rate.  
Timber of oak and dense undergrowth of chaparral.  
November 5, 1895.

-----  
East on a random line between sections 10 and 15.  
Var. 14° 20' E.

40.00 Set temporary quarter section corner.  
79.80 Intersect north and south line 20 lks. north of corner  
to sections 10, 11, 14 and 15, thence  
North 89° 50' W. on true line between sections 10 and 15.  
Var. 14° 15' E.

Descend.

2.54 Cross gulch 2 lks. wide, course SW. and ascend.  
18.00 Enter heavy timber, bears N. and S. on top of low spur  
bears N. and S. and descend.  
22.00 Cross ravine. 6 lks. wide, course N. and ascend.  
24.00 Leave timber, bears N. and S. on top of low spur, bears  
N. and S. and descend.  
26.85 Cross gulch 4 lks. wide, course N. and ascend.  
30.00 Top of spur bears N. and S. and descend.  
32.00 Cross gulch, 3 lks. wide, course N. and ascend.  
33.75 Top of spur, bears N. and S. and descend.  
39.90 Set a post, 3 ft. long, 3 inches square, with marked stone  
12 inches in the ground for quarter section corner,  
marked  $\frac{1}{4}$  S. on N. face, and raised a mound of stone  
around post. Pits impracticable.

x x x x x  
-----