

DEPARTMENT OF THE INTERIOR
OFFICE OF U. S. SURVEYOR GENERAL

C.S.
9174

San Francisco California.

February 5, 1923., 201

I, John Plover, U. S. Surveyor General for California, do hereby certify that the annexed transcript of the field notes of sections 13, 14, 15, 22, 23 and 24 T.1 S., R. 17 W., S. 3. W., is a

true and literal exemplification of the said field notes which are on file in this office.

John Plover
United States Surveyor General
for California.

T.1 S.

				R.17W.	R.16W.
9	10	11	12	17	
	14+15	10	6+7		
16	¹³ 15	⁹ 14	⁵ 13	18	
	¹⁴ 12+13	¹⁰ 9	⁶ 4+5		
21	¹¹ 22	⁸ 23	⁴ 24	2	19
	¹² 11	⁷ 8	³ 4		
28	27	26	3 25	30	
			35	-36	

October-November—1895



Nov. 25, 1884

T. 1 S., R. 17 W., S. B. M.

Chains South on a true line bet. secs. 7 and 12 Va. 14° 30' East

x x

80.00 Set a sandstone 30 x 12 x 10 ins., 22 ins. in the ground for cor. to secs. 7, 12, 13 and 18, marked with 2 notches on N., and 4 notches on S. edges, from which bears:

A live Oak 16 ins. dia. S. 32½° E., 48 lks. dist., marked T. 1 S., R. 16 W., S. 18 B. T.

A live Oak 12 ins. dia. S. 11½° W., 45 lks. dist. marked T. 1 S. R. 17 W. S. 13 B. T.

No other trees within limits;

Raised a stone mound alongside. Pits impracticable.

Land mountainous Soil 3rd rate

Scattering oak and sycamore timber and dense undergrowth of Chaparral.

x x Oct. 8th. 1895.

South on a true line bet. secs. 13 and 18.

Va. 14° 42' East

Ascend.

1.10 Top of low spur bears NE. and SW. and descend.

2.45 Cross canon 12 lks. wide, Course N. 50° E., and ascend.

17.50 Enter dense brush bears E. and W.

33.00 Top of ridge bears E. and W. and descend.

40.00 Set a sandstone 28 x 20 x 6 ins. 16 ins. in the ground for ¼ sec. cor. marked ¼ on W. face and raised a stone mound alongside. Pits impracticable.

54.41 Cross canon 12 lks. wide Course N. 40° E., and ascend

62.50 Top of ridge bears E. and W. and descend.

71.18 Cross gulch 9 lks. wide. Course E. and ascend

75.00 Cross road bears NE. and SW.

80.00 Set a sandstone 30 x 12 x 5 ins. 15 ins. in the ground for cor. to secs. 13, 18, 19 and 24 marked with 3 notches on N. and S. edges; from which bears-

A live Oak 12 ins. dia. N. 7½° E. 91 lks. dist., marked T. 1 S., R. 16 W., S. 19 B. T.

T.1 S., R.16 W., S 19 B T

No other tree within limits

Dug pits 18 x 18 x 12 ins., in secs. 13 and 24, 5½ ft. dist. and raised an earth mound, 2 ft. high 4½ ft. base alongside. corner stone.

Land mountainous. Soil 3rd rate

Scattering oak and sycamore timber and dense undergrowth of chaparral.

October 9th. 1895.

South on a true line bet. secs. 19 and 24

Va. 14°42' East

Ascend

- 2.00 Top of low spur bears E. and W. and descend
- 3.71 Cross canon 10 lks. wide; course E. and ascend.
- 29.00 Top of ridge bears E. and W. and descend.
- 34.72 Cross gulch 8 lks. wide, course SE. and ascend.
- 39.00 Top of spur bears E. and W. and descend.
- 40.00 Set a sandstone 34 x 20 x 12 ins. in a stone mound, for ½ sec. marked ½ on W. face. Too rocky to set in the ground. Pits impracticable.
- 41.27 Cross gulch 7 lks. wide, course S. 80° E. and ascend
- 51.00 Top of spur bears E. and W. and descend
- 77.00 Cross canon 14 lks. wide Course E. and ascend
- 77.90 Cross road bears E. and W.
- 80.00 Set a sandstone 18 x 12 x 6 ins 12 ins in the ground for cor. to secs. 19, 24, 25 and 30 marked with 4 notches on N. and 2 notches on S. edges and raised a stone mound alongside.
- Pits impracticable. Land mountainous. Soil 3rd rate:
Scattering oak timber and dense undergrowth of chaparral.

October 10th. 1895

Subdivisions of T. 1 S., R. 17 W., S. B. N.

From the corner to sections 25, 26, 35 and 36

I run

North between sections 25 and 26

Var. 14° 30' East

x x x

80.00

Set a sandstone 28 x 20 x 8 inches, 21 inches in the ground for corner to sections 23, 24, 25 and 26 marked with 2 notches on S. and 1 notch on E. edges from which bears a sycamore 16 in dia. N. 33 1/2° E., 21 links distant marked T. 1 S., R. 17 W., S. 24 B T

sycamore 14 in dia. S. 79 1/4° W 11 links distant marked T. 1 S R 17 W S 26 B T

Live oak 18 in, dia S. 64 1/2° E. 12 links distant marked T 1 S R 17 W., S 25 B T

No other tree within limits

Raised a mound alongside corner stone.

Pits impracticable. x x
October 28, 1895.

East on a random line between sections 24 and 25

Var. 14° 15' East

40.00

Set temporary quarter section corner.

80.18

Intersect East boundary of township 21 links north of corner to sections 19, 24, 25 and 30 previously described

Thence I run

North 89° 51' W on true line between sections 24 and 25

Var. 14° 33' east

Descend

15.50

Cross gulch 6 lks. wide Course N. 10° E and ascend.

21.15

Cross road bears NE and SW.

2.15

Cross road bears NW and SW.

1.50

Cross fence bears NE and SW and enter field

1.00

Set a sandstone 20 x 12 x 9 inches 19 inches in the ground for quarter section corner marked 1/2 on N. face from which

Subdivisions T.1 S., R.17 W., S.B.M.

No other tree within limits

Raised a mound of stone alongside corner stone

Pits impracticable.

- 49.00 Top of ridge bears NE. & SW. and descend
- 55.00 Leave field and cross fence bears NE. and SW.
- 79.85 Cross ravine 6 links wide Course SW. and ascend.
- 80.18 The corner to sections 23, 24, 25 and 26.

Land mountainous

Soil third rate.

Scattering timber and dense undergrowth of chaparral.

North between sections 23 and 24

Var. 14° 15' East

Ascend

- 28.00 Top of spur bears E and W. and descend.
- 38.60 Cross gulch 4 links wide, course E. and ascend.
- 40.00 Set a sandstone 34 x 11 x 9 inches 25 inches in the ground for quarter section corner marked $\frac{1}{2}$ on W face Dug pits 18 x 18 x 12 inches N. and S. of stone $5\frac{1}{2}$ ft. distant and raised an earth mound $1\frac{1}{2}$ feet high $3\frac{1}{2}$ feet base alongside.

45.50 Top of spur bears NW. and SE and descend.

51.00 Cross gulch 3 lks. wide, Course S 60° E and ascend

- 80.00 Set a sandstone 26 x 12 x 10 inches 19 inches in the ground for corner to sections 13, 14, 23 and 24, marked with 3 notches on S. and 1 notch on E. edges Dug pits in each section $5\frac{1}{2}$ ft. distant and raised an earth mound 2 ft. high $4\frac{1}{2}$ ft. base alongside.

Land mountainous.

Soil third rate.

Scattering oak timber and dense undergrowth of chaparral

October 29, 1895.

East on a random line between sections 13 and 24.

Var. 14° 14' East

- 40.00 Set temporary quarter section corner

Subdivisions T.1 S., R.17 W., S.B.M.

79.94	Intersect East boundary of township 19 links south of corner to sections 13, 18, 19 and 24 previously described Thence I run South 89° 52' West on a true line between sections 13 and 24, Var. 14° 42' East Ascend
6.50	Cross trail bears NE and SW.
28.00	Top of ridge bears NE. and SW. and descend.
31.00	Cross low sag bears NE and SW. and ascend.
34.50	Top of ridge bears N and S. and descend.
39.40	Cross gulch 4 links wide Course NE. and ascend.
39.97	Set a sandstone 14 x 12 x 8 inches 9 inches in the ground for quarter section corner marked $\frac{1}{4}$ on N. face and raised a stone mound alongside. Pits impracticable.
62.00	Top of ridge bears NW. and SE. and descend.
79.94	The corner to sections 13, 14, 23 and 24. Land mountainous. Soil third rate. Scattering timber and dense undergrowth of same and Chaparral.
	<hr/> North between sections 13 and 14 <div style="text-align: right;">Var. 14° 14' East</div> Ascend
1.00	Top of ridge bears E. and W. and descend
13.00	Cross gulch 3 links wide course NE. and ascend
17.50	Top of spur bears N 55° E and S 55° W and descend
25.40	Cross gulch 3 lks. wide Co. NE and ascend
33.00	Top of spur bears NE and SW and descend
37.92	Cross gulch 3 lks. wide Course NE. and ascend
40.00	Set a sandstone 20 x 16 x 10 inches 15 inches in the ground for quarter section corner marked $\frac{1}{4}$ on W. face Dug pits 18 x 18 x 12 inches N and S of stone 50 feet distant and raised an earth mound $1\frac{1}{2}$ feet high 30 feet base alongside.
40.20	Top of Sierra Madre de Santa Monica mountains, bears N 60° E and S 60° W and descend

- 46.50 Cross ravine 6 lks.wide. Course E.and ascend
- 54.50 Top of ridge bears E.and W.and descend.
- 62.80 Cross gulch 5 links wide Course E.and ascend.
- 69.70 Top of spur bears NE.and SW.and descend.
- 74.54 Cross gulch 3 links wide Course E.and ascend
- 76.50 Top of spur bears NE. and SW and descend
- 80.00 Set a sandstone 20 x 14 x 12 inches 15 inches in the ground
for corner to sections 11,12,13 and 14 marked with 1 notch
on E. and 4 notches on S.edges
Dug pits 18 x 18 x 12 inches in each section $5\frac{1}{2}$ feet distant
and raised an earth mound 2 feet high $4\frac{1}{2}$ feet base along
side.
Land mountainous.
Soil third rate,
Scattering oak timber and dense undergrowth of chaparral
- October 30, 1895
-
- East on a random line between section 12 and 13
Var. $14^{\circ} 30'$ East
- 40.00 Set temporary quarter section corner
- 80.28 Intersect east boundary of township 24 links south of
corner to sections 7,12,13 and 18, previously described
Thence I run
South $89^{\circ} 50'$ West on a true line between sections 12 and
13. Var. $14^{\circ} 42'$ East
Ascend
- 1.40 Cross road bears NE and SW
- 1.45 Cross wire fence bears N and S.
- 3.00 Enter cultivated land bears N and S
- 12.50 Cross road and enter vineyard bears N and S.
- 17.00 Cross road and leave vineyard bears N and S
- 17.10 Leave cultivated land bears N and S.
- 28.00 Top of spur bears N. 15° E. and S. 15° W. and descend
- 30.00 Cross gulch 6 links wide, Course N. 10° E. and ascend.
- 35.00 Top of spur bears N. and S. and descend.
- 38.75 Cross gulch 4 links wide Course N. 15° E. and ascend

Subdivisions T.1 S., R. 17 W., S.B.H.

40.14	Set a sandstone 30 x 14 x 10 inches 22 inches in the ground for quarter section corner marked $\frac{1}{4}$ on N. face from which bears a Live Oak 15 in dia S 25° E. 57 links distant marked S B T Live Oak 8 in dia S 12 $\frac{3}{4}$ ° W 32 links distant marked $\frac{1}{2}$ S B T
51.50	Top of spur bears N and S. and descend.
56.00	Cross gulch 4 links wide Course N. 3° W. and ascend
63.00	Top of spur bears N. 60° E. and S. 60° W. and descend
67.00	Cross gulch 3 lks. wide Course N. and ascend.
75.10	Top of spur bears NE. and SW and descend.
80.28	The corner to sections 11, 12, 13 and 14 Land mountainous. Soil second and third rate. Scattering oak timber and dense undergrowth of chaparral <p style="text-align: center;">x x</p> From the corner to sections 23, 24, 25 and 26 run west on a true line between section 23 and 26 <p style="text-align: right;">Var. 14° 15' East</p> Ascend
.20	Top of low spur bears N and S and descend
.48	Cross ravine 6 links wide Course N 50° W and ascend.
10.00	Top of spur bears N and S and descend
17.20	Cross same ravine 8 links wide Course S. 60° W. and ascend.
39.00	Top of spur bears N. 20° E. and S. 20° W. and descend.
40.00	Set a sandstone 22 x 18 x 14 inches in a stone mound. for quarter section corner marked $\frac{1}{4}$ on N face Pits impracticable. Too rocky to set stone in earth
50.86	Cross gulch 2 links wide Course S. 15° W. and ascend
58.50	Top of spur bears NE. and SW. and descend
72.40	Enter Mateo Canon and cross creek 20 links wide Course S. 15° W.
75.00	Leave Mateo Canon bears N. and S. and ascend.



Subdivisions T.1 S., R.17 W., S.P.M.

	East on a random line between sections 14 and 23 Var. 14° 15' East
40.00	Set temporary quarter section corner
79.92	Intersect N and S line 31 links S. of corner to sections 13, 14, 23 and 24
	Thence I run South 89° 47' West on a true line between sections 14 and 23 Var. 14° 14' East
	Descend
3.10	Cross head of gulch Course S. and ascend.
6.00	Top of spur bears N. and S. and descend
20.16	Cross head of gulch. Course S. 12° W. and ascend.
26.50	Top of spur bears N. and S. and descend.
39.96	Set a sandstone 17 x 15 x 10 inches 11 inches in the ground for quarter section corner marked $\frac{1}{4}$ on N face and raised a stone mound alongside Pits impracticable.
44.87	Cross gulch 3 links wide, Course S. 10° W and ascend
59.00	Top of spur bears NW. and SE. and descend.
71.64	Cross Mateo canon 8 links wide course S. and ascend.
79.92	The corner to sections 14, 15, 22 and 23. Land mountainous; Soil third rate. Scattering oak timber and dense undergrowth of chaparral.
	November 4, 1895
	North between sections 14 and 15 Var. 14° 15' East
	Ascend
14.00	Top of spur bears NW and SE and descend
21.76	Cross gulch 4 links wide, course S. 40° E. and ascend.
40.00	Set a sandstone 27 x 15 x 9 inches 20 inches in the ground for quarter section corner marked $\frac{1}{4}$ on W. face and raised a stone mound alongside. Pits impracticable.
45.00	Top of Sierra Madre de Santa Monica Mountains bears N.

70°E., and S. 70°W., and descend.

76.60 Cross gulch 4 links wide, course W. and ascend

80.00 Set a sandstone 22 x 14 x 10 inches, 16 inches in the
for corner to sections 10, 11, 14 and 15 marked
ground with 2 notches on E., and 4 notches on S. edges
and raised a mound of stone alongside.

Pits impracticable.

Land mountainous.

Soil third rate.

Scattering sycamore and oak timber and dense undergrowth
of chaparral.

East on a random line between sections 11 and 14

Var. 14° 15' East

40.00 Set a temporary quarter section corner

80.19 Intersect N and S. line 18 links N. of corner to sections
11, 12, 13 and 14

Thence I run

North 89° 52' W. on a true line between sections 11 and
14.

Var. 14° 30' east.

Descend

5.90 Cross gulch 5 links wide, course N. 10° E and ascend

9.00 Top of spur bears N. and S. and descend.

18.77 Cross gulch 4 links wide, course N. 10° W and ascend.

29.74 Top of spur bears N. and S. and descend.

35.73 Cross ravine 20 links wide, course N. 44° E., and ascend.

40.09 Set a sandstone 24 x 14 x 10 inches 18 inches in the
ground for quarter section corner marked $\frac{1}{4}$ on N. face
and raised a stone mound alongside

Pits impracticable.

58.72 Top of divide bears N. 10° E. and S. 10° W. and descend.

80.19 The corner to sections 10, 11, 14 and 15

Land mountainous.

Soil third rate.

Timber of oak and dense undergrowth of chaparral.

November 5, 1895

Subdivisions T.1 N., R.17 W., S.B.M.

From the corner to sections 22, 23, 26 and 27 I run
West on a true line between sections 22 and 27

Var. 14° 06' E

Ascend

- 6.56 Top of ridge bears NW. and SE. and descend.
- 10.00 Cross wash 10 links wide, course N. 80° E. and ascend.
- 25.00 Top of ridge bears N. and S. and descend.
- 31.00 Cross low sag bears N. and S. and ascend
- 34.00 Top of spur, bears NE. and SW. and descend.
- 39.00 Cross trail bears N. and S.
- 40.00 Set a sandstone 28 x 14 x 10 inches 21 inches in the
ground for quarter section corner, marked $\frac{1}{2}$ on N. face
and raised a stone mound alongside.
- Pits impracticable.
- 40.50 Cross gulch 8 links wide, course SW. and ascend.
- 42.50 Top of spur bears N. and S. and descend.
- 55.25 Cross canon 25 links wide, course S 10° W. and ascend.
- 56.50 Top of spur bears N. and S. and descend.
- 73.85 Cross canon 10 links wide, course S. and ascend.
- 75.00 Top of spur bears N. and S. and descend.
- 80.00 Set a sandstone 30 x 12 x 10 inches, 22 inches in the
ground, for corner to sections 21, 22, 27 and 28 marked
with 2 notches on S., and 3 notches on E. edges and
raised a stone mound alongside.
- Pits impracticable.
- Land mountainous.
- Soil third rate
- Scattering oak timber and dense undergrowth of chaparral.

x x x x x x

From the corner to sections 21, 22, 27 and 28, I run
North between sections 21 and 22.

Var. 14° 18' east.

Ascend.

- 18.00 Top of spur bears NW. and SE. and descend.
- 40.00 Set a sandstone 16 x 14 x 14 inches, 11 inches in the

ground for quarter sections corner, marked $\frac{1}{4}$ on W. face and raised a stone mound alongside.

Pits impracticable.

45.00 To foot of perpendicular bluff, impossible to chain To avoid same I offset E. 3.00 chains, thence N. 15.00 chains, thence W. 3.00 chains to true line counting distances from corner to sections 21, 22, 27 and 28.

62.00 Cross gulch 4 links wide course S. 15° E. and ascend

80.00 Set a granite stone 30 x 16 x 8 inches 22 inches in the ground for corner to sections 15, 16, 21 and 22 marked with 3 notches on S. and E. edges and raised a stone mound alongside.

Land mountainous

Pits impracticable.

Soil third rate.

Scattering oak timber and dense undergrowth of chaparral.

East on a random line between sections 15 and 22.

Var. 14° 15' east

40.00 Set temporary quarter section corner

79.81 Intersect north and south line 22 links north of corner to sections 14, 15, 22 and 23

Thence I run

North 89° 51' West on a true line between sections 15 and 22. Var. 14° 15' east

Ascend.

5.00 Top of spur bears N. and S. and descend.

11.00 Cross gulch 3 links wide, course S. 30° E. and ascend.

15.00 Top of spur bears NW. and SE. and descend.

39.90 Set a sandstone 36 x 20 x 8 inches 27 inches in the ground for quarter section corner marked $\frac{1}{4}$ on N. face and raised a stone mound alongside.

Pits impracticable.

46.00 Cross gulch 5 links wide, course S. 30° E. and ascend.

59.00	Top of spur bears N. 25° W. and S. 25° E. and descend.
70.00	Cross gulch course S. and ascend
79.81	The corner to sections 15, 16, 21 and 22. Land mountainous Soil third rate Scattering oak timber and dense undergrowth of chaparral.
November 9, 1895	
	North between sections 15 and 16 Var. 14° 15' east Ascend
.10	To foot of perpendicular bluff impossible to chain To avoid same, offset W. 150 links, thence N. 1.90 chains thence E. 150 links to true line, thence N. counting distance from corner to sections 15, 16, 21 and 22:
6.50	Top of Sierra Madre de Santa Monica mountains bears E. and W. and descend.
9.92	Cross gulch 3 links wide course NW. and ascend.
11.50	Top of spur bears NW. and SE. and descend.
13.50	To foot of perpendicular bluff impossible to chain to avoid which I offset E. 2.50 chains, thence N. 3.50 chains, thence W. 2.50 chains to line, thence N. counting distances from corner to sections 15, 16, 21 and 22.
24.00	Cross gulch 5 links wide, course W. and ascend
25.50	To foot of perpendicular bluff impossible to chain, to avoid which I offset W. 69 links; thence N 50 links thence E. 69 links to line, thence N. counting distance from corner to sections 15, 16, 21 and 22 Descend.
28.50	Cross gulch 3 links wide course N. 65° W. and ascend.
31.00	Top of spur bears E. and W. and descend.
37.00	Cross gulch 4 links wide course NW and ascend.
40.00	Set a sandstone 30 x 20 x 12 inches 22 inches in the ground for quarter section corner, marked $\frac{1}{4}$ on W. face.

and raised a stone mound alongside.

Pits impracticable.

68.00 Top of spur bears NW. and SE. and descend.

71.50 Cross gulch 5 links wide course NW. and ascend

72.50 Top of spur bears NW and SE. and descend.

78.00 Cross gulch 3 links wide, course N. 25° E, and ascend

80.00 Top of spur bears NW. and SE. and set a sandstone 24 x

x 16 x 12 inches 18 inches in the ground for corner to sections 9, 10, 15 and 16, marked with 4 notches on S.

and 3 notches on E. edges and raised a stone mound along side.

Pits impracticable.

Land mountainous.

Soil third rate

Scattering oak timber and dense undergrowth of chaparral.

East on a random line between sections 10 and 15

Var. 14° 20' East.

40.00 Set temporary quarter section corner

79.80 Intersect north and south line 20 links north of corner

to sections 10, 11, 14 and 15 thence I run

North 89° 50' West on a true line between sections 10 and 15.

Var. 14° 15' east

Descend.

2.54 Cross gulch 2 links wide course SW and ascend.

18.00 Enter heavy timber bears N. and S. on top of low spur bears N. and S. and descend.

22.00 Cross ravine 6 links wide, course N. and ascend.

24.00 Leave timber bears N. and S. on top of low spur^{bears} N and S and descend.

26.85 Cross gulch 4 links wide course N. and ascend.

30.50 Top of spur bears N. and S. and descend.

32.00 Cross gulch 3 links wide, course N. and ascend

33.75 Top of spur bears N and S and descend

39.90 Set a post 3 feet long, 3 inches square, with marked stone 12 inches in the ground for quarter section corner

marked $\frac{1}{4}$ S on N. face and raised a mound of stone around post.

Pits impracticable.

- 41.50 Cross gulch 3 links wide, course NW., and ascend.
 - 43.00 Top of low spur bears N. and S. and descend.
 - 46.22 Cross gulch 5 links wide, course NE. and ascend.
 - 47.35 Cross road bears NE. and SW.
 - 50.00 Top of spur bears N. and S. and descend.
 - 54.00 Cross ravine 5 links wide, course NE. and ascend.
 - 59.00 Top of spur bears NE. and SW. and descend.
 - 60.90 Cross gulch 4 links wide course NE. and ascend.
 - 63.50 Top of spur bears NE. and SW and descend.
 - 66.15 Cross ravine 3 links wide, course NE. and ascend.
 - 68.30 Top of spur bears NE. and SW. and descend.
 - 72.62 Cross gulch 3 links wide, course N. and ascend
 - 74.50 Top of spur bears NE. and SW. and descend.
 - 75.93 Cross gulch 3 links wide, course NE. and ascend.
 - 77.30 Top of low spur, bears N. and S. and descend.
 - 79.54 Cross gulch 4 links wide, course N. and ascend.
 - 79.80 The corner to sections 9, 10, 15 and 16
- Land mountainous
- Soil third rate.
- Heavy oak timber for 6.00 chains,
- The remainder scattering oak timber and dense undergrowth of chaparral

November 11, 1895.