

COPIED FROM PHOTOGRAPHIC COPIES

FURNISHED BY

U. S. GENERAL LAND OFFICE

WASHINGTON, D. C.

R.18W.		R.17W.
36		31

1		2 6

12		2 7

13		1 18
T.6N.		T.6N.
24		1 19

25		30

36		31

1		6
R.18W.		R.17W.

W.B. T 6 N., R. 17 W., S.B.M.

From the Corner to Township 6 North, Ranges 17 and 18
West, I run,
North on true line on West Boundary of Section 31
Variation 14°25' East

Ascend.

- 40.00 Set stone, 14x16x10, in stone mound 4 feet in diameter at base, by 2 feet in height, for $\frac{1}{4}$ section corner.
- 50.00 Set post, 4 inches square, 1 foot in earth 1 foot above stone mound $4\frac{1}{2}$ feet in diameter at base, by 2 feet in height for corner to sections 30-31-25-36,

from which bears a
Pine 10 in. dia. N. 12 $\frac{1}{2}$ ° E. 78 lks. dist.
Land mountainous. Soil 2nd and 3rd rate.
Timber and undergrowth of Pine, Oak and Chaparral.

North, on West Boundary of Section 30.
Variation 14°25' East.

Ascend.

- 11.50 Top of Spur, bears North East and South West and descend.
- 40.00 Set stone 20x16x12, in stone mound 4 feet in diameter at base, by 2 feet in height for $\frac{1}{4}$ section corner.
- 58.25 Cross near head of Gulch, course South West and ascend.
- 50.00 The point for corner to sections falling on steep hillside, a place not suitable to build mound I continue North 13.19 chains and set post 4 inches square 1 foot in earth 1 foot above stone mound $4\frac{1}{2}$ feet in diameter at base by 2 feet in height for witness to corner to sections 19-30-24-25.
Land mountainous. Soil 2nd and 3rd rate.
Timber and undergrowth of oak and chaparral.
-

North, on West Boundary of Section 19.
Variation 14°25' East.

Ascend.

- 13.19 Witness Post, and descend.
- 40.00 Set Post, 4 inches diameter, 1 foot in earth 1 foot above earth mound, 4 feet in diameter at base by 2 feet in height, and dug pit, 24 x 18 x 12 8 links East for $\frac{1}{4}$ section corner. The line in advance falling on steep side hill I offset East 6.64 chains, and run North on offset line 40.00 chains to the line between sections 18 - 19 to a White Oak 48 inches diameter, which I mark for witness to corner to sections 18 - 19 - 13 - 24. The true corner falls on steep side hill 6.64 chains West of this point, in a place not suitable to build a mound.
Land mountainous. Soil 2nd rate.
Timber and undergrowth of Oak and Chaparral.
-

North, on West Boundary of section 18, on offset line 6.64 chains,
East

Variation 14°25' East.

Descend.

W.B. T 6 N., R. 17 W., S.B.M.

- 20.00 Offset West 6.64 chains to West Boundary of Section 18 and continue North.
- 33.00 Counting distance from true corner to sections 18 - 19 - 24 - 13, a small lake bears West, about 9.00 chains.
- 40.00 Set Post 4 inches diameter, 1 foot in earth 1 foot above Stone mound 4 feet in diameter at base by 2 feet in height for $\frac{1}{4}$ section corner
from which bears a
White Oak 36 in. dia. S. 68°W. 39 lks. dist.
White Oak 20 in. dia. N. 56 $\frac{1}{2}$ °E. 122 lks. dist.
- 43.39 Top of Ridge, bears North East and South West and descend.
- 55.15 Cross trail from Oak Flat to Fort Tejon bears East and West, and leave flag.
- 58.00 Cross Creek, 20 links wide, Course West and ascend.
- 58.40 To foot of steep, abrupt slide of mountain to a cluster of White Oak trees.

As the true corner will fall on this slide of mountain, I mark one of these trees measuring 10 inches diameter for Witness to corner to sections 7 - 12 - 13 - 18.
I then proceed North, on West Boundary of section 7, to summit of high Ridge to a point from which my flag left at 55.15 chains North of corner to sections 18-19-13-24, bears South and run a base 5.00 chains West to a point from which my flag bears S. 8°25' E. which gives by calculation a distance of 35.20 chains to said flag; from this deduct 24.85 chains, the distance of the flag South of the true corner to sections 12-13-7-18, leaves me 10.35 chains, North of corner to sections 12-13-7-18 at which point I set post 4 inches square 1 foot in earth 1 foot above earth mound 4 feet in diameter at base by 2 feet in height and dug pits, 24x18x12, 8 links distant at 4 angles for Witness to corner to sections 7-18-12-13.

Land mountainous. Soil 2nd and 3rd rate.
Timber and undergrowth of Oak and Chaparral.

North on West Boundary of Section 7.

Variation 14°25' East.

Counting the distance from the true corner to sections 12-13-7-18.

- 10.35 Witness Post and descend.
- 40.00 Set Stone, 16x12x8, in stone mound 4 feet in diameter at base, by 2 feet in height for $\frac{1}{4}$ section corner.
- 69.10 Cross Gulch, 25 links wide course South West and ascend.
- 80.00 Set Stone, 20x16x10 in Stone mound 4 feet in diameter at base by 2 feet in height for corner to sections 1-6-7-12.

Land mountainous. Soil 2nd rate.

Timber and undergrowth of Oak and Chaparral.

April 14th, 1880.

North, on West Boundary of Section 6

Variation 14°25' East

- Ascend.
- 40.00 Set Post 4 inches diameter 1 foot in earth 1 foot above Stone mound 4 feet in diameter at base by 2 feet in height, for $\frac{1}{4}$ section corner,
from which bears a
Rock 10x10x10 feet N. 28 $\frac{1}{2}$ ° 175 lks. dist.

W.B. T 6 N., R. 17 W., S.B.M.

- 60.00 Summit of Spur bears North West and South East and descend.
- 80.00 Set post 4 inches square, 1 foot in earth 1 foot above Stone mound $4\frac{1}{2}$ feet in diameter at base, by 2 feet in height for corner to Townships 6 and 7 North Ranges 17 and 18.
Land mountainous. Soil 2nd rate.
Timber and undergrowth of Oak and Chaparral.
-