

Copied from Photographic Copies  
 Furnished by  
 U. S. General Land Office  
 Washington, D. C.

FD-1230

R8W.

31	32	33	34	35	36
30	29	28	27	26	25
19	20	21	22	23	24
18	17	16	15	14	13
7	8	9	10	11	12
6	5	4	3	2	1

T5N.

Henry Hancock.  
Deputy Surveyor.

Sworn and subscribed to in Camp. Tl. Tp. 5 N. R. W. before  
me on this 29th day of Novr. 1855.

I Frank Lecourneur, do solemnly swear that I will well and  
truly perform the duties of compassman according to instruc-  
tions given me and to the best of my skill and ability.  
Frank Lecourneur.

Henry Hancock.  
Deputy Surveyor.

Sworn and subscribed to in camp. Fractional township 5 N.  
R. 8 W. before me on this 29th day of November A. D. 1855.

Township No. 5 North. Range No. 8 West. Mer.

We, William Muloch and Jacob Bell, do solemnly swear;  
that we will faithfully, execute the duties of Chain  
Carriers; that we will level the chain upon uneven  
Ground, and plumb the <sup>line</sup> tally.-----

OATHS OF ASSISTANTS.

Wm J. B. M.

SUBDIVISION OF TOWNSHIP NO. 5 N. OF BASE, R. 8 W.  
SAN FERNARDINO MERIDIAN.

Commenced Thursday Nov. 29th, 1855. The variation and adjustment of chaining being known by a recent survey of the exterior lines performed by the same parties that are now employed in the work of subdivision.

North between Sections 35 & 36.

Var. 14° 8' E.

40.00 Set gr. Sec. post and charred stake in mound with trench and pits as per instructions.  
80.00 Set sec. post and charred stake in mound with trench and pits as per instructions. cor. of Secs. 26, 25, 35 & 36.

Land level. Soil a second rate sandy loam.

East on Random between Sections 25 & 36.  
Var. 14° 8' E.

40.00 Set temporary gr. Sec. post.  
47.00 Across dry arroyo, 15 lks wide, course N. E.  
80.50 Intersected East boundary 27 lks. south of cor. of Secs. 25, 36, 30 & 31, from which I run

West on a true line between Sections 25 & 36.  
Var. 14° 20' E.

40.25 Set a post for gr. Sec. corner, and charred stake in mound with trench and pits as per instructions.  
80.50 To cor. of Secs. 26, 25, 35 & 36. Land level. Soil second rate. Sandy loam mixed with lime.

North Between Sections 25 & 26.  
Var. 14° 8' E.

40.00 Set a post for gr. Sec. corner drive charred stake and dig trench as per instructions from which bears a Spanish Bayonet 8 in. diam. N. 62° E. dist. 106 links.

80.00 Set a post for corner of Sections 23, 26, 24 & 25. Drive charred stake and dig trench as per instructions from which a Spanish Bayonet 12 in. diam. bears S. 72° E. dist. 69 links. Another Spanish Bayonet 15 in. diam bears N. 36° W dist. 123 links.  
Level land. Soil a second rate sandy loam.

East on a random between Sections 24 & 25.  
Var. 14° 8' E.

40.00 Set a post for temporary gr. sec. corner.  
62.50 Across dry Arroyo, 15 lks. wide, course N.

40.00	Set post for temporary gr. sec. corner. Var. 14.81 E.
80.00	East on Random between Sections 12 & 13. ----- Level Land. Spanish Bayonet 12 in. diam. S. 69° W. dist. 155 lks. 12 in. diameter bears S. 55° E. dist. 315 lks. Another trench as per instructions from which a Spanish Bayonet Set a post for corner to Sections 11, 14, 12 & 13, and dig trench and pits as per instructions. Set a post for gr. section corner and raised mound with Spanish Bayonet 12. in. diam. 14.87 80.00 Var. 12.81 E.
40.08	West on a true line between Sections 13 & 24. Var. 14.29 E.
80.16	Set a post for gr. sec. corner and raised mound with trench and pits as per instructions. To corner of Sections 14, 23, 13 & 24. Land level. Soil third rate.
40.00	Set a post for temporary gr. sec. corner. Across cry Arroyo., 15 lks wide, course N. Intersected East boundary 72 lks. South of Cor. of Secs. 13, 24, 18 & 19, from which I run--
55.50	
80.16	
40.00	East on Random between Sections 13, & 24. Var. 14.89 E.
40.00	Set post for gr. sec. corner dig trench as per instructions from which a Spanish Bayonet 8 in. diam. bears S. 89° E. dist. 37 lks.
80.00	Set a post for cor. of Secs. 14, 23, 13 & 24, and raised a mound with trench and pits as per instructions. Land level. Soil third rate.
40.00	North between Sections 23 & 24. Var. 14.81 E.
40.06 1/2	Set a post for gr. Sec. corner and raised a mound with trench and pits as per instructions. To corner of Sections 23, 26, 24 & 25. Land level. Soil same as last mile.
80.13	West on a true line between Sections 24 & 25. Var. 14.47 E.
80.13	Intersected East Boundary 90 lks. South of Corner of Secs. 24, 25 19 & 30. From which I run--

T. S. N. R. & W.

56.00

Across dry Arroyo, 50 lks wide, course N. Intersected East boundary 85 lks South of cor. to Secs. 12, 13, 7 & 18, from which I run--

West on a true line between Sections 12 & 13.

Var. 14081 E.

40.06

Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions.

To cor. of secs. 11, 12, 14, 13. Land level. Soil third rate.

80.12

North between Sections 11 & 12.

Var. 14081 E.

40.00

Set a post for gr. sec. corner from which a Spanish Bayonet 18 in. diam, bears S. 51° E. dist. 109 links. Another Spanish Bayonet 12 in. diam bears S. 34 W. dist. 287 links.

79.50

Across dry Arroyo, 15 lks. wide, course N. E. Set a post for cor. of Secs. 2, 11, 1 & 12, from which a Spanish Bayonet 8 in. diam. bears N. 25° E. dist. 202 lks. A Spanish Bayonet 30 in. diam bears S. 54° E. dist. 233 lks. A Spanish Bayonet 24 in. diam bears S. 87° W. dist. 61 lks. Another Spanish Bayonet 20 in. diam bears N. 77° W. dist. 133 lks. Same as last mile.

16.00

Across dry Arroyo, 20 lks wide, course N. W. Set a post for temporary gr. sec. post.

40.00

Intersected the East boundary 89 lks S. of cor. of Secs. 1, 12, 6 & 7, from which I run--

West on a true line between Sections 1 & 12.

Var. 14081 E.

40.09

Set a post for gr. sec. corner and raised mound with trench and pits as per instructions.

80.18

To cor. of Secs. 2, 11, 1 & 12. Land level. Soil third rate.

19.50

Across dry Arroyo 20 lks wide, course N. W. Set a post for gr. sec. cor. and raised mound with trench and pits as per instructions.

86.79

Intersected the 1st Standard North 97 1/2 lks West of the half mile corner of the 4 1/2rd Mile Standard corner as established by Col. R. Norris and set a post for C. corner of Sections 1 and 2, and raised a mound with trench and pits as per instructions. Land Level. Soil third rate.

North between Sections 34 & 35.

Var. 14081 E.

36.50 Enter dry Arroyo, course N. banks some three feet high. Set a post for gr. sec. corner 100 lks East of true corner to avoid Arroyo in a witness mound with trench and pits as per instructions. 45.00 Leave Arroyo, course N. E. 55.00 Enter same Arroyo again, course N. W. 77.50 Leave same again, course N. W. 80.00 Set a post for corner of Secs. 27, 28, 26 & 35, and dig trench as per instructions from which a Spanish Bayonet 6 in. diam. bears S. 86° W. dist. 31 links another Spanish Bayonet 6 in. diam. bears S. 83° E. dist. 127 lks. Land level. Soil second rate.

East on Random between Sections 26 & 35. Var. 14° 8' E.

40.00 Set post for temporary gr. section corner. Intersected N. & S. line 22 lks North of cor. of Secs. 26, 35, 25 & 36, from which I run--

West on a true line between Sections 26 & 35. Var. 13° 59' E.

40.04 1/2 Set a post for gr. sec. corner from which bears a Spanish Bayonet 6 in. diam. S. 20° E. dist. 89 lks. Another Spanish Bayonet 5 in. diam. N. 16° W. 89 lks dist. To cor. of Secs. 26, 34, 26, & 35.

Land level. Soil second rate generally.

North between Sections 26 & 27. Var. 14° 8' E.

40.00 Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions. 43.50 Across dry Arroyo 1 chain wide, course N. E. banks 5 feet high. 52.00 Across same Arroyo, now 7 chs. wide, course N. W. banks 3 feet high. 80.00 Set a post for corner of Secs. 22, 27, 23 & 26, and dig trench as per instructions, from which a Spanish Bayonet 12 in. diam bears S. 69° E. dist. 87 lks. Another Spanish Bayonet 12 in. diam, bears N. 33° E. dist. 85 lks. Same as last mile.

East on a random between Sections 23 & 26. Var. 14° 8' E.

40.00 Set a post for temporary gr. sec. corner. Across dry Arroyo 50 lks. wide, course N. W. Intersected N. & S. line 15 lks. North of corner of Sections 23, 26, 24 & 25, from which I run-- 54.50 80.08 West on a true line between Sections 23 & 26. Var. 14° 2' E.

40.04 Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions. 80.08 To cor. of Sec. 22, 27, 23 & 26. Land level. Soil a second rate sand loam.

North between Sections 22 & 23. Var. 14081E.

40.00 Set a post for gr. sec. corner and dig trench as per instructions from which a Spanish Bayonet 6 in. diam. bears S. 281 E. dist. 19 links. 80.00 Set a post for corner of Secs. 15, 22, 14, 23, and dig trench as per instructions from which a Spanish Bayonet 6 in. diam. bears N. 290 W. dist. 78 lks. a Spanish Bayonet 8 in. diam. S. 190 E. dist 246 lks. Land level. Soil a second rate sand loam.

East on a random between Sections 14 & 23. Var. 14081E.

40.00 Set a post for temporary gr. sec. corner. Intersected N. & S. line 32 lks. South of corner of Secs. 14, 23, 13 & 24, from which I run--

West on a true line between Sections 14 & 23. Var. 140221E.

39.927 Set a post for gr. sec. corner and dig trench as per instructions, from which a Spanish Bayonet 10 in. diam. bears N. 44 West, dist. 201 links. 79.85 To corner of Sec. 15, 22, 14 & 23. Land level. Soil a second rate sand loam.

North between Sections 14 & 15. Var. 14081E.

40.00 Set a post for quarter section corner and dig a trench as per instructions, from which a Spanish Bayonet 8 in. diam. bears N. 78 E. dist 216 links. 80.00 Set a post for cor. of Secs. 10, 15, 11 & 14, and dig trench as per instructions, from which a Spanish Bayonet 10 in. diam. bears S. 57 E. distant 150 lks. Another Spanish Bayonet 8 in. diam. N. 43 W. dist. 250 lks. Land level. Soil second. rate.

East on a random between Sections 11 & 14. Var. 14081E.

15.50 Across dry arroyo 50 lks. wide; banks 7 feet high, course N. W. Set a post for temporary gr. sec. corner. 40.00 Intersected N. & S. line 6 lks. South of corner of Secs. 11, 14, 12 & 13.--from which I run-- 80.08

West on a true line between Sections 11 & 14.  
Var. 14°11' E.

40.03 Set a post for quarter Section corner and raised a mound with trench and pits as per instructions.  
To cor. of Secs. 10, 15, 11 & 14. First half mile rolling land. Last half level. Soil a second rate sand loam.  
December 1st.

North between Sections 10 & 11.  
Var. 14°8' E.

39.50 Across dry Arroyo, 10 lks. wide, course N. W. Set a post for gr. Sec. corner from which a Spanish Bayonet 10 in. diam. bears N. 14° E. dist. 85 lks. Another Spanish Bayonet 8 in. diam. S. 39 W. dist 174 lks. Set a post corner to Secs. 3, 10, 2 & 11, and raised a mound with trench and pits as per instructions. Land level. Soil a second rate sand loam.

16.00 East on random between Sections 2 & 11.  
Var. 14°8' E.  
16.00 Across dry Arroyo, 20 lks wide, course North. To another dry Arroyo, 20 lks. wide, course North. Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions.  
54.50 To dry Arroyo, 20 lks wide, course North. Intersected N. & S. line, 35 lks. South of Cor. of Secs. 2, 11, 1 & 12. From which I run--  
West on a true line between Sections 2 & 11.  
Var. 14°23' E.

39.98 Set a post for gr. sec. corner and raised mound with trench and pits as per instructions.  
To corner of Sections 3, 10, 2 & 11.  
Land gently rolling. Soil third rate.

North between Sections 2 & 3.  
Var. 14°8' E.

40.00 Set a post for gr. Sec. corner from which a Spanish Bayonet 18 in. diam. bears N. 77° E. dist. 74 links. A Spanish Bayonet 20 in. diam bears No. 25° W. dist 300 links.

46.39 A Spanish Bayonet 10 in. diam.  
To junction of two dry Arroyos, 15 lks. wide, course North. ~~XX~~  
67.00 Leave Arroyo now, 25 lks. wide, course N. W.  
72.00 Across another dry Arroyo, 25 lks. wide, course N. E.  
77.00 Enter dry Arroyo.  
78.50 Leave same, course N. W.  
86.55 Intersected the 1st Standard North 9.10 chs. West of the half mile corner of the 44th Standard Mile, as established by Col R. Norris, and set a post for C. corner to Secs. 2 & 3 and raised mound with trench and pits as per instructions at point of intersection.



T. 5 N., R. 8 W.

Land level. Soil third rate.

North between Sections 33 & 34.

Var. 14081E.

Set a post for gr. sec. corner and raised mound with

trench and pits as per instructions.

Set a post for corner of Secs. 28, 33, 27 & 34, and raised

a mound with trench and pits as per instructions.

Land level. Soil second rate generally.

40.00

80.00

Bottom of Page

East on a random between Sections 27 & 34.

Var. 14081E.

Across dry Arroyo, 20 lks. wide, course North.

To another dry Arroyo, 20 lks. wide, course North.

Set a post for gr. sec. corner and raised a mound with

trench and pits as per instructions.

To dry Arroyo 20 lks. wide, course North.

Intersected N. & S/ lines 35 lks. South of cor. of Secs.

2, 11, 1 & 12.--from which I run.

West on a true line between Sections 2 & 11.

Var. 14023E.

Set a post for gr. sec. corner and raised mound with

trench and pits as per instructions.

To corner of Sections 3, 10, 2 & 11.

Land gently rolling. Soil third rate.

North between Sections 2 & 3.

Var. 14081E.

Set a post for gr. sec. corner from which a Spanish

Bayonet 18 in. diam. bears N. 77° E. dist. 84 lks.

A Spanish Bayonet 20 in. diam. bears N. 25° W. dist. 200 lks.

A Spanish Bayonet 10 in. diam.

To junction of two dry Arroyos 15 lks wide, course North.

Leave Arroyo now, 25 lks. wide, course N. W.

Across another dry Arroyo 25 lks. wide, course N. E.

Enter dry Arroyo.

Leave same, course N. W.

Intersected the 1st Standard North 9.10 chs. West of the

half mile corner of the 44th Standard Mile as established

by Col R. Morris, and set a post for C. corner to Sections

2 & 3, and raised mound with trench and pits as per instruc-

tions at point of intersection.

Land level. Soil third rate.

North between Sections 33 & 34.

Var. 14081E.

Set a post for gr. sec. corner and raised mound with

trench and pits as per instructions.

Set a post for corner of Secs. 28, 33, 27 & 34, and raised

a mound with trench and pits as per instructions.

46.39

47.50

67.00

72.00

77.00

78.50

86.55

40.00

79.96

39.98

79.96

54.50

40.00

23.00

16.00

Page 17

Page 14

Level land. Soil second rate generally.

East on a random between Sections 27 & 34.  
Var. 14081E.

Set a post for temporary qr. sec. corner.  
To dry Arroyo 30 lks wide, banks 3 feet high.

Leave same, course N. W.  
Intersected M. & S. line 14 lks. South of cor. of Sections  
27, 28, 34 & 35, from which I run--

West on a true line between Sections 27 & 34.

Var. 14034E.

40.02 Set a post for qr. sec. corner and raised mound with trench  
and pits as per instructions. To cor. of Secs. 28, 33, 27 & 34. Land level. Soil third rate.

Var. 14081E.

32.54 A Spanish Bayonet 8 in. diam.  
40.00 Set a post for quarter Section corner and raised mound with  
trench and pits as per instructions.  
80.00 Set a post for cor. to sections 21, 28, 22 & 27, and dig  
trench as per instructions from which bears a Spanish Bayonet  
8 in. diam. S. 74.0 W. dist 175 lks. Another Spanish Bayonet  
8 in. diam. S. 63.0 E. dist. 150 lks. Level land.  
Soil second rate sand loam.  
December 3, 1855.

East on random between Sections 22 & 27.  
Var. 14081E.

40.00 Set a post for temporary qr. sec. corner.  
Across dry Arroyo 15 lks. wide, course M.  
80.32 Intersected M. & S. line 3 lks South of cor of Secs. 22, 27,  
23 & 26, from which I run--

West on a true line between Secs. 22 & 27.  
Var. 14091E.

40.16 Set a post for qr. sec. corner and raised a mound with  
trench and pits as per instructions.  
80.32 To cor of Secs. 21, 28, 22 & 27. Land level. Soil a second  
rate sand loam.

North between Sections 21 & 22.  
Var. 14081E.

40.00 Set a post for quarter Section corner from which A  
Spanish Bayonet 12 in. diam. bears S. 74.0 E. dist 140 lks.  
80.00 A Spanish Bayonet 8 in. diam. bears N. 53.0 W. dist. 200 lks.  
Set a post for corner of sections 16, 21, 15 & 22, and raised  
a mound with trench and pits as per instructions. Land level.  
Soil a second rate sand loam.

40.00 East on Random between Sections 15 & 22.  
 Var. 14°8'E.

40.00 Set a post for temporary gr. sec. corner.  
 Across dry Arroyo 50 lks. wide, course N. W.  
 Intersected N. & S. line 20 lks N. of cor. of Secs. 15,  
 22, 14 & 23.--from which I run--

40.18 West on a true line between Sections 15 & 22.  
 Var. 13°59'E.

40.18 Set a post for gr. Sec. corner from which a Spanish  
 Bayonet 8 in. diam. bears N. 37°W. dist. 100 lks.  
 A Spanish Bayonet 8 in. diam. bears S. 56°W. dist. 88 lks.  
 To corner of Secs. 16, 21, 15 & 22. Land level. Soil  
 third rate.

31.78 A Spanish Bayonet 12 in. diam.  
 40.00 Set a post for gr. sec. corner and raised a mound with  
 trench and pits as per instructions.  
 80.00 Set a post for corner of Sections 9, 16, 10 & 15, and dig  
 trench as per instructions from which a Spanish  
 Bayonet 10 in. diam. No. 31°W. dist 105 lks. Land  
 level. Soil a second rate sand loam.

40.00 East on Random between Sections 10 & 15.  
 Var. 14°8'E.

40.00 Set a post for temporary gr. sec. corner.  
 Across dry Arroyo 50 lks. wide, banks 3 feet high, course  
 N. W.  
 Intersected N. & S. line 26 lks. North of corner of Secs.  
 10, 15, 11 & 14, from which I run--

40.21 1/2 West on a true line between Sections 10 & 15.  
 Var. 13°57'E.

80.43 Set a post for gr. sec. corner and dig trench as per in-  
 structions, from which a Spanish Bayonet 8 in. diam. bears  
 S 18°E. dist. 63 lks.  
 To corner of Secs. 9, 16, 10 & 15. Land level. Soil second  
 rate sand loam.

40.00 North between Sections 9 & 10.  
 Var. 14°8'E.

40.00 Set a post for gr. sec. corner and dig trench as per  
 instructions from which a Spanish Bayonet 10 in. diam.  
 bears S. 47°W. dist. 30 lks.  
 To a Spanish Bayonet 15 in. diam.

52.33

80.00 Set a post for cor. of Secs. 4, 9, 3 & 10, and raised mound with trench and pits as per instructions.  
Land level. Soil a second rate sand loam.

East on random between Sections 3 & 10. Var. 14-8. E.

40.00 Set a temporary qr. sec. corner.  
47.50 To base of Rocky hill.  
48.00 To top of N. E. slope of spur of same, ascent 15 feet.  
50.00 To East base of spur.  
80.42 Intersected N. & S. line 41 lks. North of cor. of Secs. 3, 10, 2 & 11.--from which I run.

West on a true line between Sections 3 & 10. Var. 13.50. E.

40.21 Set a post for qr. sec. corner and raised a mound with trench and pits as per instructions.  
80.42 To corner of Secs. 4, 9, 3 & 10. Land level and soil second rate. Sand loam principally.

North between Sections 3 & 4. Var. 14.8. E.

40.00 Set a post for qr. sec. corner and raised mound with trench and pits as per instructions.  
55.00 To base of Spur (of South point of Mountain on North).  
57.00 To top of E. slope of Spur.  
60.00 To North base of Spur.  
86.60 Intersected the 1st Standard North 8.69 chs. West of the half mile corner of the 5th Standard Mile as established by Col. R. Norris, and set a post for C. cor. of Secs. 3 & 4, and raised mound with trench and pits as per instructions, at point of intersections. Soil second rate Generally.  
Tuesday, December 4th.

North between Sections 32 & 33. Var. 14.8. E.

3.50 Cross Wagon road to West.  
40.00 Set a post for qr. sec. corner and raised a mound with trench and pits as per instructions.  
80.00 Set a post for corner to Secs. 29, 32, 28 & 33, and raised a mound with trench and pits as per instructions.  
Land level. Soil a second rate sand loam.

East on random between Sections 28 & 33. Var. 14.8. E.

40.00 Set a post for temporary qr. sec. corner.  
80.50 Intersected N. & S. line 54 lks North of cor. of Secs. 28, 33, 27, 34, from which I run--

West on a true line between Sections 28 & 33. Var. 13.45. E.

40.25 Set a post for quarter Section corner and raised Mound with trench and pits as per instructions.  
80.50 To cor. of Secs. 29, 28 & 33. Land level and principally of a second rate. Soil a sandy loam.

North between Sections 28 & 29.

Var. 14081E.

40.00 Set a post for gr. Sec. corner from which a Spanish Bayonet 8 in. diam. bears N. 25° W. dist. 135 links. A Spanish Bayonet 10 in. diam. bears S. 56 1/2 E. dist. 118 links.  
80.00 Set a post for cor. of Secs. 20, 29, 21 & 28, and raised mound with trench and pits as per instructions. Land level. Soil a second rate sand loam.

East on random between Sections 21 & 28.

Var. 14081E.

40.00 Set a post for temporary gr. sec. corner. Intersected N. & S. line 46 lks. North of cor. of Secs. 21, 28, 22 & 27. --from which I run--

West on a true line between Sections 21 & 28.

Var. 130481E.

40.16 1/2 Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions.  
80.33 To cor. of Secs. 20, 29, 21 & 28. Land level. Soil a second rate sand loam.

North between Sections 20 & 21.

Var. 14081E.

40.00 Set a post for a gr. sec. corner and raised mound with trench and pits as per instructions.  
80.00 Set a post for corner to Sections 17, 20, 16 & 21, and raised a mound with trench and pits as per instructions. Land level. Soil a second rate sand loam.

East on random between Sections 16 & 21.

Var. 14081E.

40.00 Set a post for temporary gr. sec. corner. To dry arroyo 15 lks. wide, course N. Intersected N. & S. line 10 lks. South of cor. of Secs. 16, 21, 15 & 22, from which I run--

West on a true line between Sections 16 & 21.

Var. 14081E.

40.15 Set a post for gr. sec. corner and raised mound with trench and pits as per instructions. Soil a Second rate sand loam.  
80.30 To corner of Secs. 17, 20, 16 & 21. Land level. Soil a

40.00 North between Sections 16 & 17.  
Var. 14081E.  
40.00 Set a post for gr. sec. corner and raised mound with trench and pits as per instructions.  
80.00 Set a post for corner to Sections 8, 17, 9 & 16, and raised mound with trench and pits as per instructions. Land level. Soil a second rate sand loam.

40.00 East on random between Sections 9 & 16.  
Var. 14081E.  
40.00 Set a post for temporary gr. sec. corner. Intersected N. & S. line 29 lks. North of cor. of secs. 9, 16, 10 & 15, from which I run--  
80.08 West on a true line between Secs. 9 & 16.  
Var. 130561E.  
40.04 Set a post for gr. sec. corner and raised mound with trench and pits as per instructions.  
80.08 To cor of Secs. 8, 17, 9 & 16. Land level. Soil a second rate sand loam.

40.00 North between sections 8 & 9.  
Var. 14081E.  
40.00 Set a post for gr. sec. corner and raised a mound with trench and pits as per instructions.  
80.00 Set a post for corner of Secs. 5, 8, 4 & 9, and raised mound with trench and pits as per instructions. Land level. Soil a second rate sand loam.

40.00 East on random between Sections 4 & 9.  
Var. 14081E.  
40.00 Set a post for temporary gr. sec. corner. To dry Arroyo 30 lks. wide, course N. Intersected N. & S. line 22 lks North of cor. of Secs. 4, 9, 3 & 10 from which I run--  
67.50  
79.70

39.85 West on a true line between Sections 4 & 9.  
Var. 130581E.  
40.00 Set a post for gr. sec. corner and dig trench as per instructions from which a Spanish Bayonet 12 in. diam. bears S. 50 1/2 E. dist 74 links.  
79.70 To corner of Sections 5, 8, 4 & 9. Land level. Soil a second rate sand loam.