

Copied from Photographic Copies
 furnished by
 U.S. General Land Office
 Washington, D.C.

R.II W.

31	32	33	34	35	36	31	
6	5	8 4	5 3	3 2	2 1	6	
	9	8	4	3	1		
7	8	7 9	4 10	3 11	1 12	7	T.I.N.
	6	7	4	1			
18	17	6 16	15	14	13	18	

Surveyed by Geo. W. Pearson in 1884

T. 1 N. R. 11 W. S. B. M.

Chains

From the corner to Sections 11-12-13 and 14 which is a sand stone 36 x 20 x 10 ins. marked with 1 notch on the E. and 4 notches on S. edges, with large mound of rocks around.

I run

North, between Sections 11 and 12.

Variation 14° 31' E.

Descend.

28.70
40.00

Gulch 12 lks. wide, course S.E. and ascend.
Set sand stone 19 x 11 x 10 ins. 14 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised mound of stone alongside.

Pits impracticable.

45.50
57.00
80.00

Top of ridge bears N.W. and S.E. and descend.

Gulch 10 lks. wide, course S.E. and ascend.

Set sand stone 12 x 10 x 9 ins. 7 ins. in the ground for cor. to Secs. 1-2-11 and 12 marked with 5 notches on the S. and 1 notch on the E. edges and raised mound of stone alongside.

Pits impracticable.

Land mountainous.

Soil, 3rd rate.

Timber, none.

Dense undergrowth of chaparral.

East on a random line between Secs. 1 and 12.

Variation 14°31' E.

40.00
80.60

Set temporary 1/4 sec. cor.

Intersect east boundary of Tp. 47 lks. N. of the cor. to Secs. 1-6-7 and 12 which is a well preserved post 4 x 4 ins. firmly set in mound of rocks and marked.

T. 1 N. Sec. 6 on the N.E.

Range 10 W. Sec. 7 on the S.E.

Range 11 W. Sec. 12 on the S.W. and Sec. 1 on the N.W.

faces with 5 notches on the S. and 1 notch on the N. corners.

Thence, I run

N. 89°40' West on a true line between Secs. 1 and 12 with same variation.

Ascend.

24.50
37.50
40.30

Top of high spur bears S. and descend.

Gulch 40 lks. wide, course S. and ascend.

Set granite stone 13 x 10 x 6 ins. 8 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised mound of stone alongside.

Pits impracticable.

80.60

The cor. to Secs. 1-2-11 and 12.

Land mountainous.

Soil, 3rd rate.

Timber, none.

Dense undergrowth of chaparral.

T. 1 N. R. 11 W. S. B. M.

Chains

North, on a random line between Secs. 1 and 2.
Variation $14^{\circ} 31'$ E.

40.00 Set temporary $1/4$ sec. cor.
79.60 Intersect north boundary of Tp. 50 lks. W. of cor. to Secs. 1-2-35 and 36.

Thence, I run
S. $0^{\circ} 21'$ W. on a true line between Secs. 1 and 2 with same variation.
Ascend.

19.00 Summit of Divide bears E. and W. and descend.
39.60 Set granite stone $18 \times 12 \times 5$ ins. 13 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on W. face and raised mound of stone alongside.

Pits impracticable.
57.00 Gulch 10 lks. wide, course S.W. and ascend.
79.60 The cor. to Secs. 1-2-11 and 12.

Land, mountainous.
Soil, 3rd rate.
Timber, none.
Dense undergrowth of chaparral.

West, on a random line, between Secs. 11 and 14.
Retracing.

Variation $14^{\circ} 31'$ E.
40.00 After diligent search being unable to find old corner, I set temporary $1/4$ section corner.
80.49 Intersect N. and S. line 38 lks. N. of cor. to Secs. 10-11-14 and 15 which is part of decayed post in mound of rocks partially destroyed. I rebuilt corner by setting sand stone $19 \times 11 \times 8$ ins. 14 ins. in the ground for cor. to Secs. 10-11-14 and 15 marked with 2 notches on the E. and 4 notches on the W. edges and rebuilt mound of rocks around.

Thence, I run
N. $89^{\circ} 44'$ East on a true line between Secs. 11 and 14 with same variation
Descend.

6.00 Gulch 10 lks. wide, course S. and descend.
17.50 Ravine 45 lks. wide, course S. 10° west and ascend.
40.24 Set granite stone $18 \times 12 \times 6$ ins. 13 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on N. face and raised mound of stone alongside.

Pits impracticable.
71.20 Summit of ridge bears N. 20° W. and S. 20° E. and descend.
80.49 The cor. to Secs. 11-12-13 and 14.

Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in ravine.
Dense undergrowth of chaparral.

T. 1 N. R. 11 W. S. B. M.

Chains

From the established cor. to Secs. 10-11-14 and 15.
I run

North, between Secs. 10 and 11.

Variation $14^{\circ} 31'$ E.

Ascend.

25.00

Summit of spur bears S.W. and descend.

40.00

Set granite stone 15 x 11 x 9 ins. 10 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on W. face and raised mound of stone alongside.

Pits impracticable.

80.00

Set sand stone 18 x 10 x 9 ins. 13 ins. in the ground for cor. to Secs. 2-3-10 and 11 marked with 5 notches on the S. and 2 notches on the E. edges and raised mound of stone alongside.

Land, mountainous.

Soil, 3rd rate.

Timber, none.

Dense undergrowth of chaparral.

East, on a random line between Secs. 2 and 11.

Variation $14^{\circ} 31'$ E.

40.00

Set temporary $1/4$ sec. cor.

80.56

Intersect N. and S. line 23 lks. S. of cor. of Secs. 1-2-11 and 12.

Thence I run

S. $89^{\circ} 50'$ west on a true line between Secs. 2 and 11 with same variation.

Descend.

6.20

Gulch 30 lks. wide, course S. and ascend.

37.70

Summit of ridge bears N. and S. and descend.

40.28

Set granite stone 20 x 11 x 9 ins. 15 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on N. face and raised mound of stone alongside.

Pits impracticable.

47.50

Head of gulch, course S. and ascend.

61.50

Top of ridge, bears N. 30° E. and S. 30° W. and descend.

80.56

The cor. to Secs. 2-3-10 and 11.

Land, mountainous.

Soil, 3rd rate.

Timber, none.

Dense undergrowth of chaparral.

April 12th, 1884.

North, on a random line between Secs. 2 and 3.

Variation $14^{\circ} 31'$ E.

40.00

Set temporary $1/4$ sec. cor.

80.12

Intersect north boundary of township 19 lks. W. of cor. to Secs. 2-3-34 and 35.

Thence, I run

S. $0^{\circ} 5'$ west on a true line between Secs. 2 and 3 with same variation.

Descend.

T. 1 N. R. 11 W., S. B. M.

Chains

- 40.12 Set granite stone 11 x 10 x 8 ins. 6 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised mound of stone alongside.
Pits impracticable.
- 50.00 Ravine, 60 lks. wide, course S. 15° W. and ascend.
- 80.12 The cor. to Secs. 2-3-10 and 11.
Land, mountainous.
Soil, 3rd rate.
Timber, none.
Dense undergrowth of chaparral.

West on a random line between Secs. 10 and 15, retracing.
Variation 14° 31' E.

- 36.00 Unable to find witness corner.
- 40.00 Set temporary 1/4 sec. cor.
- 50.00 Unable to find witness corner.
- 80.51 Intersect N. and S. line 46 lks. N. of cor. to Secs. 9-10-15 and 16 which is a post in remains of earth mound, marked T. 1 N. Section 10 on N.E.
Range 11 W. Section 15 on S.E. Section 16 on the S.W. and Section 9 on the N.W. faces.
I rebuilt corner by resetting post, we dug pits and rebuilt earth mound around.
Thence I run
N. 89°40' East on a true line between Secs. 10 and 15 with same variation.
Descend.
- 17.00 Gulch 20 lks. wide, course S.W. and ascend.
- 25.00 Top of ridge bears N. and S. and descend.
- 40.26 Set granite stone 20 x 11 x 7 ins. 15 ins. in the ground for 1/4 sec. cor. marked 1/4 on the north face and raised mound of stone alongside.
Pits impracticable.
- 46.00 Enter Santa Anita Canon, course S.
- 46.90 Santa Anita Creek 11 lks., course S.
- 48.00 Leave Canon, course S. and ascend.
- 66.00 Point of spur bears S. and descend.
- 80.51 The cor. to Secs. 10-11-14 and 15.
Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in canon.
Dense undergrowth of chaparral.

North, between Sections 9 and 10.
Variation 14° 31' East.

- Ascend.
- 28.00 Summit of ridge bears N. 50° W. and S. 50° E. and descend.
- 40.00 Set granite stone 15 x 12 x 5 ins. 10 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised mound of stone alongside.
Pits impracticable.
- 47.00 Head of gulch, course S.W. and ascend.

T. 1 N. R. 11 W. S. B. M.

Chains.

70.00 Summit of ridge bears N. 50° W. and S. 50° E. and descend.
 80.00 Set granite stone 24 x 11 x 6 ins. 10 ins. in the ground
 for cor. to Secs. 3-4-9 and 10 marked with 5 notches on the
 S. and 3 notches on the E. edges and raised mound of stone
 alongside.
 Pits impracticable.
 Land, mountainous.
 Soil, 3rd rate.
 Timber, none.
 Dense undergrowth of chaparral.

 East, on a random line between Secs. 3 and 10.
 Variation 14° 31' E.

40.00 Set temporary 1/4 sec. cor.
 80.71 Intersect N. and S. line 34 lks. S. of cor. to Secs.
 2-3-10 and 11.
 Thence, I run
 S. 89° 45' West on a true line between Secs. 3 and 10 with
 same variation.
 Descend.
 16.65 Ravine 55 lks. wide, course S. and ascend.
 38.00 Point of spur bears S. and descend.
 40.36 Set granite stone 14 x 10 x 4 ins. 9 ins. in the ground for
 1/4 sec. cor. marked 1/4 on N. face and raised mound of
 stone alongside.
 Pits impracticable.
 42.00 Enter Santa Anita Canon, course S.E.
 43.09 Santa Anita Creek 10 lks. wide, course S.E.
 44.50 Leave canon, course S.E. and ascend.
 78.20 Top of spur bears N.E. and descend.
 80.71 The cor. to Secs. 3-4-9 and 10.
 Land, mountainous.
 Soil, 3rd rate.
 Timber, pine and oak in canon.
 Dense undergrowth of chaparral.

April 14th, 1884.

 North, on a random line between Secs. 3 and 4.
 Variation 14° 31' E.

40.00 Set temporary 1/4 sec. cor.
 80.41 Intersect north boundary of township, 31 lks. east of corner
 to Sections 3-4-33 and 34.
 Thence, I run
 S. 0° 13' East on a true line between Secs. 3 and 4 with
 same variation.
 Descend.
 22.00 Cross spring branch 5 lks. wide, course S. 20° W. and ascend.
 38.00 Low point of hill bears West and descend.
 40.41 Set granite stone 16 x 11 x 8 ins. 11 ins. in the ground
 for 1/4 sec. cor. marked 1/4 on W. face and raised mound of
 stone alongside.
 Pits impracticable.
 43.50 Enter Santa Anita Canon, course S. 50° E.
 44.12 Santa Anita Creek, 11 lks. wide, course S. 50° E.

T. 1 N. R. 11 W. S. B. M.

Chains
45.00
80.41

Leave Canon, course S. 50° E.
The cor. to Secs. 3-4-9 and 10.
Land, mountainous.
Soil, 3rd rate.
Timber, scattering pine and oak in canon.
Dense undergrowth of chaparral.

From the cor. to Secs. 16-17-20 and 21 which is a well preserved post firmly set in ground marked
T. 1 N. Section 16 on the N.E.
R. 11 W. Section 21 on the S.E.
Section 20 on S.W. and Section 17 on N.W. faces with earth mound and pits around post.
I run
North, between Sections 16 and 17.

Variation 14° 31' E.

40.00 Ascending gradually.
After diligent search, being unable to find witness corner which was set 3.00 chains East, I set "at the proper point" a sand stone 19 x 12 x 10 ins. 14 ins. in the ground for 1/4 sec. cor. marked 1/4 on W. face and raised mound of stone alongside.

56.00 Pits impracticable.
Unable to find witness corner.
80.00 Set a granite stone 19 x 12 x 10 ins. 14 ins. in the ground for cor. to Secs. 8-9-16 and 17 marked with 4 notches on S. and E. edges and raised mound of stone alongside.

Pits impracticable.
Land, rolling.
Soil, 2nd rate.
Timber, none.
Dense undergrowth of chaparral.

West, on a random line between Secs. 8 and 17.

Variation 14° 31' E.

40.00 Set temporary 1/4 sec. cor.
80.45 Intersect N. and S. line 39 lks. S. of cor. to Secs. 7-8-17 and 18 which is a part of decayed post in mound of rocks partially destroyed, I rebuilt corner by setting granite stone 15 x 10 x 9 ins. 10 ins. in the ground for cor. to Secs. 7-8-17 and 18 marked with 4 notches on the S. and 5 notches on the E. edges and raised mound of stone alongside.

Pits impracticable.
Thence, I run
S. 89° 43' E. on a true line between Secs. 8 and 17 with same variation.

39.00 Ascend.
Summit of ridge bears N. and S. and descend.
40.24 Set granite stone 12 x 10 x 9 ins. 7 ins. in the ground for 1/4 sec. cor. marked 1/4 on N. face and raised mound of stone alongside.

80.48 Pits impracticable.
The corner to Sections 8-9-16 and 17.
Land, mountainous.
Soil, 3rd rate.
Timber, none.
Dense undergrowth of chaparral.

T. 1 N. R. 11 W. S. B. M.

Chains

East, on a random line between Secs. 9 and 16.
Variation $14^{\circ}31'$ E.

- 40.00 Set temporary $1/4$ sec. cor.
80.18 Intersect N. and S. line 40 lks. N. of cor. to Secs. 9-10-15 and 16.
Thence, I run
N. $89^{\circ}43'$ west on a true line between Secs. 9 and 16 with same variation.
Ascend.
30.00 Top of spur bears S. 50° W. and descend.
40.09 Set sand stone $16 \times 11 \times 7$ ins. 11 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on N. face and raised mound of stone alongside.
Pits impracticable.
70.00 Enter Little Santa Anita Canyon, course south.
70.50 Little Santa Anita Creek 9 lks. wide, course south.
71.20 Leave canon, course S. and ascend.
75.00 Wilson's trail bears N. and S.
80.18 The corner to Sections 8-9-16 and 17.
Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in canon.
Dense undergrowth of chaparral.

North, between Sections 8 and 9,
Variation $14^{\circ}31'$ E.

- Ascend gradually.
32.50 Gulch 20 lks. wide, course S.E.
40.00 Set sand stone $16 \times 12 \times 5$ ins. 11 ins. in the ground for $1/4$ sec. cor. marked $1/4$ on W. face and raised mound of stone alongside.
Pits impracticable.
42.00 Wilson's trail bears N.W. and S.E.
53.00 Leave slope of mountain and descend.
58.00 Enter Little Santa Anita Canon, course S.E.
58.40 Little Santa Anita Creek 9 lks. wide, course S.E.
59.00 Leave canon, course S.E. and ascend.
80.00 Set granite stone $19 \times 11 \times 7$ ins. 14 ins. in the ground for cor. to Secs. 4-5-8 and 9 marked with 5 notches on S. and 4 notches on the E. and raised mound of stone alongside.
Pits impracticable.
Land, mountainous.
Soil, 2nd rate.
Timber, pine and oak in canon.
Dense undergrowth of chaparral.

April 15th, 1884.

T. 1 N. R. 11 W. S. B. M.

Chains

East, on a random line between Sections 4 and 9.
Variation $14^{\circ}31'$ E.

- 40.00 Set temporary 1/4 sec. cor.
79.90 Intersect N. and S. line 22 lks. S. of cor. to Secs. 3-4-9
and 10.
Thence, I run
S. $89^{\circ}51'$ West on a true line between Secs. 4 and 9 with
same variation.
Ascend.
18.00 Summit of ridge bears N.W. and S.E. and descend.
39.95 Set granite stone 12 x 10 x 4 ins. 7 ins. in the ground
for 1/4 sec. cor. marked 1/4 on N. face and raised mound of
stone alongside.
Pits impracticable.
40.50 Ravine 60 lks. wide, course S. and ascend.
72.35 Top of ridge bears N. and S. and ascend.
79.90 The cor. to Secs. 4-5-8 and 9.
Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in ravine.
Dense undergrowth of chaparral.

North on a random line between Secs. 4 and 5.
Variation $14^{\circ}31'$ E.

- 40.00 Set temporary 1/4 sec. cor.
80.51 Intersect north boundary of township 37 lks. west of cor. to
Secs. 4-5-32 and 33.
Thence, I run
South $0^{\circ}16'$ W. on a true line between Secs. 4 and 5 with
same variation.
Descend.
17.00 Enter Santa Anita Canon, course S. 50° E.
17.46 Santa Anita Creek 10 lks. wide, course S. 50° E.
19.40 Leave canon, course S. 90° E. and ascend.
40.51 Set granite stone 19 x 11 x 7 ins. 14 ins. in the ground
for 1/4 sec. cor. marked 1/4 on W. face and raised mound of
stone alongside.
Pits impracticable.
42.00 Top of ridge bears N.W. and S.E. and descend.
80.51 The cor. to Secs. 4-5-8 and 9.
Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in the ravines and canons.
Dense undergrowth of chaparral.

T. 1 N. R. 11 W. S. B. M.

Chains.

West, on a random line between Sections 5 and 8.
Variation 14° 31' E.

40.00 Set temporary 1/4 sec. cor.
80.25 Intersect N. and S. line 15 lks. N. of cor. to Secs.
5-6-7 and 8
Thence, I run
N. 89°54' East on a true line with same variation.
Descend.
31.00 Trail bears N.W. and S.E.
40.13 Set granite stone 15 x 10 x 7 ins. 10 ins. in the ground
for 1/4 sec. cor. marked 1/4 on N. face and raised mound
of stone alongside.
Pits impracticable.
47.10 Enter Little Santa Anita Canon, course S.
48.00 Little Santa Anita Creek, 7 lks. wide, course S.
48.45 Leave Canon and ascend.
80.25 The cor. to Secs. 4-5-8 and 9.
Land, mountainous.
Soil, 3rd rate.
Timber, pine and oak in Canon.
Dense undergrowth of chaparral.

April 16th, 1884.

General Description.

This portion of this township surveyed by me, contains nearly all mountain land which can be classed as 2nd and 3rd rate.

There is some bottom land along Santa Anita Creek, 1st class.

Pine and Oak timber of good quality is found along Santa Anita Creek and its tributaries.

This portion of the township is generally valuable for its timber and water.
