

Copied from Photographic Copies  
 furnished by  
 U. S. General Land Office  
 Washington D. C.



				R. W.	
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36
6	5	4	3	2	1

T. 2 N.

N. 0°12' East on a true line between sections 25 and 26. Var. 14°29' East.  
 Summit of ridge bears N. E. and S. W. and descend.  
 Set sand stone 12 x 9 x 6 ins. 7 ins. in the ground for 1/4 section corner marked 1/4 on west face, and raised mound of stone alongside. Pits impracticable.  
 Gulch 30 lks. wide course N. E. and ascend. 59.00

East on a random line between sections 25 and 36. Var. 14°29' East.  
 Set a temporary 1/4 section corner. Intersect east boundary of township 59 lks. S. of the corner to sections 25-30-31 and 36  
 Thence I run S. 89° 35' west on a true line between sections 25 and 36 with same variation.  
 Having 40 lks. wide course N. E. and ascend. 17.00  
 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for 1/4 section corner marked 1/4 on N. face and raised mound of stone alongside. Pits impracticable.  
 The corner to sections 25-26-35 and 36. Land mountains. Soil 3rd rate. Timber pine and Oak in ravine. Dense undergrowth of Chaparral. 80.54

From the established corner to sections 1-2-35 and 36 on the south boundary of township I run north 0° 12' east on a true line between sections 35 and 36. Var. 14°29' East.  
 Descend. Having 40 lks. wide course N. 80° E. and ascend. 5.20  
 Top of spur bears N. 80° E. and descend. 20.00  
 Gulch 30 lks. wide course N. 60° E. and ascend. 36.00  
 Set post 4 x 4 ins. 4 feet long and deep marked stone 12 ins. in the ground for 1/4 section corner marked 1/4 S. on the W. face and raised mound of stone alongside. Pits impracticable. 40.00  
 Set granite stone 11 x 10 x 9 ins. 6 ins. in the ground for corner to sections 25-26-35 and 36 marked with 1 notch on the S. and E. edges and raised mound of stone alongside. Pits impracticable. Land mountains. Soil 3rd rate. Timber some. Dense undergrowth of chaparral. 80.00

T. 2 N. R. 11 W. S. B. M.

Dense undergrowth of Chaparral.

Timber none.

Soil 3rd rate.

Land mountains.

The corner to sections 23-24-25 and 26.

Pits impracticable.

mound of stone alongside.

For 1/4 section corner marked 1/4 on W. face and raised

Set granite stone 23 x 14 x 7 ins. in the ground

Top of spur bears N. E. and descend.

Ascend.

same variation.

S. 0°27' west on a true line between sections 23 and 24 with

Thence I run

Section 14 on the N. W. faces

Section 23 on the S. W. and

on the N. E. section 24 on the S. E.

In large mound of rocks marked T.P. 2 N. R. 11 W. Sec. 13

and 24 which is a well preserved post 4 x 4 ins. firmly set

To a point 62 lks. west of corner to sections 13-14-23

Set a temporary 1/4 section corner.

Var. 14°29' East.

North on a random line between sections 23 and 24.

80.31

40.16

30.00

80.31

40.00

Dense undergrowth of Chaparral.

Timber none.

Soil 3rd rate.

Land mountains.

The corner to sections 23-24-25 and 26.

Pits impracticable.

stone alongside.

section corner marked 1/4 on N. face and raised mound of

Set sand stone 19 x 11 x 9 ins. 1/4 ins. in the ground for 1/4

Top of spur bears N. 10° E. and descend.

Gulch 10 lks. wide near head course N. 10° E. and ascend.

Top of spur bears N. 15° E. and S. 40° W. and descend.

Ascend.

same variation.

S. 89°48' W. on a true line between sections 24 and 25 with

Thence I run

sections 19-24-25 and 30.

Intersect east boundary of T.P. 28 lks. south of corner to

Set temporary 1/4 section corner.

Var. 14°29' East.

East on a random line between sections 24 and 25.

80.47

61.00

40.24

38.00

20.00

8.50

80.47

40.00

Dense undergrowth of Chaparral.

Timber none.

Soil 3rd rate.

Land mountains.

Pits impracticable.

mound of stone alongside.

notches on the S. and 1 notch on the E. edges and raised

For corner to sections 23 x 24 x 25 and 26 marked with 2

Set granite stone 13 x 12 x 10 ins. 8 ins. in the ground

80.00

T. 2 N. R. 11 W. S. B. M.

North 0° 12' East on a true line between sections 26 and 27. Var. 14° 29' E.

Ascend.  
Set granite stone 12 x 12 x 9 ins. 7 ins. in the ground for 1/4 section corner marked 1/4 on W. face and dug pits 18 x 18 x 12 ins. N. and S. of stone 5-1/2 feet dist. and raised mound of earth 1-1/2 feet high, 3-1/2 feet base alongside.

72.60  
Top of spur bears N. W. and descend.  
Set sand stone 11 x 11 x 9 ins. 6 ins. in the ground for corner to sections 22-23-26 and 27 marked with 2 notches on E. and S. edges and dug pits 18 x 18 x 12 ins. in each section 5-1/2 feet distance and raised mound of earth 2-1/2

East on a random line between sections 26 and 35. Var. 14° 29' East.

40.00  
Set temporary 1/4 section corner. Intersect N. and S. line 37 lks. N. of corner to sections 25-26-35 and 36  
Thence I run  
N. 89° 44' West on a true line between sections 26 and 35  
With same variation and ascend.  
Summit of ridge bears N. E. and S. E. and descend.  
30.00  
Head of gulch course N. 10° E. and ascend.  
40.30  
Set granite stone 12 x 10 x 9 ins. 7 ins. in the ground for 1/4 section corner marked 1/4 on N. face and raised mound of stone alongside. Pits impracticable.

41.00  
Summit of ridge bears N. and S. and descend.  
80.60  
The corner to sections 26-27-34 and 35.  
Land mountains.  
Soil 3rd rate.  
Timber none.  
Dense undergrowth of Chaparral.

From the corner to sections 2-3-34 and 35 I run North 0° 12' East on a true line between sections 34 and 35. Va. 14° 29' East.

19.25  
Ascend.  
Summit of divide between San Gabriel and Santa Anita bears N. 75° W. and S. 75° E. and descend.

40.00  
Set granite stone 18 x 12 x 9 ins. 13 ins. in the ground for 1/4 section corner marked 1/4 on W. face and raised mound of stone alongside. Pits impracticable.

59.00  
Gulch 30 lks. wide course N. W. and ascend.  
80.00  
Set sand rock 18 x 14 x 10 ins. 13 ins. in ground for corner to sections 26-27-34 and 35 marked with 1 notch on the S. and 2 notches on the E. edges and raised mound of stone alongside. Pits impracticable.

Timber none.  
Soil 3rd rate.  
Land mountains.  
Dense undergrowth of Chaparral.

I. 2 N. R. 11 W. S. B. M.

\*\*\*\*\*

feet high 4-1/2 feet base alongside.

Land mountains.

Soil 2nd rate.

Timber none.

Dense undergrowth of Chaparral.

April 18th 1884.

40.00  
80.41

East on a random line between sections 25 and 26.  
Var. 14' 29' East.  
Set temporary 1/4 section corner.  
Intersect N. and S. line 27 lks. S. of corner to sections  
23-24-25 and 26  
Thence I run  
S. 89° 48' West on a true line between sections 25 and 26  
with same variation.  
Ascend.  
Summit of ridge bears N. 10° W. and S. 10° E. and descend.  
Set post 4 x 4 ins. and deep marked stone 12 ins. in the  
ground for 1/4 section corner marked 1/4 on N. face and  
dug pits 18 x 18 x 12 ins. E. and W. of post 5-1/2 feet  
base alongside.  
Having 80 lks. wide course north and ascend.  
The corner to sections 22-23-26 and 27.

66.00  
80.41

Land mountains.  
Soil 3rd rate.  
Timber, pine and oak in ravine.  
Dense undergrowth of Chaparral.

40.00  
80.43

North on a random line between sections 22 and 23.  
Var. 14' 29' East.  
Set temporary 1/4 section corner.  
To a point 37 lks. west of corner to sections 14-15-22  
and 23 which is a post 4 x 4 ins. marked with Tp. 2 N.  
R. 11 W. section 14 on N. E. section 23 on S. E. section 22  
on S. W. and section 15 on N. W. faces, firmly set in mound  
of rocks,  
from which bears a live oak 16 ins. in diam.  
N. 27-1/2° E. 29 lks. dist.  
Thence I run  
S. 0° 16' West on a true line between sections 22 and 23  
with same variation.  
Ascending.  
Point of spur bears N. W. and descend.  
Set sand stone 12 x 11 x 7 ins. 7 ins. in the ground for 1/4  
section corner marked 1/4 on W. face and raised mound of  
stone alongside.  
Pits impracticable.  
Cutch 80 lks. wide course N. W. and ascend.  
The corner to sections 22-23-26 and 27.

60.50  
80.43

Land mountains.  
Soil 3rd rate.  
Timber none.  
Dense undergrowth of Chaparral.

East on a random line between sections 27 and 34.  
 Var. 14°29' East.  
 Set temporary 1/4 section corner.  
 Intersect N. and S. line 30 lks. N. of corner to sections  
 26-27-34 and 35  
 Thence I run  
 N. 89°44' west on a true line between sections 27 and 34 with  
 same variation.  
 Descend,  
 Gulch 35 lks. wide course N. and ascend.  
 Set granite stone 15 x 11 x 7 ins. 10 ins. in the ground  
 for 1/4 section corner marked 1/4 on N. face and raised  
 mound of stone alongside.  
 Pits impracticable.  
 Summit of ridge bears N. and S. and descend.  
 Enter timber bears N. and S.  
 The corner to sections 27-28-33 and 34.  
 Land mountains.  
 Soil 3rd rate.  
 Timber 6.80 cbs.  
 73.20 cbs. dense undergrowth of chaparral.

40.00  
 80.55  
 17.00  
 40.27  
 70.00  
 73.20  
 80.55

From the corner to sections 3-4-33 and 34 on the south  
 boundary of Tp. 1 run  
 North 0°12' East between sections 33 and 34  
 Var. 14°29' East  
 Ascend  
 Set granite stone 26 x 11 x 4 ins. 18 ins. in the ground for  
 1/4 section corner marked 1/4 on west face and raised mound  
 of stone alongside.  
 Pits impracticable.  
 Summit of divide bears N. 85° W. and S. 85° E. and descend.  
 Enter timber bears N. W. and S. E.  
 Set post 6 x 6 ins. 4-1/2 feet long with marked stone 12 ins.  
 in the ground for corner to sections 27-28-33 and 34 marked  
 Tp. 2 N. section 27 on N. E.  
 R 11 W. section 34 on S. E.  
 Section 33 on the S. W. and section 28 on the N. W. faces  
 from which a  
 pine bears N. 31° E. 67 lks. dist. 14 ins. diam marked  
 T. 2 N. section 27 B.T.  
 pine 16 ins. diam. bears S. 11-1/4° E. 1.11 cbs. dist.  
 marked R. 11 W. section 34 B. T.  
 pine 18 ins. diam. bears S. 23° W. 91 lks. dist. marked  
 section 33 B. T.  
 pine 26 ins. diam. bears N. 42° W. 43 lks. dist. marked  
 section 28 B. T.  
 Land mountains.  
 Soil 1st and 3rd rate.  
 Timber pine and Oak.  
 Dense undergrowth of Chaparral brush.

40.00  
 43.20  
 66.00  
 80.00

T. 2 N. R. 11 W. S. B. M.

\*\*\*\*\*

I. 2 N. R. 11 W. S. B. M.

\*\*\*\*\*

North 0°12' East between sections 27 and 28.

Var. 14°29' East.

Descend along spur.

Set sand stone 12 x 10 x 9 ins. 7 ins. in the ground for

1/4 section corner marked 1/4 on W. face,

from which bears a  
pine 14 ins. diam. W. 15° E. 69 lks. dist. marked 1/4 S.B.T.  
pine 28 ins. diam. bears S. 19° W. 85 lks. dist. marked 1/4  
S. B. T.

40.00

40.50

Top of spur bears N.

Thence along summit and west slope of spur.

73.00

Leave timber bears E. and W.

Set granite stone 20 x 11 x 10 ins. 15 ins. in the ground for  
corner to sections 21-22-27 and 28 marked with 2 notches in  
the S. and 3 notches on the E. edges and raised mound of stone  
alongside.

80.00

Pits impracticable.

Land 73 obs. timber and mountains.

Soil 2nd rate.

7.00 Dense undergrowth of Chaparral.

40.00

Set temporary 1/4 section corner.

Intersect N. and S. line 30 lks. N. of corner to sections

22-23-27- and 26

Thence I run

N. 89° 47' west on a true line between sections 22 and 27.

10.00

Top of spur bears N. 20° W. and descend.

Cut on 30 lks. wide course W. and ascend.

29.00

Set granite stone 16 x 11 x 8 ins. 11 ins. in the ground for  
1/4 section corner marked 1/4 on N. face and raised mound of  
stone alongside.

40.21

Pits impracticable.

The corner to sections 21-22-27 and 28.

80.42

Land mountains.

Soil 3rd rate.

Timber none.

Dense undergrowth of Chaparral.

40.00

Set temporary 1/4 section corner.

To a point 26 lks. west of corner to sections 15-16- 21 and

22 which is a post greatly decayed in mound of rocks

partially destroyed. I rebuilt corner by setting sand stone  
12 x 9 x 6 ins. 7 ins. in the ground for corner to sections  
21-22-15 and 16 marked with 3 notches on the S. and E edges  
and raised mound of stone alongside.

Pits impracticable.

North on a random line between sections 21 and 22 retracing

40 obs.

Var. 14° 29' East.

Unable to find old corner.

40.00 Set temporary 1/4 section corner.  
 Intersect N. and S. line 21 lks. S. of corner.  
 Thence I run  
 S. 89° 51' west on a true line between sections 28 and 33  
 with same variation.  
 Descend.  
 Leave timber bears N. and S.  
 Gulch 30 lks. wide course N. W. and ascend.  
 Set granite stone 13 x 12 x 11 ins. 8 ins. in the ground  
 for 1/4 section corner marked 1/4 on W. face and raised  
 mound of stone alongside.  
 Pits impracticable.  
 Top of ridge bears N. and S. and descend.  
 Gulch 30 lks. wide course W. and ascend.  
 80.52 The corner to sections 28-29-32 and 33.  
 Land mountains.

40.00 East on a random line between sections 28 and 33  
 Var. 14° 29' East.  
 40.00 Set temporary 1/4 section corner.  
 Intersect N. and S. line 21 lks. S. of corner.  
 Thence I run  
 S. 89° 51' west on a true line between sections 28 and 33  
 with same variation.  
 Descend.  
 Leave timber bears N. and S.  
 Gulch 30 lks. wide course N. W. and ascend.  
 Set granite stone 13 x 12 x 11 ins. 8 ins. in the ground  
 for 1/4 section corner marked 1/4 on W. face and raised  
 mound of stone alongside.  
 Pits impracticable.  
 Land mountains.  
 Timber 44.20 cbs.  
 Dense undergrowth of Chaparral, 35.80 cbs.  
 Soil 2nd and 3rd rate.

21.50 Enter timber bears E. and W.  
 Set a sand stone 15 x 11 x 8 ins. 10 ins. in the ground  
 for 1/4 section corner marked 1/4 on W. face  
 from which bears a  
 pine 19 ins. diam. N. 30° W. 32 lks. dist. marked 1/4 S.B.T.  
 pine 26 ins. diam. S. 20° W. 32 lks. dist. marked 1/4 S.B.T.  
 and raised mound of stone alongside.  
 Summit of divide bears E. and W. and descend.  
 Leave timber bears E. and W.  
 Gulch 30 lks. wide course N. E. and ascend.  
 Set granite stone 18 x 11 x 7 ins. 13 ins. in the ground  
 for corner to sections 28-29-32 and 33 marked with 1 notch  
 on the S. and 4 notches on the E. edges and raised mound of  
 stone alongside.  
 Pits impracticable.  
 Land mountains.  
 Timber 44.20 cbs.  
 Dense undergrowth of Chaparral, 35.80 cbs.  
 Soil 2nd and 3rd rate.

\*\*\*\*\*  
 T. 2 N. R. 11 W. S. B. M.



East on a random line between sections 21 and 28  
 Var. 1/4 29' East.  
 40.00 Set temporary 1/4 section corner.  
 80.40 Interest N. and S. line 28 lks. N. of corner to sections  
 21-22-28 and 27  
 Thence I run  
 N. 89° 48' W. on a true line between sections 21 and 28  
 with same variation.  
 22.80 Gulch 40 lks. wide course N. 20° W. and ascend.  
 40.20 Set granite stone 19 x 12 x 8 ins. 1/4 ins. in the ground  
 for 1/4 section corner marked 1/4 on N. face and raised  
 mound of stone alongside.  
 42.00 Pits impracticable.  
 Top of spur bears N. and descend.  
 63.50 Gulch 60 lks. wide course N. and ascend.  
 80.40 The corner to sections 20-21-28 and 29.  
 Land mountains.  
 Soil 3rd rate.  
 Timber none.  
 Dense undergrowth of Chaparral.

N. 0° 12' E. between sections 28 and 29  
 Var. 1/4 29' East.  
 40.00 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground for  
 1/4 section corner marked 1/4 on W. face and raised mound  
 of stone alongside.  
 Pits impracticable.  
 74.75 Point of spur bears N. E. and descend.  
 80.00 Set granite stone 16 x 11 x 10 ins. 11 ins. in the ground  
 for corner to sections 20-21-28 and 29 marked with 2 notches  
 on S. and 4 notches on E. edges raised mound of stone  
 alongside.  
 Pits impracticable.  
 Land mountains.  
 Soil 3rd rate.  
 Timber none.  
 Dense undergrowth of Chaparral.

April 19th 1884.

Soil 3rd rate.  
 Timber fine.  
 Dense undergrowth of Chaparral.

\*\*\*\*\*  
 T. 2 N. R. 11 W. S. B. M.

Ascend.  
 Summit of ridge bears E. and W. and descend.  
 38.50 Set granite stone 16 x 11 x 9 ins. in the ground  
 for 1/4 section corner marked 1/4 on W. face and raised  
 mound of stone alongside.  
 63.00 Gulch 40 lks. wide course S. W. and ascend.  
 80.00 Set sand stone 22 x 11 x 6 ins. 17 ins. in the ground for  
 corner to sections 29-30-31 and 32 marked with 5 notches  
 on E. and 1 notch on the S. edges and raised mound of stone  
 alongside.  
 Pits impracticable.  
 Land mountains.  
 Soil 3rd rate.  
 Timber none.  
 Dense undergrowth of Chaparral.

From the corner to sections 5-6-31 and 32 on the S.  
 boundary of the township  
 I run  
 N. 0° 12' E. between sections 31 and 32  
 Var. 14° 29' East

---

North on a random line between sections 20 and 21 retracing  
 40 chs.  
 Var. 14° 29' East.  
 40.00 After diligent search being unable to find 1/4 section corner  
 I set temporary 1/4 section corner.  
 80.37 To a point 3/4 lks. west of corner to sections 16-17-20 and  
 21 which is a well preserved post firmly set in mound of  
 rocks marked T. 2 N. R. 11 W. section 16 on N. E. section  
 21 on S. E. section 20 on S. W. and section 17 on N. W. faces.  
 from which bears  
 An Alder tree 8 ins. diam. N. 18-1/2° W. 60 lks. dist.  
 marked T. 2 N. R. 11 W. section 17 B. T.  
 Thence I run  
 S. 0° 15' west on a true line between sections 20 and 21  
 with same variation.  
 Ascending.  
 40.18 Set granite stone 19 x 11 x 7 ins. 14 ins. in the ground for  
 1/4 section corner marked 1/4 on W. face and raised mound  
 of stone alongside.  
 Pits impracticable.  
 The corner to sections 20-21-28- and 29.  
 Land mountains.  
 Soil 3rd rate.  
 Timber none.  
 Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

\*\*\*\*\*

Ascend.  
 Summit of divide bears E. and W. and descend.  
 Set sand stone 13 x 10 x 6 ins. 8 ins. in the ground for 1/4  
 section corner marked 1/4 on N. face and raised mound of  
 stone along side.  
 Pits impracticable.  
 64.30  
 80.00  
 Set granite stone 16 x 11 x 9 ins. 11 ins. in the ground for  
 corner to sections 19-20-29 and 30 marked with 2 notches  
 on S. and 5 notches on the E. edges and raised mound of stone  
 along side.  
 Pits impracticable.

N. 0°12' E. between sections 29 and 30.  
 Var. 14°29' East.

As this line can only be run a portion of the distance  
 I run  
 West on a true line between sections 30 and 31.  
 Var. 14° 29' East.  
 Ascending.  
 Set a granite stone 16 x 11 x 7 ins. 11 ins. in the ground  
 for 1/4 section corner marked 1/4 on N. face and raised  
 mound of stone along side.  
 Pits impracticable at foot of very steep ascent.  
 It being impracticable to measure the line any farther I  
 drop the line at this point.  
 Land mountains.  
 Soil 3rd rate.  
 Timber none.  
 Dense undergrowth of Chaparral.

April 21st 1884.

East on a random line between sections 29 and 32  
 Var. 14° 29' East.  
 40.00  
 80.60  
 Set temporary 1/4 section corner.  
 Intersect N. and S. line 49 lks. N. of corner to sections  
 28-29-32 and 33  
 Thence I run  
 N. 89°39' west on a true line between sections 29 and 32  
 with same variation.  
 Ascend.  
 Set granite stone 19 x 12 x 6 ins. 14 ins. in ground for 1/4  
 section corner marked 1/4 on N. face and raised mound of  
 stone along side.  
 Pits impracticable.  
 42.00  
 50.90  
 Summit of divide bears N. and S. and descend.  
 Wilsons trail bears N. and S.  
 Gulch 20 lks. wide course S. and ascend.  
 71.80  
 73.00  
 Leave timber N. and S.  
 The corner to sections 29-30-31 and 32.  
 Land mountains.  
 Soil 3rd rate.  
 Timber pine.  
 Dense undergrowth of Chaparral.

T. 2 N. R. 11 W. S. B. M.

Dense undergrowth of Chaparral.

Timber none.  
 Soil 3rd rate.  
 Land mountains.  
 The corner to sections 19-20-29 and 30.  
 On summit of spur bears N. E. and descend.  
 Pits impracticable.  
 Mound of stone along side.  
 for 1/4 section corner marked 1/4 on N. face and raised  
 Set granite stone 10 x 11 x 6 ins. 13 ins. in the ground  
 Ascending.  
 same variation.  
 N. 89°48' E. on a true line between sections 19 and 30 with  
 Thence I run  
 rebuilt earth mound around stone  
 4 notches on N. and 2 notches on S. edges and redug pits and  
 ground for corner to sections 19-24-25 and 30 marked with  
 by setting granite rock 16 x 12 x 10 ins. 11 ins. in the  
 in earth mound with pits nearly destroyed. I rebuilt corner  
 to sections 19-24-25 and 30 which is a post greatly decayed  
 intersect west boundary of township 27 lks. N. of corner  
 Set temporary 1/4 section corner.  
 40.00  
 80.32  
 West on a random line between sections 19 and 30  
 Var. 14° 29' East.

Dense undergrowth of Chaparral.

Timber none.  
 Soil 3rd rate.  
 Land mountains.  
 The corner to sections 19-20-29 and 30.  
 Gulch 40 lks. wide course N. 20° E. and ascend.  
 Top of spur bears N. and descend.  
 Trail bears N. and S.  
 Pits impracticable.  
 Mound of stone along side.  
 for 1/4 section corner marked 1/4 on N. face and raised  
 Set granite stone 14 x 9 x 8 ins. 9 ins. in the ground  
 Ascend.  
 with same variation.  
 N. 89°43' west on a true line between sections 20 and 29  
 Thence I run  
 20-21-28 and 29  
 intersect N. and S. line 40 lks. N. of corner to sections  
 Set temporary 1/4 section corner.  
 40.00  
 80.29  
 East on a random line between sections 20 and 29  
 Var. 14° 29' East.

Dense undergrowth of Chaparral.

Timber none.  
 Soil 3rd rate.  
 Land mountains.

T. 2 N. R. 11 W. S. B. M.