

North on a random line between Secs. 9 and 10.
 Va. 14th 28th E.
 To a point 5.8 chs. East of $\frac{1}{2}$ sec. cor. which is a granite stone
 5 ins. above ground, marked with $\frac{1}{2}$ on W. face, with mound of stone
 alongside.

40.55

Descend.
 Gulp 20 lks. wide course S. 10^o W. and
 Ascend.
 Top of Ridge bears N. 15^o E. and S. 15^o W. and descend.
 San Gabriel River 40 lks. wide, course S. 10^o W. in canon 1.90 ch.
 wide, course S. 10^o W. and ascend.
 Set granite stone 15 x 14 x 3 ins. in the ground for $\frac{1}{2}$ sec.
 corner marked $\frac{1}{2}$ on N. face and raised a mound of stone alongside.
 pits impracticable.
 Top of Ridge bears N. 15^o E. and S. 15^o W. and descend.
 The cor. to Secs. 9, 10, 15 and 16.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Oak along River.
 Dense undergrowth of chaparral.

74.44

59.00

37.22

29.00

18.00

3.00

East on a random line between Secs. 10 and 15,
 Var. 14th 28th East.
 S. 89^o 52' West on a true line bet. Sections 10 and 15,
 Thence I run,
 on the S. and 2 notches on the E. edges with mound of stone alongside
 which is a granite stone 8 ins. above ground marked with 4 notches
 Interest N. & S. line 18 lks. S. of cor. to Secs. 10, 11, 14 and 15,
 Set temporary $\frac{1}{2}$ sec. cor.
 Var. 14th 28th E.

74.44

40.00

North between Sections 15 and 16.
 Var. 14th 28th E.
 Ascend along W. slope of ridge.
 Top of Ridge, bears N. and S. 5^o E.
 Thence,
 Along summit.
 Leave summit bears N. 15^o E. and S. and descend.
 Set granite stone 14 x 11 x 7 ins. in the ground for $\frac{1}{2}$ sec.
 corner marked $\frac{1}{2}$ on W. face and raised a mound of stone alongside.
 pits impracticable.
 Set sand rock 18 x 12 x 4 ins. 13 ins. in the ground for cor. to
 Sections 9, 10, 15 and 16, marked with 4 notches on the South and 3
 Notches on the E. edges and raised mound of stone alongside.
 pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.
 March 17th, 1884.

80.00

40.00

27.00

9.00

The corner to Secs. 15, 16, 21 and 22.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Oak on River.
 Dense undergrowth of chaparral.

80.30

CHAINS:

Tp. J. N., R. & W., S. B. M.

Descend.
 Ravine 1.50 ch. wide, course west and ascend.
 Point of spur bears west and descend.
 San Gabriel River 75 lks. wide.
 Course S.W. in canon, 3.50 chs. wide, course S.W. and ascend.
 Set granite stone 24 x 12 x 6 ins. 16 ins. in the ground for $\frac{1}{2}$ sec. cor. marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. Pits impracticable.
 Point of spur bears S.W. and descend.
 Set granite rock 13 x 12 x 6 ins. 8 ins. in the ground for corner to sections 28, 29, 32 and 33, marked with 1 notch on the S. and 4 notches on the E. edges and raised mound of stone alongside. Pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Oak along river.
 Dense undergrowth of chaparral.

40.00
 40.00
 47.50
 66.00
 80.50

From the established cor. to sections 32, 33, 4 and 5, on the S. Boundary of Tp. 1 run,
 North between sections 32 and 33
 Var. 1 $\frac{1}{2}$ 28' E.
 Descend.
 Ravine 1.50 ch. wide, course west and ascend.
 Point of spur bears west and descend.
 San Gabriel River 75 lks. wide.
 Course S.W. in canon, 3.50 chs. wide, course S.W. and ascend.
 Set granite stone 24 x 12 x 6 ins. 16 ins. in the ground for $\frac{1}{2}$ sec. cor. marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. Pits impracticable.
 Point of spur bears S.W. and descend.
 Set granite rock 13 x 12 x 6 ins. 8 ins. in the ground for corner to sections 28, 29, 32 and 33, marked with 1 notch on the S. and 4 notches on the E. edges and raised mound of stone alongside. Pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Oak along river.
 Dense undergrowth of chaparral.

2.75
 13.50
 27.00
 27.50
 56.70
 67.80

From the established cor. to sections 32, 33, 4 and 5, on the S. Boundary of Tp. 1 run,
 North between sections 32 and 33
 Var. 1 $\frac{1}{2}$ 28' E.
 Descend.
 Ravine 60 lks. wide, course S.W. and ascend.
 Point of spur bears S. 50° W. and descend.
 Gulch, 30 lks. wide, course S. 50° W. and ascend.
 The corner to Secs. 9, 10, 15 and 16.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Hook in ravine.
 Dense undergrowth of chaparral.

2.00
 17.60
 27.60
 40.55

Ip. 3 N., R. 8 W., S. B. M. CHAIRS;

These 1 run,
 S. 7° 15' East on a true line between Secs. 9 and 10,
 Var. 1 $\frac{1}{2}$ 28' E.

Leave timber bears N. and S. about 15 chs.
 Set granite stone 20 x 10 x 9 ins. 15 ins. in the ground for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ on N. face and raised mound of stone alongside. Pits impracticable.
 San Gabriel River 70 lks. wide, course S. 20° W. and ascend.
 Top of spur bears S. and descend.
 The cor. to Secs. 28, 29, 32 and 33.
 Land mountainous.
 Soil 3rd rate.
 Timber pine and Oak 13.50 chs.
 Dense undergrowth of chaparral 66.70

North between sections 20 and 21.
 Var. 14° 28' E.

Descend.
 Gulch 35 lks. wide, course S. 50° W. and ascend.
 Set sand stone 25 x 16 x 4 ins. in the ground for 1/2 sec.
 corner, marked 1 on W. face and raised mound of stone along side.
 Pits impracticable.
 Top of spur bears S.W. and descend.
 Set sand rock 26 x 15 x 7 ins. in the ground for corner
 to Boos. 16, 17, 20 and 21, marked with 3 notches on the S. and 4

59.00
 40.00
 19.00

Ascend.
 Summit of ridge, bears N. and S. and
 Ascend.
 Having 80 lks. wide, course S. and ascend.
 Point of spur bears S.E. and descend.
 Gulch 30 lks. wide, course S.E. and ascend.
 Set granite stone 14 x 10 x 6 ins. 9 ins. in the ground for 1/2 sec.
 corner, marked 2 on N. face and raised mound of stone along side.
 Pits impracticable.
 Top of ridge bears N. 7 S. and descend.
 The cor. to Boos. 20, 21, 28 and 29.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.
 March 18th, 1864

79.94
 58.00
 39.97
 30.00
 21.00
 16.50
 1.50

Ascend.
 Summit of ridge, bears N. and S. and
 Ascend.
 Having 80 lks. wide, course S. and ascend.
 Point of spur bears S.E. and descend.
 Gulch 30 lks. wide, course S.E. and ascend.
 Set granite stone 14 x 10 x 6 ins. 9 ins. in the ground for 1/2 sec.
 corner, marked 2 on N. face and raised mound of stone along side.
 Pits impracticable.
 Top of ridge bears N. 7 S. and descend.
 The cor. to Boos. 20, 21, 28 and 29.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.
 March 18th, 1864

40.00
 79.94

East on a random line bet. sections 21 and 28.
 Var. 14° 28' E.

North between sections 28 and 29.
 Var. 14° 28' E.

Descend.
 Gulch 30 lks. wide.
 Course west and ascend.
 Set granite stone 16 x 11 x 5 ins. in the ground for 1/2 sec.
 corner marked 1 on W. face and raised mound of stone along-
 side.
 Pits impracticable.
 Top of spur bears S. 40° W. and descend.
 Set sand stone 17 x 12 x 5 ins. in the ground for corner
 to sections 20, 21, 28 and 29, marked with 2 notches on the S. and
 4 notches on the E. edges, and raised mound of stone along side.
 Pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.

42.50
 60.00
 40.00
 9.50

I. J. K., R. S. W., S. B. K.

Sp. 3 N., N. S. N., S. B. N.

notches on the E. edges and dug pits 18 x 12 ins. in each see
5 1/2 ft. dist., and raised mound of earth 2 ft. high 4 1/2 ft. base
alongside.
Land mountainous.
Soil 3rd rate.
Timber none, dense undergrowth of ophaxial.

East on a random line between sections 16 and 21.
Var. 14e 281 E.

Set temporary § sec. cor.
Intersect N. and S. line 18 lks. N. of cor. to sections 15, 16, 21
& 22,
Thence I run,
N. 89° 52' West on a true line bet. secs. 16 and 21.
Var. 14e 281 E.

40.00
Set sand stone 15 x 11 x 7 ins. in the ground for § sec.
Cor. marked § on N. face and raised mound of stone alongside.
Pits impracticable.
Having 50 lks. wide, course S. 5° W. and ascend.
Summit of ridge bears N. and S. and descend.
The cor. to secs. 16, 17, 20 and 21.
Land mountainous.
Soil 3rd rate.
Timber none.
Dense undergrowth of ophaxial.

40.05
Set sand stone 15 x 11 x 7 ins. in the ground for § sec.
Cor. marked § on N. face and raised mound of stone alongside.
Pits impracticable.

48.00
Having 50 lks. wide, course S. 5° W. and ascend.
Summit of ridge bears N. and S. and descend.

69.00
The cor. to secs. 16, 17, 20 and 21.

North between sections 16 and 17.
Var. 14e 281 E.

11.00
Gulch 40 lks. wide, course S. 50° W. and ascend.
Top of ridge, bears N.E. and S.W. and descend.

36.00
Set granite stone 19 x 11 x 8 ins. 14 ins. in the ground for §

sec. cor., marked § on N. face and raised mound of stone alongside.
Pits impracticable.

78.00
Gulch, 60 lks. wide, course S. 60° W. and ascend.

Set sand stone 16 x 12 x 4 ins. in the ground for corner
to secs. 8, 9, 16 and 17, marked with 4 notches on S. and E. edges
and raised mound of stone alongside.
Pits impracticable.
Land mountainous.
Soil 3rd rate.
Timber none.
Dense undergrowth of ophaxial.

80.00

East on a random line bet. secs. 9 and 16.
Var. 14e 281 E.

40.00
Set temporary § sec. cor.
Intersect N. and S. line 27 lks. N. of corner to secs. 9, 10, 15
and 16.
80.22

These I run
 N. 89° 48' West on a true line bet. Secs. 9 and 16.
 Var. 1 1/4° E.
 Descend.
 Run 70 lks. wide, course S. and ascend.
 Set granite stone 16 x 12 x 4 ins. in the ground for 1/2 sec. corner, marked 1/2 on N. face and raised mound of stone alongside. Pite impracticable.
 Ridge bears N. & S. and descend.
 Run 40 lks. wide, course S.W. and ascend.
 The corner to Secs. 8, 9, 16 and 17.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.
 March 19th, 1884.

North between Sections 8 and 9.
 Var. 1 1/4° E.
 Ascend.
 Top of spur bears S. 40° N. and descend.
 Set sand stone 16 x 9 x 8 ins. 11 ins. in the ground for 1/2 sec. cor. marked 1/2 on W. face and raised mound of stone alongside. Pite impracticable.
 Gulch 60 lks. wide, course S.W. and ascend.
 Set granite stone 19 x 11 x 4 ins. 15 ins. in the ground for corner to sections 4, 5, 8 and 9, marked with 4 notches on the N. and 5 notches on the S. edges, and raised mound of stone alongside. Pite impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.

East on a random line between Secs. 4 and 9.
 Var. 1 1/4° E.
 Set temporary 1/2 sec. cor. intersect N. and S. line 46 lks. N. of cor. to Secs. 3, 4, 9 and 10 which is a granite stone 10 ins. above ground marked with 5 notches on N. and 3 notches on the East edges.
 From which bears a yellow pine 48 ins. diam. N. 6 1/2° W. 43 lks. dist., marked Tp. 3 N. yellow pine 48 ins. diam. N. 8 W., Sec. 4 B.T.
 Yellow pine 42 ins. diam. S. 59 1/2° W. 43 lks. dist., marked Tp. 3 N. yellow pine 40 ins. diam. N. 18° E. 80 lks. dist., marked Tp. 3 N. R. 8 W., Sec. 3 B.T.
 Yellow pine 36 ins. diam. S. 67 3/4° E. 75 lks. dist., marked Tp. 3 N., Sec. 10 B.T.
 Bald peak bears S. 87° West.
 These I run
 N. 89° 40' West on a true line between Secs. 4 & 9.
 Var. 1 1/4° E.
 Descend.
 Gulch 30 lks. wide, course South and ascend.
 Set granite stone 14 x 10 x 6 ins. 9 ins. in the ground for 1/2 sec. cor. marked 1/2 on N. face and raised mound of stone alongside. Pite impracticable.
 Top of ridge bears N. & S. and descend.
 Gulch 40 lks. wide, course S. 50° W. and ascend.

63.00
 55.10
 7.50
 37.72
 40.00
 75.45

30.00
 40.00
 60.56
 80.00

18.00
 40.11
 43.50
 78.00
 80.22

Tp. 3 N., R. 8 W., S. B. M.

Sp. 3 N., R. 8 W., S. 8. N.

75.45 The corner to Secs. 4, 5, 8 and 9. Bald Peak bears S. 85° West.

Land mountains. Soil 3rd rate. Timber scattering pine and Oak. Dense undergrowth of chaparral.

North on the true line between Secs. 4 and 5. Var. The 281 E.

25.40 Summit of divide between Rock Creek and San Gabriel River, bears E. 4 W. and descend along ridge.

40.00 Set Granite stone 20 x 11 x 6 ins. in the ground for 1/2 sec. cor., marked 4 on N. face and raised a mound of stone along-side. Pits impracticable.

82.78 Intersection North boundary of Township at a point 4.80 chs. S. 87° 20' E. of cor. to Secs. 4, 5, 32 and 33 at point of intersection. Set a Granite stone 19 x 12 x 6 ins. in ground for clearing cor. to Secs. 4 and 5, Tp. 3 N., R. 8 W., marked C.O. with 4 notches on the E. and 2 notches on the West edges, and raised mound of stone alongside. Pits impracticable.

Land mountains. Soil 3rd rate. Timber none.

Dense undergrowth of chaparral.

From the corner to Sections 31, 32, 5 and 6 on the S. boundary of Township, 1 km North between Sections 31 and 32. Var. The 281 E.

29.00 Gulch 20 lks. wide, course S. 60° W. and ascend. Set Granite stone 16 x 12 x 5 ins. in the ground for 1/2 sec. cor. marked 4 on N. face and raised mound of stone alongside.

27.80 Pits impracticable. Top of spur bears S. W. and descend. Set Granite stone 21 x 12 x 9 ins. in the ground for corner to Secs. 29, 30, 31 and 32, marked with 5 notches on the N. and 1 notch on the S. edges and dug pits 18 x 12 ins. in each Sec- tion 5/4 ft. dist., and raised mound of earth 2 ft. high, 4 1/2 ft. base alongside.

Land mountains. Soil 3rd rate. Timber none.

Dense undergrowth of chaparral.

East on a random line between Secs. 29 and 32. Var. The 281 E.

40.00 Set temporary 1/2 sec. cor. Intersection N. and S. line 30 lks. S. of cor. to Secs. 28, 29, 32 and 33. Those I km Var. The 281 E.

Descend.

Sp. 3 N., R. 8 W., S. 8. N.

11.65 Having 80 lbs. wide, course S. 10° W. and ascend. Set granite stone 12 x 11 x 7 ins. 7 ins. diam. the ground for 1/2 sec. cor. marked 1/2 on N. face and raised a mound of stone alongside. Pits impracticable. Top of ridge bears N. and S. and descend. The corner to sections 29, 30, 31 and 32. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of chaparral.

61.00

80.50

West on a true line between Secs. 30 and 31. Var. 1/4° 28' E.

20.75 Descending. Having 60 lbs. wide, course S. W. and ascend. Set sand stone 17 x 11 x 5 ins. 12 ins. in the ground for 1/2 sec. cor. marked 1/2 on N. face and dug pits 18 x 18 x 12 ins. E. and W. of stone 1/2 ft. dist., and raised mound of earth 1 1/2 ft. high and 3/4 ft. base, alongside. Top of ridge bears N. and S. and descend.

40.00

52.70

71.20 Having 1.20 ch. wide, course S. E. and ascend. To a point 10.76 chs. S. of cor. to Secs. 25, 30, 31 and 36, which is a post 4 x 4 ins. firmly set in large mound of rocks and marked Sp. 3 N., Sec. 30 on the N. E. R. 8 W. Sec. 30 on the S. E. Sp. 3 N., Sec. 36 on the S. W. and R. 9 W. Sec. 25 on the N. W. faces from which bears a

82.14

pine 14 ins. diam. N. 2 1/2° W. 1.44 chs. dist. marked 1. 3 N., R. 9 W., Sec. 25 S. E. pine 10 ins. diam. N. 40° E. 2.09 chs. dist. marked 1. 3 N., R. 8 W., Sec. 30, S. E. I destroyed the marks on N. E. and S. E. faces of post, also on S. E. to Sec. 30, and at the point of intersection set a post 4 x 4 ins. 1/2 ft. long with marked stone 12 ins. in the ground for closing cor. to Secs. 30 and 31, marked 1. 3 N., R. 8 W., C. O. on the N. Sec. 30 on N. and Sec. 31 on S. faces and dug pits 18 x 18 x 12 ins. N. S. 4 E. of post and raised earth mound 2 ft. high, 1/2 ft. base around post. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of chaparral.

North between sections 29 and 30. Var. 1/4° 28' E.

20.50

Descend. Having 30 lbs. wide, course S. W. and ascend. Set granite stone 12 x 11 x 6 ins. 7 ins. in the ground for 1/2 sec. cor. marked 1/2 on N. face and raised mound of stone alongside. Pits impracticable. Top of spur bears S. 60° W. and descend.

40.00

67.50

Dense undergrowth of chaparral.

Timber none.

Soil 3rd rate.

Land mountainous.

Plts impracticable.

and 2 notches on south edges and raised mound of stone alongside.

along corner to Secs. 19 and 30, marked C.C. with 4 notches on N. side of granite stone 16 x 10 x 9 ins. in the ground for

intersections.

I destroyed marks on N.E. and S.E. faces of post and at point of

S.E. R. 9 W. Sec. 25 on S.W. and Tp. 3 N., Sec. 24 on N.W. faces.

mound of rocks marked Tp. 3 N., Sec. 19 on N.E. R. 8 W., Sec. 30 on

Secs. 19, 24, 25 and 30, which is a post 4 x 4 ins. firmly set in

intersect west boundary of Tp. at a point 10.20 chs. S. of cor. to

Plts impracticable.

marked 4 on N. face and raised a mound of stone alongside.

Set sand rock 19 x 12 x 6 ins. in the ground for 4 sec. cor.

Ascend.

Gulch 30 lks. wide, course S. 60° W. and

Descend.

West on a true between Secs. 19 and 30.
Var. 14° 28' E.

Dense undergrowth of chaparral.

Timber Pine and Oak in ravine.

Soil 3rd rate.

Land mountainous.

The corner to Secs. 19, 20, 29 and 30.

Descend.

Top of ridge bears N. and S. and

Plts impracticable.

cor. marked 4 on N. face and raised a mound of stone alongside.

Set granite stone 14 x 11 x 7 ins. 9 ins. in the ground for 4 sec.

Ascend.

Timbered ravine 1.00 ch. wide, course S. and

Descend.

N. 89° 56' West on a true line bet. Secs. 20 and 29,
Thence, 1 run
Var. 14° 28' E.

Set temporary 4 section cor.
Intersect N. and S. line 10 lks. N. of corner to Secs. 20, 21, 28 &
29,

Var. 14° 28' E.

East on a random line between Secs. 20 and 29,
Var. 14° 28' E.

Dense undergrowth of chaparral.

Timber none.

Soil 3rd rate.

Land mountainous.

Plts impracticable.

notches on E. edges and raised mound of stone alongside.

Set sand stone 20 x 10 x 6 ins. 15 ins. in ground for corner to
Secs. 19, 20, 29 and 30, marked with 2 notches on the S. and 5

Tp. 3 N., R. 8 W., S. B. M.

82.76

40.00

20.60

79.80

60.50

39.90

18.00

79.80

40.00

80.00

Dr. J. M., R. B. W., B. B. M.

North between sections 19 and 20,
Var. 14, 28, E.

17.00

Descend.
Head of gulch, course S.W. and

40.00

Ascend.
Set granite stone 14 x 9 x 6 ins. 9 ins. in the ground for sec. cor.

45.00

Summit of ridge, bears N. & S. 20° E. and along summit.

50.00

Set granite stone 14 x 6 x 6 ins. 9 ins. in the ground for corner to

secs. 17, 18, 19 and 20, marked with 3 notches on S. and 5 notches

on the east edge and raised mound of stone alongside.

Plts impracticable.

Land mountainous.

Soil 3rd rate.

Timber none.

Dense undergrowth of sphaeral.

East on a random line between Secs. 17 and 20
Var. 14, 28, E.

40.00

Set temporary sec. cor.

50.20

Intersect N. & S. line 33 lks. N. of corner to Secs. 17, 16, 20 and 21,
Thence I run

N. 89° 46' West on a true line bet. Secs. 17 and 20.
Var. 14, 28, E.

10.00

Descend.
Gulch 20 lks. wide, course S.W. and

20.50

Ascend.
Point of spur bears S.W. and

38.50

Timbered Ravine 80 lks. wide, course S. and

40.10

Ascend.
Set post 4 x 4 ins. 4 ft. long with marked stone 12 ins. in the

ground for sec. cor., marked § S. and face

from which bears a

line 20 ins. diam. N. 35° E. 100 lks. dist.

57.00

Descend.
Top of spur bears S.E. and

70.15

Ascend.
Gulch 30 lks. wide, course S.E. and

80.20

The corner to Secs. 17, 18, 19 and 20.

Land mountainous.

Soil 3rd rate.

Timber pine in Ravine.

Dense undergrowth of sphaeral.

West on a true line between Secs. 18 and 19,
Var. 14, 28, E.

18.50

Descend.

Gulch 10 lks. wide, course S.W. and

Ascend.

40.00
50.41
11.00
21.00
40.11

Get temporary & sec. corner. Intersect N. and S. line 16 lks. S. of corner to Secs. 8, 9, 16 and 17. These I run S. 89° 53' West on a true line between Secs. 8 and 17. Var. 1 1/2 28' E. Ascend. Low point of spur, bears S. 10° W. and Descend. Having 50 links wide, course S. 10° W. and Ascend. Set sand stone 15 x 12 x 4 ins. in the ground for & sec. cor. marked & on N. face and raised mound of stone alongside.

East on a random line between Secs. 8 and 17, Var. 1 1/2 28' E.



23.50
40.00
58.00
70.00
80.00

Along summit. Leave summit and Descend. Set Granite stone 16 x 11 x 5 ins. in the ground for & sec. cor. marked & on W. face and raised mound of stone alongside. Plat impracticable. Quick 50 lks. wide, course W. and Ascend. Top of spur bears N. and Descend. Set Granite stone 20 x 11 x 6 ins. in the ground for corner to Secs. 7, 8, 17 and 18, marked with 4 notches on S. and 5 notches on the E. edges and raised mound of stone alongside. Plat impracticable. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of chaparral.

North between sections 17 and 18, Var. 1 1/2 258' E.



40.00
66.20
83.14

Set Granite stone 14 x 10 x 9 ins. in the ground for & sec. cor., marked & on N. face and raised mound of stone alongside. Plat impracticable. Summit of spur, bears S. 15° W. and Descend. Intersect West boundary of township at a point 10.52 chs. S. of corner to sections 13, 18, 19 and 24, which is a post 4 x 4 ins. firmly set in mound of rocks and marked Tp. 3 N., Sec. 18 on N.E. R. 8 W., Sec. 19 on S.E. R. 9 W., Sec. 24 on S.W. and Tp. 3 N., Sec. 13 on N.W. faces. I destroyed marks on N.E. and S.E. faces of post and at point of intersection set a post 6 x 6 ins. 4 1/2 ft. long with marked stone 12 ins. in the ground for closing cor. to Secs. 18 and 19, marked Tp. 3 N., R. 8 W., C.C. on the East, Sec. 18 on North and Section 19 on South faces, and raised mound of stone around post. Plat impracticable. Land mountainous. Soil 3rd rate. Timber none. Dense undergrowth of chaparral.

Tp. 3 N., R. 8 W., S. B. M.

Ascend.
 Top of ridge bears N. and W. and along summit. 11.00
 Leave summit and
 Descend.
 Set sand rock 23 x 14 x 6 ins. in ground for 1/2 sec. corner, 40.00
 marked 1/2 on W. face and dug pits 18 x 12 ins. N. and S. of
 stone and raised a mound of earth 1 1/2 ft. high 3/4 ft. base alongside.
 Gully 10 lks. wide, course S.W. and
 Ascend.
 Set granite stone 18 x 13 x 6 ins. in ground for corner to 80.00
 sections 5, 6, 7 and 8, marked with 5 notches on S. and E. edges and
 raised mound of stone alongside.
 Pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.

North between sections 7 and 8, Var. 14 281 E.

Ascend.
 Top of spur bears South and 6.40
 Descend.
 Gully 20 lks. wide, course S. and ascend. 18.50
 Set granite stone 16 x 10 x 4 ins. in the ground for 1/2 sec. 40.00
 corner, marked 1/2 on N. face and raised mound of stone alongside.
 Pits impracticable.
 Summit of high ridge about 300 ft. above sec. corner, bears N. 50° E. 47.60
 and S. 50° W. and descend.
 Intersect East boundary of Township at a point 9.90 chs. South of 82.50
 Cor. to sec. 7, 12, 13 and 18, which is a sand rock 20 x 10 x 6 ins.
 firmly set in mound of rocks and at point of intersection I set a
 granite stone 19 x 16 x 5 ins. in the ground for clearing
 corner to sec. 7 and 18, marked C.C. with 4 notches on S. and 2
 notches on the N. edges and raised mound of stone alongside.
 Pits impracticable.
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.

West on a true line bet. Secs. 7 and 18, Var. 14 281 E.

Pits impracticable. 43.50
 Top of spur bears S.E. and
 Descend.
 Gully near head 10 lks. wide, course South and second. 52.00
 Top of ridge bears N. and S. and 59.00
 Descend.
 Gully 10 lks. wide, course South and 70.00
 Ascend.
 The corner to Secs. 7, 8, 17 and 18 80.41
 Land mountainous.
 Soil 3rd rate.
 Timber none.
 Dense undergrowth of chaparral.