



May 31, 1928.

For California.

Office Cadastral Engineer

Frank E. Barker

I, FRANK E. BARKER, Office Cadastral Engineer, do hereby certify that the annexed transcript of the field notes of fractional Township 2 North, Range 17 West, San Bernardino Meridian, is a full, true and literal exemplification of said notes, as they remain on file and of record in this office.

San Francisco, California.

Public Survey Office,

GENERAL LAND OFFICE.

DEPARTMENT OF THE INTERIOR

County Surveyor's Map No. 9367

Survey by Henry Hancock, Deputy Surveyor.
Contract of December 31, 1853.

Township 1 North, Range 16 West,
S. B. M.

On west boundary of section 6.

x x x x x x x x x x x x x x x x

Set township post and charred stake in mound, corner

of Townships 1 and 2 N., Ranges 16 and 17 W., with

trench and pits as per instructions.

June 2.

On West Boundary Township 2 N., R. 16 West.

North, west boundary of section 31.

Across trail from ranch El Escorpion to Los Angeles,

course S.E.

Set quarter section post, and charred stake in mound

with trench and pits as per instructions.

Set section post and charred stake in mound, corner

of sections 30, 25, 36, 31, with trench and pits as

per instructions.

Second rate limestone soil.

North on west boundary of section 30.

Across main road between mission San Fernando and

San Buenaventura, course west.

Set quarter section post and charred stake in mound

with trench and pits as per instructions.

42.00

To base of hills.

50.00

Top of west slope of hill. a 40

55.00

Pass in hills.

65.00

Top of hill. a 200

73.00

Across trail between hills. d 150

75.00

Top of east slope of hill. a 15

Township 2 North, Range 16 West.

77.50 Base of hill. a 50
 80.00 Set section post and charred stake in mound, in valley, corner of sections 19, 24, 25, 30, with trench and pits as per instructions; from this corner a tree in the valley near the terminus of a dry arroyo, coming from the mountain, skirted with timber, bears S. 63° east and a rock in mountain some 25 chains west of the head of the cañon out of which the dry arroyo starts, N. 12° E.

On west boundary of section 19.

6.50 To dry arroyo, course S. E. about 10 links wide.
 16.00 Across cart trail to west.
 32.00 Base of spur of hill.
 40.00 Set quarter section post and charred stake, from which
 B. oak 6 in. diameter S 24 E 288 links.
 46.00 Top of hill.
 66.00 Base of hill and valley.
 80.00 Set section post and charred stake, corner of sections 18, 13, 24, 19; from which bears
 A white oak 18 in. diameter N. 83° W. 112 links.
 " " " " 22 " " S. 30 1/2° W. 297 "
 " " " " 26 " " S. 63° E. 263 "
 " " " " 17 " " N. 70° E. 293 "

North and the tree on dry arroyo before taken bears south 26 east, and the rock do do N. 17 1/2° east. Soil of the valley, second rate and dry.

On west boundary of section 18.

11.64 Black oak 8 inches diameter on line.

a 80

a 30

Township 2 North, Range 16 West.

40.00 Set quarter section post and charred stake from which

bears

A white oak 18 inches S. 87 1/2 west, 185 links dist.

and A white oak 17 inches diameter S. 73 E. 706 links

dist.

80.00 Set section post and charred stake in mound, corner of

sections 7, 12, 13, 18, with trench and pits as per in-

structions.

Soil, second rate but dry, with scattering timber.

On west boundary of section 7.

25.06

Live oak 6 inches diameter.

40.00

Set quarter section post at base of mountain, from which

bears

A black oak 12 inches diameter S. 2 1/2 W. 155 links.

A black oak 10 inches diameter S. E. 153 links.

S.W. corner of granite boulder, 50 feet high and 60 feet

thick S. 32 east, 39 links dist.

I find it impracticable to extend the line any farther.

Township 2 North, Range 17 West.

West on south boundary of section 36.

Variation 13° 30'

40.00

Set quarter section post and charred stake in mound,

with trench and pits as per instructions.

80.00

Set section post and charred stake in mound, corner of

sections 36, 35, 2, 1, with trench and pits as per in-

structions.

Soil, second rate.

Township 2 North, Range 17 West.

On south boundary of section 35.
35.00 Across trail to N.
40.00 Set quarter section post and charred stake, with trench
and pits as per instructions.
68.50 Across trail, course S.E.
80.00 Set section post and charred stake in mound, with trench
and pits as per instructions, at base of hills, corner
of sections 35, 34, 3, 2.
Soil, second rate, but dry, from this corner, towards S.E.
point of an oak grove in the valley at the base of the
mountain, and within small hills in which is situated the
ranch house of the ranch "El Escorpion" bearing S.W.,
which ranch, contains 2 leagues.

On south boundary of section 34.
12.50 North slope of hill. a 40
19.00 Ravine, course N. a 30
26.50 Top of hill. a 40
32.00 Ravine and across trail. a 40
40.00 Set quarter section post and charred stake in mound, with
trench and pits as per instructions; from which bears
S.E. corner of point of timber, S.88 W.
59.50 Ravine or gulch about 70 links wide. a 250
62.00 Across road, course S.W.
71.50 Ravine, course S.E.
80.00 Set section post and charred stake in rock mound, corner
of sections 34, 33, 3, 4; from which bears
A walnut N.67 E. 37 links dist.
Ranch house bears S.39 E.

Township 2 North, Range 17 West.

On south boundary of section 35.

To top of a mountain spur. 400

Across dry arroyo to S.E. about 12 links wide. 24.00

Across old trail. 27.00

To base of mountain. 29.50

Set post and charred stake, from which bears a

B. oak 7 inches diameter N. 13 1/2 W. 1 1/4 links distant.

Black oak 24 inches diameter 14 links distant.

" " " 24 " " S. 15 1/2 E. 208 links

distant.

Finding it too rough to measure further west on account of

the roughness of the mountain, I discontinue it.

Book 164-26

Survey by Henry Hancock, Deputy Surveyor,
Contract of October 1st, 1857.

Survey executed November 9th - 18th, 1857.

N. Bdy T. 2 N., R. 18 W. S. B. M.

East on the N. bdy of sec. 1.

x x

80.00 Set a sandstone rock 28 in. long, 14 in. wide and 6 in. thick

for cor. to Tps. 2 and 3 N., Rs. 17 and 18 W., San B. M.

from the peaks of the mountain on the S. of valley before

taken bear respectively and in the order above mentioned,

S. 24 E. and S. 65 1/2 E.

Land, undulating.

Soil, 2d rate.

On the N. Bdy of Tps. 2 N., R. 17 W.,
S. B. M.

va. 13 201 E.

East on the N. bdy of sec. 6.

N. Bdy T. 2 N., R. 17 W., S. B. M.

- 40.00 Set a post for $\frac{1}{2}$ sec. cor. and deposited 3 rubble rock, 3 in. dia. and dug trench as per instructions. From which
- 64.50 A W. oak 15 in. dia. bears S. 40 W. 500 lks. dist. Across dry arroyo 50 lks. wide, course S. with water some 20 chs. N.
- 65.00 To W. base of central portion of a high hill. Set a rock 14 in. long, 13 in. wide, and 10 in. thick for cor. to secs. 5, 6, 31 and 32, on the W. face of hill. Land, principally undulating. Soil, 2d rate.
- 80.00 East on the N. bdy of sec. 5.

- 6.00 To a point on N. side of the pinnacle of hill, some 300 feet above the valley. To East base.
- 40.00 Set a rock 14 in. long, 11 in. wide, and 2 $\frac{1}{2}$ in. thick for $\frac{1}{2}$ sec. cor.
- 80.00 Set a rock 15 in. long, 6 in. wide, and 4 in. thick for a cor. of secs. 4, 5, 32 and 33. From which
- A W. oak 30 in. dia. bears N. 5 E. 329 lks. dist. Land, hilly. Soil, 2d rate. Undergrowth, sage.

- 40.00 East on the N. Bdy of sec. 4. Va. 13° 20' E.
- 40.00 Set a rock for $\frac{1}{2}$ sec. cor. 16 in. long, 14 in. wide and 2 $\frac{1}{2}$ in. thick. To a sandstone boulder, 10 ft. long, 4 ft. high and 4 ft. 2 $\frac{1}{2}$ in. thick.
- 42.00

40.00 Set a rock 13 in. long, 12 in. wide and 7 in. thick for $\frac{1}{2}$

Va. 13° 20' E.

South bet. secs. 13 and 18.

Soil 2d rate.

A W. oak 11 in. dia. N. 66 $\frac{1}{2}$ E. 318 lks. dist.

From which bears

80.00 Set a rock 14 in. long, 7 in. wide and 6 in. thick.

To base of mountain on the S.

56.00 Cross a dry arroyo 50 lks. wide, course W.

cor.

40.00 Set a rock 17 in. long, 9 in. wide and 4 in. thick for $\frac{1}{2}$ sec.

36.00 Across trail, course E.

Va. 13° 20' E.

South bet. secs. 7 and 12.

Land, level; soil, 2d rate.

per instructions.

charred stake and raised a mound with trench and pits as

80.00 Set a post for a cor. to secs. 1, 6, 7 and 12; drove a

a mound with trench and pits as per instructions.

40.00 Set a post for $\frac{1}{2}$ sec. cor. drove a charred stake and raised

S. bet secs. 1 and 6.

Va. 13° 20' E.

South bet. Rs. 17 and 18 W., Tp. 2 N.

W. Bdy of T. 2 N., R. 17 W., S. B. M.

18 W.

further, I return to cor. of Tps. 2 and 3 N., Rs. 17 and

of a rocky range and finding it impracticable to measure

thick, in center of ravine, course S. on the S.W. face

N. Bdy. T. 2 N., R. 17 W., S. B. M.

W. Hwy T 2 N., R. 17 W., S. B. M.

From which bears

A sycamore 14 in. dia. S. 15 $\frac{1}{2}$ W. 231 lks. dist.
" " 28 in. dia. S. 15 E. 318 lks. dist.

45.50 Across dry arroyo 40 lks. wide, course N.W. on the S. side
of a cañada, some 10 chs. wide from E.

80.00 Set a rock 24 in. long, 16 in. wide and 3 in. thick, for
corn. to secs. 13, 18, 19 and 24.

Land, broken.
Soil, 3d rate.

South bet. secs. 19 and 24.

Va. 13 $\frac{1}{2}$ 20 $\frac{1}{2}$ E.

14.20 Across cañon 1 ch. wide, from the S.E. to a sycamore 15 in
dia. beyond which it is impracticable for the mountain.

Nov. 18th, 1857.

1.2 N., R. 16 W., S. B. M.

40.00 To 1/2 sec. post in rock mound, from which witness trees bear as follows:

A blk oak 15 in. dia. S. 27° W. 155 lks.

" " " " 18 " " S. 46° E. 153 "

The S.W. corner of a sandrock boulder, 30 ft. high &

60 ft. thick, bears N. 30 E. 40 lks. dist.

The north point of a sandrock bluff bears S. 72° E. 3 chs

dist.

Leave valley and ascend hill.

Summit of sandrock ledge, N.E. and S.W.

Foot of N. slope of ridge and enter small valley 10 chs

wide, N. & S. Leave valley and ascend steep hill E. and W.

Point for cor. to secs. 1, 6, 7 & 12.

It being on steep hillside, at 80.60 chs. set a sandrock

20 x 14 x 10 in irregular mound of sandrock for witness

cor. as per ins.

Land, first part level, 2nd rate.

Last part hilly & broken, 3rd rate.

Timber, first part live & black oak.

North, bet. secs. 1 & 6.

Va. 15° 10' E.

1.00

Summit of hill E. & W.

5.00

Top of hill and run over broken ground.

23.00

To the right and S. bank of Canada de los Alisos, running

S. 73° E. with perpendicular banks, 50 ft. high.

Set a sandstone 18 x 9 x 6.

I cause a flag to be set on the north and left bank of the

Canada, and in line bet. secs. 1 & 6, and run a base

East from said sandstone 5 chs. E. to a point from which

the flag bears N. 30° W. which gives by calculation for

the distance across the Canada

T. 2 N., R. 16 W., S. B. M.

on the said line bet. secs. 1 & 6, 8.66 chs. to which

add 23. chs. the distance to the canada makes

To the flag on the left and north bank of canada to

which point I proceeded and set a shale rock 16 x 11 x

8 in place of the flag.

Ascend spur of hill bears S. 10° W.

61.00 To the left and E. bank of a deep, dry ravine, runs S. 20° W

To the right and west bank of ravine.

73.50 To summit of ridge runs S. 60° E. 1 ch. wide.

77.00 Foot of a ridge and ascend.

80.00 Set a sandrock 24 x 16 x 11 for cor. to Tps. 2 & 3 N.,

Rs. 16 & 17 W. in an irregular mound of sandrock, as per

ins. 60 lks. from the summit of the E. point of a hill,

running N. 80° W.

Land, broken valley.

3rd rate with chamisal brush.

South Bay of T. 3 N., R. 17 W.

San Bernardino Meridian.

West on a true line along the S. by of sec. 36.

Va. 15° 10' E.

8.00

Summit of main ridge S. 20° W.

10.00

Cross do & descend.

17.00

Cross a dry ravine 60 lks wide, S. 20° W.

23.00

Summit of ridge S. 22° W.

28.00

Cross do and descend.

33.00

" a ravine 80 lks. wide at foot of descent.

39.50

Summit of ridge S. W. and continue down gently sloping

descent.

40.00

Set a sand rock 18 x 12 x 7 for 1/4 sec. cor. in an irreg-

ular mound of sandrock, as per ins.

S. Bdy W. 3 N., R. 17 W., S. B. M.

47.28 To the left and E. bank of the Canada de los Alisos

running S. 25° E. with perpendicular banks 50 ft. high.

Set a sand rock 14 x 9 x 6.

I cause a flag to be set on the right & west bank and
in line of the true S. bdy of sec. 36; thence from the

said sand rock I run a base north 6.00 chs.

From which the flag bears S. 53° W., which gives by cal-

culatation for the distance across the Canada on the pro-

longation of this line 7.96 chs. which added to 47.28 chs

makes

55.24 To the flag on the right and W. bank of the Canada to which

point I proceed and place a sand rock in line of the flag,

15 x 10 x 5.

63.00 Smt of ridge N. W. & S. E.

67.00 Cross do and descend.

73.00 Cross a 80 lks. wide, S. 60° E.

77.50 Top of bank of ravine.

80.00 Set sandrock 24 x 16 x 10, for cor to secs. 1, 2, 35 and 36,

in irregular mound of rocks as per ins.

Land, broken, 3rd rate.

West on a true line along the S. bdy of sec. 35.

Va. 15° 10' E.

13.00 Cross a dry ravine, 60 lks. wide, S. 60° E.

25.00 Cross a dry ravine 100 lks. wide, S. 65° E.

33.00 Set a sand rock 20 x 14 x 8, for cor. to frag. secs.

2 & 35, and raised an irregular mound of sand rock as

per instructions.

Land, same as last mile.

It is impracticable to run the line any further west on

account of the mountainous character of the country.

I therefore stop at this point.

May 25th, 1872.

Book 362-20 Survey by J.R. Glover, Deputy Surveyor,

Contract of November 20th, 1884.

Survey commenced August 5th, 1895.

Survey completed August 21st, 1895.

Resurvey. N.W. Boundary line Rancho San Fernando, through

T. 2 N., R. 16 & 17 W., S. B. M.

From station 30 on N.W. boundary line of Rancho San Fer-

nando, which is a post set firmly in the ground marked

S.F. on S.E. face, Sta. 30 with a stone mound which I re-

build around post. I run

S. 38° W. along the boundary on a random line.

Variation 14° 30' E.

273.63 To a point 9 lks N. 52° W. from station No. 31, which is

a post set firmly in the ground marked S.F. on S.E. face

station 31, with a stone mound which I rebuild around

post. August 5th and 6th, 1895.

Thence N. 37° 59' E. on a true line along boundary.

Variation 14° 30' E.

Descend.

4.63 Cross gulch 20 lks. wide, course south and ascend.

28.63 Top of spur bears northwest and southeast and descend.

57.85 Cross gulch 10 lks. wide, course south and ascend.

63.23 Top of round hill, bears north and south and descend.

71.63 Enter valley bears northwest and southeast.

81.25 Cross wire fence bears northwest and southeast.

An oak tree 3/4 in. dia. marked S.F.

90.23 Cross gulch 10 lks. wide, course south.

Leave level valley and over rolling land.

101.63 Cross road bears east and west.

Resurvey
N.W. Boundary Line Rancho San Fernando, through
T. 2 N., R. 17 W., S. B. M.

102.13 A telegraph line bears east and west.
 132.63 Cross road bears northwest and southeast.
 152.63 A road bears N. 37° 59' E. and S. along same.
 180.13 Cross road bears north and south.
 221.63 Leave road bears N. 37° 59' E. and E.
 221.88 Enter corn field bears northwest and southeast.
 231.63 Leave corn field bears northwest and southeast.
 238.38 Cross wash, 15 links wide, course south.
 Leave rolling land and ascend through chaparral.
 266.63 Top of hill bears north and south and descend.
 To station No. 30. 273.63
 Land, for about 19.00 chains level valley.
 For about 148.00 chains, rolling, remainder rough and
 broken.
 Soil, second and third rate.
 Scattering oak timber and dense undergrowth of chaparral.
 August 7, 1895.

From station No. 31, on boundary I run
 S. 39° W. on a random line.
 Variation 14° 30' E.
 8.30 To station No. 32, which is a post set firmly in the ground
 marked S.F. No. 32, on S.E. face, with a stone mound which
 I rebuild around post.
 Thence I run
 N. 39° E. on a true line along boundary.
 Variation 14° 30' E.
 Over rolling land.
 To station No. 31. 8.30
 Land, rolling; soil, third rate.
 Dense undergrowth of chaparral.

Resurvey
 N.W. Boundary Line Rancho San Fernando, through
 T. 2 N., R. 17 W., S. B. M.

From station No. 32 on boundary I run

N. 85° 26' W. on a random line along boundary.

Variation 14° 30' E.

72.64 To a point 15 links S. 4° 34' W. of station No. 33, which

is a post set firmly in the ground, marked S.F. No. 33

on S. face, with a stone mound which I rebuild around

post. Thence I run

S. 85° 19' E. on a true line along boundary.

Variation 14° 30' E.

Descend.

4.39 Cross gulch 6 links wide, course southeast and ascend.

8.64 Top of spur bears north and south and descend.

14.16 Cross gulch 7 links wide, course south and ascend.

20.64 Top of spur bears north and south and descend.

42.14 Cross road bears north and south.

42.64 House bears N. 4.00 chains dist.

43.64 Cross Spring branch 4 links wide, course south and

ascend.

49.64 Top of ridge bears north and south and descend.

56.64 Enter cultivated land in low sag bears northeast and southwest

and ascend.

57.10 Leave cultivated land bears northeast and southwest.

60.64 Top of spur bears north and south and descend.

65.10 Cross low sag bears north and south and ascend.

72.64 To station No. 32.

Land, broken and mountains.

Soil, second and third rate.

Dense undergrowth of chaparral.

August 8, 1895.

W. Boundary Line Rancho San Fernando, through
T. 2 N., R. 17 W., S. B. M.

Resurvey

From station No. 33 on boundary I run
S. 11° 32' W. on random line along boundary.
Variation 14° 30' E.
To a point 18 links S. 89° 28' W. of station No. 34, which
is an iron post set firmly in cement at the foot of
an old stump lying on the ground, marked S. F. 34
August 9th and 10th, 1895.
Thence N. 11° 29' E. on a true line along boundary.
Variation 14° 40' E.
Ascend.

- 44.22 Cross road bears east and west.
- 65.42 Top of spur bears east and west and descend.
- 69.92 Cross road in low sag bears east and west and ascend.
- 82.37 A post set firmly in the ground, bears east 84 links dist.
- 88.42 Top of spur bears east and west and descend.
- 104.51 A stone set firmly in the ground, marked H. A. 3 bears E. 7 links dist.
- 104.62 Cross road bears east and west.
- 105.42 Cross creek 10 links wide, course east and ascend.
- 122.42 Top of spur bears northwest and southeast and descend.
- 123.20 A post set firmly in the ground.
- 128.42 Cross Gulch 4 links wide, course east and ascend.
- 139.42 Top of spur bears east and west and descend.
- 154.42 Cross Gulch 4 links wide, course east and ascend.
- 155.92 Top of spur bears east and west and descend.
- 163.30 A post set firmly in the ground.
- 178.62 Cross Gulch 5 links wide, course east and ascend.
- 184.32 Cross wood road on top of ridge bears east and west and descend.

W. Boundary line San Fernando Rancho through
T. 2 N., R. 17 W., S. B. M.

191.92 Cross ravine, 2 links wide, course southeast and ascend
over open land.

193.22 Leave open land bears east and west and descend.

201.10 To station No. 33.

Land, rough, broken and mountainous.

Soil, third rate.

Scattering oak timber and dense undergrowth of chamisal

and chaparral.

August 12th, 1895.