

DEPARTMENT OF THE INTERIOR
 GENERAL LAND OFFICE

Public Survey Office,
 San Francisco, California.
 September 22, 1930.

I, FRANK E. BARKER, do hereby certify that the annexed transcript of field notes of the North Boundary of T. 4 N., R. 10 W., S. B. M. as surveyed by Burnham and Warner, in 1912: the portion of West Boundary of T. 5 N., R. 10 W., S. B. M. as surveyed by Guy Redwine, in 1915, and Sections 25 and 36, T. 5 N., R. 11 W., S. B. M. as surveyed by John L. Warboys, in 1926, is a true and literal exemplification of said field notes, as the same remain on file and of record in this office.

FRANK E. BARKER (Sgd.)
 Office Cadastral Engineer for
 California.

R. 11 W.	23	24	19	20		
	26	25	30	29		
	35	36	31	32	33	34
T. 4 N.	2	1	6	5	4	3
	11	12	7	8	9	10
						11

T. 5 N.

R. 10 W.

Chains

448-7

T. 4 N., R. 10 W., S. B. M.

Survey executed by N. J. Burnham, Temporary Transitman,
and A. Parker Warner, U. S. Transitman.

Under instructions dated Sept. 10, 1912.

West Boundary

North bet. secs. 1 and 6.
* * * * *

92.75 To a point due west of the cor. of secs. 3, 4, 33 and

34, on the N. Bdy. of T. 4 N., R. 10 W., where I set

temp. cor. for Tps. 4 and 5 N., Rs. 10 and 11 W.

Dec. 9, 1912.

Resurvey of Portion of N. Bdy. of T. 4 N., R. 10 W.,
S. B. M.

November 27; at 8h 30m. A.M., l.m.t. I set off 34.28'

on the lat. arc; 21° 07' S. on the decl. arc, and deter-

mine a meridian with the solar at the cor. of secs. 2, 3,

34, and 35, which is a pine post 3 ins. square, 12 ins.

above ground, firmly set, marked and witnessed as des-

cribed by the Surveyor General.

Thence I retrace

West on a random line bet. secs. 3 and 34.

40.00 After diligent search, fail to find any evidence of old

½ sec. cor.

80.23 Fall 47 lks. S. of cor. of secs. 3, 4, 33 and 34, which

is a granite stone 12x12x8 ins. above ground, firmly set,

marked with 3 notches on E. and W. edges.

Traces of old charred stake found.

No bearings available.

S. 89° 40' E. on a true line bet. secs. 3 and 34.

Over level desert through scattering sage brush, juniper

and manzanita brush.

Resurvey of Portion of T. 4 N., R. 10 W., S. B. M.

Chains

10.20 Middle of dry wash, 2.50 lks. wide, course N. Ascend.


19.60 Top of spur bears N. and S. Descend.

25.70 Dry wash 20 lks. wide, course N. Ascend.

40.00 Dry wash, 20 lks. wide, course N.

40.11 7/8 Set an iron post 3 ft. long, 1 in. dia. 24 ins. in the

Ground for 1/4 sec. cor. with brass cap marked



Dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist.

and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high N. of

cor.

November 27; at this 1/4 sec. cor. I set off 210 10' S. on

the decl. arc, and at 11h. 48m. 1.m.t. observe the sun on

the meridian; the resulting lat. is 34° 28'

41.40 Road from Pallett's Ranch to Little Rock bears NW. &

S. E.

64.90 Road from West's Ranch to Little Rock bears N. 40° W.

and S. 40° E. Ascend.

73.00 Top of spur bears N. and S. Descend.

The cor. of secs. 2, 3, 34 and 35.

Land, level and rolling, drains NW.

Soil, sandy and rocky, 4th rate.

Scattering sage brush, juniper, manzanita and yucca palms

S. Bdy of T. 5 N., R. 10 W., S. B. M.

From the cor. of secs. 3, 4, 33 and 34, I run

West on a plank line along the S. bdy. of T. 5 N., R. 10 W.

setting temp. 1/4 sec. and sec. cor., at intervals of 40.00

chains and at 246.10 chs. intersect the temp. cor. of Ips.

4 and 5 N., Rs. 10 and 11 W., set on December 9.

Set a granite stone 20x12x8 ins. 15 ins. in the ground

for cor. of Ips. 4 and 5 N., Rs. 10 and 11 W., marked with

6 notches on each edge and raise a mound of stone 2 ft.

Chains.

S. Bdy. of T. 5 N., R. 10 W., S. B. M.

base, 1 1/2 ft. high S. of cor.

November 27-30 and December 10, 1912

Knowing that a closing corner of secs. 5 and 6, 4 & 5, and 3 & 4 of T. 4 N. will be necessary, I establish cor.

for secs. 31, 32 and 33 only, at T. 5 N., R. 10 W.

From cor. of Tps. 4 and 5 N., Rs. 10 and 11 W., I run

East on a true line along the S. bdy. of sec. 31.

Descend over rocky S.E. slope, through scattering juniper

and pine brush.

Ravine 75 lks. wide, course NE. Ascend.

Top of spur bears NE. and SW. Descend.

Middle of dry wash 300 lks. wide, course N. Ascend.

Top of spur bears N. and S. Descend.

Dry wash 50 lks. wide, course N. Ascend.

Set an iron post 3 ft. long, 1 in. in dia. 2 1/2 ins. in the

ground for 1/4 sec. cor. for sec. 31 only, of T. 5 N. with

brass cap marked

S 31

and raise a mound of stone 2 ft. base, 1 1/2 ft. high N. of cor.

Dry wash 40 lks. wide, course N. Ascend.

Top of low spur bears N. 10° E. Descend.

Dry wash 50 lks. wide, course N. Ascend.

Top of spur bears NE. and SW. Descend.

Set an iron post 3 ft. long, 2 ins. in dia. 2 1/2 ins. in

the ground for cor. of secs. 31 and 32 only, of T. 5 N.

with brass cap marked

T 5 N R 10 W.
S 31 S 32

and raise a mound of stone 2 ft. base, 1 1/2 ft. high W. of cor.

Land, mountainous and broken, drains N. E. and N.

Soil, rocky and sandy, 4th rate.

Scattering pine, juniper and yucca palms.

Chains

South Bdy of T. 5 N., R. 10 W., S. B. M.

East on a true line along the S. bdy of sec. 32.

Descend over broken E. slope through scattering pine,

juniper and yucca palms.

2.00 Dry wash 50 lks. wide, course NW. Ascend.

17.50 Top of spur bears N. and S. Descend.

20.00 Dry wash 50 lks. wide, course NE. Ascend.

25.60 Top of spur bears NE. and SW., descend.

28.90 Dry wash, 10 lks. wide, course NE. Ascend.

31.70 Top of spur bears NE. and SW. Descend.

40.00 Set an iron 3 ft. long, 1 in. dia. 24 ins. in the ground

for 1/4 sec. cor. for sec. 32 only, of T. 5 N. with brass

cap marked

S 32

and raise a mound of stone 2 ft. base, 1 1/2 ft. high N. of

cor.

40.20 Dry wash 10 lks. wide, course N. Ascend.

43.10 Road bears NE. and SW.

52.70 Top of spur bears N. and S. Descend.

79.00 Dry wash 50 lks. wide, course N. Ascend.

80.00 Set an iron post, 3 ft. long, 2 ins. dia. 24 ins. in

the ground, for cor. of secs. 32 and 33, only, of T. 5 N.,

with brass cap marked

T 5 N R 10 W

S 32 S 33

and raise a mound of stone 2 ft. base, 1 1/2 ft. high W.

of cor.

Land, broken and hilly, drains N.

Soil, rocky and gravelly; 4th rate.

Scattering pine, juniper, sage brush and yucca palms.

Chains

South Bdy. of T. 5 N., R. 10 W., S. B.M.

East on a true line along the S. bdy of Sec. 33.

Ascend over broken hills, through scattering pine, juniper

and yucca palms.

21.85

Dry wash, 60 lks. wide, course N. 60° E.

Top of spur bears N. and S. Descend.

40.00

Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the

Ground for $\frac{1}{4}$ sec. cor. for sec. 33 only of T. 5 N., with

brass cap marked

S 33

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high N. of

cor.

49.60

Dry wash 10 lks. wide, course N. Ascend.

Top of spur bears N. and S. Descend.

53.90

Dry wash 20 lks. wide, course N. Ascend.

Top of spur bears N. and S. Descend.

62.80

Dry wash 20 lks. wide, course N. Ascend.

Top of spur bears NE. and SW. Descend.

69.00

Dry wash 10 lks. wide, course N.

Ascend slightly, thence

80.00

The cor. of secs. 3, 4, 33 and 34.

Land, broken and hilly, drains N.

Soil, rocky and sandy; 4th rate.

Scattering pine, juniper and yucca palms.

December 10, 1912.

Subdivisions of T. 4 N., R. 10 W., S. B. M.

443-2

chains

Survey executed by N. J. Burnham, Temporary Transitman,
A. Parker Warner, U. S. Transitman &
A. W. Brown, U. S. Surveyor.

Under instructions dated September 10, 1912 and January

11, 1917.

From the cor. of secs. 4 and 9, I run

N. 0° 21' W. on a true line along the E. bdy. of sec. 4.

Intersect N. bdy of Tp. 95 lks. S. 89° 40' E. of cor. of secs.

91.57

3 and 4, 33 and 34, which now becomes the cor. of secs.

33 and 34.

At the point of intersection I set an iron post 3 ft.

long, 2 ins. dia. 2 1/2 ins. in the ground for closing cor.

of secs. 3 and 4, with brass cap mkd.

T	5	N	R	10	W
S	33	S	34		
<hr/>					
S	4	S	3		
I	4	N	R	10	W

and raise a mound of stone 2 ft. base, 1 1/2 ft. high S. of cor.

December 26, 1912.

N. 0° 21' W. on a true line bet. secs. 4 and 5.

Intersect N. bdy of Tp. 85 lks. E. of cor. of secs. 32

91.89

& 33.

At the point of intersection I set an iron post, 3 ft.

long, 2 ins. dia. 2 1/2 ins. in the ground for closing cor.

of secs. 4 and 5, with brass cap mkd.

T	5	N	R	10	W
S	32	S	33		
<hr/>					
S	4	S	4		
I	4	N	R	10	W

and raise a mound of stone 2 ft. base, 1 1/2 ft. high S. of cor.

Chains

Subdivisions of T. 4 N., R. 10 W., S. B. M.

Land, broken, drains N.

Soil, sandy and rocky; 3rd and 4th rates.

Scattering oak, pine, juniper and yucca palms.

December 28, 1912.

January 10; at 9h. 10m., a.m., l.m.t. I set off 34° 27'

on the lat. arc, 21° 56' S. on the decl. arc; and determine

a meridian with the solar at the cor. of secs. 5, 6, 7

and 8.

Thence I run

N. 0° 31' W. on a true line bet. secs. 5 and 6.

Intersect N. bdy of Tp. 60 lks. E. of cor. of secs. 31

and 32. At the point of intersection I set an iron

post, 3 ft. long, 2 ins. dia. 24 ins. in the ground,

for closing cor. of secs. 5 and 6, with brass cap mkd.

T 5 N	R 10 W
S 31	S 32
O O	

S 6	S 5
T 4 N	R 10 W

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high S.

of cor.

January 10, 1913.

92.20

At the point of intersection, I set a granite stone

of stone.

W., I therefore destroy the markings on the N. edge

This cor. now becomes the cor. of T. 4 N., R. 10 and 11

2 ft. base, 1 1/2 ft. high S. of cor.

marked with 6 notches on each edge; with mound of stone

which is a granite stone 8 x 8 x 6 ins. above ground,

E. of the cor. of T. 4 and 5 N., R. 10 and 11 W.,

sect the N. bdy of Sec. 6, T. 4 N., R. 10 W., at 8.39 chs.

cors. at intervals of 40 chs. and at 160.52 chs. inter-

South on a random line, setting temp. 4 sec. and sec.

of subdivisions of T. 5 N., R. 10 W., I run

Township, described in book of survey and resurvey

from the cor. of secs. 19, 24, 25 and 30, on W. bdy of

Survey made by Guy Hedwige, U. S. Surveyor, and
A. Parker Warner, U. S. Transitman.
Under instructions dated Jan. 14, 1914, Oct. 1, 1914,
January 18, 1915, Jan. 20, 1915.

444-24

West Bdy. of T. 5 N., R. 10 W.

and witnessed as described by Surveyor General.

S 24 on NW. face;

R 11 W S 25 on SW., and

S G E R 47 R 10 W S 30 on SE.

T 5 N S 19 on NE.

square, 24 ins. above ground, filled with cement, marked

19, 24, 25 and 30, which cor. is an iron post, 4 ins.

Intersect W. bdy of T. 5 N. of the cor. of secs.

77.53

West on a random line bet. secs. 19 and 30.

From the cor. of secs. 19, 20, 29 and 30, I run

Survey made by Guy Hedwige, U. S. Surveyor,
Under instructions dated January 20, 1915.

444-23

Chains

Resurvey of the Subdivisions of T. 5 N., R. 10 W.

Chains

West Bdy. of T. 5 N., R. 10 W., S. B. M.

24 x 12 x 6 ins. on surface rock, for cor. of Ts. 5 N. Rs. 10 and 11 W., marked with 6 notches on N., E. and W. edges; and raise a mound of stone 2 ft. base, 1 1/2 ft.

high N. of cor.

Thence I run

North on a true line bet. secs. 31 and 36.

Ascend over rocky ground, through scrub live oak.

13.20

Dry wash, 2 chs. wide, course W. Ascend.

15.40

Top of spur, bears E. and W. Descend.

32.15

Foot of descent; enter narrow dry wash.

40.13

Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the

ground, for 1/4 sec. cor., with brass cap marked

S 36 1/4 S 31

and raise a mound of stone 2 ft. base, 1 1/2 ft. high W. of

cor.

44.90

Leave wash, bears N. 60° E.

Ascend.

56.45

Top of spur, bears E. and W.

Descend.

80.10

Dry wash, 15 lks. wide, course N. 60° E.

Ascend.

80.26

Set a granite stone 18 x 12 x 9 ins. 12 ins. in the

ground, for cor. of secs. 25, 30, 31 and 36, marked with

1 notch on S. and 5 notches on N. edge; and raise a

mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor.

Land, hilly, drains N. and NE.

Soil, gravelly, rocky, 3d and 4th rates.

Timber, juniper and scrub live oak.

Undergrowth, same.

Chains

West Bdy. of T. 5 N., R. 10 W., S. B. M.

North on a true line bet. secs. 25 and 30.

Ascend through jumper.

5.55 Top of ascent.

Descend.

33.90 Foot of descent.

Enter plowed land, bears E. and W. (R.D. Sander's field)

40.13 Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the

ground for $\frac{1}{2}$ sec. cor. with brass cap marked

S 25 $\frac{1}{2}$ S 30

As this cor. falls in a cultivated field, I do not dig

pits nor raise a mound.

50.00 Leave plowed land, bears E. and W.

Ascend.

55.00 Top of hill, bears E. and W.

Descend.

61.50 Wide arroyo, course E.

Ascend.

80.26 The cor. of secs. 19, 24, 25 and 30.

Feb. 8, 1915.

Resurvey and Survey of the S.Bdy. of T. 5 N., R. 11 W.

Chains 446.1

Survey made by John L. Warboys, U. S. Surveyor,

Under Special Instructions dated June 25, 1926.

And Assignment Instructions dated August 14, 1926.

From the cor. of T. 5 N., Rs. 10 and 11 W.

West on a random line along N. bdy of Sec. 6, T. 4 N.,

R. 10 W.

The old cor. of T. 4 N., Rs. 10 and 11 W.

The old cor. of T. 5 N., Rs. 10 and 11 W., is a granite

stone 12 x 6 ins., 10 ins. above ground, marked (+)

on top, with 6 grooves on N., E. and W. edges, and

witnessed by a mound of stone N. of cor.

Alongside and S. is an iron post, 2 ins. dia. 10 ins.

above ground, with a brass cap marked

COUNTY SURVEYORS

T 5 N

36 31

T 4 N

MONUMENT

Alongside and S. of granite stone,

Set an iron post, 3 ft. long, 3 ins. dia. 28 ins. in

the ground, for cor. of T. 5 N., Rs. 10 and 11 W., with

brass cap marked

T 5 N

R 11 W R 10 W

S 36 S 31

S 6

T 4 N R 10 W

1926

From which

A jumper 6 ins. dia. bears N. 49 7/8° E. 45 lks. dist.

marked T 5 N R 10 W S 31 BT.

A jumper 4 ins. dia. bears N. 58° W., 51 lks. dist.

marked T 5 N R 11 W S 36 BT.

Thence

West on a true line along S. bdy of sec. 36 and N. bdy of sec. 6, T. 4 N., R 10 W.

Over rolling hills, through scattering jumper. Ascend

Resurvey and Survey of the S. bdy. of T. 5 N., R. 11 W.

Chains

8.10 Spur, slopes N. Descend steep W. slope 15 ft. to rocky E. slope 165 ft. to

8.45 The old cor. of T. 4 N., Rs. 10 and 11 W., which is a granite stone, 8 x 6 ins. 6 ins. above ground, marked with 6 notches on E. and W. edges.

Alongside and S. is an iron post, 2 ins. dia. 10 ins. above ground, with a brass cap marked

COUNTY SURVEYORS
T 5 N
1 6
T 4 N
MONUMENT

Alongside and S. of granite stone,

Set an iron post, 3 ft. long, 3 ins. dia. 28 ins. in the ground, for cor. of T. 4 N., Rs. 10 and 11 W., with brass cap marked

T 5 N R 11 W
S 36
S 1 S 6
R 11 W R 10 W
T 4 N
1926

from which

A juniper 4 ins. dia. bears S. 45° E. 45 lks. dist.,

marked T 4 N R 10 W S 6 BL.

A live oak 5 ins. dia. bears S. 49½° W. 54 lks. dist.

marked T 4 N R 11 W S 1 BL.

Thence

West on a true line along S. bdy of sec. 36.

Over rough, mountainous land, through scattering pinyon

and live oak.

Descend steep W. slope 110 ft. to

4.20 Ravine, course N. Ascend steep, rocky N. 70° E. slope

355 ft. to

16.70 Spur slopes N. 10° E. Descend steep NW. slope 50 ft. to

19.30 Ravine, course N. Ascend steep N. 60° E. slope 75 ft. to

21.40 Spur, slopes N. 20° E. Descend steep NW. slope 85 ft. to

23.90 Ravine, course N. 10° W. Ascend NE. slope 115 ft. to

25.00 Small spur, slopes N. Descend W. slope 45 ft. to

Resurvey and Survey of the S. bdy of T. 5 N., R. 11 W.

chains

25.70 Havné, course N. 20° E. Ascend steep E. slope 45 ft. to
 26.90 Spur, slopes N. Descend N. 60° W. slope 25 ft. to
 27.70 Havné, course N. 20° E. Ascend very steep N. 60° E. slope
 170 ft. to
 A point 40.00 chs. in departure from the SE. cor. of Tp.
 Set an iron post, 3 ft. long, 1 in. dia. 27 ins. in the
 ground, for $\frac{1}{2}$ sec. cor. of sec. 36 only, with brass cap

marked

$\frac{1}{2}$ S 36

1926

from which

A juniper 5 ins. dia. bears N. 32 3/4° E. 58 lks.
 dist. marked $\frac{1}{2}$ S 36 B T.

A juniper 6 ins. dia. bears N. 73 3/4° W. 36 lks.
 dist. marked $\frac{1}{2}$ S 36 B T.

Ascend 40 ft. to

33.10 Spur slopes N. Descend N. 60° W. slope 165 ft. to

38.30 Havné, course N. 20° W. Ascend NE. slope 210 ft. to

39.40 Small spur, slopes N. 20° W. Descend NW. slope 40 ft. to

42.10 Havné, course NE. Ascend E. slope 90 ft. to

44.90 Spur slopes N. 10° W. Descend NW. slope 50 ft. to

47.30 Havné, course NE. Ascend E. slope 205 ft. to

54.30 Spur, slopes N. Descend W. slope 155 ft. to

59.80 Enter bottom of canyon, bears N. and S.

60.90 Leave canyon bottom, bears N. 20° E. and S. Ascend N. 60°

E., slope 230 ft. to

71.55 A point 80.00 chs. in departure from SE. cor. of Tp.

Set an iron post, 3 ft. long, 2 ins. dia. 6 ins. in the

ground to solid rock, marked with a cross (x) and

supported by a mound of stone, for cor. of sec. 35

and 36 only, with brass cap marked

T 5 N R 11 W
 S 35 S 36

1926

Spur, slopes N. Descend W. slope 30 ft. to	32.10
Wash, course N. 20° W. Ascend NE. slope 55 ft. to	26.30
Wash, course N.	22.30
Wash, course N. Descend 10 ft. to	20.50
Wash, course N. Ascend 20 ft. to	17.00
Wash, 15 lks. wide, course N. Descend 20 ft. to	10.90
Dim road, bears N. and S. 20° E.	10.60
Wash, course N. 10° W. Descend 15 ft. to	6.70
Havine, course N. Ascend 5 ft. to	1.30
Spur, slopes N. Descend 15 ft. to	0.45

Over rolling and very broken general N. slope through scattering juniper and desert brush. Ascend 2 ft. to N. 89° 52' W. on a true line along S. bdy of sec. 24. Thence

T 5 N S 19 on NE.
 S G F R 47 R 10 W S 30 on SE.
 R 11 W S 25 on SW. and
 S 24 on NW. faces, with traces of pits N. and S. of cor.

Letters cast in iron)
 24 ins. above ground, in a mound of stone, marked (with a cast iron post (filled with concrete), 4 ins. square, The cor. of secs. 19, 24, 25 and 30 on E. bdy of Tp. 18

Resurvey of a portion of subdivisions T. 5 N., R. 11 W.

Land, rough mountains.
 Soil, rock, gravel, sand.
 Timber, scattering piñon and live oak.
 Undergrowth, scattering juniper and desert brush.
 S. Fork of triple piñon, 12 ins. dia. bears N. 30 E. 42 lks. dist. marked T 5 N R 11 W. S 36 BT.
 A piñon 14 ins. dia. bears N. 50 1/2° W. 70 lks. dist., marked T 5 N R 11 W S 35 BT.

From which

Chains

Resurvey and Survey of the S. Bdy of T. 5 N., R. 11 W.

Resurvey of a portion of the subdivisions T. 5 N., R. 11 W.

Chains

34.60	Ravine, course N.
36.80	Wash, course N.
39.80	Wash, course N. 20° W.
40.15	Mid point of S. bdy of sec. 24, and also of N. bdy of sec. 23, hereinafter described, Set an iron post, 3 ft. long, 1 in. dia. 26 ins. in the ground, for § sec. cor. of secs. 24 and 25, with brass cap marked
	§ 24 § 25 1926
	From which
	A juniper 4 ins. dia. bears N. 55° W. 20 lks. dist. marked § 24 BT.
	A juniper 8 ins. dia. bears S. 32° W. 50 lks. dist. marked § 25 BT.
40.79	The old § sec. cor. which is a juniper stake 3 x 2 ins. 18 ins. above ground, in an old mound of stone, marked § S on N. and SGR on S. face, witnessed by a mound of stone, N. of cor. As this cor. no longer remains a § sec. cor., I destroy the markings § on the stake. Alongside and S. of stake, on top of spur, sloping N. Set an iron post 3 ft. long, 1 in. dia. 22 ins. in the ground, supported by a mound of stone, for angle point, with brass cap marked
	AP T 5 N R 11 W § 24 § 25 1926
	Thence
1. 20	Wash, course N. 20° E. Ascend 15 ft. to Descend 15 ft. to
2.00	Spur, slopes N. Descend 80 ft. to
3.30	Ravine, course N. Ascend 90 ft. to
9.60	Spur, slopes NW. Descend 45 ft. to
14.90	Small ravine, course S. Ascend 20 ft. to

Resurvey of a Portion of the Subdivisions of T 5 N., R. 11 W.


Chains

Spur, slopes S. 20° E. Descend 15 ft. to	17.30
Wash, course S. 20° W. Descend, 20 ft. to	18.00
Wash, course N. 70° W. Descend 60 ft. to	22.20
Wash, course S. W. Descend 40 ft. to	28.50
Large wash, course N. W.	33.70
Wash, course N. W. Ascend 20 ft. to	36.90
Spur, slopes N. 30° W. Descend 20 ft. to	38.70
Having, course N. 20° W. Ascend 2 ft. to	39.40
The old closing cor. of secs. 23 and 24, which is a gran-	39.50

ite stone, 14 x 12 ins., 12 ins. above ground marked
 C C on N. face, with 1 notch on E. and 2 notches on S.
 edges, and witnessed by a mound of stone N. of cor.
 I find, later, that this cor. also serves for the closing
 cor. of secs. 25 and 26.

Alongside and S. of old stone, set an iron post, 3 ft.
 long, 2 ins. dia. 24 ins. in the ground, supported by
 a mound of stone, for closing cor. of secs. 23 and 24,
 and also for closing cor. of secs. 25 and 26, with brass

cap marked



from which

A juniper 8 ins. dia. bears S. 30 E. 77 lks. dist.
 marked T 5 N R 11 W S 25 C C BL. (New BL)

A juniper 5 ins. dia. bears N. 48° W. 23 lks. dist.
 marked T 5 N R 11 W S 23 C C BL. (New BL)

land, rough and broken, general N. slopes.

Soil, rock, gravel, sand.

Timber, scattering juniper.

Undergrowth, small juniper, greasewood, yuccas, desert brush.

Survey of Subdivisions of T. 5 N., R. 11 W.

Chains

From the cor. of secs. 35 and 36, on S. bdy of Tp.,
 hereinafter described.

N. 0° 01' W. bet. secs. 35 and 36.

Over mountainous land through scattering timber and
 brush. Descend N. slope 60 ft. to

3.00	Havine, course NE. Ascend 30 ft. to
8.80	Spur, slopes N. 60° E. Descend steeply 115 ft. to
12.70	Havine, course E. Ascend steeply 45 ft. to
14.30	Spur, slopes N. 60° E. Descend 105 ft. to
17.60	Havine, course N. 60° E. Ascend 25 ft. to
21.90	Spur, slopes N. 60° E. Descend 70 ft. to
23.20	Havine, course E. Ascend S. slope 145 ft. to
29.00	Spur, slopes N. 30° E. Descend N. 20° W. slope 135 ft. to
39.30	Havine, course NE. Ascend 15 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked

†
 S 35 S 36
 1926

From which

A Juniper 5 ins. dia. bears N. 55° E. 42 lks. dist.
 marked $\frac{1}{4}$ S 36 BL.

A Juniper 6 ins. dia. bears S. 44° W. 31 lks. dist.
 marked $\frac{1}{4}$ S 35 BL.

Ascend SE. slope 50 ft. to

Spur, slopes N. 60° E. Descend NE. slope 275 ft. to

Drain, course E. Ascend SE. slope 55 ft. to

Spur, slopes NE. Descend N. slope 40 ft. to

Set an iron post, 3 ft. long, 2 ins. dia. 12 ins. in

the ground to solid rock, marked with a cross (x),

supported by a mound of stone for cor. of secs. 25, 26,

35 and 36, with brass cap marked

T 5 N R 11 W
 S 26 S 25
 S 35 S 36
 1926

Thence S. 89° 41' W. on a true line bet. secs. 25 and 36. Over rolling and broken hills, through scattering juniper an desert brush. Ascend 30 ft. to

T 5 N
R 11 W R 10 W
S 25 S 30
S 36 S 31
1926

Alongside and N. of old stone, set an iron post, 3 ft. long, 2 ins. dia. 12 ins. in the ground to solid rock, marked with a cross (x) supported by a mound of stone, for cor. of secs. 25, 30, 31 and 36, on E. bdy of Tp., with brass cap marked

East on a random line bet. secs. 25 and 36. Set temp. 7 sec. cor. Fall 1/4 lks. S. of the old cor. of secs. 25, 30, 31 and 36 on E. bdy of Tp. which is a granite stone 12 x 9 ins. 10 ins. above ground, marked with 5 grooves on N. and 1 groove on top, witnessed by a mound of stone W. of cor.

40.00
80.20

From which
A live oak 9 ins. dia. bears N. 43 1/2° E. 89 lks. dist. marked T 5 N R 11 W S 25 BT.
A pinyon, 10 ins. dia. bears S. 15 1/2° E. 145 lks. dist. marked T 5 N R 11 W S 36 BT.
A live oak 6 ins. dia. bears S. 24 1/2° W. 126 lks. dist. marked T 5 N R 11 W S 35 BT.
A live oak 7 ins. dia. bears N. 69° W. 56 lks. dist. marked T 5 N R 11 W S 26 BT.
Land, rough mountains.
Soil, rock, gravel, sand.
Timber, scattering pinyon, live oak, yuccas.
Undergrowth, small juniper, manzanita, greasewood, desert brush.

Chains

Survey of Subdivisions of T. 5 N., R. 11 W.