

DEPARTMENT OF THE INTERIOR
GENERAL LAND OFFICE

Public Survey Office,
San Francisco, California.

September 22, 1930.

I, FRANK E. BARKER, do hereby certify that the annexed transcript of field notes of the North Boundary of T. 4 N., R. 10 W., S. B. M. as surveyed by Burnham and Warner, in 1912: the portion of West Boundary of T. 5 N., R. 10 W., S. B. M. as surveyed by Guy Redwine, in 1915, and Sections 25 and 36, T. 5 N., R. 11 W., S. B. M. as surveyed John L. Warboys, in 1926, is a true and literal exemplification of said field notes, as the same remain on file and of record in this office.

R.11W.

R.10W.

FRANK E. BARKER (Sgd.)

Office Cadastral Engineer for
California.

T.5N.

23	24	19	20			
26	25	30	29			
35	36	31	32	33	34	35
2	1	6	5	4	3	2
11	12	7	8	9	10	11

T.4N.

T. 4 N., R. 10 W., S. B. M.

Chains 448-7

Survey executed by N. J. Burnham, Temporary Transitman,
and A. Parker Warner, U. S. Transitman.

Under instructions dated Sept. 10, 1912.

West Boundary

North bet. secs. 1 and 6.

* * * * *

92.75 To a point due west of the cor. of secs. 3, 4, 33 and
34, on the N. Bdy. of T. 4 N., R. 10 W., where I set
temp. cor. for Tps. 4 and 5 N., Rs. 10 and 11 W.

Dec. 9, 1912.

Resurvey of Portion of N. Bdy. of T. 4 N., R. 10 W.,
S. B. M.

November 27; at 8h 30m. A.M., l.m.t. I set off $34^{\circ} 28'$
on the lat. arc; $21^{\circ} 07'$ S. on the decl. arc, and deter-
mine a meridian with the solar at the cor. of secs. 2, 3,
34, and 35, which is a pine post 3 ins. square, 12 ins.
above ground, firmly set, marked and witnessed as des-
cribed by the Surveyor General.

Thence I retrace

West on a random line bet. secs. 3 and 34.

40.00 After diligent search, fail to find any evidence of old
 $\frac{1}{4}$ sec. cor.

80.23 Fall 47 lks. S. of cor. of secs. 3, 4, 33 and 34, which
is a granite stone 12x12x8 ins. above ground, firmly set,
marked with 3 notches on E. and W. edges.

Traces of old charred stake found.

No bearings available.

S. $89^{\circ} 40'$ E. on a true line bet. secs. 3 and 34.

Over level desert through scattering sage brush, juniper
and manzanita brush.

Resurvey of Portion of N.bdy of T.4 N., R.10 W., S.B.M.

Chains

- 10.20 Middle of dry wash, 2.50 lks. wide, course N. Ascend.
 19.60 Top of spur bears N. and S. Descend.
 25.70 Dry wash 20 lks. wide, course N. Ascend.
 40.00 Dry wash, 20 lks. wide, course N.
 40.11½ Set an iron post 3 ft. long, 1 in. in dia. 24 ins. in the ground for ¼ sec. cor. with brass cap marked

$$\begin{array}{r} S \ 34 \\ \hline S \ 3 \end{array}$$

Dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist. and raise a mound of earth 3½ ft. base, 1½ ft. high N. of cor.

November 27; at this ¼ sec. cor. I set off 21° 10' S. on the decl. arc, and at 11h. 48m. l.m.t. observe the sun on the meridian; the resulting lat. is 34° 28'

- 41.40 Road from Pallett's Ranch to Little Rock bears NW. & S. E.
 64.90 Road from West's Ranch to Little Rock bears N. 40° W. and S. 40° E. Ascend.
 73.00 Top of spur bears N. and S. Descend.
 80.23 The cor. of secs. 2, 3, 34 and 35.
 Land, level and rolling, drains NW.
 Soil, sandy and rocky, 4th rate.
 Scattering sage brush, juniper, manzanita and yucca palms.

S. Bdy of T. 5 N., R. 10 W., S. B. M.

From the cor. of secs. 3, 4, 33 and 34, I run West on a blank line along the S. bdy. of T. 5 N., R.10 W. setting temp. ¼ sec. and sec. cors, at intervals of 40.00 chains and at 246.10 chs. intersect the temp. cor. of Tps. 4 and 5 N., Rs. 10 and 11 W., set on December 9.
 Set a granite stone 20x12x8 ins. 15 ins. in the ground for cor. of Tps. 4 and 5 N., Rs. 10 and 11 W., marked with 6 notches on each edge and raise a mound of stone 2 ft.

S. Bdy. of T. 5 N., R. 10 W., S. B. M.

Chains.

base, $1\frac{1}{2}$ ft. high S. of cor.

November 27-30 and December 10, 1912

Knowing that a closing corner of secs. 5 and 6, 4 & 5, and 3 & 4 of T. 4 N. will be necessary, I establish cors. for secs. 31, 32 and 33 only, of T. 5 N., R. 10 W.

From cor. of Tps. 4 and 5 N., Rs. 10 and 11 W., I run East on a true line along the S. bdy. of sec. 31.

Descend over rocky S.E. slope, through scattering juniper and pine brush.

5.00 Ravine 75 lks. wide, course NE. Ascend.
7.00 Top of spur bears NE. and SW. Descend.
19.00 Middle of dry wash 300 lks. wide, course N. Ascend.
25.60 Top of spur bears N. and S. Descend.
34.20 Dry wash 50 lks. wide, course N. Ascend.
46.10 Set an iron post 3 ft. long, 1 in. in dia. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. for sec. 31 only, of T. 5 N. with brass cap marked

S 31
1

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

76.80 Dry wash 40 lks. wide, course N. Ascend.
80.90 Top of low spur bears N. 10° E. Descend.
83.80 Dry wash 50 lks. wide, course N. Ascend.
85.80 Top of spur bears NE. and SW. Descend.
86.10 Set an iron post 3 ft. long, 2 ins. in dia. 24 ins. in the ground for cor. of secs. 31 and 32 only, of T. 5 N. with brass cap marked

T 5 N R 10 W.
S 31 S 32

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land, mountainous and broken, drains N. E. and N.

Soil, rocky and sandy, 4th rate.

Scattering pine, juniper and yucca palms.

South Bdy of T. 5 N., R. 10 W., S. B. M.

Chains

East on a true line along the S. bdy of sec. 32.

Descend over broken E. slope through scattering pine,
juniper and yucca palms.

- 2.00 Dry wash 30 lks. wide, course NW. Ascend.
17.50 Top of spur bears N. and S. Descend.
20.00 Dry wash 30 lks. wide, course NE. Ascend.
25.60 Top of spur bears NE. and SW., descend.
28.90 Dry wash, 10 lks. wide, course NE. Ascend.
31.70 Top of spur bears NE. and SW. Descend.
40.00 Set an iron 3 ft. long, 1 in. dia. 24 ins. in the ground
for $\frac{1}{4}$ sec. cor. for sec. 32 only, of T. 5 N. with brass
cap marked

S 32
 $\frac{1}{4}$

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high N. of
cor.

- 40.20 Dry wash 10 lks. wide, course N. Ascend.
43.10 Road bears NE. and SW.
52.70 Top of spur bears N. and S. Descend.
79.00 Dry wash 50 lks. wide, course N. Ascend.
80.00 Set an iron post, 3 ft. long, 2 ins. dia. 24 ins. in
the ground, for cor. of secs. 32 and 33, only, of T. 5 N.,
with brass cap marked

T 5 N R 10 W
S 32 S 33

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W.
of cor.

Land, broken and hilly, drains N.

Soil, rocky and gravelly; 4th rate.

Scattering pine, juniper, sage brush and yucca palms.

South Bdy. of T. 5 N., R. 10 W., S. B.M.

Chains

East on a true line along the S.bdy of Sec. 33.

Ascend over broken hills, through scattering pine, juniper and yucca palms.

21.85 Dry wash, 60 lks. wide, course N. 60° E.

27.90 Top of spur bears N. and S. Descend.

40.00 Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the ground for $\frac{1}{4}$ sec. cor. for sec. 33 only of T. 5 N., with brass cap marked

S 33
 $\frac{1}{4}$

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of cor.

49.60 Dry wash 10 lks. wide, course N. Ascend.

53.90 Top of spur bears N. and S. Descend.

60.00 Dry wash 20 lks. wide, course N. Ascend.

62.80 Top of spur bears N. and S. Descend.

64.80 Dry wash 20 lks. wide, course N. Ascend.

69.00 Top of spur bears NE. and SW. Descend.

77.70 Dry wash 10 lks. wide, course N.

Ascend slightly, thence

80.00 The cor. of secs. 3, 4, 33 and 34.

Land, broken and hilly, drains N.

Soil, rocky and sandy; 4th rate.

Scattering pine, juniper and yucca palms.

December 10, 1912.

Subdivisions of T. 4 N., R. 10 W., S. B. M.

Chains 443-2

Survey executed by N. J. Burnham, Temporary Transitman,
A. Parker Warner, U. S. Transitman &
A. W. Brown, U. S. Surveyor.

Under instructions dated September 10, 1912 and January
11, 1917.

From the cor. of secs. 4 and 9, I run

N. 0° 2' W. on a true line along the E. bdy. of sec. 4.

91.57

Intersect N. bdy of Tp. 95 lks. S. 89° 40' E. of cor. of secs.
3 and 4, 33 and 34, which now becomes the cor. of secs.
33 and 34.

At the point of intersection I set an iron post 3 ft.
long, 2 ins. dia. 24 ins. in the ground for closing cor.
of secs. 3 and 4, with brass cap mkd.

T 5 N	R 10 W
S 33	S 34
O C	

S 4	S 3
T 4 N	R 10 W

and raise a mound of stone 2 ft. base, 1½ ft. high S. of cor.

December 26, 1912.

N. 0° 2' W. on a true line bet. secs. 4 and 5.

X
91.89

Intersect N. bdy of Tp. 85 lks. E. of cor. of secs. 32
& 33.

At the point of intersection I set an iron post, 3 ft.
long, 2 ins. dia. 24 ins. in the ground for closing cor.
of secs. 4 and 5, with brass cap mkd.

T 5 N	R 10 W
S 32	S 33
O C	

S 5	S 4
T 4 N	R 10 W

and raise a mound of stone 2 ft. base, 1½ ft. high S. of cor.

Subdivisions of T. 4 N., R. 10 W., S. B. M.

Chains

Land, broken, drains N.

Soil, sandy and rocky; 3rd and 4th rates.

Scattering oak, pine, juniper and yucca palms.

December 28, 1912.

January 10; at 9h. 10m., a.m., l.m.t. I set off $34^{\circ} 27'$ on the lat. arc., $21^{\circ} 56'$ S. on the decl. arc; and determine a meridian with the solar at the cor. of secs. 5, 6, 7 and 8.

Thence I run

N. $0^{\circ} 3'$ W. on a true line bet. secs. 5 and 6.

92.20

Intersect N. bdy of Tp. 60 lks. E. of cor. of secs. 31 and 32. At the point of intersection I set an iron post, 3 ft. long, 2 ins. dia. 24 ins. in the ground, for closing cor. of secs. 5 and 6, with brass cap mkd.

T 5 N	R 10 W
S 31	S 32
	0 0
<hr/>	
	S 6 S 5
T 4 N	R 10 W

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.

January 10, 1913.

Resurvey of the Subdivisions of T. 5 N., R. 10 W.

Chains 444-23

Survey made by Guy Redwine, U. S. Surveyor,
Under instructions dated January 20, 1915.

From the cor. of secs. 19, 20, 29 and 30, I run
West on a random line bet. secs. 19 and 30.

77.53 Intersect W. bdy of Tp. 36 lks. N. of the cor. of secs.
19, 24, 25 and 30, which cor. is an iron post, 4 ins.
square, 24 ins. above ground, filled with cement, marked

T 5 N S 19 on NE.

S G F R 47 R 10 W S 30 on SE.

R 11 W S 25 on SW., and

S 24 on NW. face;

and witnessed as described by Surveyor General.

West Bdy. of T. 5 N., R. 10 W.

444-24

Survey made by Guy Redwine, U. S. Surveyor, and
A. Parker Warner, U. S. Transitman.
Under instructions dated Jan. 14, 1914, Oct. 1, 1914,
January 18, 1915, Jan. 20, 1915.

From the cor. of secs. 19, 24, 25 and 30, on W. bdy of
Township, described in book of survey and resurvey
of Subdivisions of T. 5 N., R. 10 W., I run
South on a random line, setting temp. $\frac{1}{4}$ sec. and sec.
cors. at intervals of 40 chs. and at 160.52 chs. inter-
sect the N. bdy of Sec. 6, T. 4 N., R. 10 W., at 8.39 chs.
E. of the cor. of Ts. 4 and 5 N., Rs. 10 and 11 W.,
which is a granite stone 8 x 8 x 6 ins. above ground,
marked with 6 notches on each edge; with mound of stone
2 ft. base, $1\frac{1}{2}$ ft. high S. of cor.
This cor. now becomes the cor. of Ts. 4 N., Rs. 10 and 11
W., I therefore destroy the markings on the N. edge
of stone.

At the point of intersection, I set a granite stone

West Bdy. of T. 5 N., R. 10 W., S. B. M.

Chains

24 x 12 x 6 ins. on surface rock, for cor. of Ts. 5 N.
Rs. 10 and 11 W., marked with 6 notches on N., E. and
W. edges; and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft.
high N. of cor.

Thence I run

North on a true line bet. secs. 31 and 36.

Ascend over rocky ground, through scrub live oak.

13.20 Dry wash, 2 chs. wide, course W. Ascend.

15.40 Top of spur, bears E. and W. Descend.

32.15 Foot of descent; enter narrow dry wash.

40.13 Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., with brass cap marked

S 36 $\frac{1}{4}$ S 31

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high W. of
cor.

44.90 Leave wash, bears N. 60° E.

Ascend.

56.45 Top of spur, bears E. and W.

Descend.

80.10 Dry wash, 15 lks. wide, course N. 60° E.

Ascend.

80.26 Set a granite stone 18 x 12 x 9 ins. 12 ins. in the
ground, for cor. of secs. 25, 30, 31 and 36, marked with
1 notch on S. and 5 notches on N. edge; and raise a
mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high W. of cor.

Land, hilly, drains N. and NE.

Soil, gravelly, rocky, 3d and 4th rates.

Timber, juniper and scrub live oak.

Undergrowth, same.

West Bdy. of T. 5 N., R. 10 W., S. B. M.

Chains

North on a true line bet. secs. 25 and 30.

Ascend through juniper.

5.55 Top of ascent.

Descend.

33.90 Foot of descent.

Enter plowed land, bears E. and W. (R.D.Sander's field)

40.13 Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in the
ground for $\frac{1}{4}$ sec. cor. with brass cap marked

S 25 $\frac{1}{4}$ S 30

As this cor. falls in a cultivated field, I do not dig
pits nor raise a mound.

50.00 Leave plowed land, bears E. and W.

Ascend.

55.00 Top of hill, bears E. and W.

Descend.

61.50 Wide arroyo, course E.

Ascend.

80.26 The cor. of secs. 19, 24, 25 and 30.

Feb. 8, 1915.

Resurvey and Survey of the S.Bdy. of T. 5 N., R. 11 W.

Chains 446,1

Survey made by John L. Warboys, U. S. Surveyor,
Under Special Instructions dated June 25, 1926.
And Assignment Instructions dated August 14, 1926.

From the cor. of T. 5 N., Rs. 10 and 11 W.
West on a random line along N. bdy of Sec. 6, T. 4 N.,
R. 10 W.

8.45 The old cor. of T. 4 N., Rs. 10 and 11 W.

The old cor. of T. 5 N., Rs. 10 and 11 W., is a granite
stone 12 x 6 ins., 10 ins. above ground, marked (+)
on top, with 6 grooves on N., E. and W. edges, and
witnessed by a mound of stone N. of cor.
Alongside and S. is an iron post, 2 ins. dia. 10 ins.
above ground, with a brass cap marked

COUNTY SURVEYORS

T 5 N
36 31

T 4 N
MONUMENT

Alongside and S. of granite stone,
Set an iron post, 3 ft. long, 3 ins. dia. 28 ins. in
the ground, for cor. of T. 5 N., Rs. 10 and 11 W., with
brass cap marked

T 5 N

R 11 W R 10 W
S 36 S 31

S 6
T 4 N R 10 W
1926

From which

A juniper 6 ins. dia. bears N. $49\frac{1}{2}^{\circ}$ E. 45 lks. dist.
marked T 5 N R 10 W S 31 BT.

A juniper 4 ins. dia. bears N. 58° W., 51 lks. dist.
marked T 5 N R 11 W S 36 BT.

Thence

West on a true line along S.bdy of sec. 36 and N. bdy
of sec. 6, T. 4 N., R 10 W.

Over rolling hills, through scattering juniper. Ascend

Resurvey and Survey of the S. bdy. of T.5 N., R.11 W.

Chains

rocky E. slope 165 ft. to

8.10 Spur, slopes N. Descend steep W. slope 15 ft. to

8.45 The old cor. of T. 4 N., Rs. 10 and 11 W., which is a granite stone, 8 x 6 ins. 6 ins. above ground, marked with 6 notches on E. and W. edges.

Alongside and S. is an iron post, 2 ins. dia. 10 ins. above ground, with a brass cap marked

COUNTY SURVEYORS

$$\begin{array}{r} T\ 5\ N \\ \hline 1\ 6 \\ T\ 4\ N \\ \hline \end{array}$$

 MONUMENT

Alongside and S. of granite stone,

Set an iron post, 3 ft. long, 3 ins. dia. 28 ins. in the ground, for cor. of T. 4 N., Rs. 10 and 11 W., with brass cap marked

$$\begin{array}{r} T\ 5\ N\ R\ 11\ W \\ \hline S\ 36 \\ \hline S\ 1\ S\ 6 \\ R\ 11\ W\ R\ 10\ W \\ T\ 4\ N \\ 1926 \end{array}$$

From which

A juniper 4 ins. dia. bears S. 45° E. 45 Lks. dist., marked T 4 N R 10 W S 6 BT.

A live oak 5 ins. dia. bears S. 49½° W. 54 lks. dist. marked T 4 N R 11 W S 1 BT.

Thence

West on a true line along S. bdy of sec. 36.

Over rough, mountainous land, through scattering pinyon and live oak.

Descend steep W. slope 110 ft. to

4.20 Ravine, course N. Ascend steep, rocky N. 70° E. slope 355 ft. to

16.70 Spur slopes N. 10° E. Descend steep NW. slope 50 ft. to

19.30 Ravine, course N. Ascend steep N. 60° E. slope 75 ft. to

21.40 Spur, slopes N. 20° E. Descend steep NW. slope 85 ft. to

23.90 Ravine, course N. 10° W. Ascend NE. slope 115 ft. to

25.00 Small spur, slopes N. Descend W. slope 45 ft. to

Resurvey and Survey of the S. bdy of T. 5 N., R. 11 W.

Chains

- 25.70 Ravine, course N. 20° E. Ascend steep E. slope 45 ft. to
 26.90 Spur, slopes N. Descend N. 60° W. slope 25 ft. to
 27.70 Ravine, course N. 20° E. Ascend very steep N. 60° E. slope
 170 ft. to
 31.55 A point 40.00 chs. in departure from the SE. cor. of Tp.
 Set an iron post, 3 ft. long, 1 in. dia. 27 ins. in the
 ground, for $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap
 marked

$\frac{1}{4}$ S 36

1926

From which

A juniper 5 ins. dia. bears N. 32 3/4° E. 58 lks.
 dist. marked $\frac{1}{4}$ S 36 B T.

A juniper 6 ins. dia. bears N. 73 3/4° W. 36 lks.
 dist. marked $\frac{1}{4}$ S 36 B T.

Ascend 40 ft. to

- 33.10 Spur slopes N. Descend N. 60° W. slope 165 ft. to
 38.30 Ravine, course N. 20° W. Ascend NE. slope 210 ft. to
 39.40 Small spur, slopes N. 20° W. Descend NW. slope 40 ft. to
 42.10 Ravine, course NE. Ascend E. slope 90 ft. to
 44.90 Spur slopes N. 10° W. Descend NW. slope 50 ft. to
 47.30 Ravine, course NE. Ascend E. slope 205 ft. to
 54.30 Spur, slopes N. Descend W. slope 155 ft. to
 59.80 Enter bottom of canyon, bears N. and S.
 60.90 Leave canyon bottom, bears N. 20° E. and S. Ascend N. 60°
 E., slope 230 ft. to
 71.55 A point 80.00 chs. in departure from SE. cor. of Tp.
 Set an iron post, 3 ft. long, 2 ins. dia. 6 ins. in the
 ground to solid rock, marked with a cross (x) and
 supported by a mound of stone, for cor. of secs. 35
 and 36 only, with brass cap marked

T 5 N R 11 W
 S 35 S 36

1926

Resurvey and Survey of the S. Bdy of T. 5 N., R. 11 W.

Chains

From which

S. Fork of triple pinyon, 12 ins. dia. bears
N. 3° E. 42 lks. dist. marked T 5 N R 11 W. S 36 BT.

A pinyon 14 ins. dia. bears N. 50½° W. 70 lks. dist.,
marked T 5 N R 11 W S 35 BT.

Land, rough mountains.

Soil, rock, gravel, sand.

Timber, scattering pinyon and live oak.

Undergrowth, scattering juniper and desert brush.

Resurvey of a portion of Subdivisions T. 5 N., R. 11 W.

The cor. of secs. 19, 24, 25 and 30 on E. bdy of Tp. is
a cast iron post (filled with concrete), 4 ins. square,
24 ins. above ground, in a mound of stone, marked (with
letters cast in iron)

T 5 N S 19 on NE.
S G F R 47 R 10 W S 30 on SE.
R 11 W S 25 on SW. and
S 24 on NW. faces, with traces of pits N. and S. of cor.

Thence

N. 89° 52' W. on a true line along S. bdy of sec. 24.

Over rolling and very broken general N. slope through
scattering juniper and desert brush. Ascend 2 ft. to

0.45	Spur, slopes N. Descend 15 ft. to
1.30	Ravine, course N. Ascend 5 ft. to
6.70	Wash, course N. 10° W. Descend 15 ft. to
10.60	Dim road, bears N. and S. 20° E.
10.90	Wash, 15 lks. wide, course N. Descend 20 ft. to
17.00	Wash, course N. Ascend 20 ft. to
20.50	Wash, course N. Descend 10 ft. to
22.30	Wash, course N.
26.30	Wash, course N. 20° W. Ascend NE. slope 55 ft. to
32.10	Spur, slopes N. Descend W. slope 30 ft. to

Resurvey of a Portion of the Subdivisions T. 5 N., R. 11 W.

Chains

34.60 Ravine, course N.
 36.80 Wash, course N.
 39.80 Wash, course N. 20° W.
 40.15 Mid point of S. bdy of sec. 24, and also of N. bdy of

sec. 23, hereinafter described,

Set an iron post, 3 ft. long, 1 in. dia. 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of secs. 24 and 25, with brass cap marked

$\frac{1}{4}$ $\frac{S \ 24}{S \ 25}$
 From which 1926

A juniper 4 ins. dia. bears N. 55° W. 20 lks. dist. marked $\frac{1}{4}$ S 24 BT.

A juniper 8 ins. dia. bears S. 32° W. 50 lks. dist. marked $\frac{1}{4}$ S 25 BT.

40.79 The old $\frac{1}{4}$ sec. cor. which is a juniper stake 3 x 2 ins. 18 ins. above ground, in an old mound of stone, marked $\frac{1}{4}$ S on N. and SGFR on S. face, witnessed by a mound of stone, N. of cor. As this cor. no longer remains a $\frac{1}{4}$ sec. cor., I destroy the markings $\frac{1}{4}$ on the stake. Alongside and S. of stake, on top of spur, sloping N. Set an iron post 3 ft. long, 1 in. dia. 22 ins. in the ground, supported by a mound of stone, for angle point, with brass cap marked

AP
 T 5 N R 11 W
 $\frac{S \ 24}{1926}$

Thence

N. 89° 58' W. on a true line along S. bdy of sec. 24.

Descend 15 ft. to

1. 20 Wash, course N. 20° E. Ascend 15 ft. to
 2.00 Spur, slopes N. Descend 80 ft. to
 3.30 Ravine, course N. Ascend 90 ft. to
 9.60 Spur, slopes NW. Descend 45 ft. to
 14.90 Small ravine, course S. Ascend 20 ft. to

Resurvey of a Portion of the Subdivisions of T 5 N., R. 11 W.

Chains

17.30 Spur, slopes S. 20° E. Descend 15 ft. to
 18.00 Wash, course S. 20° W. Descend, 20 ft. to
 22.20 Wash, course N. 70° W. Descend 60 ft. to
 28.80 Wash, course S. W. Descend 40 ft. to
 33.70 Large wash, course N. W.
 36.90 Wash, course N. W. Ascend 20 ft. to
 38.70 Spur, slopes N. 30° W. Descend 20 ft. to
 39.40 Ravine, course N. 20° W. Ascend 2 ft. to
 39.50 The old closing cor. of secs. 23 and 24, which is a granite stone, 14 x 12 ins., 12 ins. above ground marked C C on N. face, with 1 notch on E. and 2 notches on S. edges, and witnessed by a mound of stone N. of cor. I find, later, that this cor. also serves for the closing cor. of secs. 25 and 26.
 Alongside and S. of old stone, set an iron post, 3 ft. long, 2 ins. dia. 24 ins. in the ground, supported by a mound of stone, for closing cor. of secs. 23 and 24, and also for closing cor. of secs. 25 and 26, with brass cap marked

	CC	
T 5 N		R 11 W
S 23		S 24
S 26		S 25
	CC	
	1926	

From which

A juniper 8 ins. dia. bears S. 30° E. 77 lks. dist. marked T 5 N R 11 W S 25 C C BT. (New BT)

A juniper 5 ins. dia. bears N. 48° W. 23 lks. dist. marked T 5 N R 11 W S 23 CC BT. (New BT)

Land, rough and broken, general N. slope.

Soil, rock, gravel, sand.

Timber, scattering juniper.

Undergrowth, small juniper, greasewood, yuccas, desert brush.

Survey of Subdivisions of T. 5 N., R. 11 W.

Chains

From the cor. of secs. 35 and 36, on S. bdy of Tp.,
hereinbefore described.

N. 0° 01' W. bet. secs. 35 and 36.

Over mountainous land through scattering timber and
brush. Descend N. slope 60 ft. to

3.00 Ravine, course NE. Ascend 30 ft. to
8.80 Spur, slopes N. 60° E. Descend steeply 115 ft. to
12.70 Ravine, course E. Ascend steeply 45 ft. to
14.30 Spur, slopes N. 60° E. Descend 105 ft. to
17.60 Ravine, course N. 60° E. Ascend 25 ft. to
21.90 Spur, slopes N. 60° E. Descend 70 ft. to
23.20 Ravine, course E. Ascend S. slope 145 ft. to
29.00 Spur, slopes N. 30° E. Descend N. 20° W. slope 135 ft. to
39.30 Ravine, course NE. Ascend 15 ft. to
40.00 Set an iron post, 3 ft. long, 1 in. dia. 24 ins. in
the ground, for $\frac{1}{4}$ sec. cor. with brass cap marked

S 35 $\frac{1}{4}$ S 36
1926

From which

A juniper 5 ins. dia. bears N. 55 $\frac{1}{2}$ ° E. 42 lks. dist.
marked $\frac{1}{4}$ S 36 BT.

A juniper 6 ins. dia. bears S. 44 $\frac{1}{2}$ ° W. 31 lks. dist.
marked $\frac{1}{4}$ S 35 BT.

Ascend SE. slope 50 ft. to

45.70 Spur, slopes N. 60° E. Descend NE. slope 275 ft. to
68.30 Drain, course E. Ascend SE. slope 55 ft. to
75.10 Spur, slopes NE. Descend N. slope 40 ft. to
80.00 Set an iron post, 3 ft. long, 2 ins. dia. 12 ins. in
the ground to solid rock, marked with a cross (x),
supported by a mound of stone for cor. of secs. 25, 26,
35 and 36, with brass cap marked

T 5 N R 11 W
S 26 S 25
S 35 S 36
1926

Survey of Subdivisions of T. 5 N., R. 11 W.

Chains

From which

A live oak 9 ins. dia. bears N. $43\frac{1}{2}^{\circ}$ E. 89 lks. dist.
marked T 5 N R 11 W S 25 BT.

A pinyon, 10 ins. dia. bears S. $15\frac{1}{4}^{\circ}$ E. 145 lks. dist.
marked T 5 N R 11 W S 36 BT.

A live oak 6 ins. dia. bears S. $24\frac{1}{4}^{\circ}$ W. 126 lks. dist.
marked T 5 N R 11 W S 35 BT.

A live oak 7 ins. dia. bears N. 69° W. 56 lks. dist.
marked T 5 N R 11 W S 26 BT.

Land, rough mountains.

Soil, rock, gravel, sand.

Timber, scattering pinyon, live oak, yuccas.

Undergrowth, small juniper, manzanita, greasewood, desert brush.

East on a random line bet. secs. 25 and 36.

40.00 Set temp. $\frac{1}{4}$ sec. cor.

80.20 Fall 44 lks. S. of the old cor. of secs. 25, 30, 31 and
36 on E. bdy of Tp. which is a granite stone 12 x 9 ins.
10 ins. above ground, marked with 5 grooves on N. and 1
groove on top, witnessed by a mound of stone W. of
cor.

Alongside and N. of old stone, set an iron post, 3 ft.
long, 2 ins. dia. 12 ins. in the ground to solid rock,
marked with a cross (x) supported by a mound of stone,
for cor. of secs. 25, 30, 31 and 36, on E. bdy of Tp.,
with brass cap marked

T 5 N	
R 11 W	R 10 W
S 25	S 30
S 36	S 31
1926	

Thence

S. $89^{\circ} 41'$ W. on a true line bet. secs. 25 and 36.

Over rolling and broken hills, through scattering
juniper an desert brush. Ascend 30 ft. to

Survey of Subdivisions of T. 5 N., R. 11 W.

Chains

1.80 Low saddle, bears N. and S. Descend 25 ft. to
 11.00 Drain, course NW. Ascend 100 ft. to
 17.30 Spur, slopes N. Descend steep W. slope 75 ft. to
 20.80 Enter canyon bottom, bears NE. and SW.
 Ascend 40 ft. to
 30.10 Leave canyon bottom, bears N. 20° E. and S. 20° W.
 Ascend 80 ft. to
 33.00 Spur, slopes N. 30° E. Descend 110 ft. to
 37.40 Enter canyon bottom, bears N. 10° E. and S. 10° W.
 Ascend 10 ft. to
 38.50 Leave canyon bottom, bears N. 10° E. and S. 10° W.
 Ascend 25 ft. to
 39.50 Rocky spur, slopes S. Descend 5 ft. to
 40.10 Set an iron post, 3 ft. long, 1 in. dia. 18 ins. in the
 ground, to solid rock, supported by a mound of stone,
 for $\frac{1}{4}$ sec. cor. with brass cap marked

$$\begin{array}{r} \frac{1}{4} \quad \text{S } 25 \\ \hline \text{S } 36 \\ 1926 \end{array}$$

From which

A live oak 10 ins. dia. bears N. 73½° W. 130 lks.
 dist. marked $\frac{1}{4}$ S 25 B1.

A juniper, 6 ins. dia. bears S. 39° E. 25 lks.
 dist. marked $\frac{1}{4}$ S 36 BT.

A juniper post, 4 ins. square, 18 ins. above ground
 in a mound of stone, marked $\frac{1}{4}$ S A J bears N. 19½° E.
 38 lks. dist. (Local surveyor's cor.)

Descend 5 ft. to

40.60 Ravine, course S. 60° E. Ascend 120 ft. to
 45.60 Spur, slopes N. Descend 96 ft. to
 48.80 Ravine, course N. 10° W. Ascend 140 ft. to
 55.90 Spur, slopes SE. Descend 10 ft. to
 65.70 Drain, course SE. Ascend 140 ft. to
 77.90 Spur, slopes N. Descend 20 ft. to

Survey of Subdivisions of T. 5 N., R. 11 W.

Chains

80.20 The cor. of secs. 25, 26, 35 and 36.
Land, rolling and broken hills.
Soil, rock, gravel, sand.
Timber, scattering juniper, yuccas.
Undergrowth, small juniper, greasewood, desert brush.

N. 0° 01' W. bet. secs. 25 and 26.

Over rolling and broken hills, through scattering timber
and brush. Descend 115 ft. to

7.40 Wash, course W. Ascend 30 ft. to
10.20 Spur, slopes SW. Descend NW. slope 100 ft. to
19.30 Drain, course W. Ascend 10 ft. to
24.70 Spur, slopes S. 30° W. Descend 65 ft. to
31.40 Drain, course N. 60° E. Ascend 5 ft. to
34.20 Spur, slopes NW. Descend N. slope 90 ft. to
40.00 Set an iron post, 3 ft. long, 1 in. dia. 26 ins. in the
ground for $\frac{1}{4}$ sec. cor., with brass cap marked

S 26 $\frac{1}{4}$ S 25
1926

From which

A juniper, 6 ins. dia. bears S. 34 $\frac{1}{2}$ ° E. 27 lks. dist.
marked $\frac{1}{4}$ S 25 BT.

A live oak 5 ins. dia. bears N. 57 $\frac{1}{2}$ ° W. 33 lks. dist.
marked $\frac{1}{4}$ S 26 BT.

Descend 45 ft. to

43.50 Ravine, course E. Ascend S. slope 80 ft. to
50.20 Spur, slopes S. 60° E. Descend 10 ft. to
51.80 Ravine, course S. 60° E. Ascend 95 ft. to
55.10 Steep spur, slopes S. 60° E. Descend 370 ft. to
67.00 Enter ravine, course N. 10° W. Descend 25 ft. to
69.50 Leave ravine, course NE. Ascend 20 ft. to

Survey of Subdivisions of T. 5 N., R. 11 E.

Chains

70.80 Small spur, slopes E. Descend 35 ft. to
73.90 Same ravine, course N. 60° W. Ascend 10 ft. to
75.80 Low spur, slopes NW. Descend 70 ft. to
80.96 The closing cor. of secs. 23 and 24, which also becomes
the closing cor. of secs. 25 and 26. hereinbefore des-
cribed.

Land, rolling and broken hills.

Soil, rock, gravel, sand.

Timber, scattering juniper, live oak, yuccas.

Undergrowth, small juniper, desert brush.
