

West Boundary of T. 1 S., R. 18 W., S. B. M.

363-10

Survey made by James R. Glover, Deputy Surveyor,
Contract dated July 2d, 1896.
Survey executed October 14 - 16, 1896.

South between sections 13 and 18, ascending.

80.00 Set a granite stone 18 x 14 x 12 ins. 12 ins. in the ground,
for corner to sections 18, 19, 13 and 24, marked with 3
notches on N. and S. edges, and raised a mound of stone
2 feet base, 1½ feet high W. of corner. Pits impracticable.
From which

A live oak 9 ins. diam. bears N. 10° E. 92 lks. dist.
marked T 1 S R 18 W S 18 BT.

A live oak 9 ins. diam. bears S. 89° E. 112 lks. dist.
marked T 1 S R 18 W S 19 BT.

No other trees within limits.

This corner is about 200 feet above canon.

October 16, 1896 at 7h.30m. A.M., l.m.t. I set off 04' N.
on the lat arc, 9° 13' S. on the decl. arc and determine a
true meridian with the solar.

South between sections 19 and 24. Ascend.

28.00 Top of ridge bears N.W. and S.E. and descend.

40.00 Set a sandstone 22 x 18 x 14 ins. 16 ins. in the ground
for ¼ section corner, marked ¼ on W. face and raised a
mound of stone 2 feet base, 1½ feet high W. of corner.
Pits impracticable.

61.00 Cross gulch, 8 lks. wide, course S. 20° W. and ascend.

75.00 Top of spur trends west and descend.

78.00 Cross gulch, 6 lks. wide, course west and ascend.

80.00 Set a sandstone 24 x 18 x 8 ins. 18 ins. in the ground
for 24, 25, 19 and 30, marked with 2 notches on S. and 4
notches on N. edges, and raised a mound of stone, 2 feet
base, 1½ feet high W. of corner.
Pits impracticable.

Land, broken and mountainous.

West Boundary of Township 1 S., R. 18 W., S. B. M.

Soil, 3d rate.

Timber, oak.

Dense undergrowth of chaparral.

South between sections 25 and 30; ascend.

20.00 Top of ridge bears E. and W. and descend.

38.50 Cross gulch 8 lks. wide, course N.W. and ascend.

40.00 Set a sandstone 20 x 12 x 8 ins. 15 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on W. face, and raised a mound of stone 2 feet base, $1\frac{1}{2}$ feet high W. of corner.

Pits impracticable.

45.00 Top of spur, trends west and descend.

74.50 Cross same canon, 50 lks. wide, course S. 80° E. and ascend.

80.00 Set a sycamore post, 4 feet long, 4 ins. square, with marked stone 24 ins. in the ground for corner to sections

30, 31, 25 and 36, marked T 1 S 30 on NE.

R 18 W S 31 on SE. R 19 W. S 36 on SW. and S.

25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, and raised a mound of stone 2 feet base, $1\frac{1}{2}$ feet high W. of corner.

Pits impracticable.

On north side of gulch, 8.00 chs. east of canon.

Land, broken and mountainous.

Soil, 3d rate.

Timber, oak.

Dense undergrowth same and chaparral.

South between sections 31 and 36, ascending.

24.00 Top of spur trends S. 80° E. 100 feet above corner & descend.

29.75 Enter flat bears NW. and SE. 100 feet below spur.

30.00 Bandy's house bears East, 175 lks. dist.

34.86 Intersect Rancho Topanga Malibu Sequit, at a point N. 79° 07' W. 5.25 chs. dist. from corner T.M.No.9, which is a

West Boundary of Township 1 S., R. 15 W., S. E. M.

sycamore post 4 ins. square, 12 ins. above ground, marked and witnessed as described by the Surveyor General, and set a sycamore post 4 feet long, 4 ins. square, 24 ins. in the ground, for closing corner to fractional sections 31 and 36, marked

C.C.T. 1 S. on the N. R 15 W S 31 on E. and

R 19 W S 36 on W. faces, with 6 notches on N.E. and W. faces and raised a mound of stone 2 feet base, 1½ feet high N. of corner.

Pits impracticable.

Land, broken and mountainous.

Soil, 2d and 3d rate.

Timber, oak.

Dense undergrowth, chaparral.

Oct. 16, 1896.

363-12

Survey by James R. Glover, Deputy Surveyor,
Contract dated September 7, 1896.
Survey executed September 25, - October 8, 1896.

Resurvey of Rancho Topanga Malibu Sequit.

September 30: At 7h.0m. a.m., l.m.t. I set off 34° 02' W. on the lat arc; 3° 06' S. on the decl. arc and determine a true meridian at corner T.M.No.9.

From corner T.M.No.9, which is a sycamore tree, marked and witnessed as described by the Surveyor General.

Thence I run

S. 86½° E. on a random line and at

85.01 I arrive at a point 12 lks. north of corner T.M. No. 8.

Thence I run

N. 86° 25' W. on a true line.

Ascend over very rough and broken land, covered with dense chaparral.

40.00 Set a sandstone 14 x 12 x 12 ins. 9 ins. in the ground marked ½ M.T.M. on side of stone facing ranch and raised

Resurvey of Rancho Topanga Malibu Sequit, T 1 S., Rs. 18 & 19 W., SBM.

a mound of stone 2 feet base, $1\frac{1}{2}$ feet high, in ranch at right angle to line.

Pits impracticable.

42.00 Top of ridge bears N. and S. +320 feet above canon and descend.

80.00 Set a sandstone 12 x 12 x 12 ins. 8 ins. in the ground, marked L.M.T.M. on side of stone facing ranch and raised a mound of stone 2 feet base, $1\frac{1}{2}$ feet high in ranch, at right angle to line.

Pits impracticable.

85.01 To corner T.M. No. 9, to place of beginning in bottom of Zuma Canon, the bed is 2.00 chs. wide, course S.E.

Land, broken and mountainous.

Soil, 3d rate. Timber, oak.

Dense undergrowth of chaparral.

From corner T.M.No. 10 (in T.1 S., R.19 W.) which is an oak 14 ins. diam. marked and witnessed as described by the Surveyor General, I run

S. 80° E. on a random line and at

150.70 I arrive at a point N. 10° E. 232 lks. dist. from corner T.M.No.9.

Thence

N. 79° 07' W. on a true line. Ascend.

40.00 Set a sandstone 24 x 10 x 6 ins. 18 ins. in the ground marked $\frac{1}{2}$ M.T.M. on side of stone facing ranch, and raised a mound of stone 2 feet base, $1\frac{1}{2}$ feet high, in ranch at right angle to line.

Pits impracticable.

47.00 Top of ridge bears N.W. and S.E. and descend.

62.00 Cross canon 12 lks. wide, course S.E. and ascend.

75.00 Top of ridge bears N. and S. and descend.

80.00 Set a sandstone 14 x 12 x 10 ins. 9 ins. in the ground.

Resurvey of Rancho Malibu Sequit in T. 1 S., R. 18 & 19 W., SBM.

marked I.M.T.M. on side of stone, facing ranch and raised a mound of stone, 2 feet base, $1\frac{1}{2}$ feet high, in ranch at right angle to line.

Pits impracticable.

110.30 Cross canon 20 lks. wide, course S. 40° W. and ascend.

120.00 Set a sandstone 20 x 14 x 12 ins. 15 ins. in the ground marked $\frac{1}{2}$ M.T.M. on side of stone facing ranch and raised a mound of stone 2 feet base, $1\frac{1}{2}$ feet high in ranch at right angle to line.

Pits impracticable.

150.72 To corner T.M.No.10, on east side of Canada Las Trancas, 100 lks. wide, course south.

Land, broken and mountainous.

Soil, 3d rate.

Timber, oak and sycamore.

Dense undergrowth, chaparral.

September 30, 1896.

Subdivisions T. 1 S., R. 19 W., S. B. M.

363-17

Survey made by James R. Glover, Deputy Surveyor,
Contract dated Nov. 7, 1896.
Survey executed December 7 - 17, 1896.

See Page 15

East on a random line between Sections 13 and 24.

80.40 Intersect E. boundary of Township 24 lks. N. of corner to sections 13, 18, 19 and 24, which is a sandstone set firmly in the ground, marked with 3 notches on N. and S. edges, with a stone mound 2 feet base, 1½ feet high W. of corner.

December 8, 1896, at 8h. 0m. a.m., l.m.t. I set off 34° 04' N. on the lat. arc; 22° 46' S. on the decl. arc and determine a true meridian with the solar.

See Page 16

0° 01' E. on a true line between sections 23 and 24.

80.00 Set a sandstone 24 x 12 x 10 ins. 18 ins. in the ground for corner to sections 23, 24, 25 and 26, marked with 1 notch on E. and 2 notches on S. edges, and raised a stone mound, 2 feet high, 3½ feet base W. of corner. Pits impracticable.

East on a random line between sections 24 and 25.

40.00 Set temporary ¼ section corner.

79.89 Intersect E. boundary of Township 18 lks. S. of corner to sections 19, 24, 25 and 30, which is a sandstone set firmly in the ground, marked with 4 notches on N. and 2 notches on S. edges, with a stone mound 2 feet base, 1½ feet high W. of corner.

Thence I run

S. 89° 52' W. on a true line between sections 24 and 25. Descend through dense chaparral.

12.04 Zuma Canon, 50 lks. wide, 150 feet below section corner, course S., ascend.

35.40 Top of spur 250 feet above Zuma Canon, bears NE. and S.W.

Subdivisions T. 1 S., R. 19 W., S. B. M.

Descend.

2636.37
39.94½ Set a sandstone 30 x 14 x 6 ins. 22 ins. in the ground for
¼ section corner, marked ¼ on N. face and raised a stone
mound 2 feet base, 1½ feet high _____ of corner.

Pits impracticable.

46.06 Gulch 10 lks. wide, 155 feet below top of spur, course
N. 45° E.

Ascend.

75.20 Top of ridge 550 feet above gulch, bears N. 10° W. and
S. 10° E.

Descend.

79.89 The corner to sections 23, 24, 25 and 26, 60 feet below
top of ridge.

Land, mountainous.

Soil, 3d rate.

Scattering oak timber.

Dense undergrowth of chaparral.

Mountainous land, 79.89 chs.

S. 0° 01' E. on a true line between sections 25 and 26.

Ascend through dense brush.

17.00 Top of ridge, 200 feet above section corner bears N. 70° E.
and S. 70° W.

Descend.

38.09 Gulch 10 lks. wide, 550 feet below top of ridge, course
S. 45° W., ascend.

40.00 Set a sandstone 30 x 12 x 10 ins. 22 ins. in the ground
for ¼ section corner, marked ¼ on W. face and raised a
stone mound 2 feet base, 1½ feet high W. of corner.

Pits impracticable.

44.00 Top of spur 70 feet above gulch bears E. and W.

Descend.

51.60 Gulch 15 lks. wide, 200 feet below top of spur, course

Subdivisions T. 1 S., R. 19 W., S. B. M.

- S.W., ascend.
- 61.50 Top of spur 300 feet above gulch, bears E. and W.
Descend.
- 69.80 Gulch 8 links wide, 200 feet below top of spur, course
W., ascend.
- 74.25 Top of spur 200 feet above gulch, bears E. and W.
Descend.
- 77.90 Gulch, 8 lks. wide, 124 feet below top of ridge, course
W., ascend.
- 80.00 Set a sandstone 20 x 14 x 4 ins. 15 ins. in the ground
for corner to sections 25, 26, 35 and 36, marked with
1 notch on S. and E. edges, and raised a stone mound,
2 feet base, 1½ feet high W. of corner.
Pits impracticable.
Corner set 100 feet above gulch.
Land, mountainous.
Soil, 3d rate.
Scattering oak timber.
Dense undergrowth of chaparral.
Mountainous land, 80.00 chs.
-
- East on a random line between sections 25 and 36.
- 40.00 Set temporary ¼ section corner.
- 80.12 Intersect E. boundary of Township 18 lks. N. of corner
to sections 25, 30, 31 and 36, which is sycamore post set
firmly in the ground, marked
- T 1 S 30 on N.E.
R 18 W S 31 on S.E.
R 19 W S 36 on S.W. and
S 25 on N.W. faces,
with 5 notches on N. and 1 notch on S. edges, with a stone
mound, 2 feet base, 1½ feet high W. of corner.

Subdivisions T. 1 S., R. 19 W., S. B. M.

Thence I run

N. 89° 52' W. on a true line between sections 25 and 36.
Ascend through dense chaparral.

- 37.00 Top of spur bears N.W. and S.E., descend.
- 40.06 Set a sandstone 18 x 12 x 8 ins. 12 ins. in the ground for $\frac{1}{4}$ section corner, marked $\frac{1}{4}$ on N. face and raised a stone mound covered with earth, 4 feet base, 2 $\frac{1}{2}$ feet high N. of corner.
- 44.35 Canon, 20 lks. wide, 150 feet below top of spur, course S. 70° W., ascend.
- 56.00 Top of ridge 200 feet above canon, bears N. and S.
Descend.
- 60.25 Gulch 8 lks. wide, 75 feet below top of ridge, course S., ascend.
- 67.00 Top of spur 70 feet above gulch, bears N. 80° E. and S. 80° W.
Descend.
- 80.12 The corner to sections 25, 26, 35 and 36.
Land, mountainous.
Soil, 3d rate.
Timber of oak.
Dense undergrowth of chaparral.
-
- S. 00° 01' E. on a true line between sections 35 and 36;
ascend.
- 2.20 Top of spur, 50 feet above section corner bears E. and W., descend.
- 8.19 Gulch 10 lks. wide, 150 feet below top of spur, course S. 80° W.
Ascend.
- 15.00 Top of spur 175 feet above gulch bears N. 75° E. and S. 75° W., descend.

Subdivisions T. 1 S., R. 19 W., S. B. M.

19.39 Intersect boundary line of Rancho Topanga Malibu Sequit 6.85 chs. N. 79° 07' W. from 1 mile corner, which is a sandstone 12 x 10 x 5 ins. above the ground, previously set by me, under instructions of September 7, 1896, and set a sandstone 30 x 8 x 6 ins. 22 ins. in the ground, for closing corner to sections 35 and 36, marked C. C. on N. with 1 groove on E. and 5 grooves on W. faces, and raised a mound of stone 2 feet base, 1½ feet high N. of corner.

Pits impracticable.

Land mountainous.

Soil, 3d rate.

No timber.

Dense undergrowth of chaparral.

Mountainous land, 19.39 chs.

December 8, 1896.

172.21

Survey made by H. Washington, Deputy Surveyor, Contract dated October 4th, 1852. Survey executed March 8th - 11th, 1853.

South Bdy. T.1 S., R.18 & 19 W., S.B.M.

West 6th Mile on S. boundary of T. 1 S., R. 18 W.

50.00 Set 6th Mile (Charred stake and charred post) post of sycamors, corner to S. 31 T. 1 S., R. 18 W. S 36 T.1 S. R.19 W. S 6 T. 2 S., R. 18 W. S. 1 T. 2 S. 19 W. from which

the center of 4 pits bears N. 45° E. 9 lks. N. 45° W. 9 lks. S. 45° E. 9 lks. S. 45° W. 9 lks.

Note: The East boundary of T.1 S., R.19 W. could not be run from this corner, owing to abrupt hills and mountains, with accuracy.