

Surveys and surveys in Section 5, T. 4 N., R. 14 W., were executed with Bull & Bull transit No. 21849, and Gurley transit No. 38123. For description and tests of instrumental equipment see surveys in T. 4 N., R. 15 W., executed under this group.

T. 4 N., R. 14 W. was originally surveyed by W. H. Norway in 1879. Surveys executed by Los Angeles County in 1925 present a re-orientation of original corners then extent, with brass capped iron posts, 2 ins., in diameter, firmly set in concrete base. These monuments are substantial and permanent, and are adopted with only slight modification in the present survey.

Preliminary to survey all lines of the governing survey were retraced and the positions thoroughly verified. The true line results are given herein. Azimuth determination is by projection or polaris observation recorded in T. 5 N., R. 14 W., maintained by successive angulation throughout the survey.

The observed magnetic declination is 15° E.

The surveys herein noted were undertaken to provide a basis for disposal of public land, under Act of June 1, 1938, 52 Stat. 609; U.S.C. 682a.

Dependent Resurvey of a Portion of the Subdivision

T. 4 N., R. 14 W.

The cor. of secs. 4, 5, 8 and 9 is marked by an iron post monument, 2 ins. diam., 6 ins. above ground, firmly set in concrete base, 6 ins. diam., additionally mark brass cap to read

COUNTY SURVEYOR
T. 4 N.
S 5 8 4
R 14 W 8 8 5 9
US BLM 1947
RE 2177
MONUMENT

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 36' E., bet. sec. 4 and 5.

Over mountainous land, through scattered undergrowth.

Desc. 125 ft. over NW slope.

Draw, course SW. Ang. 100 ft. over S. slope.

Short spur, slopes E. Along E. slope.

Point for S. 1/16 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, with a granite stone 8 x 5 x 4 ins., marked + buried alongside, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision

T. 4 N., R. 14 W.

Chains

S 7/16

S 5 | S 4

1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Gully, course SE. Asc. 115 ft. over S. slope.

Spur, slopes SE. Desc. 35 ft. over NE. slope.

Gully, course E., turning to SE. Asc. 70 ft. over S. slope.

Shoulder of spur, extending E.

Head of ravine, course S. 80° E. Asc. 95 ft. over SE. slope.

39.94

The 7 sec. cor. of secs. 4 and 5, marked with an iron post monument, 2 ins. diam., 6 ins. above ground, firmly set in concrete base, 6 ins. diam. Alongside is the original corner stake, a weathered jumper post, 2 ins. square, 16 ins. long.

Additionally mark brass cap to read

COUNTY SURVEYOR

W. H. N.

S 5 | S 4

7 COR

US BLM 1947

MONUMENT

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

N. 0° 40' E., beginning new measurement.

Asc. 20 ft. over SE. slope.

Top of ascent, and across ridge-spur, extending to SW.

1.00

Desc. 140 ft. over NW. slope.

2.50

Draw, course SW. Asc. 85 ft. over S. slope.

9.50

Spur, slopes SW. Desc. 30 ft. over W. slope.

13.20

Gully, course S. 70° W. Asc. 75 ft. over SW. slope.

16.00

Point for N. 1/16 sec. cor. of secs. 4 and 5, at proper-
flonate measurement.

20.57

Set an iron post, 3 ft. long, 1 in. diam., 2 1/2 ins. in the ground, to bedrock, and in a mound of stone 4 ft. base, to top, with brass cap mkd.

N 7/16

S 5 | S 4

1947

Dependent Resurvey of a Portion of the Subdivision

7.4 N., R. 14 W.

Chains

41.02	The cor. of sec. 4, 5, 32 and 33, on N. bdy. of the T.P., marked by an iron post, mkd. and witnessed as described in the 1947 resurvey, executed under this group.
	Land, rolling mountains.
	Soll, rocky, 3rd. rate.
	Scattered cedar, Greenwood, sage and grass.
38.60	Draw, course W., Asc. 25 ft.
35.70	Small spur, slopes N. 80° W. Desc. 25 ft.
32.70	Gully, course W. Asc. 40 ft.
30.80	Gully, course N. 70° W.
27.50	Short spur, slopes W. Desc. 50 ft. over NW. slope.
24.00	Change of slope to W.
	Continue ascent 50 ft. over SW. slope.

From the cor. of sec. 4, 5, 8 and 9.

N. 89° 45' W., bet. sec. 5 and 8.

Over mountainous land, through scattered undergrowth.

Desc. 175 ft. over NW slope.

Draw, course SW. Asc. 60 ft. over SE. slope.

Short spur, slopes S. Desc. 25 ft.

Gully, course S. Asc. 100 ft. over E. slope.

Spur, slopes S. 20° E. Along S. slope.

Desc. 45 ft. over W. slope.

Having, course S. Asc. 70 ft. over E. slope.

Point for E. 1/16 sec. cor., of sec. 5 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, with brass cap mkd.

E 76 S 5 8

1947

Bury a granite stone, 6 x 4 x 3 ins., marked + alongside iron post.

Continue ascent 100 ft. over E. slope, along spur from W., here turning to the S.

Change of slope to SE., and continue ascent.

Along S. slope.

Head of gully, course SE.

Dependent Highway of a Portion of the Subdivision

E. 4 N., R. 14 W.

Chains

Asc. 115 ft. over E. slope.

Small spur, slopes SE., change of slope to SE, continue ascent.

Ridge, bears NE. and SW. Desc. 90 ft. over NW. slope.

The 7 sec. cor., of sec. 5 and 8, marked by an iron post monument, 2 ins. diam., 8 ins. above ground, firmly set in concrete base. Additionally mark brass cap to read

COUNTY SURVEYOR

1947

R 14 W S 5

S 8

1/2 COR

US BLM 1947

MONUMENT

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

N. 89° 11' W., beginning new measurement.

Along N. slope.

Change of slope to NW.; desc. 60 ft.

Change of slope to SW.; desc. 220 ft.

Having, course N. 70° W., turning to W. Continue descent

Point for W. 1/16 sec. cor., of sec. 5 and 8.

Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in the ground, with brass cap mkd.

W 1/2 S 5

S 8

1947

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

Continue descent 10 ft.

Draw, course S. 20° W. Over S. slope.

Gully, course SE. Asc. 125 ft. over NE. slope.

Ridge, bears NE. and SW. Desc. 75 ft. over NW. slope.

The cor. of Secs. 5, 6, 7 and 8, marked by an iron post. 2 ins. diam., in concrete form 6 ins. diam., 8 ins. above ground, firmly set, and in a flat mound of stone to top. Additionally mark brass cap to read

COUNTY SURVEYOR

1947

S 6 S 5

R 14 W S 8

US BLM 1947

RE 2177

MONUMENT

Dependent Survey of a Portion of the Subdivision

P. 4N., R. 14 W.

Chain

From the corner, an iron post, 2 ins. diam., firmly set, flush in concrete base, 6 ins. diam., marking the original witness corner monument, bears N. 88° 15' W., 65.5 lks. dist. (Record: West, 65 lks. distant.)

From this witness corner monument, the original bearing tree

A white oak, 14 ins. diam., bears S. 49° W., 53.4 lks. dist., the old disk is partially covered by overgrowth, markings are visible but not now legible. (Record: S. 51 1/2° W., 51 lks. dist.)

Land, mountainous.

Soil, rocky, brd. rate.

Scattered cedar and oak; grove brush, sage and cañt.

N. 20 1/2° W., bet. sec. 5 and 6.

Over mountainous land, through scattered undergrowth.

Desc. 100 ft. over N. slope.

Gully, course NW. Asc. 75 ft. over SW. slope.

Spur, drops sharply to NW. Desc. 210 ft. over changing N. to N. slope.

Ravine, course NW., Asc. 70 ft. over S. slope.

Point of sharp, narrow spur, slopes N. 20° W., from S. 60° E.

Point for S. 1/16 sec. cor., of sec. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., 3 1/4 ins. in the ground, with brass cap mkd.

S 1/4

S 6 | S 5

1947

Bury a granite stone, 8 x 6 x 5 ins., marked + alongside iron post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Desc. 80 ft. over N. slope.

Foot of slope, and enter wash, in Tick Canyon, course SW.

Leave wash. Asc. 35 ft. over gradual slope of bench land.

Road, unimproved, bears irregularly NE. and SW., following Tick Canyon.

Telephone line, bears N. 80° E. and S. 80° W., in Tick Canyon.

Asc. 150 ft. over an increasing SW. slope.

Spur, slopes SE. Desc. 25 ft. over E. slope.

38.30

31.50

29.10

28.00

25.60

20.34

20.00

16.50

7.10

4.00

Dependent Survey of a Portion of the Subdivision

T. 4 N., R. 14 W.

Chains

40.68

The 1/2 sec. cor., marked by an iron post, 2 ins. diam., 12 ins. above ground, firmly set in concrete base, 6 ins. diam., and in a half mound of stone, 3 ft. base, to top, additionally mark brass cap to read

COUNTY SURVEYOR
J. H. N.
SEC 61 SEC 5
R. 14 W. 1/2 COR
US BLM 1947
MONUMENT

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 20 1/2 W., beginning new measurement.

Over E. slopes; desc. 10 ft.

Having, course S. 30° E., draining from the N. Asc. 95 ft. over SW. slope.

Short spur, slopes SW. Over W. slope.

Gully, course SW. Asc. 115 ft. over SW. slope.

Head of Gully, course S. 70° W.

Point for N. 1/16 sec. cor., of sec. 5 and 6, at proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., 3 1/2 ins. in the ground, with granite stone 8 x 6 x 3 ins., marked + de- posted alongside, with brass cap mkd.

N 1/2

S 6 / S 5

1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor. Continue ascent 80 ft. over broken SW. slope.

Gully, course SW.

Gully, course SW.

Having, course S. 70° W.

Spur, slopes S. 70° W. Desc. 90 ft. over NW slope.

Gully, course SW. Asc. 50 ft. over S. slope.

The cor. of sec. 5, 6, 31 and 32, on N. bdy. of the T. P., marked by an iron post, mkd. and witnessed as described in the 1947 survey, executed under this group.

Land, broken mountains. Soil, rocky, grad. rate. Scattered granite brush, sage and caati.

40.71

39.20

36.00

34.50

31.00

25.90

Chains

Subdivision of Sec. 5, T.4 N., R.14 W.

From the 7/8 sec. cor., of Sec. 5 and 8.

N.0°12'W., on the N. and S. center line of Sec. 5.

Over mountainous land, through scattered undergrowth, desc. 150 ft. over N. slope.

Having, course N.70°W. Along broken W. slope; asc. 35 ft.


Spur, slopes N.70°W. Desc. 150 ft.

Having, course W. Desc. 25 ft. over NW. slope, in canyon, course SW.

20.15

Point for center S.1/16 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor.

Desc. 10 ft. over flat NW slope.

Wash, 20 lbs, wide, course SW., in canyon.

23.70

Asc. 170 ft. over SE. slope.

27.20

Gully, course SE.

Change of slope to E.

29.00

Hidge, bears NE. and SW. Desc. 190 ft. over N. slope, changing to NE.


39.00

Having, course N.20°W., turning to W. Along W. slope, descend slightly.

40.30

Point for center 7/8 sec. cor., at intersection with the E. and W. center line of Sec. 5.

Set an iron post, 3 ft. long, 2 ins. diam., 34 ins. in the ground, with granite stone 8 x 6 ins., marked + buried alongside, with brass cap mkd.



Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. N.0°12'W., beginning new measurement.

Along W. slope; asc. slightly.

2.50

Small spur, slopes N.80°W. Desc. 50 ft. over N. slope.

4.30

Shallow draw, course N.80°W.

5.60


Old roadway, bears E. and W.

Chains

Subdivision of sec. 5, T.4N., R.14 W.

- 6.00 Draw, course S.70°W. Asc. 30 ft.
- 9.20 Small spur, slopes W. Desc. 20 ft.
- 10.70 Ravine, course W. Asc. 80 ft.
- 14.00 Spur, slopes W. Desc. 50 ft.
- 15.90 Ravine, course N.80°W. Asc. 100 ft. over SW. slope.
- 19.70 Spur, slopes W. Desc. 30 ft. over N. slope.
- 20.42 Point for center N. 1/16 sec. cor., at proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., 35 ins. in the ground, with a granite stone 6 x 5 x 4 ins., marked + deposited alongside, with brass cap mkd.



Make a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor. Desc. 150 ft. over a decreasing N. slope.

End of stub roadway, from west, in turn around at old camp site.

27.40 Some roadway, bearing to SW., in shallow draw, course W. Asc. 35 ft.

29.00 Point of spur, sloping W. Desc. 25 ft.

Gully, course W.

32.00 Point of spur, 25 ft. high, sloping W.

35.00 Shallow ravine, course W. Asc. 65 ft.

Point of spur, slopes W. Desc. 50 ft.

40.50 Drain, course W. Asc. 10 ft.

40.73 The 1/2 sec. cor., of secs. 5 and 32, on N. bdy. of the T.P., marked by an iron post, 2 ins. diam., mkd. and witnessed as described in the 1947 resurvey, executed under this group.

From the 1/2 sec. cor., of secs. 5 and 6.

S.89°13'E., on the E. and W. center line of sec. 5.

Desc. 75 ft. over E. slope.

Ravine, course S.30°E. Asc. 50 ft. over SW. slope.

6.65 Point of spur, sloping W., Desc. 115 ft. over E. slope.

8.53 Telephone line, on wood poles, bears N.37°E. and S.34°W.

Subdivision of Sec. 5, T. 4 N., R. 14 W.

Chain

Roadway, bears NE. and SW., following 1/2k canyon.

15.85

Wash, 40 lks, wide, 2 ft. deep, course S. 40° W.

Avg. 20 ft. over gradual W. slope, changing to NW.

20.91

Point for center W. 1/16 sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 3 1/2 ins. in the ground, with a granite stone, 7 x 6 x 3 ins., marked + buried alongside, with brass cap mkd.

W 1/16
S 5
1947

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Avg. 100 ft. over gradually increasing NW. slope.

31.80

Residence, at East ranch, bears N. 57° W., about 5.00 chs. Dist.

Change of slope to N., continue gradual ascent.

Having, course N. 60° W. Avg. 15 ft. over W. slope.

41.20

The center 1/2 sec. cor., at intersection with the N. and S. center line.

S. 89° 15' E., beginning new measurement.

Avg. 65 ft. over W. slope.

3.40

Spur, slopes NW., turning to W. over N. slope.

Having, course NW. Avg. 110 ft. over SW. slope.

7.20

Low divide, bears NE. and SW. Desc. 40 ft. over SE. slope.

16.00

Wash, 15 lks, wide, 2 ft. deep, in shallow draw, course SW.

19.50

Point for center E. 1/16 sec. cor.

19.93

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, and in a flat mound of stone, 4 ft. base, to top, with brass cap mkd.

E 1/16
S 5
1947

Avg. 250 ft. over NW. slope.

34.70

Draw, course NW.

Ridge, bears NE. and SW. Desc. 15 ft.

38.50

The 1/2 sec. cor. of secs. 4 and 5.

39.86

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

From the E. 1/16 sec. cor., of secs. 5 and 8.
 N.0°14'E., on the N. and S. center line of SE. 1/4 of Sec. 5.
 Desc. 20 ft. over NE. slope.
 Ravine, course SE. Asc. 200 ft. over broken W. slope,
 along E. side of ravine, draining from N.
 14.50 Head of ravine, course S.20°W. Asc. 80 ft. over S. slope.
 Ridge, bears N.E. and SW. Desc. 50 ft. over NE. slope.
 18.80 Point for SE. 1/16 sec. cor., at intersection with the E.
 and W center line of SE 1/4 sec. 5.
 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the
 ground, with brass cap mkd.
 SE 1/16
 S 5
 1947

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
 Desc. 80 ft. over NE. slope.

23.00 Ravine, course NW. Asc. 50 ft. over W. slope.

27.70 Spur, slopes NW. Desc. 140 ft. over NE. slope.

23.00 Ravine, course NW., Asc. 40 ft.

26.70 Gully, course W.

28.70 Point of spur, slopes W. Desc. 40 ft. over NW slope.

40.12 The center E. 1/16 sec. cor.

From the center S. 1/16 sec. cor.

S.89°28'E., on the E. and W. center line of the SE. 1/4 of Sec. 5.
 Asc. 55 ft. over an increasing W. slope.

2.10 Point of spur, sloping NW. Along N. slope.

4.25 Short ravine, course NW. Asc. 150 ft. over SW. slope.

8.00 Spur, slopes NW. along N. slope.

10.40 Gully, near head, course NW. Asc. 55 ft.

12.70 Short spur, slopes NW. continue ascent 100 ft. over NW.
 slope.

16.60 Head of ravine, course NW.

18.90 Shoulder of spur, breaks sharply to NW. Desc. slightly
 over NE. slope.

19.75 The SE. 1/16 sec. cor.

29.10	Gully, course SW. Continue ascent 50 ft. over S. slope.
28.00	Havine, course NE. Ascent, 20 ft.
27.60	Top of broken bluff, 20 ft. high; continue descent 120 ft. over N. slope.
	Continue descent 60 ft. over NE. slope.
	NE 1/16 S 5 1947
20.47	Point for NE. 1/16 sec. cor., at intersection with the E. and W. center line of NE. sec. 5. Set an iron post, 3 ft. long, 1 in. diam., 26 in. in the ground, to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mrd.
17.50	Spur, breaks to the W.; divide bears E. and W., turning to the S. Desc. 85 ft. over N. slope, changing to NE.
10.50	Same wash, 5 lks. wide, course S. 20° W. Asc. 105 ft. over S slope.
7.60	Same wash, course S. 30° E.; continue ascent 70 ft.
5.50	Wash, 10 lks. wide, in shallow ravine, course S. 15° W.
0.60	Wash, 15 lks wide, in shallow draw, course SW. Asc. 75 ft. over broken S. slope, along E. side of ravine, from N.
	Over NW slope.
	N. 0° 16' E., on the N. and S. center line of the NE. 1/4 sec. 5. From the center E. 1/16 sec. cor.
39.55	The S. 1/16 sec. cor., of sec. 4 and 5.
37.00	Small spur, slopes SE. Desc. 45 ft. over E. slope.
34.75	Gully, course SE. Asc. 15 ft.
32.00	Short spur, slopes SE. Desc. 95 ft. over E. slope.
29.90	Havine, course SE. Asc. 55 ft.
27.00	Shoulder of spur, breaking to SE. Desc. 120 ft. over E. slope.
23.00	Drain, course SE.
22.35	Ridge, bears NE. and SW. along S. slope.
Chain	Asc. 20 ft., across swale in N. slope, near top of ridge.
	Subdivision of Sec. 5, T. 4N., R. 14 W.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chain

Small spur, W. desc. 50 ft.

Gully, course SW. Asc. 100 ft. over S. slope.

Spur, slopes N.70°W. Desc. 35 ft.

Gully, course N.70°W., along W. slope.

40.86

The N. 1/16 sec. cor. of sec. 5 and 32, on N. bdy. of the T.4, marked by an iron post, 1 in. diam., firmly set, and under witness as described in the 1947 survey, executed under this group.

From the center N. 1/16 sec. cor.

S.89°26' E., on the E. and W. center line of the N. 1/2 Sec. 5.

Asc. 150 ft. over general N. slope, near top of spur, extending to the west.

Head of gully, course NW.; change of slope to W., sec. 70 ft.

Change of slope to E., spur extends to NW.

The N. 1/16 sec. cor.

Desc. 30 ft. over E. slope.

Head of gully, course N. Asc. 90 ft. over NW. slope.

Drain, course N.20°W.

Bridge, bears N. and S., turning to W.; spur extends to S.

Desc. 75 ft. over E. slope.

Shallow draw, course S., turning to SW. Asc. 50 ft. over SW. slope.

37.30

Gully, course SW. Continue ascent 70 ft. over W. slope.

The N. 1/16 sec. cor. of sec. 4 and 5.

40.16

From the W. 1/16 sec. cor. of sec. 5 and 8.

N.1°26' W., on the N. and S. center line of the SW 1/4 of sec. 5.

Desc. slightly, over gradual NW. slope.

Wash, 15 lbs, wide, in draw, course S.50°W. Asc. 110 ft. over SE. slope.

2.50

Short spur, sloping E. Desc. slightly, over W. slope.

Havine, course SE. Asc. 110 ft. over S. slope.

12.30

Spur, slopes SE.; continue ascent 70 ft. over SE. slope.

17.30

Head of havine, course SE.; change of slope to S.

Subdivision of Sec. 5, T.4N., R.11W.

Chains

18.00 Ridge, bears N. and SW. Desc. 50 ft. over N. slope. Point for SW 1/16 sec. cor., at intersection with the E. and W. center line of SW 1/4.

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with granite stone 6 x 5 x 4 ins., marked + buried alongside, with brass cap mkd.

SW 1/16 S 5
1947

Make a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor. Desc. 130 ft. over N. slope.

24.20 Having, course NW. Asc. 35 ft. over SW. slope.

27.00 Change of slope to NW. Desc. 40 ft.

22.00 Point of spur, sloping NW. Desc. 120 ft. over N. slope.

25.00 Foot of slope, enter tick canyon, course SW. Desc. 30 ft. over gradual N. slope.

40.48 The center W. 1/16 sec. cor.

From the S. 1/16 sec. cor., of sec. 5 and 6.

S. 89° 27' E. on the E. and W. center line of the SW 1/4 of sec. 5.

Asc. 65 ft. over N. slope, near top of small spur, from SR.

5.70 Short spur, slopes NW. Desc. 35 ft.

6.70 Having, course NW. Asc. 95 ft. over W. slope.

9.20 Short spur, slopes NW. Desc. 40 ft. over N. slope.

13.00 Having, course NW. Asc. 130 ft. over W. slope.

19.30 Spur, slopes NW. Desc. 10 ft.

20.44 The SW 1/16 sec. cor.

Asc. 60 ft., across saddle, near top of ridge.

26.00 Ridge, bears N. and S. 70° W. Desc. 170 ft. over an in-creasing S. to E. slope.

27.20 Wash, 20 lbs. wide, 2 ft. deep, in draw, course SW.

Asc. 20 ft. over bottom land, draining NW.

40.90 The center S. 1/16 sec. cor.

Chain

Subdivision of Sec. 5, T.4 N., R.14 W.

- From the center W. 1/16 sec. cor.
- N.1°30'W., on the N and S center line of the NW 1/4 of sec. 5.
- Desc. 15 ft. over N. slope.
- Enter wash, in Tick Canyon, course SW.
- Leave wash. Asc. 30 ft. over gradual SR. slope.
- 6.20
- Head, bears E. and SW.
- 11.00
- Wash, 5 lks. wide, course SE. Asc. 125 ft., along top of spur, from the north.
- 17.70
- Telephone line, bears NE. and SW.
- 19.00
- Leave spur, slopes S., from N. 20°E. Along W. slope.
- 20.38
- Point for NW. 1/16 sec. cor., at intersection with the E. and W. center line of the NW 1/4.
- Set an iron post, 3 ft. long, 1 in. diam., 34 ins. in the ground, with a granite stone 6 x 5 x 5 ins., marked + buried alongside, with brass cap marked.
- NW 1/6 S 5
- 1947
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
- Continue over W. slope.
- 21.50
- Gross spur, in shallow saddle, bearing SE., from N. 20°W. Asc. 110 ft. over SE. slope.
- 27.30
- Small spur, slopes S. 60°E.
- 32.25
- Gully, course SE. Asc. 45 ft. over S. slope.
- 34.00
- Spur, slopes E. Desc. 95 ft. over broken NW. slope.
- 40.70
- Point for W. 1/16 sec. cor., of sec. 5 and 32, on N. bdy. of T.4 N. 1/2°W., 44.5 lks. dist., from the witness corner. This witness cor. is marked by an iron post, 1 in. diam., firmly set, and referred as described in the 1947 resurvey, executed under this group.
- From the N. 1/16 sec. cor., of sec. 5 and 6.
- S 89°27'E., on the E. and W. center line of the NW 1/4 of Sec. 5.
- Along S. slope.
- 0.65
- Head of gully, course S. 60°W. Asc. 55 ft. over W. slope.
- 1.80
- Change of slope to S.
- 4.30
- Spur, slopes S. Desc. 90 ft.
- 7.60
- Headings, course S. Asc. 50 ft.