

T.4 N., R.14 W.

Chains

Resurveys and surveys in Section 5, T.4 N., R.14 W., were executed with Buff & Buff transit No. 24849, and Gurley transit No. 38123. For description and tests of instrumental equipment see surveys in T.4N., R.15 W., executed under this Group.

T.4 N., R.14 W. was originally surveyed by W. H. Norway in 1879. Resurveys executed by Los Angeles County in 1925 present a remonumentation of original corners then extant, with brass capped iron posts, 2 ins., in diameter, firmly set in concrete base. These monuments are substantial and permanent, and are adopted with only slight modification in the present resurvey.

Preliminary to resurvey all lines of the governing survey were retraced and the positions thoroughly verified. The true line results are given herein. Azimuth determination is by projection or Polaris observation recorded in T.5 N., R.14 W., maintained by successive angulation throughout the survey.

The observed magnetic declination is $15\frac{1}{2}^{\circ}$ E.

The surveys herein noted were undertaken to provide a basis for disposal of public land, under Act of June 1, 1938, 52 Stat. 609; U.S.C. 682a.

Dependent Resurvey of a Portion of the Subdivision

T.4 N., R.14 W.

The cor. of secs. 4, 5, 8 and 9 is marked by an iron post monument, 2 ins. diam., 6 ins. above ground, firmly set in concrete base, 6 ins. diam., Additionally mark brass cap to read

COUNTY SURVEYOR
T4N
S 5 S 4
R14W S 8 S 9
US BLM 1947
RE 2177
MONUMENT

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $0^{\circ}36'$ E., bet. secs. 4 and 5.

Over mountainous land, through scattered undergrowth.

Desc. 125 ft. over NW slope.

10.00 Draw, course SW. Asc. 100 ft. over S. slope.

15.00 Short spur, slopes E. Along E. slope.

19.97 Point for S. $1/16$ sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, with a granite stone 8 x 5 x 4 ins., marked + buried alongside, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision

T.4 N., R.14 W.

Chains

S $\frac{1}{16}$
S 5 | S 4
1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

- 20.55 Gully, course SE. Asc. 115 ft. over S. slope.
- 27.20 Spur, slopes SE. Desc. 35 ft. over NE. slope.
- 29.00 Gully, course E., turning to SE. Asc. 70 ft. over S. Slope.
- 32.60 Shoulder of spur, extending E.
- 35.40 Head of ravine, course S.80°E. Asc. 95 ft. over SE. slope.
- 39.94 The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, marked with an iron post monument, 2 ins. diam., 6 ins. above ground, firmly set in concrete base, 6 ins. diam. Alongside is the original corner stake, a weathered juniper post, 2 ins. square, 16 ins. long.

Additionally mark brass cap to read

COUNTY SURVEYOR
T4N
S 5 | S 4
 $\frac{1}{4}$ COR
US BLM 1947
MONUMENT

Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.

N.0°40'E., beginning new measurement.

Asc. 20 ft. over SE. slope.

- 1.00 Top of ascent, and across ridge-spur, extending to SW.
- 2.50 Desc. 140 ft. over NW. slope.
- 9.50 Draw, course SW. Asc. 85 ft. over S. slope.
- 13.20 Spur, slopes SW. Desc. 30 ft. over W. slope.
- 16.00 Gully, course S.70°W. Asc. 75 ft. over SW. slope.
- 20.57 Point for N. $\frac{1}{16}$ sec. cor. of secs. 4 and 5, at proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., $2\frac{1}{4}$ ins. in the ground, to bedrock, and in a mound of stone 4 ft. base, to top, with brass cap mkd.

N $\frac{1}{16}$
S 5 | S 4
1947

Dependent Resurvey of a Portion of the Subdivision

T.4 N., R.14 W.

Chains

- Continue ascent 50 ft. over SW. slope.
- 24.00 Change of slope to W.
- 27.50 Short spur, slopes W. Desc. 50 ft. over NW. slope.
- 30.80 Gully, course N.70°W.
- 32.70 Gully, course W. Asc. 40 ft.
- 33.70 Small spur, slopes N.80°W. Desc. 25 ft.
- 38.60 Draw, course W., Asc. 25 ft.
- 41.02 The cor. of secs. 4, 5, 32 and 33, on N. bdy. of the TP., marked by an iron post, mkd. and witnessed as described in the 1947 resurvey, executed under this group.
- Land, rolling mountains.
Soil, rocky, 3rd. rate.
Scattered cedar, greasewood, sage and casti.

From the cor. of secs. 4, 5, 8 and 9.

N.89°45'W., bet. secs. 5 and 8.

Over mountainous land, through scattered undergrowth.

Desc. 175 ft. over NW slope.

- 8.00 Draw, course SW. Asc. 60 ft. over SE. slope.
- 10.50 Short spur, slopes S. Desc. 25 ft.
- 11.50 Gully, course S. Asc. 100 ft. over E. slope.
- 14.50 Spur, slopes S.20°E. Along S. slope.
- 15.50 Desc. 45 ft. over W. slope.
- 16.00 Ravine, course S. Asc. 70 ft. over E. slope.
- 19.65 Point for E. 1/16 sec. cor., of secs. 5 and 8.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the ground, with brass cap mkd.

E $\frac{1}{16}$ S $\frac{5}{8}$

1947

Bury a granite stone, 6 x 4 x 3 ins., marked + alongside iron post.

Continue ascent 100 ft. over E. slope, along spur from W., here turning to the S.

- 22.50 Change of slope to SE., and continue ascent.
- 26.00 Along S. slope.
- 27.80 Head of gully, course SE.

Dependent Resurvey of a Portion of the Subdivision

T.4 N., R.14 W.

Chains

- Asc. 115 ft. over E. slope.
- 29.75 Small spur, slopes SE., Change of slope to SE, continue ascent.
- 34.50 Ridge, bears NE. and SW. Desc. 90 ft. over NW. slope.
- 39.30 The $\frac{1}{4}$ sec. cor., of secs. 5 and 8, marked by an iron post monument, 2 ins. diam., 8 ins. above ground, firmly set in concrete base. Additionally mark brass cap to read

COUNTY SURVEYOR

T4N

R 14W $\frac{S 5}{S 8}$

$\frac{1}{4}$ COR

US BLM 1947
MONUMENT

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
N. $89^{\circ}44'$ W., beginning new measurement.

Along N. slope.

- 1.20 Change of slope to NW.; desc. 60 ft.
- 4.00 Change of slope to SW.; desc. 220 ft.
- 12.30 Ravine, course N. 70° W., turning to W. Continue descent 50 ft. over NW. slope.
- 20.00 Point for W. $1/16$ sec. cor., of secs. 5 and 8.
Set an iron post, 3 ft. long, 2 ins. diam., 32 ins. in the ground, with brass cap mkd.

$W \frac{1}{16} \frac{S 5}{S 8}$
1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.
Continue descent 10 ft.

- 21.00 Draw, course S. 20° W. Over S. slope.
- 31.40 Gully, course SE. Asc. 135 ft. over NE. slope.
- 36.20 Ridge, bears NE. and SW. Desc. 75 ft. over NW. slope.
- 40.00 The cor. of Secs. 5, 6, 7 and 8, marked by an iron post. 2 ins. diam., in concrete form 6 ins. diam., 8 ins. above ground, firmly set, and in a flat mound of stone to top. Additionally mark brass cap to read

COUNTY SURVEYOR

T4N

R14W $\frac{S6}{S7} \frac{S 5}{S 8}$

US BLM 1947
RE 2177
MONUMENT

Dependent Resurvey of a Portion of the Subdivision

T.4N., R.14 W.

Chains

From the corner, an iron post, 2 ins. diam., firmly set, flush in concrete base, 6 ins. diam., marking the original witness corner monument, bears N.88°15' W., 65.3 lks. dist. (Record: West, 65 lks. distant.)

From this witness corner monument, the original bearing tree

A white oak, 14 ins. diam., bears S.49°W., 53.4 lks. dist., the old blaze is partially closed by overgrowth, markings are visible but not now legible. (record: S.51½° W., 51 lks. dist.)

Land, mountainous.

Soil, rocky, 3rd. rate.

Scattered cedar and oak; creosote brush, sage and cacti.

N.2°45'W., bet. secs. 5 and 6.

Over mountainous land, through scattered undergrowth.

Desc. 100 ft. over N. slope.

4.00 Gully, course NW. Asc. 75 ft. over SW. slope.

7.10 Spur, drops sharply to NW. Desc. 210 ft. over changing NE to N. slope.

16.50 Ravine, course NW., Asc. 70 ft. over S^W. Slope.

20.00 Point of sharp, narrow spur, slopes N.20°W., from S.60°E.

20.34 Point for S. 1/16 sec. cor., of secs. 5 and 6.

Set an iron post, 3 ft. long, 2 ins. diam., ¾ ins. in the ground, with brass cap mkd.

S 1/16
S 6 | S 5
1947

Bury a granite stone, 8 x 6 x 5 ins., marked + alongside iron post.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.

Desc. 80 ft. over N. slope.

23.60 Foot of slope, and enter wash, in Tick Canyon, course SW.

28.00 Leave wash. Asc. 35 ft. over gradual slope of bench land.

29.10 Road, unimproved, bears irregularly NE. and SW., following Tick Canyon.

31.50 Telephone line, bears N.80°E. and S.80°W., in Tick Canyon.

Asc. 150 ft. over an increasing SW. slope.

38.30 Spur, slopes SE. Desc. 25 ft. over E. slope.

Dependent Resurvey of a Portion of the Subdivision

T.4 N., R.14 W.

Chains

- 40.68 The $\frac{1}{4}$ sec. cor., marked by an iron post, 2 ins. diam., 12 ins. above ground, firmly set in concrete base, 6 ins. diam., and in a half mound of stone, 3 ft. base, to top, Additionally mark brass cap to read

COUNTY SURVEYOR
T4N
SEC 6 | SEC 5
R14W $\frac{1}{4}$ COR
US BLM 1947
MONUMENT

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
N.2°45'W., beginning new measurement.

Over E. slope; desc. 10 ft.

- 5.50 Ravine, course S.30°E., draining from the N. Asc. 95 ft. over SW. slope.
13.00 Short spur, slopes SW. Over W. slope.
15.00 Gully, course SW. Asc. 115ft. over SW. slope.
20.00 Head of gully, course S.70°W.
20.40 Point for N. 1/16 sec. cor., of secs. 5 and 6, at proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., 34 ins. in the ground, with granite stone 8 x 6 x 3 ins., marked + deposited alongside, with brass cap mkd.

N $\frac{1}{16}$
S 6 | S 5
1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
Continue ascent 80 ft. over broken SW. slope.

- 25.90 Gully, course SW.
31.00 Gully, course SW.
34.50 Ravine, course S.70°W.
36.00 Spur, slopes S.70°W. Desc. 90 ft. over NW slope.
39.20 Gully, course SW Asc. 50 ft. over S. slope.
40.71 The cor. of Sec. 5, 6, 31 and 32, on N. bdy. of the Tp., marked by an iron post, mkd. and witnessed as described in the 1947 resurvey, executed under this Group.

Land, broken mountains.
Soil, rocky, 3rd. rate.
Scattered creosote brush, sage and cacti.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

From the $\frac{1}{4}$ sec. cor., of Sec. 5 and 8.

N.0°12'W., on the N. and S. center line of Sec. 5.

Over mountainous land, through scattered undergrowth; desc. 150 ft. over N. slope.

- 5.85 Ravine, course N.70°W. Along broken W. slope; asc. 35 ft.
- 9.00 Spur, slopes N.70°W. Desc. 150 ft.
- 17.50 Ravine, course W. Desc. 25 ft. over NW. Slope, in canyon, course SW.
- 20.15 Point for center S.1/16 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 32 ins. in the the ground, with brass cap mkd.

C
S $\frac{1}{16}$ S 5
C
1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Desc. 10 ft. over flat NW slope.

- 23.70 Wash, 20 lks, wide, course SW., in canyon.
- Asc. 140 ft. over SE. slope.

27.20 Gully, course SE.

29.00 Change of slope to E.

30.50 Ridge, bears NE. and SW. Desc. 190 ft. over N. slope, changing to NE.

39.00 Ravine, course N.20°W., turning to W. Along W. slope, descend slightly.

40.30 Point for center $\frac{1}{4}$ sec. cor., at intersection with the E. and W. center line of Sec. 5.

Set an iron post, 3 ft. long, 2 ins. diam., 34 ins. in the ground, with granite stone 8 x 6 x 6 ins., marked + buried alongside, with brass cap mkd.

C $\frac{1}{4}$ S 5
1947

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

N.0°12'W., beginning new measurement.

Along W. slope; asc. slightly.

- 2.50 Small spur, slopes N.80°W. Desc. 50 ft. over N. slope.
- 4.30 Shallow draw, course N. 80°W.
- 5.60 Old roadway, bears E. and W.

Subdivision of Sec. 5, T.4N., R.14 W.

Chains

- 6.00 Draw, course S.70°W. Asc. 30 ft.
- 9.20 Small spur, slopes W. Desc. 20 ft.
- 10.70 Ravine, course W. Asc. 80 ft.
- 14.00 Spur, slopes W. Desc. 50 ft.
- 15.90 Ravine, course N.80°W. Asc. 100 ft. over SW. slope.
- 19.70 Spur, slopes W. Desc. 30 ft. over N. slope.
- 20.42 Point for center N. 1/16 sec. cor., at proportionate measurement.

Set an iron post, 3 ft. long, 1 in. diam., 33 ins. in the ground, with a granite stone 6 x 5 x 4 ins., marked + deposited alongside, with brass cap mkd.

$$\begin{array}{c} \text{C} \\ \text{N } \frac{1}{16} \text{ S } 5 \\ \text{C} \\ 1947 \end{array}$$

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
Desc. 150 ft. over a decreasing N. slope.

- 26.15 End of stub roadway, from west, in turn around at old camp site.
- 27.40 Same roadway, bearing to SW., in shallow draw, course W.
Asc. 35 ft.
- 29.00 Point of spur, sloping W. Desc. 25 ft.
- 29.80 Gully, course W.
- 32.00 Point of spur, 25 ft. high, sloping W.
- 35.00 Shallow ravine, course W. Asc. 65 ft.
- 37.80 Point of spur, slopes W. Desc. 50 ft.
- 40.50 Drain, course W. Asc. 10 ft.
- 40.73 The ¼ sec. cor., of secs. 5 and 32, on N. bdy. of the Twp., marked by an iron post, 2 ins. diam., mkd. and witnessed as described in the 1947 resurvey, executed under this Group.

From the ¼ sec. cor., of secs. 5 and 6.

S.89°13'E., on the E. and W. center line of Sec. 5.

Desc. 75 ft. over E. slope.

- 2.50 Ravine, course S.30°E. Asc. 50 ft. over SW. slope.
- 6.65 Point of spur, sloping S., Desc. 115 ft. over E. slope.
- 8.53 Telephone line, on wood poles, bears N.34°E. and S.34°W.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

15.85 Roadway, bears NE. and SW., following Tick canyon.

16.60 Wash, 40 lks, wide, 2 ft. deep, course S.40°W.

Asc. 20 ft. over gradual W. slope, changing to NW.

20.91 Point for center W. 1/16 sec. cor.

Set an iron post, 3 ft. long, 2 ins. diam., 34 ins. in the ground, with a granite stone, 7 x 6 x 3 ins., marked + buried alongside, with brass cap mkd.

W 1/16
C ——— C
S 5
1947

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.

Asc. 100 ft. over gradually increasing NW. slope.

31.80 Residence, at goat ranch, bears N.57°W., about 5.00 chs. Dist.

Change of slope to N., continue gradual ascent.

41.30 Ravine, course N.60°W. Asc. 15 ft. over W. slope.

41.82 The center 1/4 sec. cor., at intersection with the N. and S. center line.

S.89°13'E., beginning new measurement.

Asc. 65 ft. over W. slope.

3.40 Spur, slopes NW., turning to W. Over N. slope.

7.30 Ravine, course NW. Asc. 110 ft. over SW. slope.

16.00 Low divide, bears NE. and SW. Desc. 40 ft. over SE. slope.

19.50 Wash, 15 lks, wide, 2 ft. deep, in shallow draw, course SW.

19.93 Point for center E. 1/16 sec. cor.

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, and in a flat mound of stone, 4 ft. base, to top, with brass cap mkd.

E 1/16
C ——— C
S 5
1947

Asc. 250 ft. over NW. slope.

34.70 Drain, course NW.

38.50 Ridge, bears NE. and SW. Desc. 15 ft.

39.86 The 1/4 sec. cor. of secs. 4 and 5.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

From the E. 1/16 sec. cor., of secs. 5 and 8.

N.0°14'E., on the N. and S. center line of SE. 1/4 of Sec. 5.

Desc. 20 ft. over NE. slope.

- 3.50 Ravine, course SE. Asc. 200 ft. over broken W. slope, along E. side of ravine, draining from N.
- 14.50 Head of ravine, course S.20°W. Asc. 80 ft. over S. slope.
- 18.80 Ridge, bears NE. and SW. Desc. 50 ft. over NE. slope.
- 20.07 Point for SE. 1/16 sec. cor., at intersection with the E. and W center line of SE 1/4 sec. 5.
Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.
SE 1/16
S 5
1947
- Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
Desc. 80 ft. over NE. slope.
- 23.00 Ravine, course NW. Asc. 30 ft. over W. slope.
- 27.70 Spur, slopes NW. Desc. 140 ft. over NE. slope.
- 33.00 Ravine, course NW., Asc. 40 ft.
- 36.70 Gully, course W.
- 38.70 Point of spur, slopes W. Desc. 40 ft. over NW slope.
- 40.12 The center E. 1/16 sec. cor.

From the center S. 1/16 sec. cor.

S.89°28'E., on the E. and W. center line of the SE. 1/4 of Sec. 5.

Asc. 55 ft. over an increasing W. slope.

- 2.10 Point of spur, sloping NW. Along N. slope.
- 4.25 Short ravine, course NW. Asc. 130 ft. over SW. slope.
- 8.00 Spur, slopes NW. along N. slope.
- 10.40 Gully, near head, course NW. Asc. 55 ft.
- 12.70 Short spur, slopes NW. continue ascent 100 ft. over NW. slope.
- 16.60 Head of ravine, course NW.
- 18.90 Shoulder of spur, breaks sharply to NW. Desc. slightly over NE. slope.
- 19.75 The SE. 1/16 sec. cor.

Subdivision of Sec. 5, T.4N., R.14 W.

Chains

- Asc. 20 ft., across swale in N. slope, near top of ridge.
- 22.35 Ridge, bears NE. and SW. along S. slope.
- 23.00 Drain, course SE.
- 24.00 Shoulder of spur, breaking to SE. Desc. 120 ft. over E. slope.
- 29.90 Ravine, course SE. Asc. 55 ft.
- 32.00 Short spur, slopes SE. Desc. 95 ft. over E. slope.
- 34.75 Gully, course SE. Asc. 15 ft.
- 37.00 Small spur, slopes SE. Desc. 45 ft. over E. slope.
- 39.53 The S. 1/16 sec. cor., of secs. 4 and 5.

From the center E. 1/16 sec. cor.

N.0°16'E., on the N. and S. center line of the NE. 1/4 sec. 5.

Over NW slope.

- 0.60 Wash, 15 lks wide, in shallow draw, course SW.
Asc. 75 ft. over broken S. slope, along E. side of ravine, from N.
- 5.50 Wash, 10 lks. wide, in shallow ravine, course S.15°W.
- 7.60 Same wash, course S.30°E.; continue ascent 70 ft.
- 10.50 Same wash, 5 lks. wide, course S.20°W. Asc. 105 ft. over S slope.
- 17.50 Spur, breaks to the W.; divide bears E. and W., turning to the S. Desc. 85 ft. over N. slope, changing to NE.
- 20.47 Point for NE. 1/16 sec. cor., at intersection with the E. and W. center line of NE. 1/4 sec. 5.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, to bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

NE 1/16

S 5
1947

Continue descent 60 ft. over NE. slope.

- 24.60 Top of broken bluff, 20 ft. high; continue descent 120 ft. over N. slope.
- 28.00 Ravine, course NW. Ascent. 20 ft.
- 29.10 Gully, course SW. Continue ascent 50 ft. over S. slope.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

- 30.50 Small spur, W.; desc. 50 ft.
- 32.40 Gully, course SW. Asc. 100 ft. over S. slope.
- 35.20 Spur, slopes N.70°W. Desc. 35 ft.
- 38.10 Gully, course N.70°W., Along W. slope.
- 40.86 The E. 1/16 sec. cor. of sec. 5 and 32, on N. bdy. of the TP., marked by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the 1947 resurvey, executed under this Group.

From the center N. 1/16 sec. cor.

S.89°26'E., on the E. and W. center line of the NE. 1/4 Sec. 5.
Asc. 150 ft. over general N. slope, near top of spur,
extending to the west.

- 13.80 Head of gully, course NW.; change of slope to W., asc. 70 ft.
- 16.00 Change of slope to N., spur extends to NW.
- 20.07 The NE. 1/16 sec. cor.
Desc. 30 ft. over NE. slope.
- 22.20 Head of gully, course N. Asc. 90 ft. over NW. slope.
- 27.60 Drain, course N.20°W.
- 28.10 Ridge, bears N. and S., turning to W.; spur extends to S.
Desc. 75 ft. over E. slope.
- 33.00 Shallow draw, course S., turning to SW. Asc. 50 ft. over SW. slope.
- 37.30 Gully, course SW. Continue ascent 70 ft. over W. slope.
- 40.16 The N. 1/16 sec. cor. of secs. 4 and 5.

From the W. 1/16 sec. cor. of secs. 5 and 8.

N.1°26'W., on the N. and S. center line of the SW 1/4 of sec. 5.

Desc. slightly, over gradual NW. slope.

- 2.50 Wash, 15 lks. wide, in draw, course S.30°W. Asc. 140 ft. over SE. slope.
- 9.40 Short spur, sloping E. Desc. slightly, over E. slope.
- 12.30 Ravine, course SE. Asc. 110 ft. over S. slope.
- 15.30 Spur, slopes SE.; continue ascent 70 ft. over SE. slope.
- 17.30 Head of ravine, course SE.; change of slope to S.

Subdivision of Sec. 5, T.4N., R.14 W.

Chains

- 18.00 Ridge, bears NE. and SW. Desc. 50 ft. over NE. slope.
- 20.26 Point for SW. $1/16$ sec. cor., at intersection with the E. and W. center line of SW. $\frac{1}{4}$.
- Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with granite stone 6 x 5 x $\frac{1}{4}$ ins., marked + buried alongside, with brass cap mkd.
- SW $1/16$ S 5
1947
- Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
- Desc. 130 ft. over NE. slope.
- 24.20 Ravine, course NW. Asc. 35 ft. over SW. slope.
- 27.00 Change of slope to NW.; desc. 40 ft.
- 32.00 point of spur, sloping NW. Desc. 120 ft. over NE. slope.
- 35.00 Foot of slope, enter Tick Canyon, course SW. Desc. 30 ft. over gradual N. Slope.
- 40.48 The center W. $1/16$ sec. cor.
-
- From the S. $1/16$ sec. cor., of secs. 5 and 6.
- S. $89^{\circ}27'E.$, on the E. and W. center line of the SW. $\frac{1}{4}$ of sec. 5.
- Asc. 65 ft. over NE. slope, near top of small spur, from SE.
- 3.70 Short spur, slopes NW. Desc. 35 ft.
- 6.70 Ravine, course NW. Asc. 95 ft. over W. slope.
- 9.20 Short spur, slopes NW. Desc. 40 ft. over NE. slope.
- 13.00 Ravine, course NW. Asc. 130 ft. over W. slope.
- 19.30 Spur, slopes NW. Desc. 10 ft.
- 20.44 The SW. $1/16$ sec. cor.
- Asc. 60 ft., across swale, near top of ridge.
- 26.00 Ridge, bears NE. and S. $70^{\circ}W.$ Desc. 170 ft. over an increasing S. to SE. slope.
- 37.20 Wash. 20 lks. wide, 2 ft. deep, in draw, course SW.
- Asc. 20 ft. over bottom land, draining NW.
- 40.90 The center S. $1/16$ sec. cor.
-

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

From the center W. $1/16$ sec. cor.

N. $1^{\circ}30'W.$, on the N and S center line of the NW $\frac{1}{4}$ of sec. 5.
Desc. 15 ft. over N. slope.

- 2.90 Enter wash, in Tick Canyon, course SW.
- 6.20 Leave wash. Asc. 30 ft. over gradual SE. slope.
- 6.30 Road, bears E. and SW.
- 11.00 Wash, 5 lks. wide, course SE. Asc. 125 ft., along top of spur, from the north.
- 17.70 Telephone line, bears NE. and SW.
- 19.00 Leave spur, slopes S., from N. $20^{\circ}E.$ Along W. slope.
- 20.38 Point for NW. $1/16$ sec. cor., at intersection with the E. and W. center line of the NW. $\frac{1}{4}$.

Set an iron post, 3 ft. long, 1 in. diam., $3\frac{1}{4}$ ins. in the ground, with a granite stone 6 x 5 x 5 ins., marked + buried alongside, with brass cap marked

NW $\frac{1}{16}$ S 5
1947

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
Continue over W. Slope.

- 21.50 Cross spur, in shallow saddle, bearing SE., from N. $20^{\circ}W.$ Asc. 110 ft. over SE. slope.
- 27.30 Small spur, slopes S. $60^{\circ}E.$
- 32.25 Gully, course SE. Asc. 45 ft. over S. slope.
- 34.00 Spur, slopes E. Desc. 95 ft. over broken NE. slope.
- 40.70 Point for W. $1/16$ sec. cor., of secs. 5 and 32, on N. bdy. of TP., N. $42^{\circ}W.$, $4\frac{1}{4}$ lks. dist., from the witness corner. This witness cor., is marked by an iron post, 1 in. diam., firmly set, mkd. and referenced as described in the 1947 resurvey, executed under this Group.

From the N. $1/16$ sec. cor., of secs. 5 and 6.

S $89^{\circ}27'E.$, on the E. and W. center line of the NW. $\frac{1}{4}$ of Sec. 5.

Along S. Slope.

- 0.65 Head of gully, course S. $60^{\circ}W.$ Asc. 55 ft. over W. slope.
- 1.80 Change of slope to S.
- 4.30 Spur, slopes S. Desc. 90 ft.
- 7.60 Ravine, course S. Asc. 50 ft.

Subdivision of Sec. 5, T.4 N., R.14 W.

Chains

- 9.50 Spur, slopes S.20°E. Desc. 200 ft. over NE. slope.
- 17.50 Draw, course S. Asc. 45 ft. over W. slope.
- 21.38 The NW. 1/16 sec. cor.
- Asc. 10 ft. over W. slope.
- 21.80 Spur, slopes S. Desc. 105 ft. over E. slope.
- 23.00 Telephone line, bears NE. and SW.
- 28.00 Short ravine, course SE. Continue descent 20 ft., over gradual SE. slope.
- 31.80 Wash, 10 lks. wide, course S.20°E. Road crosses wash at this point, bearing N.10°E. and S.10°W., following the general course of Tick Canyon.
- 34.50 Tick Canyon wash, 20 lks. wide, course SW. Asc. 170 ft. over broken NW. slope.
- 42.76 The center N. 1/16 sec. cor.

General Description.

This is a rolling mountainous region, the main drainage being southwesterly in Tick Canyon, from the north center of the section. Another canyon, rising near the northeast corner parallels Tick Canyon about one half mile to the East; a third courses through the extreme southeast corner. The intervening ridges rise about 500 feet to a maximum elevation of 2500 feet above sea level.

The soil is a rocky gravel of poor quality. A very scattered growth of oak and scrub cedar is found along the ridges; lesser verdure consists of greasewood, sagebrush, buckwheat and various forms of cacti.

An unimproved roadway leads up Tick Canyon, from the Soledad Highway about two miles distant. One resident, engaged in goat culture, is located in the west central portion of the section. Water has been developed here, and living quarters; and essential corral and shed facilities are noted.

There is no commercial value attaching to the land beyond the sparse browse native to the area in general. Accessibility is afforded only in Tick Canyon, and water development will be limited to the canyon floor.
