



B.M. Elev. 144.39 P.M. North side
 frame of M.H. 6+40.00 Graham Ave.
 Sheet 3 A.C.T. 686

1. Use Standard Manhole Frames and Covers, S-a-117
2. Use Standard Strength Pipe, except as noted.
3. Use Cement mortar for all vitrified clay pipe joints.
4. All structures shall be brick sewer structures, S-a-104.
5. Resurface all trench within paved areas to meet L.A. County Road Department requirements.

NOTE: Before any connection for the disposal of Liquid Industrial Waste is made to this sewer, detailed Plans must be submitted to and a Permit secured from the County Engineer.

NOTE: No representative of the County Engineer will survey or lay out any portion of the work. The owner or his authorized representative shall furnish the County Engineer with grade sheets and stationing for all pipe connections and shall provide stakes for them at their proper locations with stationing plainly marked. Any change in locations shall be requested in writing by the owner of this tract and approved by the County Engineer. No changes shall be made in these plans without approval of the County Engineer.

PROFILE ALIGNMENT AND GRADE OF
**SANITARY SEWERS
 TO BE CONSTRUCTED IN
 PRIVATE PROPERTY
 TO SERVE
 A. ROOKE COOPERAGE CO.
 ALL OF LOT 13 AND A PORTION OF LOT 14
 NADEAU VILLA TRACT
 L.S. 15-10**

**PRIVATE CONTRACT NO. 816
 W.S. 7**
SHEET 1 OF 1 SHEETS
**PREPARED IN THE OFFICE OF
 LUDWIG BROTHERS ENGINEERS**

BY Harvey F. Ludwig
 RE 6641
 FOR LEGEND
 SEE PLAN No. S-a-64

NOTE: Grades to which this improvement is to be constructed are shown on Plans and Profile. Grade points for top of curb, center line of street or center line of alley are shown by cross mark. Profiles. All points between designated points the grade shall be established so as to conform to a straight line drawn between said designated points. Elevations are in feet above U.S.G.S. datum or mean sea level. This drawing and the data hereon are hereby made a part of the specifications. Work shall be constructed according to specifications on file in the office of the County Engineer and shall be prosecuted only in the presence of the County Engineer. Before work can be started the Contractor must obtain a permit to excavate in County Streets from the L.A. County Road Dept., 211 So. Main St., and make a deposit with the County Engineer of a Roadway League flag sufficient to cover the cost of construction inspection and record plans. If work is to be done on a State Highway a permit must be obtained from the State of California, Division of Highways, 808 State Bldg. after making the deposit with the County Engineer.

COUNTY OF LOS ANGELES, CALIFORNIA
 APPROVED FOR THE COLLECTION OF LIQUID INDUSTRIAL WASTE ONLY
Arthur DeLott
 Industrial Waste Engineer, Office of County Engineer
 APPROVED AK Gregory
 CHIEF DEPUTY COUNTY ENGINEER
 APPROVED C. R. Campbell
 ASST. CHIEF ENGINEER OF COUNTY SANITATION DISTRICT NO. 1
 CHECKED BY L. Moore June 2, 1948
 Office of County Engineer, R. S. 5323

Private 816

50