



- (1) USE STANDARD MANHOLE FRAME AND COVER 5'-0\"/>
 - (2) USE
 - (3) USE CEMENT MORTAR FOR ALL VITRIFIED CLAY PIPE JOINTS, IN PUBLIC STREETS, UNLESS OTHERWISE SPECIFIED.
 - (4) RESURFACE ALL TRENCH WITHIN PAVED AREA TO MEET LOS ANGELES COUNTY ROAD DEPT REQUIREMENTS.
 - (5) ENCASE FOUR FEET OF SEWER AT POINTS OF INTERFERENCE WITH POLES AS PER S-4-119.
 - (6) ALL STRUCTURES SHALL BE ON CENTER LINES UNLESS OTHERWISE NOTED.
- THIS DRAWING AND THE DATA HEREON ARE HEREBY MADE A PART OF THE SPECIFICATIONS.
- WORK SHALL BE CONSTRUCTED ACCORDING TO SPECIFICATIONS ON FILE IN THE OFFICE OF THE COUNTY ENGINEER AND SHALL BE PROSECUTED ONLY IN THE PRESENCE OF THE COUNTY ENGINEER.
- BEFORE WORK CAN BE STARTED, THE CONTRACTOR MUST OBTAIN A PERMIT TO EXCAVATE IN COUNTY STREETS FROM THE L.A. COUNTY ROAD DEPT, 211 SOUTH MAIN ST. AND MAKE A DEPOSIT WITH THE COUNTY ENGINEER, THROUGH LEASE BUREAU, SUFFICIENT TO COVER THE COST OF CONSTRUCTION INSPECTION AND RECORD PLANS.
- ELEVATIONS ARE IN FEET ABOVE U.S.C. DATUM.
- NOTE:
THE OWNER OR HIS AUTHORIZED AGENT SHALL FURNISH THE COUNTY ENGINEER WITH PROBE SHEETS AND STAKES OF ALL HOUSE CONNECTIONS AS A 3\"/>

B.M. ELEV 247.67 CUT-400
IN P.P. # 225373 E 3 W
COR WALNUT ST & FERN AVE

PROFILE SCALES
HOR. 1" = 40'
VER. 1" = 4'

P.C. 1015

bc