



P.C. 1052  
 6.10.52

TRIM LINE?

(8921)

B.M. Elev. 350.21 R.R. S&S  
 10 Tamarack tree N.E. Cor.  
 10TH & Live Oak Ave.

Use Standard Manhole frames and covers, S-a-117, except as noted.  
 Use Standard Strength pipe.  
 Use cement mortar for all vitrified clay pipe joints.  
 Construct house connections with 1/4" rise per foot to property line.  
 All structures shall be brick sewer structures, S-a-104, except as noted.

**PROFILE, ALIGNMENT AND GRADE OF  
 SANITARY SEWERS  
 TO BE CONSTRUCTED IN  
 LIVE OAK AVENUE  
 BETWEEN 376 FEET EAST OF 10TH AVE  
 AND 406 FEET EAST OF 10TH AVE.**

NOTE:  
 Before making any construction, and before final acceptance of this work, County Sanitation District should be notified in order that required inspection may be made.

NOTE:  
 No representative of the County Engineer will supervise any portion of the work. The owner or his authorized representative shall furnish the County Engineer with grade scales and elevations for all of the construction. All work shall be done in accordance with the specifications and standards of the County Engineer. Any change in location shall be requested in writing by the owner or his representative. All construction shall be made in these plans without approval of the County Engineer.

PRIVATE CONTRACT NO. 1052  
 W.S. 46  
 SHEET 1 OF 1 SHEETS  
 PREPARED IN THE OFFICE OF  
 KARL F. TUTTLE  
 BY *Karl F. Tuttle*  
 RE. 2000 MAY 18 1949

FOR LEGEND  
 SEE PLAN No. S-4-64

NOTE:  
 Grades to which this improvement is to be constructed are shown on Plans and Profile. Grade points for top of curb center line of street or center line of alley are shown by circles on Profile. All points between designated points the grade shall be established so as to conform to a straight line drawn between said designated points.  
 Elevations are in feet above U.S.G.S. datum or mean sea level.  
 This drawing and the data hereon are hereby made a part of the specifications. Work shall be constructed according to specifications on file in the office of the County Engineer and shall be executed only in the presence of the County Engineer.  
 Before work can be started the Contractor must obtain a permit to excavate in County Streets from the L.A. County Road Dept., 211 S. Main Street, and make a deposit with the County Engineer, 828 County Eng. Bldg., sufficient to cover the cost of construction inspection, and record plans. If work is to be done in a State Highway, a permit must be obtained from the State of California, division of highways, 808 State Bldg. after making the deposit with the County Engineer, COUNTY OF LOS ANGELES, CALIFORNIA.

INDEX MAP  
 Scale 1"=600'

APPROVED *Karl F. Tuttle*  
 COUNTY ENGINEER

APPROVED *John R. Smith*  
 CHIEF ENGINEER OF COUNTY  
 SANITATION DISTRICT NO. 15

CHECKED BY *John R. Smith* May 4, 1949  
 Office of County Engineer, R.E. No. 6322

TRIM LINE