



Profile	Alignment and Grade of
	<b>SANITARY SEWERS</b>
	<b>TO BE CONSTRUCTED FOR</b>
	<b>LAMB TRANSPORTATION CO.</b>
	<b>IN FUTURE ALAMEDA STREET</b>
	FROM 223 RD. ST. TO 590 FEET SOUTH
	<b>PRIVATE CONTRACT NO. 1081</b>
	<b>W.S. 30</b>
	JULY 1949
	<b>SHEET 1 OF 1 SHEETS</b>
	<b>PREPARED IN THE OFFICE OF</b>
	<b>LUDWIG BROTHERS ENGINEERS</b>

1. Use Standard Manhole Frames and Covers, S-a-117  
 2. Use Standard Strength Pipe, except as noted  
 3. Use Cement mortar for all vitrified clay pipe joints  
 4. All structures shall be brick sewer structures, S-a-104, except as noted  
 5. Resurface all trench within paved area to meet L.A. County Road Department requirements

**NOTE:**  
 No representative of the County Engineer will survey or lay out any portion of the work. The contractor on this authorized representative shall furnish the County Engineer with grade sheets and elevations for all connections and branches and shall provide plans for them at their proper locations with stationing plainly marked. Any change in locations shall be requested in writing by the contractor or his representative. All structures shall be made in these plans without approval of the County Engineer.

BY *Harvey F. Ludwig*  
 RE 6641  
 FOR LEGEND  
 SEE PLAN No. S-a-64  
 JUL 13 1949  
 COUNTY OF LOS ANGELES, CALIFORNIA

**NOTE:**  
 Grades to which this improvement is to be constructed are shown on Plans and Profile. Grade points for top of curb, center line of street or center line of alley are shown by circles on Profiles. All points between designated points the grade shall be established so as to conform to a straight line drawn between said designated points. Elevations are in feet above U.S.G.S. datum or mean sea level. This drawing and the data hereon are hereby made a part of the specifications. Work shall be constructed according to specifications on file in the office of the County Engineer and shall be prosecuted only in the presence of the County Engineer. Before work can be started the Contractor must obtain a permit to excavate in County Streets from the L.A. County Road Dept., 211 So. Main St., and make a deposit with the County Engineer, 428 County Engineer Bldg. sufficient to cover the cost of construction inspection and record plans. If work is to be done on a State Highway a permit must be obtained from the State of California, Division of Highways, 608 State Bldg. after making the deposit with the County Engineer.

APPROVED FOR PRE-TREATMENT AND COLLECTION OF LIQUID INDUSTRIAL WASTES  
*Arthur J. Pickett* 7-5-49  
 INDUSTRIAL WASTE ENGINEER, OFFICE OF COUNTY ENGINEER

APPROVED *[Signature]*  
 OFFICE ENGINEER  
 FOR CHIEF ENGINEER OF COUNTY SANITATION DISTRICT NO. 8

CHECKED BY *James T. Roston* July 7, 1949  
 Office of County Engineer, R.E. 3103

PC. 1081  
 J.N. 3163  
 INDEX MAP  
 SCALE 1" = 600'





