



USE STANDARD 8" DRAIN PIPE
USE CONCRETE MORTAR PORTALS WITH RIBBED GLAZED PIPE JOINTS
ENCASE FOUR FEET OF SEWER AT POINTS OF INTERFERENCE WITH POLES &
CONSTRUCT HOUSE CONNECTIONS WITH 1/4" RISE PER FOOT TO THE CURB
ALL STRUCTURES SHALL BE BUILT WITH STRUCTURE AS PER PLAN NO.
USE STANDARD MANHOLE FRAMES AND COVERS AS PER PLAN NO. 5-6-127
RESURFACE ALL TRENCHES WITHIN PAVED AREA TO MEET LOS ANGELES
STATE HIGHWAY REQUIREMENTS
NO REVISIONS SHALL BE MADE IN THESE PLANS WITHOUT APPROVAL OF THE
NO REPRESENTATIVE OF THE COUNTY ENGINEER WILL SURVEY OR LAY OUT
THE WORK
THE OWNER OR HIS AUTHORIZED REPRESENTATIVE SHALL FURNISH THE CURB
GRADE SHEETS AND STATIONS OF ALL HOUSE CONNECTIONS AND Y BRANCHES
PROVIDE STAKES FOR THEM AT THEIR PROPER LOCATIONS WITH STATIONING
ANY CHANGE OF LOCATION SHALL BE REQUESTED IN WRITING BY THE OWNER
REPRESENTATIVE



