



14.053		PROFILE ALIGNMENT AND GRADE OF SANITARY SEWERS TO BE CONSTRUCTED IN WESTERN AVE BETWEEN ROSECRANS AVE AND A POINT 631' FROM THE AND ROSECRANS AVE BETWEEN WESTERN AVE AND A POINT 1300' WEST THEREOF 2ND RLV	
(1) USE STANDARD MANHOLE FRAME AND COVER, 5'-0" DIA.		COUNTY ROAD DEPT. REQUIREMENTS IN ACCORDANCE WITH PERMITS.	
(2) USE STANDARD STRENGTH PIPE (EXCEPT AS NOTED)		(5) ENCASE FOUR FEET OF SEWER AT POINTS OF INTERFERENCE WITH POLES AS PER S.B. 119	
(3) USE CEMENT MORTAR FOR ALL VITRIFIED CLAY PIPE JOINTS		(6) ALL STRUCTURES SHALL BE BRICK SEWER STRUCTURES, 5'-6" DIA.	
(4) RESURFACE ALL TRENCH WITHIN PAVED AREA TO MEET LOS ANGELES		(7) STOPPERS TO BE INSTALLED WITH JOINT COMPOUND BY MANUFACTURER AT	
COUNTY ROAD DEPT. REQUIREMENTS IN ACCORDANCE WITH PERMITS.		THE POINTS OF INTERFERENCE	
(5) ENCASE FOUR FEET OF SEWER AT POINTS OF INTERFERENCE WITH POLES AS PER S.B. 119		(8) CONCRETE PAUGHMENT TO BE CUT NOT LESS THAN 2' IN DEPTH WITH	
(6) ALL STRUCTURES SHALL BE BRICK SEWER STRUCTURES, 5'-6" DIA.		CONCRETE SAW SPURS SEE 80	
(7) STOPPERS TO BE INSTALLED WITH JOINT COMPOUND BY MANUFACTURER AT		(9) INSTALL WIRE AND TAG AT END OF ALL CONNECTIONS SPEC. SEC. 20	
THE POINTS OF INTERFERENCE			
(8) CONCRETE PAUGHMENT TO BE CUT NOT LESS THAN 2' IN DEPTH WITH			
CONCRETE SAW SPURS SEE 80			
(9) INSTALL WIRE AND TAG AT END OF ALL CONNECTIONS SPEC. SEC. 20			

NOTE: THE OWNER OR HIS AUTHORIZED REPRESENTATIVE SHALL FURNISH THE COUNTY ENGINEER WITH GRADE SHEETS AND STATIONS OF ALL EXISTING SANITARY SEWERS AND PROVIDE STREET DIMENSIONS AT THEIR PROPER LOCATIONS WITH STATIONING, HANDY, NAMED, AND CHANGE OF LOCATION SHALL BE ACQUIRED IN WRITING BY THE OWNER OR HIS REPRESENTATIVE.

NO REVISIONS SHALL BE MADE IN THESE PLANS WITHOUT APPROVAL OF THE COUNTY ENGINEER.

NOTE: PROVIDE STRAITS ON THE PROPERTY LINES OR PROPERTY LINES PRODUCED, AT RIGHT ANGLES TO THE SEWER LINE AT THE CENTER LINE OF EACH MANHOLE.

before breaking into any existing structure
and before final acceptance of this work,
County Sanitation District should be notified
in order that required inspection may be made.

REVISION
MOVE MAIN LINE SEWER TO
NORTH SIDE OF STREET
REVISION APPROVED
BY R.L. Snodgrass 1-9-52
RIS. C.E. NO. 6412

Siphon approved
H.L. Snodgrass
1-10-52
L.O.

PC 1893 JN 4022

BY: *Harold Roach*
REG. C.E. NO. 5463
FOR LEGEND
SEE PLAN NO. S-8-65

NOTE: GRADES TO WHICH THIS IMPROVEMENT IS TO BE CONSTRUCTED ARE SHOWN ON PLANS AND PROFILE. GRADE POINTS FROM TOP OF CURB, CENTER LINE OF STREET OR CENTER LINE OF ALLEY ARE SHOWN BY CIRCLES ON PROFILES. AT ALL POINTS BETWEEN DESIGNATED POINTS THE GRADE SHALL BE ESTABLISHED SO AS TO CONFORM TO A STRAIGHT LINE DRAWN BETWEEN SAID DESIGNATED POINTS. ELEVATIONS ARE IN FEET ABOVE U. S. D. DATUM OR MEAN SEA LEVEL. THIS DRAWING AND THE DATA HEREON ARE HEREBY MADE A PART OF THE SPECIFICATIONS. WORK SHALL BE CONSTRUCTED ACCORDING TO SPECIFICATIONS ON FILE IN THE OFFICE OF THE COUNTY ENGINEER AND SHALL BE PROTECTED ONLY IN THE PRESENCE OF THE COUNTY ENGINEER. BEFORE WORK CAN BE STARTED, THE CONTRACTOR MUST OBTAIN A PERMIT TO EXCAVATE IN STREETS FROM THE L. A. COUNTY ROAD DEPT., 100 W. 2ND STREET, AND MAKE A DEPOSIT WITH THE COUNTY ENGINEER, 225 A COUNTY ENGINEERING BLDG., SUFFICIENT TO COVER THE COST OF CONSTRUCTION INSPECTION AND RECORD PLANS. APPROVAL OF THIS PLAN BY THE COUNTY OF LOS ANGELES DOES NOT CONSTITUTE REPRESENTATION AS TO THE ACCURACY OF THE LOCATION OR THE EXISTENCE OR NON-EXISTENCE OF ANY UNDERGROUND UTILITY, PIPE OR STRUCTURE WITHIN THE LIMITS OF THIS PROJECT. (THIS NOTE APPLIED TO ALL SHEETS)

COUNTY OF LOS ANGELES, CALIFORNIA.

APPROVED: WILLIAM J. FOX, COUNTY ENGINEER
BY: *W.J. Fox*

APPROVED BY: *H.L. Snodgrass* OFFICE ENGINEER
COUNTY OF LOS ANGELES
SANITATION DISTRICT NO. 3

CHECKED BY: *H.L. Snodgrass* 10-18-52
OFFICE OF COUNTY ENGINEER REG. C.E. NO. 6412

