



B.M. - P.T. 2178, 350 P.B. 1226-17
 Tolosa Ave. & Stephens Ave. S.E. Cor.
 Bl. Sp. in Curb S.W. of W. and C.R.

14,482

WHITTIER

- (1) USE STANDARD MANHOLE FRAMES AND COVERS, 3'-0" DIA.
 - (2) USE STANDARD STRENGTH PIPE.
 - (3) USE CEMENT MORTAR FOR ALL VITRIFIED CLAY PIPE JOINTS.
 - (4) RESURFACE ALL TRENCH WITHIN PAVED AREAS TO MEET US AR ROAD DEPARTMENT REQUIREMENTS.
 - (5) CONSTRUCT HOUSE CONNECTIONS WITH INVERT AT PROPERTY BELOW GRADE OF CURB.
 - (6) ALL STRUCTURES SHALL BE BIRCH SEWER STRUCTURES, 3'-0" DIA.
 - (7) DISCHARGE FROM FEET OF SEWER AT POINTS OF INTERFERENCE WITH PA...
- NO REPRESENTATIVE OF THE COUNTY ENGINEER SHALL SURVEY PORTION OF THE WORK.
 THE OWNER OR HIS AUTHORIZED REPRESENTATIVE SHALL FURNISH THE UNDERLIES & STATIONS OF ALL HOUSE CONNECTIONS & BRANCHES AS SHOWN ON THESE PAPERS LOCATIONS WITH EXISTING PLUMBING MANHOLES SHALL BE DEMONSTRATED IN WRITING BY THE OWNER OR HIS REPRESENTATIVE.
 NO REVISIONS SHALL BE MADE IN THESE PLANS WITHOUT APPROVAL OF STOPPERS TO BE INSTALLED WITH JOINT COMPOUND BY MANUFACTURER'S SPECS. SEE SPEC. 48
 CONCRETE FOUNDATION TO BE EXPOSED LESS THAN SEWER DEPTH. MANHOLES INSTALL WIRE & TAG PER SPEC. 53 & 48

INDEX MAP

