



SHEET 101
 SUNNYVIEW TRACT
 M.B. 128,79-81
 1956

(1) USE STANDARD MANHOLE
 (2) USE STANDARD STEEL
 (3) USE CEMENT MORTAR
 (4) RESURFACE ALL TRENCHES
 (5) CONSTRUCT HOUSE LOTS
 BELOW GRADE 0% - E.C.
 (6) INCREASE FOUR FEET
 WITH POLES AS PER
 (7) ALL STRUCTURES SH
 (8) PROVIDE STAKE'S ON
 PRODUCED AT RIGHT
 CENTER LINE - E.A.
 (9) STOPPERS TO BE IN
 MANUFACTURED AT
 (10) CONCRETE PAVEMENT
 WITH CONCRETE SAW
 (11) INSTALL WIDE 4" S
 NOTE:
 NO REPRESENTATIVE O
 LAY-OUT AND POSITION
 THE OWNER OF HIS AUT
 THE COUNTY ENGINEER
 ALL HOUSE CONNECTION
 STAKES FOR THE W AT
 PLAINLY MARKED ANY
 IN WRITING BY THE OWN
 NO REVISIONS SHALL
 APPROVAL OF THE COM
 CONSTRUCT TOPS OF A
 FINISHED GRADE

B.M. T.E. 56 ELE
 N.E. CORNER OF WA
 BOAT SPIKE IN WEST

Sunny View Tract
 M.B. 128,79-81

40