

WHITTIER BLDG. DIST. N° 11


- NOTE:**
1. Provide stakes on the property lines or property lines produced at right angle to the sewer line at the center line of each manhole.
 2. No representative of the County Engineer will survey or layout any portion of the work.
 3. The owner or his authorized representative shall furnish the County Engineer with grade sheets and stations for all house laterals and V-branches and shall provide stakes for them at their proper owner or his representative.
 4. No revisions shall be made in these plans without the approval of the County Engineer.
 5. Use standard manhole frames and covers, S-a-117.
 6. Use standard strength pipe except as noted.
 7. Use cement mortar for all vitrified clay pipe joints.
 8. Resurface all trench within paved area to meet L.A. County Road Dept. or California State Highway Dept. requirements in accordance with permit.
 9. Excise four feet of sewer at points of interference with poles, S-a-119.
 10. House laterals to be constructed with laterals at property line 6 feet below curb grade except as noted.
 11. All structures shall be brick sewer structures, S-a-104.
 12. For allowable leakage test, use Formula No. 1, Spec'n, Sec. 51.
 13. Manhole tops in unimproved Rights-Of-Way to be 6" above finish grade.

BM: L.A. CO. SUR. MON. 2-18
 1/2 of Norwalk Blvd &
 Sorensen Ave. EL 150.673

NO CHARGE FOR CONNECTION
 2' Landa 12-31-54

Before a permit is issued to connect to this sewer approval of the County Engineer shall be obtained for disposal of liquid industrial waste.

Approved by: *Richard*
 Industrial Waste Eng.



INDEX MAP
 P.C. 3313
 Scale 1" = 600'

checked 2-18-55 W. H. ...

P.C. 3313
 PAGE 1

PROFILE, ALIGNMENT AND GRADE OF
SANITARY SEWERS
 TO BE CONSTRUCTED IN
SORENSEN LANE

19,740

PRIVATE CONTRACT NO. 3313
 W. S. 33
 1 SHEET

Scale: VERT. 1" = 4'
 HORIZ. 1" = 40'

DEC. 1954

PREPARED IN THE OFFICES OF
RALPH L. BOGE
 DAVID R. EDWARDS
 CONSULTING ENGINEER
 Reg. C. E. No. 4724

FOR LEGEND SEE PLAN NO. S-a-64

NOTE:

Grades to which this improvement is to be constructed are shown on plans and profiles. Grade points for top of curbs, center line of streets, or center line of alleys are shown by circles on profiles. At all points between designated points the grade shall be established so as to conform to a straight line drawn between said designated points.

Elevations are in feet above U.S.G.S. datum or mean sea level.

This drawing and the data hereon are hereby made a part of the specifications.

Work shall be constructed according to specifications on file in the office of the County Engineer and shall be prosecuted only in the presence of the County Engineer.

Before work can be started, the contractor must obtain a permit to excavate in County streets from the L.A. County Road Dept., 108 W. 2nd St. and make a deposit with the County Engineer, 733 L.A. County Engineering Building, sufficient to cover the cost of construction inspection and record plans.

Approval of this plan by the County of Los Angeles does not constitute a representation as to the accuracy of the location or the existence or non-existence of any underground utility, pipe, or structure within the limits of this project. This note applies to all sheets.

If work is to be done in a State Highway, a permit must be obtained from the State of California, Division of Highways, 120 South Spring Street.

COUNTY OF LOS ANGELES, CALIFORNIA

Approved, William J. Fox, County Engineer

Approved, A. M. Ryan
 CHIEF ENGR. CO. SAN. DIST. NO. 11

Checked by: *A. P. Collins*
 Office Engineer

Checked by: *A. P. Collins*
 Office of County Engineer, Reg. C. E. No. 7260

SORENSEN LANE