



EAST LOS ANGELES BLDG. DIST. N° 6

NOTE:

Provide stakes on the property lines or property lines produced at right angles to the sewer line of the center line of each manhole.

The owner or his authorized representative shall furnish the County Engineer with grade sheets and stations for all house laterals and Y branches and shall provide stakes for them at their proper locations with obtaining plainly marked. Any change in location shall be requested in writing by the owner or his representative.

No revisions shall be made in these plans without the approval of the County Engineer.

1. Use standard manhole frames and covers, S-117.
2. Use standard strength pipe except as noted.
3. Use cement mortar for all vitrified clay pipe joints.
4. Resurface all trench within paved area to meet L.A. County Road Dept. or California State Highway Dept. requirements in accordance with permit.
5. Excavate four feet of sewer at points of interference with poles, S-115.
6. House laterals to be constructed with 1 1/2" rise per foot to the property line.
7. All structures shall be brick sewer structures, S-184.
8. For allowable leakage test, see Formula No. 1, Spec's., Sec. 51.
9. Manhole tops in unimproved Rights-Of-Way to be 6" above finished grade.

**PROFILE ALIGNMENT AND GRADE OF
SANITARY SEWERS
TO BE CONSTRUCTED IN
FIRST ALLEY SOUTH OF WASHINGTON BOULEVARD
FROM
FIDELIA AVENUE TO 40 FEET WEST OF FIDELIA AVENUE**

PC 3602
PAGE 1

21,504

PRIVATE CONTRACT NO. 3602
W. S. 36
ONE SHEET

Scale: $\frac{1}{4}$ " = 1'-0"
JULY, 1953
PREPARED IN THE OFFICES OF

BULLINER, PROROG & YOUNG
By *C. F. Bulliner* P.E. No. 1274
FOR LEGEND SEE PLAN NO. S-6-64

| SHEETS | PAGE |
|--------|------|
| 1 | 1 |

NOTE:

Grades to which this improvement is to be constructed are shown on plans and profiles. Grade points for top of curb, center line of streets, or center line of alleys are shown by circles on profiles. At all points between designated points, the grade shall be established so as to conform to a straight line drawn between said designated points.

Elevations are in feet above U.S.S.S. datum or mean sea level.

This drawing and the data hereon are hereby made a part of the specifications for the work to be constructed according to specifications on file in the office of the County Engineer and shall be presented only in the presence of the County Engineer.

Before work can be started, the contractor must obtain a permit to excavate in County streets from the L.A. County Road Dept., 100 W. 2nd St. and make a deposit with the County Engineer, \$m. 110, 25% of the estimated cost of construction inspection and record plans.

Approval of this plan by the County of Los Angeles does not constitute a representation as to the accuracy of the location of or the existence or non-existence of any underground utility, pipe, or structure within the limits of this project. This note applies to all sheets.

Work to be done in a State Highway, a permit must be obtained from the State of California, Division of Highways, 120 South Spring Street.

COUNTY OF LOS ANGELES, CALIFORNIA

Approved, William A. Fox, County Engineer
Approved, A. M. Egan, Chief Engineer, SAN. DIST. NO. 6

By *C. F. Bulliner* P.E. No. 1274
Checked by *R. J. ...* P.E. No. 7362
Office of County Engr., 100 W. 2nd St., Rm. 7362

P.C. 360

P.C. 3605

P.C. 3605

INDEX MAP
Scale 1/4" = 100'
PG 3602

COLLECT CHARGES
AS
INDICATED
3K Miles 2-1-55

10-10-55

Triax Line