

PUENTE BLDG. DIST. NO.2

PROVIDE STAKES ON THE PROPERTY LINES OR PROPERTY LINES PRODUCED AT RIGHT ANGLES TO THE SEWER LINE AT THE CENTER LINE OF EACH MANHOLE. NO REPRESENTATIVE OF THE COUNTY ENGINEER WILL SURVEY OR LAYOUT ANY PORTION OF THE WORK.

THE OWNER OR HIS AUTHORIZED REPRESENTATIVE SHALL FURNISH THE COUNTY ENGINEER WITH GRADE SHEETS & STATIONS FOR ALL HOUSE LATERALS AND "Y" BRANCHES AND SHALL PROVIDE STAKES FOR THEM AT THEIR PROPER LOCATIONS WITH STATIONING PLAINLY MARKED. ANY CHANGE IN LOCATION SHALL BE REQUESTED IN WRITING BY THE OWNER OR HIS REPRESENTATIVE.

NO REVISIONS SHALL BE MADE IN THESE PLANS WITHOUT THE APPROVAL OF THE COUNTY ENGINEER. .

I. USE STANDARD MANHOLE FRAMES & COVERS, S-A-117.

2. USE STANDARD STRENGTH PIPE EXCEPT AS NOTED.

3 USE CEMENT MORTAR FOR ALL VITRIFIED CLAY PIPE JOINTS.

4. RESURFACE ALL TRENCH WITHIN PAVED AREA TO MEET L.A. COUNTY ROAD DEPT. OR CALIFORNIA STATE HIGHWAY DEPT. REQUIREMENTS IN ACCORDANCE WITH PERMIT.

5. ENCASE FOUR FT. OF SEWER AT POINTS OF INTERFERENCE WITH POLES, S-A-119. 6. HOUSE LATERALS TO BE CONSTRUCTED WITH INVERTS AT PROPERTY LINE_6_ FT. BELOW CURB GRADE EXCEPT AS NOTED.

7. ALL STRUCTURES SHALL BE BRICK SEWER STRUCTURES, 8-A-104.

8. FOR ALLOWABLE LEAKAGE TESTS, USE FORMULA NO. _____, SPEC'S., SEC. 54, 9. MANHOLE TOPS IN UNIMPROVED RIGHTS-OF-WAY TO BE 6" ABOVE FINISH GRADE.

10 Private Engineer to furnish house lateral depth at property line below top of curb grade elevation for each house lateral on the grade sheet.

B.M. S.G. 1013 ELEV. 328.423 RESET L.& B.N., CENTER OF CURB RETURN, N.E. COR. AMAR RD. & GLENDORA AVE.

COLLECT CHARGES AS INDICATED.

CURS GRIDES IN MONTBROOK ST. REVISIONS APPROVED

PROFILE, ALIGNMENT AND GRADE OF SANITARY SEWERS TO BE CONSTRUCTED IN TRACT NO. 21864

PRIVATE CONTRACT NO. 4187 W.S. 38

3 F SHEET, 3 PAGES.

AUGUST, 1956 PREPARED IN THE OFFICES OF

HAROLD M. TEGART

FOR LEGEND SEE PLAN NO. S-A-64

GRADES TO WHICH THIS IMPROVEMENT IS TO BE CONSTRUCTED ARE SHOWN ON PLANS AND PROFILES. GRADE POINTS FOR TOP OF CURBS, CENTER LINE OF STREETS, OR CENTER LINE OF ALLEYS ARE SHOWN BY CIRCLES ON PROFILES. AT ALL POINTS BETWEEN DESIGNATED POINTS THE GRADE SHALL BE ESTABLISHED SO AS TO CONFORM TO A STRAIGHT LINE DRAWN BETWEEN SAID DESIGNATED POINTS.

ELEVATIONS ARE IN FEET ABOVE U.S.G.&G.S. SEA LEVEL DATUM OF 1929.
THIS DRAWING AND THE DATA HEREON ARE HEREBY MADE A PART OF THE SPECIFICATIONS. WORK SHALL BE CONSTRUCTED ACCORDING TO SPECIFICATIONS ON FILE IN THE OFFICE OF THE COUNTY ENGINEER AND SHALL BE PROSECUTED ONLY IN THE PRESENCE OF THE COUNTY ENGINEER.

BEFORE WORK CAN BE STARTED, THE CONTRACTOR MUST OBTAIN A PERMIT TO EXCAVATE IN COUNTY STREETS FROM THE L.A. COUNTY ROAD DEPT., 108 W. 2 ND. ST. AND MAKE A DEPOSIT WITH THE COUNTY ENGINEER, ROOM SIS, 253 SO. BROADWAY, SUFFICIENT TO COVER THE COST OF CONSTRUCTION INSPECTION AND RECORD PLANS. APPROVAL OF THIS PLAN BY THE COUNTY OF LOS ANGELES DOES NOT CONSTITUTE A REPRESENTATION AS TO THE ACCURACY OF THE LOCATION OF OR THE EXISTENCE OF OR NON-EXISTENCE OF ANY UNDERGROUND UTILITY, PIPE, OR STRUCTURE WITHIN THE LIMITS OF THIS PROJECT. THIS NOTE APPLIES TO ALL SHEETS. IF WORK IS TO BE DONE IN A STATE HIGHWAY, A PERMIT MUST BE OBTAINED FROM THE STATE OF CALIFORNIA, DIVISION OF HIGHWAYS, 120 SO. SPRING STREET.

COUNTY OF LOS ANGELES, CALIFORNIA

APPROVED, JOHN A. LAMBIE, COUNTY ENGINEER

APPROVED, A.M. RAWN CHIEF ENGS. CO. SAN. DIST. NO. 15

P.C. 4187

PAGE I

Trim Line



