



- GENERAL NOTES**  
(APPLY TO SEWER RECONSTRUCTION ONLY)
1. For legend, see Standard Plan S-a-64
  2. Use extra strength vitrified clay pipe for all sewer pipe.
  3. Use cement mortar for all vitrified clay pipe joints.
  4. All structures shall be brick sewer structures per S-a-104.
  5. Use standard manhole frame & cover per S-a-117.
  6. Abandoned sewers shall be sealed with brick and cement mortar per Sec 60 of Std Specs for San Sewers.
  7. Use formula "1, Section 54 of Standard Specifications for the Construction of Sanitary Sewers, to compute allowable leakage.
  8. Resurface trenches within the paved area of streets as noted on Sheet No 1 of the project drawings.

**REF. P.C. 9067** 1958 STORM DRAIN BOND ISSUE

PREPARED BY <b>JOHN A. LAMBIE</b> COUNTY ENGINEER RECOMMENDED BY <i>[Signature]</i> DESIGNER & SECTION ENGINEER	<b>REVISIONS</b> MARK DATE DESCRIPTION		LOS ANGELES COUNTY <b>FLOOD CONTROL DISTRICT</b> PROJECT NO. 526 <b>INDIAN SUMMER AVENUE</b> SANITARY SEWER RECONSTRUCTION PLAN AND PROFILE
	DRAWN BY: HIGGINSON CHECKED BY: HIGGINSON TRACED BY: HIGGINSON INCHES BY: JAMIE	DESIGNED BY: HIGGINSON CHECKED BY: YELINEK SUBMITTED BY: HIGGINSON	

REF. P.C. 9067 (S.D. PROJ. 526)