C.S.B-2155

LONG BEACH

PROPERTY CORNER
Set County Engineer Monument marked: 12" below surface at record distance (43.59') from McBride Ave. per C.S.B-2302. F.B. 2921-190, 213, 258.

Found large boat spike, washer & tin 27" below surface. See F.B. 2993-160. Set 1"x2" stake & nail flush with surface over same. F. B. 2921-190, 213, 258.

Found 1" iron pipe, plug & nail 50" below surface. See F.B. 2700-46 & C.S.B-2302. Set 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface over same. F.B. 2921-190, 213, 258.

Set 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface. F. B. 2921-188, 260.

PROPERTY CORNER
Set County Engineer Monument marked: flush with surface by intersection holding record angle from the South per O. R. D2154-582. F. B. 2921-188, 260.

PROPERTY CORNER
Set 2" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface at record angle & distance (120.00') from the West per O. R. D 2154-582. F. B. 2921-186, 262.

SECTION CORNER
Found County Engineer Monument marked: flush with surface. See F. B. 2993-153 & F. B. 3156-19. F. B. 2921-153, 183, 208, 233.

1/4 SECTION CORNER
Found County Surveyors Monument marked: flush with surface. See F. B. 2993-156. F. B. 2921-159, 192.

PROPERTY CORNER
Established at record angle & distance (299.07') from the Southeast per O.R. D838-732. Nothing set.

PROPERTY CORNER
Established at record distance (317.16') from South per O.R.D838-732. Nothing set.

Set 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." F. B. 2921-155, 234.

Set 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface. F. B. 2921-155, 234.

PROPERTY CORNER
Established by intersection holding record angle from the Northeast per O.R. D838-732. Nothing set.

Set 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface. F. B. 2921-156, 250, 255.

1/4 SECTION CORNER
Found County Surveyor Monument marked: 3" below surface. See F. B. 566-54. & F. B. 1254-30. F. B. 2921-163, 199.

1/64 SECTION CORNER
Set 2" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface by proportion between Section Corner to the West & 1/4 Section Corner to the East per C. S. B-2302. F. B. 2921-195.

PROPERTY CORNER
Set County Engineer Monument marked: flush with surface at record angle & distance (14.85') from the Southwest per C.R. 54377-180. F. B. 2921-204, 255.

PROPERTY CORNER
Set County Engineer Monument marked: flush with surface at record angle & distance (49.85') from the Southwest per C.R. 54377-180. F. B. 2921-203, 254.

(P.) - Found 1" iron pipe, conc. plug & brass tag marked "L. A. CO. ENGR." Flush with surface. See F. B. 1254-109 & F. B. 2700-115. F. B. 2921-202.

PROPERTY CORNER
Set County Engineer Monument marked: flush with surface at record angle & distance (14.85') from the Southwest per C.R. 54377-180. F. B. 2921-206, 256.

E'LY LINE OF W. 1/2 OF THE W. 1/2 OF S.W. 1/4 OF SEC. 29, T. 1 S., R. 12 W.
N. 0°05'11"W. 1313.92

N.5°16'24"E. 174.93

N.29°20'26"E. 354.34

N.16°17'40"E. 737.80

N.89°28'01"E. 1996.74

N.89°28'01"E. 2395.26

N.89°28'01"E. 1335.30

N.19°58'19"E. 347.69

N.0°26'18"W. 975.05

N.0°26'17"W. 1320.00

N.0°26'18"W. 526.47

N.0°01'59"W. 2635.24

N.0°01'59"W. ~ 264.83

N.0°01'59"W. ~ 264.35

N.0°01'59"W. 264.21

N.10°49'29"W. 299.07

N.17°12'59"W. 319.64

N.17°52'23"E. 276.62

N.89°44'11"E. 666.04

N.89°58'01"E. 120.00

N.89°58'01"E. 80.00

S.89°44'11"W. 666.04

S.62°39'51"W. 160.00

S.31°12'16"W. ~ 322.78

S.18°20'36"W. 182.09

S.8°45'22"E. 84.86

S.31°57'09"W. 128.30

S.8°45'22"E. 119.61

S.3°01'12"E. 84.86

S.6°38'52"E. 101.77

S.17°52'23"E. 276.62

S.65°39'57"W. 163.63

S.17°52'23"E. ~ 276.62

S.17°52'23"E. ~ 276.62

S.89°44'11"E. 666.04

S.89°44'11"E. 400.54

S.89°44'11"E. 445.115

S.89°44'11"E. 1335.30

S.89°44'11"E. 1335.30

S.89°44'11"E. 1335.30